1. What value is stored in scores [2] [3], and which AI model and the category doses it represent?

Okay, so the value stored in scores [2] [3] is 92. The first index is (2) which refers to the third row, which is Claude, and the second index (3) it refers to the fourth column, which is Math. This means that Claude received a score of 92 in the Math category.

2. What is the difference between scores.length and scores [0]. Length?

   Scores.length returns the number of rows in the 2D array. In this program, it definitely returns 5 because there are five AI models. Scores [0]. Length returns the number of columns in a row. It also returns 5 because there are five categories. The rows represent models, while the columns represent categories.

3. Why do we use nested loops when traveling through a two-dimensional array?

Well use nested loops because a 2D array contains both rows and columns. So, the outer loop moves through each row, and the inner loop moves through each column within that row. This allows the program to access every score in the matrix and display all the data correctly.

4. Explain why calculating a category average requires traversing a column rather than a row.

Okay, so a category average is based on the scores from all AI models in the same category. Since categories are stored in columns, the program needs to move down the column and add the values

from each row. If the program moved across a row istead, it would be calculating the average for a single AI model rather than a category, but so far everything is working perfectly.

5. What would happen if you sorted the model names but did not also rearrange their corresponding averages?

The leaderboard would become incorrect because the model names would no longer match their actual average scores. So, for example, ChatGPT might end up showing Claude's average score. This would make the rankings inaccurate and could lead to incorrect conclusions about the results.

6. How would your program need to change to accommodate a sixth AI model?

   Alright to add a sixth AI model, I would add the model's name to the model's array and add another row of scores to the scores array. Since the program uses loops and array lengths instead of hard-coded values, the averages, Seaches, and leaderboards would automatically include the new model with very few changes.

7. Why should fictional performance scores not be used to make real-world claims about which AI system is the best?

All right, the scores in this assignment were created only for programing practice and are not based on real testing. Real AI performance can change depending on the task, the data for testing, and updates to the software. Because of this, fictional scores in the code program cannot be used as evidence that one AI system is better than another in real-world situations.

Name: Edgar Rivera

Course: Object-Oriented Programming

Assignment: CampusAI — Analysis Questions

Date: October 23, 2026