

Example

May 20, 2020

#

Hands-on Example with MGWR

Notebook Outline:

An example of hedonic house price modeling using MGWR - Section 1 - Section 2 - Section 3

[Back to the main page](#)

1 Introduction to the Dataset

Please use [this link](#) to directly download a csv of the dataset

- **houses** - number of houses in the census tracts

Dependent variables

- **avg_price** - average house prices in the census tracts

OR

- **ln_avg_price** - log-transformed average house prices in the census tracts

Independent variables

- **avg_tech** - average technology related jobs in the census tracts
- **avg_unemp** - average unemployment rate in the census tracts
- **avg_index** - average number of house with a view to the waterfront
- **avg_basement** - average basements in the houses in the census tracts
- **avg_water_dist** - average distance to nearest waterfronts from the houses in the census tracts
- **avg_sqft** - average square footage of living area in houses in the census tracts
- **avg_age** - average age of housing units in the census tracts

Dependent variable distribution

Hence, we use the log-transformed dependent variable \ln_avg_price

2 Loading the Dataset

Open the [MGWR GUI software](#) on your desktop to follow along!

At this stage I am going to do the steps elaborated below live. The screenshots of the steps below will guide you if you need additional reference.

2.0.1 1. Loading the dataset and variables

2.0.2 2. Load the dependent and independent variables

3 Spatial Weighting Kernels and other Options

3.0.1 Advanced options
