10 VF101 - Vehicle Speedometer Display Management (VF101_V1_PJ3U)

Document Code: VF101_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

10.1 Purpose and Functional Overview

[REQ_VF101_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF101 - Vehicle Speedometer Display Management.

10.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF101_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF101_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF101_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF101_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF101_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF101_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF101_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF101_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF101_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF101_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF101_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF101_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF101_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF101_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF101_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF101_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF101_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

10.2 Detailed Functional Requirements & State Logic · VF101 (Part 2/27)

[REQ_VF101_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.3 Detailed Functional Requirements & State Logic · VF101 (Part 3/27)

[REQ_VF101_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.4 Detailed Functional Requirements & State Logic · VF101 (Part 4/27)

[REQ_VF101_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.5 Detailed Functional Requirements & State Logic · VF101 (Part 5/27)

[REQ_VF101_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.6 Detailed Functional Requirements & State Logic · VF101 (Part 6/27)

[REQ_VF101_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.7 Detailed Functional Requirements & State Logic · VF101 (Part 7/27)

[REQ_VF101_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.8 Detailed Functional Requirements & State Logic · VF101 (Part 8/27)

[REQ_VF101_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.9 Detailed Functional Requirements & State Logic · VF101 (Part 9/27)

[REQ_VF101_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.10 Detailed Functional Requirements & State Logic · VF101 (Part 10/27)

[REQ_VF101_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.11 Detailed Functional Requirements & State Logic · VF101 (Part 11/27)

[REQ_VF101_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.14 Detailed Functional Requirements & State Logic · VF101 (Part 12/27)

[REQ_VF101_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.15 Detailed Functional Requirements & State Logic · VF101 (Part 13/27)

[REQ_VF101_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.16 Detailed Functional Requirements & State Logic · VF101 (Part 14/27)

[REQ_VF101_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.17 Detailed Functional Requirements & State Logic · VF101 (Part 15/27)

[REQ_VF101_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.18 Detailed Functional Requirements & State Logic · VF101 (Part 16/27)

[REQ_VF101_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.19 Detailed Functional Requirements & State Logic · VF101 (Part 17/27)

[REQ_VF101_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.20 Detailed Functional Requirements & State Logic · VF101 (Part 18/27)

[REQ_VF101_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.21 Detailed Functional Requirements & State Logic · VF101 (Part 19/27)

[REQ_VF101_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.22 Detailed Functional Requirements & State Logic · VF101 (Part 20/27)

[REQ_VF101_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.23 Detailed Functional Requirements & State Logic · VF101 (Part 21/27)

[REQ_VF101_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.12 Indication Management

[REQ_VF101_IND] When V_SPEED_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate SPEEDOMETER ACTIVE.V1 on the displ

IND_ROW | SPEEDOMETER ACTIVE.V1 | When V_SPEED_Sts == ACTIVE on CAN-FD network | No (Standard SPEEDOMETER Tell

[REQ_VF101_IND] When V_SPEED_FailSts == PRESENT, the IPC cluster shall activate SPEEDOMETER FAIL.V1 on the display.

IND_ROW | SPEEDOMETER FAIL.V1 | When V_SPEED_FailSts == PRESENT | Yes - Check Vehicle Speedometer Display Mana

[REQ_VF101_IND] When CAN node timeout > V_SPEED_TIMEOUT, the IPC cluster shall activate SPEEDOMETER RECOVERY.V1 on the displa

IND_ROW | SPEEDOMETER RECOVERY.V1 | When CAN node timeout > V_SPEED_TIMEOUT | Yes - SPEEDOMETER System Recover

10.25 Detailed Functional Requirements & State Logic · VF101 (Part 23/27)

[REQ_VF101_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.26 Detailed Functional Requirements & State Logic · VF101 (Part 24/27)

[REQ_VF101_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.27 Detailed Functional Requirements & State Logic · VF101 (Part 25/27)

[REQ_VF101_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

10.14 Configuration Parameters

10.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF101_01 | V_SPEED_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Pri

PAR_ROW | PAR_VF101_02 | V_SPEED_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filtering

PAR_ROW | PAR_VF101_03 | CFG_VF101_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF101_04 | T_BCM_VF101_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

10.29 Detailed Functional Requirements & State Logic · VF101 (Part 27/27)

[REQ_VF101_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF101_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF101_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF101_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF101_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF101_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF101_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF101_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF101_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF101_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF101_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF101_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF101_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF101_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF101_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF101_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF101_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF101_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF101_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF101_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF101_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF101_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF101_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF101_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF101_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF101_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF101_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11 VF102 - Tachometer and Engine RPM Management (VF102_V1_PJ3U)

Document Code: VF102_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

11.1 Purpose and Functional Overview

[REQ_VF102_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF102 - Tachometer and Engine RPM Management.

11.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF102_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF102_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF102_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF102_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF102_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF102_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF102_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF102_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF102_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF102_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF102_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF102_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF102_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF102_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF102_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF102_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF102_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

11.2 Detailed Functional Requirements & State Logic · VF102 (Part 2/27)

[REQ_VF102_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.3 Detailed Functional Requirements & State Logic · VF102 (Part 3/27)

[REQ_VF102_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.4 Detailed Functional Requirements & State Logic · VF102 (Part 4/27)

[REQ_VF102_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.5 Detailed Functional Requirements & State Logic · VF102 (Part 5/27)

[REQ_VF102_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.6 Detailed Functional Requirements & State Logic · VF102 (Part 6/27)

[REQ_VF102_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.7 Detailed Functional Requirements & State Logic · VF102 (Part 7/27)

[REQ_VF102_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.8 Detailed Functional Requirements & State Logic · VF102 (Part 8/27)

[REQ_VF102_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.9 Detailed Functional Requirements & State Logic · VF102 (Part 9/27)

[REQ_VF102_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.10 Detailed Functional Requirements & State Logic · VF102 (Part 10/27)

[REQ_VF102_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.11 Detailed Functional Requirements & State Logic · VF102 (Part 11/27)

[REQ_VF102_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.14 Detailed Functional Requirements & State Logic · VF102 (Part 12/27)

[REQ_VF102_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.15 Detailed Functional Requirements & State Logic · VF102 (Part 13/27)

[REQ_VF102_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.16 Detailed Functional Requirements & State Logic · VF102 (Part 14/27)

[REQ_VF102_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.17 Detailed Functional Requirements & State Logic · VF102 (Part 15/27)

[REQ_VF102_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.18 Detailed Functional Requirements & State Logic · VF102 (Part 16/27)

[REQ_VF102_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.19 Detailed Functional Requirements & State Logic · VF102 (Part 17/27)

[REQ_VF102_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.20 Detailed Functional Requirements & State Logic · VF102 (Part 18/27)

[REQ_VF102_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.21 Detailed Functional Requirements & State Logic · VF102 (Part 19/27)

[REQ_VF102_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.22 Detailed Functional Requirements & State Logic · VF102 (Part 20/27)

[REQ_VF102_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.23 Detailed Functional Requirements & State Logic · VF102 (Part 21/27)

[REQ_VF102_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.12 Indication Management

[REQ_VF102_IND] When N_RPM_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate TACHOMETER ACTIVE.V1 on the display.

IND_ROW | TACHOMETER ACTIVE.V1 | When N_RPM_Sts == ACTIVE on CAN-FD network | No (Standard TACHOMETER Telltale

[REQ_VF102_IND] When N_RPM_FailSts == PRESENT, the IPC cluster shall activate TACHOMETER FAIL.V1 on the display.

IND_ROW | TACHOMETER FAIL.V1 | When N_RPM_FailSts == PRESENT | Yes - Check Tachometer and Engine RPM Managemen

[REQ_VF102_IND] When CAN node timeout > N_RPM_TIMEOUT, the IPC cluster shall activate TACHOMETER RECOVERY.V1 on the display.

IND_ROW | TACHOMETER RECOVERY.V1 | When CAN node timeout > N_RPM_TIMEOUT | Yes - TACHOMETER System Recovery |

11.25 Detailed Functional Requirements & State Logic · VF102 (Part 23/27)

[REQ_VF102_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.26 Detailed Functional Requirements & State Logic · VF102 (Part 24/27)

[REQ_VF102_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.27 Detailed Functional Requirements & State Logic · VF102 (Part 25/27)

[REQ_VF102_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

11.14 Configuration Parameters

11.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF102_01 | N_RPM_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Prima

PAR_ROW | PAR_VF102_02 | N_RPM_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filtering |

PAR_ROW | PAR_VF102_03 | CFG_VF102_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF102_04 | T_BCM_VF102_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

11.29 Detailed Functional Requirements & State Logic · VF102 (Part 27/27)

[REQ_VF102_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF102_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF102_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF102_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF102_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF102_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF102_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF102_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF102_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF102_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF102_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF102_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF102_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF102_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF102_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF102_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF102_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF102_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF102_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF102_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF102_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF102_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF102_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF102_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF102_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF102_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF102_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12 VF103 - Fuel Level Gauge and Low Fuel Warning (VF103_V1_PJ3U)

Document Code: VF103_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

12.1 Purpose and Functional Overview

[REQ_VF103_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF103 - Fuel Level Gauge and Low Fuel Warning.

12.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF103_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF103_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF103_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF103_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF103_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF103_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF103_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF103_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF103_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF103_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF103_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF103_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF103_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF103_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF103_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF103_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF103_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

12.2 Detailed Functional Requirements & State Logic · VF103 (Part 2/27)

[REQ_VF103_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.3 Detailed Functional Requirements & State Logic · VF103 (Part 3/27)

[REQ_VF103_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.4 Detailed Functional Requirements & State Logic · VF103 (Part 4/27)

[REQ_VF103_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.5 Detailed Functional Requirements & State Logic · VF103 (Part 5/27)

[REQ_VF103_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.6 Detailed Functional Requirements & State Logic · VF103 (Part 6/27)

[REQ_VF103_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.7 Detailed Functional Requirements & State Logic · VF103 (Part 7/27)

[REQ_VF103_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.8 Detailed Functional Requirements & State Logic · VF103 (Part 8/27)

[REQ_VF103_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.9 Detailed Functional Requirements & State Logic · VF103 (Part 9/27)

[REQ_VF103_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.10 Detailed Functional Requirements & State Logic · VF103 (Part 10/27)

[REQ_VF103_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.11 Detailed Functional Requirements & State Logic · VF103 (Part 11/27)

[REQ_VF103_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.14 Detailed Functional Requirements & State Logic · VF103 (Part 12/27)

[REQ_VF103_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.15 Detailed Functional Requirements & State Logic · VF103 (Part 13/27)

[REQ_VF103_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.16 Detailed Functional Requirements & State Logic · VF103 (Part 14/27)

[REQ_VF103_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.17 Detailed Functional Requirements & State Logic · VF103 (Part 15/27)

[REQ_VF103_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.18 Detailed Functional Requirements & State Logic · VF103 (Part 16/27)

[REQ_VF103_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.19 Detailed Functional Requirements & State Logic · VF103 (Part 17/27)

[REQ_VF103_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.20 Detailed Functional Requirements & State Logic · VF103 (Part 18/27)

[REQ_VF103_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.21 Detailed Functional Requirements & State Logic · VF103 (Part 19/27)

[REQ_VF103_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.22 Detailed Functional Requirements & State Logic · VF103 (Part 20/27)

[REQ_VF103_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.23 Detailed Functional Requirements & State Logic · VF103 (Part 21/27)

[REQ_VF103_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.12 Indication Management

[REQ_VF103_IND] When L_FUEL_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate FUEL LEVEL ACTIVE.V1 on the display.

IND_ROW | FUEL LEVEL ACTIVE.V1 | When L_FUEL_Sts == ACTIVE on CAN-FD network | No (Standard FUEL LEVEL Telltal

[REQ_VF103_IND] When L_FUEL_FailSts == PRESENT, the IPC cluster shall activate FUEL LEVEL FAIL.V1 on the display.

IND_ROW | FUEL LEVEL FAIL.V1 | When L_FUEL_FailSts == PRESENT | Yes - Check Fuel Level Gauge and Low Fuel Warn

[REQ_VF103_IND] When CAN node timeout > L_FUEL_TIMEOUT, the IPC cluster shall activate FUEL LEVEL RECOVERY.V1 on the display.

IND_ROW | FUEL LEVEL RECOVERY.V1 | When CAN node timeout > L_FUEL_TIMEOUT | Yes - FUEL LEVEL System Recovery |

12.25 Detailed Functional Requirements & State Logic · VF103 (Part 23/27)

[REQ_VF103_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.26 Detailed Functional Requirements & State Logic · VF103 (Part 24/27)

[REQ_VF103_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.27 Detailed Functional Requirements & State Logic · VF103 (Part 25/27)

[REQ_VF103_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

12.14 Configuration Parameters

12.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF103_01 | L_FUEL_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Prim

PAR_ROW | PAR_VF103_02 | L_FUEL_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filtering

PAR_ROW | PAR_VF103_03 | CFG_VF103_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF103_04 | T_BCM_VF103_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

12.29 Detailed Functional Requirements & State Logic · VF103 (Part 27/27)

[REQ_VF103_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF103_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF103_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF103_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF103_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF103_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF103_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF103_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF103_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF103_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF103_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF103_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF103_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF103_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF103_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF103_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF103_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF103_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF103_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF103_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF103_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF103_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF103_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF103_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF103_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF103_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF103_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13 VF104 - Engine Coolant Temperature Gauge (VF104_V1_PJ3U)

Document Code: VF104_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

13.1 Purpose and Functional Overview

[REQ_VF104_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF104 - Engine Coolant Temperature Gauge.

13.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF104_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF104_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF104_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF104_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF104_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF104_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF104_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF104_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF104_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF104_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF104_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF104_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF104_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF104_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF104_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF104_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF104_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

13.2 Detailed Functional Requirements & State Logic · VF104 (Part 2/27)

[REQ_VF104_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.3 Detailed Functional Requirements & State Logic · VF104 (Part 3/27)

[REQ_VF104_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.4 Detailed Functional Requirements & State Logic · VF104 (Part 4/27)

[REQ_VF104_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.5 Detailed Functional Requirements & State Logic · VF104 (Part 5/27)

[REQ_VF104_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.6 Detailed Functional Requirements & State Logic · VF104 (Part 6/27)

[REQ_VF104_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.7 Detailed Functional Requirements & State Logic · VF104 (Part 7/27)

[REQ_VF104_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.8 Detailed Functional Requirements & State Logic · VF104 (Part 8/27)

[REQ_VF104_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.9 Detailed Functional Requirements & State Logic · VF104 (Part 9/27)

[REQ_VF104_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.10 Detailed Functional Requirements & State Logic · VF104 (Part 10/27)

[REQ_VF104_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.11 Detailed Functional Requirements & State Logic · VF104 (Part 11/27)

[REQ_VF104_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.14 Detailed Functional Requirements & State Logic · VF104 (Part 12/27)

[REQ_VF104_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.15 Detailed Functional Requirements & State Logic · VF104 (Part 13/27)

[REQ_VF104_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.16 Detailed Functional Requirements & State Logic · VF104 (Part 14/27)

[REQ_VF104_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.17 Detailed Functional Requirements & State Logic · VF104 (Part 15/27)

[REQ_VF104_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.18 Detailed Functional Requirements & State Logic · VF104 (Part 16/27)

[REQ_VF104_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.19 Detailed Functional Requirements & State Logic · VF104 (Part 17/27)

[REQ_VF104_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.20 Detailed Functional Requirements & State Logic · VF104 (Part 18/27)

[REQ_VF104_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.21 Detailed Functional Requirements & State Logic · VF104 (Part 19/27)

[REQ_VF104_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.22 Detailed Functional Requirements & State Logic · VF104 (Part 20/27)

[REQ_VF104_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.23 Detailed Functional Requirements & State Logic · VF104 (Part 21/27)

[REQ_VF104_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.12 Indication Management

[REQ_VF104_IND] When T_COOLANT_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate COOLANT TEMP ACTIVE.V1 on the d

IND_ROW | COOLANT TEMP ACTIVE.V1 | When T_COOLANT_Sts == ACTIVE on CAN-FD network | No (Standard COOLANT TEMP

[REQ_VF104_IND] When T_COOLANT_FailSts == PRESENT, the IPC cluster shall activate COOLANT TEMP FAIL.V1 on the display.

IND_ROW | COOLANT TEMP FAIL.V1 | When T_COOLANT_FailSts == PRESENT | Yes - Check Engine Coolant Temperature Ga

[REQ_VF104_IND] When CAN node timeout > T_COOLANT_TIMEOUT, the IPC cluster shall activate COOLANT TEMP RECOVERY.V1 on the d

IND_ROW | COOLANT TEMP RECOVERY.V1 | When CAN node timeout > T_COOLANT_TIMEOUT | Yes - COOLANT TEMP System Rec

13.25 Detailed Functional Requirements & State Logic · VF104 (Part 23/27)

[REQ_VF104_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.26 Detailed Functional Requirements & State Logic · VF104 (Part 24/27)

[REQ_VF104_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.27 Detailed Functional Requirements & State Logic · VF104 (Part 25/27)

[REQ_VF104_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

13.14 Configuration Parameters

13.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF104_01 | T_COOLANT_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | P

PAR_ROW | PAR_VF104_02 | T_COOLANT_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filteri

PAR_ROW | PAR_VF104_03 | CFG_VF104_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF104_04 | T_BCM_VF104_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

13.29 Detailed Functional Requirements & State Logic · VF104 (Part 27/27)

[REQ_VF104_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF104_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF104_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF104_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF104_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF104_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF104_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF104_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF104_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF104_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF104_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF104_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF104_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF104_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF104_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF104_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF104_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF104_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF104_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF104_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF104_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF104_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF104_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF104_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF104_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF104_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF104_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14 VF105 - Total and Partial Odometer Management (VF105_V1_PJ3U)

Document Code: VF105_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

14.1 Purpose and Functional Overview

[REQ_VF105_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF105 - Total and Partial Odometer Management.

14.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF105_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF105_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF105_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF105_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF105_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF105_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF105_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF105_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF105_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF105_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF105_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF105_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF105_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF105_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF105_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF105_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF105_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

14.2 Detailed Functional Requirements & State Logic · VF105 (Part 2/27)

[REQ_VF105_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.3 Detailed Functional Requirements & State Logic · VF105 (Part 3/27)

[REQ_VF105_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.4 Detailed Functional Requirements & State Logic · VF105 (Part 4/27)

[REQ_VF105_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.5 Detailed Functional Requirements & State Logic · VF105 (Part 5/27)

[REQ_VF105_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.6 Detailed Functional Requirements & State Logic · VF105 (Part 6/27)

[REQ_VF105_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.7 Detailed Functional Requirements & State Logic · VF105 (Part 7/27)

[REQ_VF105_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.8 Detailed Functional Requirements & State Logic · VF105 (Part 8/27)

[REQ_VF105_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.9 Detailed Functional Requirements & State Logic · VF105 (Part 9/27)

[REQ_VF105_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.10 Detailed Functional Requirements & State Logic · VF105 (Part 10/27)

[REQ_VF105_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.11 Detailed Functional Requirements & State Logic · VF105 (Part 11/27)

[REQ_VF105_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.14 Detailed Functional Requirements & State Logic · VF105 (Part 12/27)

[REQ_VF105_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.15 Detailed Functional Requirements & State Logic · VF105 (Part 13/27)

[REQ_VF105_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.16 Detailed Functional Requirements & State Logic · VF105 (Part 14/27)

[REQ_VF105_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.17 Detailed Functional Requirements & State Logic · VF105 (Part 15/27)

[REQ_VF105_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.18 Detailed Functional Requirements & State Logic · VF105 (Part 16/27)

[REQ_VF105_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.19 Detailed Functional Requirements & State Logic · VF105 (Part 17/27)

[REQ_VF105_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.20 Detailed Functional Requirements & State Logic · VF105 (Part 18/27)

[REQ_VF105_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.21 Detailed Functional Requirements & State Logic · VF105 (Part 19/27)

[REQ_VF105_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.22 Detailed Functional Requirements & State Logic · VF105 (Part 20/27)

[REQ_VF105_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.23 Detailed Functional Requirements & State Logic · VF105 (Part 21/27)

[REQ_VF105_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.12 Indication Management

[REQ_VF105_IND] When D_ODO_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate ODOMETER ACTIVE.V1 on the display.

IND_ROW | ODOMETER ACTIVE.V1 | When D_ODO_Sts == ACTIVE on CAN-FD network | No (Standard ODOMETER Telltale) |

[REQ_VF105_IND] When D_ODO_FailSts == PRESENT, the IPC cluster shall activate ODOMETER FAIL.V1 on the display.

IND_ROW | ODOMETER FAIL.V1 | When D_ODO_FailSts == PRESENT | Yes - Check Total and Partial Odometer Management

[REQ_VF105_IND] When CAN node timeout > D_ODO_TIMEOUT, the IPC cluster shall activate ODOMETER RECOVERY.V1 on the display.

IND_ROW | ODOMETER RECOVERY.V1 | When CAN node timeout > D_ODO_TIMEOUT | Yes - ODOMETER System Recovery | ODOM

14.25 Detailed Functional Requirements & State Logic · VF105 (Part 23/27)

[REQ_VF105_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.26 Detailed Functional Requirements & State Logic · VF105 (Part 24/27)

[REQ_VF105_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.27 Detailed Functional Requirements & State Logic · VF105 (Part 25/27)

[REQ_VF105_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

14.14 Configuration Parameters

14.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF105_01 | D_ODO_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Prima

PAR_ROW | PAR_VF105_02 | D_ODO_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filtering |

PAR_ROW | PAR_VF105_03 | CFG_VF105_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF105_04 | T_BCM_VF105_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

14.29 Detailed Functional Requirements & State Logic · VF105 (Part 27/27)

[REQ_VF105_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF105_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF105_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF105_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF105_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF105_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF105_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF105_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF105_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF105_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF105_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF105_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF105_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF105_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF105_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF105_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF105_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF105_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF105_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF105_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF105_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF105_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF105_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF105_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF105_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF105_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF105_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15 VF106 - Trip Computer A and B Calculation (VF106_V1_PJ3U)

Document Code: VF106_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

15.1 Purpose and Functional Overview

[REQ_VF106_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF106 - Trip Computer A and B Calculation.

15.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF106_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF106_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF106_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF106_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF106_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF106_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF106_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF106_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF106_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF106_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF106_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF106_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF106_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF106_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF106_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF106_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF106_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

15.2 Detailed Functional Requirements & State Logic · VF106 (Part 2/27)

[REQ_VF106_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.3 Detailed Functional Requirements & State Logic · VF106 (Part 3/27)

[REQ_VF106_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.4 Detailed Functional Requirements & State Logic · VF106 (Part 4/27)

[REQ_VF106_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.5 Detailed Functional Requirements & State Logic · VF106 (Part 5/27)

[REQ_VF106_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.6 Detailed Functional Requirements & State Logic · VF106 (Part 6/27)

[REQ_VF106_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.7 Detailed Functional Requirements & State Logic · VF106 (Part 7/27)

[REQ_VF106_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.8 Detailed Functional Requirements & State Logic · VF106 (Part 8/27)

[REQ_VF106_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.9 Detailed Functional Requirements & State Logic · VF106 (Part 9/27)

[REQ_VF106_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.10 Detailed Functional Requirements & State Logic · VF106 (Part 10/27)

[REQ_VF106_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.11 Detailed Functional Requirements & State Logic · VF106 (Part 11/27)

[REQ_VF106_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.14 Detailed Functional Requirements & State Logic · VF106 (Part 12/27)

[REQ_VF106_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.15 Detailed Functional Requirements & State Logic · VF106 (Part 13/27)

[REQ_VF106_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.16 Detailed Functional Requirements & State Logic · VF106 (Part 14/27)

[REQ_VF106_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.17 Detailed Functional Requirements & State Logic · VF106 (Part 15/27)

[REQ_VF106_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.18 Detailed Functional Requirements & State Logic · VF106 (Part 16/27)

[REQ_VF106_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.19 Detailed Functional Requirements & State Logic · VF106 (Part 17/27)

[REQ_VF106_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.20 Detailed Functional Requirements & State Logic · VF106 (Part 18/27)

[REQ_VF106_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.21 Detailed Functional Requirements & State Logic · VF106 (Part 19/27)

[REQ_VF106_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.22 Detailed Functional Requirements & State Logic · VF106 (Part 20/27)

[REQ_VF106_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.23 Detailed Functional Requirements & State Logic · VF106 (Part 21/27)

[REQ_VF106_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.12 Indication Management

[REQ_VF106_IND] When T_TRIP_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate TRIP COMPUTER ACTIVE.V1 on the displa

IND_ROW | TRIP COMPUTER ACTIVE.V1 | When T_TRIP_Sts == ACTIVE on CAN-FD network | No (Standard TRIP COMPUTER T

[REQ_VF106_IND] When T_TRIP_FailSts == PRESENT, the IPC cluster shall activate TRIP COMPUTER FAIL.V1 on the display.

IND_ROW | TRIP COMPUTER FAIL.V1 | When T_TRIP_FailSts == PRESENT | Yes - Check Trip Computer A and B Calculati

[REQ_VF106_IND] When CAN node timeout > T_TRIP_TIMEOUT, the IPC cluster shall activate TRIP COMPUTER RECOVERY.V1 on the displa

IND_ROW | TRIP COMPUTER RECOVERY.V1 | When CAN node timeout > T_TRIP_TIMEOUT | Yes - TRIP COMPUTER System Reco

15.25 Detailed Functional Requirements & State Logic · VF106 (Part 23/27)

[REQ_VF106_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.26 Detailed Functional Requirements & State Logic · VF106 (Part 24/27)

[REQ_VF106_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.27 Detailed Functional Requirements & State Logic · VF106 (Part 25/27)

[REQ_VF106_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

15.14 Configuration Parameters

15.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF106_01 | T_TRIP_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Prim

PAR_ROW | PAR_VF106_02 | T_TRIP_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filtering

PAR_ROW | PAR_VF106_03 | CFG_VF106_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF106_04 | T_BCM_VF106_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

15.29 Detailed Functional Requirements & State Logic · VF106 (Part 27/27)

[REQ_VF106_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF106_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF106_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF106_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF106_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF106_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF106_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF106_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF106_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF106_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF106_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF106_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF106_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF106_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF106_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF106_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF106_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF106_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF106_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF106_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF106_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF106_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF106_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF106_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF106_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF106_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF106_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16 VF107 - Gear Shift Indicator (GSI) Management (VF107_V1_PJ3U)

Document Code: VF107_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

16.1 Purpose and Functional Overview

[REQ_VF107_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF107 - Gear Shift Indicator (GSI) Management.

16.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF107_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF107_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF107_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF107_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF107_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF107_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF107_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF107_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF107_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF107_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF107_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF107_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF107_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF107_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF107_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF107_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF107_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

16.2 Detailed Functional Requirements & State Logic · VF107 (Part 2/27)

[REQ_VF107_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.3 Detailed Functional Requirements & State Logic · VF107 (Part 3/27)

[REQ_VF107_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.4 Detailed Functional Requirements & State Logic · VF107 (Part 4/27)

[REQ_VF107_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.5 Detailed Functional Requirements & State Logic · VF107 (Part 5/27)

[REQ_VF107_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.6 Detailed Functional Requirements & State Logic · VF107 (Part 6/27)

[REQ_VF107_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.7 Detailed Functional Requirements & State Logic · VF107 (Part 7/27)

[REQ_VF107_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.8 Detailed Functional Requirements & State Logic · VF107 (Part 8/27)

[REQ_VF107_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.9 Detailed Functional Requirements & State Logic · VF107 (Part 9/27)

[REQ_VF107_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.10 Detailed Functional Requirements & State Logic · VF107 (Part 10/27)

[REQ_VF107_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.11 Detailed Functional Requirements & State Logic · VF107 (Part 11/27)

[REQ_VF107_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.14 Detailed Functional Requirements & State Logic · VF107 (Part 12/27)

[REQ_VF107_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.15 Detailed Functional Requirements & State Logic · VF107 (Part 13/27)

[REQ_VF107_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.16 Detailed Functional Requirements & State Logic · VF107 (Part 14/27)

[REQ_VF107_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.17 Detailed Functional Requirements & State Logic · VF107 (Part 15/27)

[REQ_VF107_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.18 Detailed Functional Requirements & State Logic · VF107 (Part 16/27)

[REQ_VF107_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.19 Detailed Functional Requirements & State Logic · VF107 (Part 17/27)

[REQ_VF107_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.20 Detailed Functional Requirements & State Logic · VF107 (Part 18/27)

[REQ_VF107_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.21 Detailed Functional Requirements & State Logic · VF107 (Part 19/27)

[REQ_VF107_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.22 Detailed Functional Requirements & State Logic · VF107 (Part 20/27)

[REQ_VF107_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.23 Detailed Functional Requirements & State Logic · VF107 (Part 21/27)

[REQ_VF107_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.12 Indication Management

[REQ_VF107_IND] When N_GSI_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate GEAR SHIFT ACTIVE.V1 on the display.

IND_ROW | GEAR SHIFT ACTIVE.V1 | When N_GSI_Sts == ACTIVE on CAN-FD network | No (Standard GEAR SHIFT Telltale

[REQ_VF107_IND] When N_GSI_FailSts == PRESENT, the IPC cluster shall activate GEAR SHIFT FAIL.V1 on the display.

IND_ROW | GEAR SHIFT FAIL.V1 | When N_GSI_FailSts == PRESENT | Yes - Check Gear Shift Indicator (GSI) Manageme

[REQ_VF107_IND] When CAN node timeout > N_GSI_TIMEOUT, the IPC cluster shall activate GEAR SHIFT RECOVERY.V1 on the display.

IND_ROW | GEAR SHIFT RECOVERY.V1 | When CAN node timeout > N_GSI_TIMEOUT | Yes - GEAR SHIFT System Recovery |

16.25 Detailed Functional Requirements & State Logic · VF107 (Part 23/27)

[REQ_VF107_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.26 Detailed Functional Requirements & State Logic · VF107 (Part 24/27)

[REQ_VF107_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.27 Detailed Functional Requirements & State Logic · VF107 (Part 25/27)

[REQ_VF107_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

16.14 Configuration Parameters

16.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF107_01 | N_GSI_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Prima

PAR_ROW | PAR_VF107_02 | N_GSI_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filtering |

PAR_ROW | PAR_VF107_03 | CFG_VF107_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF107_04 | T_BCM_VF107_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

16.29 Detailed Functional Requirements & State Logic · VF107 (Part 27/27)

[REQ_VF107_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF107_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF107_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF107_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF107_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF107_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF107_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF107_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF107_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF107_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF107_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF107_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF107_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF107_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF107_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF107_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF107_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF107_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF107_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF107_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF107_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF107_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF107_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF107_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF107_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF107_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF107_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17 VF108 - Automatic Transmission Gear Display (VF108_V1_PJ3U)

Document Code: VF108_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

17.1 Purpose and Functional Overview

[REQ_VF108_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF108 - Automatic Transmission Gear Display.

17.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF108_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF108_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF108_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF108_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF108_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF108_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF108_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF108_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF108_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF108_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF108_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF108_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF108_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF108_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF108_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF108_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF108_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

17.2 Detailed Functional Requirements & State Logic · VF108 (Part 2/27)

[REQ_VF108_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.3 Detailed Functional Requirements & State Logic · VF108 (Part 3/27)

[REQ_VF108_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.4 Detailed Functional Requirements & State Logic · VF108 (Part 4/27)

[REQ_VF108_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.5 Detailed Functional Requirements & State Logic · VF108 (Part 5/27)

[REQ_VF108_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.6 Detailed Functional Requirements & State Logic · VF108 (Part 6/27)

[REQ_VF108_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.7 Detailed Functional Requirements & State Logic · VF108 (Part 7/27)

[REQ_VF108_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.8 Detailed Functional Requirements & State Logic · VF108 (Part 8/27)

[REQ_VF108_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.9 Detailed Functional Requirements & State Logic · VF108 (Part 9/27)

[REQ_VF108_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.10 Detailed Functional Requirements & State Logic · VF108 (Part 10/27)

[REQ_VF108_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.11 Detailed Functional Requirements & State Logic · VF108 (Part 11/27)

[REQ_VF108_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.14 Detailed Functional Requirements & State Logic · VF108 (Part 12/27)

[REQ_VF108_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.15 Detailed Functional Requirements & State Logic · VF108 (Part 13/27)

[REQ_VF108_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.16 Detailed Functional Requirements & State Logic · VF108 (Part 14/27)

[REQ_VF108_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.17 Detailed Functional Requirements & State Logic · VF108 (Part 15/27)

[REQ_VF108_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.18 Detailed Functional Requirements & State Logic · VF108 (Part 16/27)

[REQ_VF108_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.19 Detailed Functional Requirements & State Logic · VF108 (Part 17/27)

[REQ_VF108_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.20 Detailed Functional Requirements & State Logic · VF108 (Part 18/27)

[REQ_VF108_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.21 Detailed Functional Requirements & State Logic · VF108 (Part 19/27)

[REQ_VF108_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.22 Detailed Functional Requirements & State Logic · VF108 (Part 20/27)

[REQ_VF108_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.23 Detailed Functional Requirements & State Logic · VF108 (Part 21/27)

[REQ_VF108_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.12 Indication Management

[REQ_VF108_IND] When T_AT_DISPLAY_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate AT GEAR ACTIVE.V1 on the displa

IND_ROW | AT GEAR ACTIVE.V1 | When T_AT_DISPLAY_Sts == ACTIVE on CAN-FD network | No (Standard AT GEAR Telltal

[REQ_VF108_IND] When T_AT_DISPLAY_FailSts == PRESENT, the IPC cluster shall activate AT GEAR FAIL.V1 on the display.

IND_ROW | AT GEAR FAIL.V1 | When T_AT_DISPLAY_FailSts == PRESENT | Yes - Check Automatic Transmission Gear Dis

[REQ_VF108_IND] When CAN node timeout > T_AT_DISPLAY_TIMEOUT, the IPC cluster shall activate AT GEAR RECOVERY.V1 on the displa

IND_ROW | AT GEAR RECOVERY.V1 | When CAN node timeout > T_AT_DISPLAY_TIMEOUT | Yes - AT GEAR System Recovery |

17.25 Detailed Functional Requirements & State Logic · VF108 (Part 23/27)

[REQ_VF108_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.26 Detailed Functional Requirements & State Logic · VF108 (Part 24/27)

[REQ_VF108_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.27 Detailed Functional Requirements & State Logic · VF108 (Part 25/27)

[REQ_VF108_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

17.14 Configuration Parameters

17.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | - | - | - | - | - | - | - | - | - | - | -

17.29 Detailed Functional Requirements & State Logic · VF108 (Part 27/27)

[REQ_VF108_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF108_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF108_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF108_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF108_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF108_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF108_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF108_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF108_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF108_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF108_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF108_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF108_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF108_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF108_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF108_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF108_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF108_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF108_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF108_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF108_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF108_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF108_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF108_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF108_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF108_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF108_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18 VF109 - Stop and Start System HMI Management (VF109_V1_PJ3U)

Document Code: VF109_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

18.1 Purpose and Functional Overview

[REQ_VF109_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF109 - Stop and Start System HMI Management.

18.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF109_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF109_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF109_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF109_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF109_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF109_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF109_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF109_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF109_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF109_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF109_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF109_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF109_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF109_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF109_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF109_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF109_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

18.2 Detailed Functional Requirements & State Logic · VF109 (Part 2/27)

[REQ_VF109_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.3 Detailed Functional Requirements & State Logic · VF109 (Part 3/27)

[REQ_VF109_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.4 Detailed Functional Requirements & State Logic · VF109 (Part 4/27)

[REQ_VF109_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.5 Detailed Functional Requirements & State Logic · VF109 (Part 5/27)

[REQ_VF109_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.6 Detailed Functional Requirements & State Logic · VF109 (Part 6/27)

[REQ_VF109_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.7 Detailed Functional Requirements & State Logic · VF109 (Part 7/27)

[REQ_VF109_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.8 Detailed Functional Requirements & State Logic · VF109 (Part 8/27)

[REQ_VF109_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.9 Detailed Functional Requirements & State Logic · VF109 (Part 9/27)

[REQ_VF109_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.10 Detailed Functional Requirements & State Logic · VF109 (Part 10/27)

[REQ_VF109_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.11 Detailed Functional Requirements & State Logic · VF109 (Part 11/27)

[REQ_VF109_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.14 Detailed Functional Requirements & State Logic · VF109 (Part 12/27)

[REQ_VF109_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.15 Detailed Functional Requirements & State Logic · VF109 (Part 13/27)

[REQ_VF109_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.16 Detailed Functional Requirements & State Logic · VF109 (Part 14/27)

[REQ_VF109_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.17 Detailed Functional Requirements & State Logic · VF109 (Part 15/27)

[REQ_VF109_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.18 Detailed Functional Requirements & State Logic · VF109 (Part 16/27)

[REQ_VF109_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.19 Detailed Functional Requirements & State Logic · VF109 (Part 17/27)

[REQ_VF109_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.20 Detailed Functional Requirements & State Logic · VF109 (Part 18/27)

[REQ_VF109_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.21 Detailed Functional Requirements & State Logic · VF109 (Part 19/27)

[REQ_VF109_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.22 Detailed Functional Requirements & State Logic · VF109 (Part 20/27)

[REQ_VF109_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.23 Detailed Functional Requirements & State Logic · VF109 (Part 21/27)

[REQ_VF109_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.12 Indication Management

[REQ_VF109_IND] When T_SS_DELAY_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate STOP START ACTIVE.V1 on the disp

IND_ROW | STOP START ACTIVE.V1 | When T_SS_DELAY_Sts == ACTIVE on CAN-FD network | No (Standard STOP START Tel

[REQ_VF109_IND] When T_SS_DELAY_FailSts == PRESENT, the IPC cluster shall activate STOP START FAIL.V1 on the display.

IND_ROW | STOP START FAIL.V1 | When T_SS_DELAY_FailSts == PRESENT | Yes - Check Stop and Start System HMI Mana

[REQ_VF109_IND] When CAN node timeout > T_SS_DELAY_TIMEOUT, the IPC cluster shall activate STOP START RECOVERY.V1 on the disp

IND_ROW | STOP START RECOVERY.V1 | When CAN node timeout > T_SS_DELAY_TIMEOUT | Yes - STOP START System Recove

18.25 Detailed Functional Requirements & State Logic · VF109 (Part 23/27)

[REQ_VF109_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.26 Detailed Functional Requirements & State Logic · VF109 (Part 24/27)

[REQ_VF109_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.27 Detailed Functional Requirements & State Logic · VF109 (Part 25/27)

[REQ_VF109_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

18.14 Configuration Parameters

18.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF109_01 | T_SS_DELAY_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF109_02 | T_SS_DELAY_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filter

PAR_ROW | PAR_VF109_03 | CFG_VF109_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF109_04 | T_BCM_VF109_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

18.29 Detailed Functional Requirements & State Logic · VF109 (Part 27/27)

[REQ_VF109_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF109_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF109_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF109_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF109_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF109_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF109_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF109_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF109_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF109_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF109_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF109_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF109_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF109_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF109_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF109_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF109_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF109_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF109_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF109_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF109_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF109_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF109_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF109_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF109_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF109_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF109_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19 VF110 - Cruise Control (CC) HMI Indication (VF110_V1_PJ3U)

Document Code: VF110_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

19.1 Purpose and Functional Overview

[REQ_VF110_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF110 - Cruise Control (CC) HMI Indication.

19.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF110_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF110_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF110_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF110_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF110_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF110_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF110_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF110_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF110_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF110_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF110_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF110_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF110_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF110_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF110_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF110_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF110_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

19.2 Detailed Functional Requirements & State Logic · VF110 (Part 2/27)

[REQ_VF110_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.3 Detailed Functional Requirements & State Logic · VF110 (Part 3/27)

[REQ_VF110_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.4 Detailed Functional Requirements & State Logic · VF110 (Part 4/27)

[REQ_VF110_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.5 Detailed Functional Requirements & State Logic · VF110 (Part 5/27)

[REQ_VF110_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.6 Detailed Functional Requirements & State Logic · VF110 (Part 6/27)

[REQ_VF110_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.7 Detailed Functional Requirements & State Logic · VF110 (Part 7/27)

[REQ_VF110_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.8 Detailed Functional Requirements & State Logic · VF110 (Part 8/27)

[REQ_VF110_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.9 Detailed Functional Requirements & State Logic · VF110 (Part 9/27)

[REQ_VF110_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.10 Detailed Functional Requirements & State Logic · VF110 (Part 10/27)

[REQ_VF110_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.11 Detailed Functional Requirements & State Logic · VF110 (Part 11/27)

[REQ_VF110_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.14 Detailed Functional Requirements & State Logic · VF110 (Part 12/27)

[REQ_VF110_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.15 Detailed Functional Requirements & State Logic · VF110 (Part 13/27)

[REQ_VF110_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.16 Detailed Functional Requirements & State Logic · VF110 (Part 14/27)

[REQ_VF110_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.17 Detailed Functional Requirements & State Logic · VF110 (Part 15/27)

[REQ_VF110_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.18 Detailed Functional Requirements & State Logic · VF110 (Part 16/27)

[REQ_VF110_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.19 Detailed Functional Requirements & State Logic · VF110 (Part 17/27)

[REQ_VF110_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.20 Detailed Functional Requirements & State Logic · VF110 (Part 18/27)

[REQ_VF110_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.21 Detailed Functional Requirements & State Logic · VF110 (Part 19/27)

[REQ_VF110_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.22 Detailed Functional Requirements & State Logic · VF110 (Part 20/27)

[REQ_VF110_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.23 Detailed Functional Requirements & State Logic · VF110 (Part 21/27)

[REQ_VF110_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.12 Indication Management

[REQ_VF110_IND] When V_CC_MIN_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate CRUISE CONTROL ACTIVE.V1 on the d

IND_ROW | CRUISE CONTROL ACTIVE.V1 | When V_CC_MIN_Sts == ACTIVE on CAN-FD network | No (Standard CRUISE CONTR

[REQ_VF110_IND] When V_CC_MIN_FailSts == PRESENT, the IPC cluster shall activate CRUISE CONTROL FAIL.V1 on the display.

IND_ROW | CRUISE CONTROL FAIL.V1 | When V_CC_MIN_FailSts == PRESENT | Yes - Check Cruise Control (CC) HMI Indi

[REQ_VF110_IND] When CAN node timeout > V_CC_MIN_TIMEOUT, the IPC cluster shall activate CRUISE CONTROL RECOVERY.V1 on the d

IND_ROW | CRUISE CONTROL RECOVERY.V1 | When CAN node timeout > V_CC_MIN_TIMEOUT | Yes - CRUISE CONTROL System

19.25 Detailed Functional Requirements & State Logic · VF110 (Part 23/27)

[REQ_VF110_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.26 Detailed Functional Requirements & State Logic · VF110 (Part 24/27)

[REQ_VF110_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.27 Detailed Functional Requirements & State Logic · VF110 (Part 25/27)

[REQ_VF110_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

19.14 Configuration Parameters

19.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF110_01 | V_CC_MIN_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Pr

PAR_ROW | PAR_VF110_02 | V_CC_MIN_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filterin

PAR_ROW | PAR_VF110_03 | CFG_VF110_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF110_04 | T_BCM_VF110_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

19.29 Detailed Functional Requirements & State Logic · VF110 (Part 27/27)

[REQ_VF110_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF110_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF110_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF110_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF110_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF110_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF110_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF110_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF110_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF110_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF110_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF110_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF110_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF110_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF110_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF110_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF110_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF110_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF110_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF110_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF110_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF110_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF110_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF110_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF110_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF110_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF110_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20 VF111 - Speed Limiter (SL) Visual and Acoustic Warning (VF111_V1_PJ3U)

Document Code: VF111_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

20.1 Purpose and Functional Overview

[REQ_VF111_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF111 - Speed Limiter (SL) Visual and Acoustic Warni

20.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF111_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF111_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF111_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF111_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF111_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF111_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF111_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF111_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF111_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF111_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF111_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF111_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF111_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF111_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF111_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF111_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF111_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

20.2 Detailed Functional Requirements & State Logic · VF111 (Part 2/27)

[REQ_VF111_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.3 Detailed Functional Requirements & State Logic · VF111 (Part 3/27)

[REQ_VF111_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.4 Detailed Functional Requirements & State Logic · VF111 (Part 4/27)

[REQ_VF111_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.5 Detailed Functional Requirements & State Logic · VF111 (Part 5/27)

[REQ_VF111_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.6 Detailed Functional Requirements & State Logic · VF111 (Part 6/27)

[REQ_VF111_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.7 Detailed Functional Requirements & State Logic · VF111 (Part 7/27)

[REQ_VF111_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.8 Detailed Functional Requirements & State Logic · VF111 (Part 8/27)

[REQ_VF111_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.9 Detailed Functional Requirements & State Logic · VF111 (Part 9/27)

[REQ_VF111_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.10 Detailed Functional Requirements & State Logic · VF111 (Part 10/27)

[REQ_VF111_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.11 Detailed Functional Requirements & State Logic · VF111 (Part 11/27)

[REQ_VF111_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.14 Detailed Functional Requirements & State Logic · VF111 (Part 12/27)

[REQ_VF111_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.15 Detailed Functional Requirements & State Logic · VF111 (Part 13/27)

[REQ_VF111_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.16 Detailed Functional Requirements & State Logic · VF111 (Part 14/27)

[REQ_VF111_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.17 Detailed Functional Requirements & State Logic · VF111 (Part 15/27)

[REQ_VF111_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.18 Detailed Functional Requirements & State Logic · VF111 (Part 16/27)

[REQ_VF111_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.19 Detailed Functional Requirements & State Logic · VF111 (Part 17/27)

[REQ_VF111_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.20 Detailed Functional Requirements & State Logic · VF111 (Part 18/27)

[REQ_VF111_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.21 Detailed Functional Requirements & State Logic · VF111 (Part 19/27)

[REQ_VF111_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.22 Detailed Functional Requirements & State Logic · VF111 (Part 20/27)

[REQ_VF111_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.23 Detailed Functional Requirements & State Logic · VF111 (Part 21/27)

[REQ_VF111_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.12 Indication Management

[REQ_VF111_IND] When V_SL_HYST_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate SPEED LIMITER ACTIVE.V1 on the dis

IND_ROW | SPEED LIMITER ACTIVE.V1 | When V_SL_HYST_Sts == ACTIVE on CAN-FD network | No (Standard SPEED LIMITE

[REQ_VF111_IND] When V_SL_HYST_FailSts == PRESENT, the IPC cluster shall activate SPEED LIMITER FAIL.V1 on the display.

IND_ROW | SPEED LIMITER FAIL.V1 | When V_SL_HYST_FailSts == PRESENT | Yes - Check Speed Limiter (SL) Visual an

[REQ_VF111_IND] When CAN node timeout > V_SL_HYST_TIMEOUT, the IPC cluster shall activate SPEED LIMITER RECOVERY.V1 on the dis

IND_ROW | SPEED LIMITER RECOVERY.V1 | When CAN node timeout > V_SL_HYST_TIMEOUT | Yes - SPEED LIMITER System R

20.25 Detailed Functional Requirements & State Logic · VF111 (Part 23/27)

[REQ_VF111_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.26 Detailed Functional Requirements & State Logic · VF111 (Part 24/27)

[REQ_VF111_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.27 Detailed Functional Requirements & State Logic · VF111 (Part 25/27)

[REQ_VF111_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

20.14 Configuration Parameters

20.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF111_01 | V_SL_HYST_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | P

PAR_ROW | PAR_VF111_02 | V_SL_HYST_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filteri

PAR_ROW | PAR_VF111_03 | CFG_VF111_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF111_04 | T_BCM_VF111_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

20.29 Detailed Functional Requirements & State Logic · VF111 (Part 27/27)

[REQ_VF111_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF111_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF111_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF111_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF111_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF111_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF111_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF111_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF111_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF111_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF111_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF111_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF111_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF111_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF111_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF111_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF111_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF111_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF111_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF111_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF111_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF111_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF111_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF111_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF111_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF111_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF111_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21 VF112 - Adaptive Cruise Control (ACC) Cluster HMI (VF112_V1_PJ3U)

Document Code: VF112_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

21.1 Purpose and Functional Overview

[REQ_VF112_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF112 - Adaptive Cruise Control (ACC) Cluster HMI.

21.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF112_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF112_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF112_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF112_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF112_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF112_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF112_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF112_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF112_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF112_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF112_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF112_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF112_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF112_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF112_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF112_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF112_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

21.2 Detailed Functional Requirements & State Logic · VF112 (Part 2/27)

[REQ_VF112_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.3 Detailed Functional Requirements & State Logic · VF112 (Part 3/27)

[REQ_VF112_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.4 Detailed Functional Requirements & State Logic · VF112 (Part 4/27)

[REQ_VF112_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.5 Detailed Functional Requirements & State Logic · VF112 (Part 5/27)

[REQ_VF112_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.6 Detailed Functional Requirements & State Logic · VF112 (Part 6/27)

[REQ_VF112_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.7 Detailed Functional Requirements & State Logic · VF112 (Part 7/27)

[REQ_VF112_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.8 Detailed Functional Requirements & State Logic · VF112 (Part 8/27)

[REQ_VF112_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.9 Detailed Functional Requirements & State Logic · VF112 (Part 9/27)

[REQ_VF112_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.10 Detailed Functional Requirements & State Logic · VF112 (Part 10/27)

[REQ_VF112_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.11 Detailed Functional Requirements & State Logic · VF112 (Part 11/27)

[REQ_VF112_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.14 Detailed Functional Requirements & State Logic · VF112 (Part 12/27)

[REQ_VF112_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.15 Detailed Functional Requirements & State Logic · VF112 (Part 13/27)

[REQ_VF112_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.16 Detailed Functional Requirements & State Logic · VF112 (Part 14/27)

[REQ_VF112_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.17 Detailed Functional Requirements & State Logic · VF112 (Part 15/27)

[REQ_VF112_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.18 Detailed Functional Requirements & State Logic · VF112 (Part 16/27)

[REQ_VF112_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.19 Detailed Functional Requirements & State Logic · VF112 (Part 17/27)

[REQ_VF112_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.20 Detailed Functional Requirements & State Logic · VF112 (Part 18/27)

[REQ_VF112_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.21 Detailed Functional Requirements & State Logic · VF112 (Part 19/27)

[REQ_VF112_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.22 Detailed Functional Requirements & State Logic · VF112 (Part 20/27)

[REQ_VF112_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.23 Detailed Functional Requirements & State Logic · VF112 (Part 21/27)

[REQ_VF112_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.12 Indication Management

[REQ_VF112_IND] When D_ACC_HEADWAY_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate ACC SYSTEM ACTIVE.V1 on th

IND_ROW | ACC SYSTEM ACTIVE.V1 | When D_ACC_HEADWAY_Sts == ACTIVE on CAN-FD network | No (Standard ACC SYSTEM

[REQ_VF112_IND] When D_ACC_HEADWAY_FailSts == PRESENT, the IPC cluster shall activate ACC SYSTEM FAIL.V1 on the display.

IND_ROW | ACC SYSTEM FAIL.V1 | When D_ACC_HEADWAY_FailSts == PRESENT | Yes - Check Adaptive Cruise Control (AC

[REQ_VF112_IND] When CAN node timeout > D_ACC_HEADWAY_TIMEOUT, the IPC cluster shall activate ACC SYSTEM RECOVERY.V1 on th

IND_ROW | ACC SYSTEM RECOVERY.V1 | When CAN node timeout > D_ACC_HEADWAY_TIMEOUT | Yes - ACC SYSTEM System Rec

21.25 Detailed Functional Requirements & State Logic · VF112 (Part 23/27)

[REQ_VF112_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.26 Detailed Functional Requirements & State Logic · VF112 (Part 24/27)

[REQ_VF112_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.27 Detailed Functional Requirements & State Logic · VF112 (Part 25/27)

[REQ_VF112_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

21.14 Configuration Parameters

21.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF112_01 | D_ACC_HEADWAY_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration

PAR_ROW | PAR_VF112_02 | D_ACC_HEADWAY_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Fil

PAR_ROW | PAR_VF112_03 | CFG_VF112_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF112_04 | T_BCM_VF112_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

21.29 Detailed Functional Requirements & State Logic · VF112 (Part 27/27)

[REQ_VF112_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF112_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF112_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF112_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF112_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF112_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF112_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF112_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF112_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF112_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF112_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF112_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF112_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF112_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF112_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF112_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF112_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF112_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF112_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF112_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF112_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF112_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF112_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF112_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF112_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF112_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF112_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22 VF113 - Lane Departure Warning (LDW) & LKA HMI (VF113_V1_PJ3U)

Document Code: VF113_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

22.1 Purpose and Functional Overview

[REQ_VF113_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF113 - Lane Departure Warning (LDW) & LKA HMI.

22.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF113_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF113_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF113_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF113_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF113_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF113_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF113_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF113_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF113_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF113_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF113_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF113_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF113_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF113_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF113_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF113_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF113_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

22.2 Detailed Functional Requirements & State Logic · VF113 (Part 2/27)

[REQ_VF113_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.3 Detailed Functional Requirements & State Logic · VF113 (Part 3/27)

[REQ_VF113_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.4 Detailed Functional Requirements & State Logic · VF113 (Part 4/27)

[REQ_VF113_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.5 Detailed Functional Requirements & State Logic · VF113 (Part 5/27)

[REQ_VF113_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.6 Detailed Functional Requirements & State Logic · VF113 (Part 6/27)

[REQ_VF113_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.7 Detailed Functional Requirements & State Logic · VF113 (Part 7/27)

[REQ_VF113_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.8 Detailed Functional Requirements & State Logic · VF113 (Part 8/27)

[REQ_VF113_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.9 Detailed Functional Requirements & State Logic · VF113 (Part 9/27)

[REQ_VF113_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.10 Detailed Functional Requirements & State Logic · VF113 (Part 10/27)

[REQ_VF113_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.11 Detailed Functional Requirements & State Logic · VF113 (Part 11/27)

[REQ_VF113_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.14 Detailed Functional Requirements & State Logic · VF113 (Part 12/27)

[REQ_VF113_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.15 Detailed Functional Requirements & State Logic · VF113 (Part 13/27)

[REQ_VF113_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.16 Detailed Functional Requirements & State Logic · VF113 (Part 14/27)

[REQ_VF113_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.17 Detailed Functional Requirements & State Logic · VF113 (Part 15/27)

[REQ_VF113_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.18 Detailed Functional Requirements & State Logic · VF113 (Part 16/27)

[REQ_VF113_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.19 Detailed Functional Requirements & State Logic · VF113 (Part 17/27)

[REQ_VF113_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.20 Detailed Functional Requirements & State Logic · VF113 (Part 18/27)

[REQ_VF113_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.21 Detailed Functional Requirements & State Logic · VF113 (Part 19/27)

[REQ_VF113_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.22 Detailed Functional Requirements & State Logic · VF113 (Part 20/27)

[REQ_VF113_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.23 Detailed Functional Requirements & State Logic · VF113 (Part 21/27)

[REQ_VF113_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.12 Indication Management

[REQ_VF113_IND] When V_LDW_ACT_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate LANE DEPARTURE ACTIVE.V1 on th

IND_ROW | LANE DEPARTURE ACTIVE.V1 | When V_LDW_ACT_Sts == ACTIVE on CAN-FD network | No (Standard LANE DEPART

[REQ_VF113_IND] When V_LDW_ACT_FailSts == PRESENT, the IPC cluster shall activate LANE DEPARTURE FAIL.V1 on the display.

IND_ROW | LANE DEPARTURE FAIL.V1 | When V_LDW_ACT_FailSts == PRESENT | Yes - Check Lane Departure Warning (LDW

[REQ_VF113_IND] When CAN node timeout > V_LDW_ACT_TIMEOUT, the IPC cluster shall activate LANE DEPARTURE RECOVERY.V1 on the

IND_ROW | LANE DEPARTURE RECOVERY.V1 | When CAN node timeout > V_LDW_ACT_TIMEOUT | Yes - LANE DEPARTURE System

22.25 Detailed Functional Requirements & State Logic · VF113 (Part 23/27)

[REQ_VF113_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.26 Detailed Functional Requirements & State Logic · VF113 (Part 24/27)

[REQ_VF113_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.27 Detailed Functional Requirements & State Logic · VF113 (Part 25/27)

[REQ_VF113_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

22.14 Configuration Parameters

22.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF113_01 | V_LDW_ACT_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | P

PAR_ROW | PAR_VF113_02 | V_LDW_ACT_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filteri

PAR_ROW | PAR_VF113_03 | CFG_VF113_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF113_04 | T_BCM_VF113_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

22.29 Detailed Functional Requirements & State Logic · VF113 (Part 27/27)

[REQ_VF113_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF113_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF113_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF113_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF113_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF113_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF113_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF113_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF113_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF113_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF113_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF113_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF113_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF113_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF113_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF113_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF113_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF113_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF113_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF113_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF113_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF113_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF113_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF113_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF113_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF113_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF113_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23 VF114 - Autonomous Emergency Braking (AEB) Warning (VF114_V1_PJ3U)

Document Code: VF114_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

23.1 Purpose and Functional Overview

[REQ_VF114_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF114 - Autonomous Emergency Braking (AEB) Warni

23.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF114_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF114_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF114_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF114_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF114_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF114_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF114_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF114_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF114_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF114_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF114_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF114_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF114_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF114_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF114_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF114_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF114_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

23.2 Detailed Functional Requirements & State Logic · VF114 (Part 2/27)

[REQ_VF114_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.3 Detailed Functional Requirements & State Logic · VF114 (Part 3/27)

[REQ_VF114_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.4 Detailed Functional Requirements & State Logic · VF114 (Part 4/27)

[REQ_VF114_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.5 Detailed Functional Requirements & State Logic · VF114 (Part 5/27)

[REQ_VF114_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.6 Detailed Functional Requirements & State Logic · VF114 (Part 6/27)

[REQ_VF114_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.7 Detailed Functional Requirements & State Logic · VF114 (Part 7/27)

[REQ_VF114_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.8 Detailed Functional Requirements & State Logic · VF114 (Part 8/27)

[REQ_VF114_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.9 Detailed Functional Requirements & State Logic · VF114 (Part 9/27)

[REQ_VF114_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.10 Detailed Functional Requirements & State Logic · VF114 (Part 10/27)

[REQ_VF114_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.11 Detailed Functional Requirements & State Logic · VF114 (Part 11/27)

[REQ_VF114_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.14 Detailed Functional Requirements & State Logic · VF114 (Part 12/27)

[REQ_VF114_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.15 Detailed Functional Requirements & State Logic · VF114 (Part 13/27)

[REQ_VF114_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.16 Detailed Functional Requirements & State Logic · VF114 (Part 14/27)

[REQ_VF114_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.17 Detailed Functional Requirements & State Logic · VF114 (Part 15/27)

[REQ_VF114_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.18 Detailed Functional Requirements & State Logic · VF114 (Part 16/27)

[REQ_VF114_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.19 Detailed Functional Requirements & State Logic · VF114 (Part 17/27)

[REQ_VF114_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.20 Detailed Functional Requirements & State Logic · VF114 (Part 18/27)

[REQ_VF114_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.21 Detailed Functional Requirements & State Logic · VF114 (Part 19/27)

[REQ_VF114_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.22 Detailed Functional Requirements & State Logic · VF114 (Part 20/27)

[REQ_VF114_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.23 Detailed Functional Requirements & State Logic · VF114 (Part 21/27)

[REQ_VF114_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.12 Indication Management

[REQ_VF114_IND] When T_AEB_POPUP_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate AEB COLLISION ACTIVE.V1 on the
IND_ROW | AEB COLLISION ACTIVE.V1 | When T_AEB_POPUP_Sts == ACTIVE on CAN-FD network | No (Standard AEB COLLIS

[REQ_VF114_IND] When T_AEB_POPUP_FailSts == PRESENT, the IPC cluster shall activate AEB COLLISION FAIL.V1 on the display.
IND_ROW | AEB COLLISION FAIL.V1 | When T_AEB_POPUP_FailSts == PRESENT | Yes - Check Autonomous Emergency Braki

[REQ_VF114_IND] When CAN node timeout > T_AEB_POPUP_TIMEOUT, the IPC cluster shall activate AEB COLLISION RECOVERY.V1 on the
IND_ROW | AEB COLLISION RECOVERY.V1 | When CAN node timeout > T_AEB_POPUP_TIMEOUT | Yes - AEB COLLISION System

23.25 Detailed Functional Requirements & State Logic · VF114 (Part 23/27)

[REQ_VF114_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.26 Detailed Functional Requirements & State Logic · VF114 (Part 24/27)

[REQ_VF114_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.27 Detailed Functional Requirements & State Logic · VF114 (Part 25/27)

[REQ_VF114_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

23.14 Configuration Parameters

23.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF114_01 | T_AEB_POPUP_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF114_02 | T_AEB_POPUP_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filte

PAR_ROW | PAR_VF114_03 | CFG_VF114_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF114_04 | T_BCM_VF114_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

23.29 Detailed Functional Requirements & State Logic · VF114 (Part 27/27)

[REQ_VF114_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF114_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF114_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF114_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF114_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF114_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF114_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF114_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF114_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF114_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF114_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF114_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF114_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF114_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF114_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF114_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF114_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF114_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF114_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF114_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF114_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF114_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF114_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF114_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF114_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF114_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF114_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24 VF115 - Blind Spot Monitoring (BSM) Indication (VF115_V1_PJ3U)

Document Code: VF115_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

24.1 Purpose and Functional Overview

[REQ_VF115_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF115 - Blind Spot Monitoring (BSM) Indication.

24.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF115_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF115_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF115_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF115_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF115_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF115_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF115_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF115_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF115_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF115_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF115_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF115_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF115_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF115_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF115_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF115_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF115_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

24.2 Detailed Functional Requirements & State Logic · VF115 (Part 2/27)

[REQ_VF115_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.3 Detailed Functional Requirements & State Logic · VF115 (Part 3/27)

[REQ_VF115_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.4 Detailed Functional Requirements & State Logic · VF115 (Part 4/27)

[REQ_VF115_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.5 Detailed Functional Requirements & State Logic · VF115 (Part 5/27)

[REQ_VF115_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.6 Detailed Functional Requirements & State Logic · VF115 (Part 6/27)

[REQ_VF115_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.7 Detailed Functional Requirements & State Logic · VF115 (Part 7/27)

[REQ_VF115_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.8 Detailed Functional Requirements & State Logic · VF115 (Part 8/27)

[REQ_VF115_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.9 Detailed Functional Requirements & State Logic · VF115 (Part 9/27)

[REQ_VF115_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.10 Detailed Functional Requirements & State Logic · VF115 (Part 10/27)

[REQ_VF115_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.11 Detailed Functional Requirements & State Logic · VF115 (Part 11/27)

[REQ_VF115_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.14 Detailed Functional Requirements & State Logic · VF115 (Part 12/27)

[REQ_VF115_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.15 Detailed Functional Requirements & State Logic · VF115 (Part 13/27)

[REQ_VF115_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.16 Detailed Functional Requirements & State Logic · VF115 (Part 14/27)

[REQ_VF115_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.17 Detailed Functional Requirements & State Logic · VF115 (Part 15/27)

[REQ_VF115_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.18 Detailed Functional Requirements & State Logic · VF115 (Part 16/27)

[REQ_VF115_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.19 Detailed Functional Requirements & State Logic · VF115 (Part 17/27)

[REQ_VF115_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.20 Detailed Functional Requirements & State Logic · VF115 (Part 18/27)

[REQ_VF115_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.21 Detailed Functional Requirements & State Logic · VF115 (Part 19/27)

[REQ_VF115_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.22 Detailed Functional Requirements & State Logic · VF115 (Part 20/27)

[REQ_VF115_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.23 Detailed Functional Requirements & State Logic · VF115 (Part 21/27)

[REQ_VF115_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.12 Indication Management

[REQ_VF115_IND] When V_BSM_MIN_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate BLIND SPOT ACTIVE.V1 on the displa

IND_ROW | BLIND SPOT ACTIVE.V1 | When V_BSM_MIN_Sts == ACTIVE on CAN-FD network | No (Standard BLIND SPOT Tell

[REQ_VF115_IND] When V_BSM_MIN_FailSts == PRESENT, the IPC cluster shall activate BLIND SPOT FAIL.V1 on the display.

IND_ROW | BLIND SPOT FAIL.V1 | When V_BSM_MIN_FailSts == PRESENT | Yes - Check Blind Spot Monitoring (BSM) Ind

[REQ_VF115_IND] When CAN node timeout > V_BSM_MIN_TIMEOUT, the IPC cluster shall activate BLIND SPOT RECOVERY.V1 on the displa

IND_ROW | BLIND SPOT RECOVERY.V1 | When CAN node timeout > V_BSM_MIN_TIMEOUT | Yes - BLIND SPOT System Recover

24.25 Detailed Functional Requirements & State Logic · VF115 (Part 23/27)

[REQ_VF115_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.26 Detailed Functional Requirements & State Logic · VF115 (Part 24/27)

[REQ_VF115_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.27 Detailed Functional Requirements & State Logic · VF115 (Part 25/27)

[REQ_VF115_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

24.14 Configuration Parameters

24.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF115_01 | V_BSM_MIN_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | P

PAR_ROW | PAR_VF115_02 | V_BSM_MIN_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filteri

PAR_ROW | PAR_VF115_03 | CFG_VF115_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF115_04 | T_BCM_VF115_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

24.29 Detailed Functional Requirements & State Logic · VF115 (Part 27/27)

[REQ_VF115_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF115_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF115_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF115_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF115_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF115_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF115_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF115_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF115_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF115_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF115_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF115_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF115_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF115_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF115_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF115_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF115_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF115_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF115_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF115_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF115_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF115_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF115_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF115_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF115_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF115_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF115_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25 VF116 - Driver Drowsiness Detection (DDD) Coffee Cup (VF116_V1_PJ3U)

Document Code: VF116_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

25.1 Purpose and Functional Overview

[REQ_VF116_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF116 - Driver Drowsiness Detection (DDD) Coffee Cu

25.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF116_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF116_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF116_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF116_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF116_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF116_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF116_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF116_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF116_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF116_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF116_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF116_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF116_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF116_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF116_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF116_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF116_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

25.2 Detailed Functional Requirements & State Logic · VF116 (Part 2/27)

[REQ_VF116_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.3 Detailed Functional Requirements & State Logic · VF116 (Part 3/27)

[REQ_VF116_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.4 Detailed Functional Requirements & State Logic · VF116 (Part 4/27)

[REQ_VF116_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.5 Detailed Functional Requirements & State Logic · VF116 (Part 5/27)

[REQ_VF116_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.6 Detailed Functional Requirements & State Logic · VF116 (Part 6/27)

[REQ_VF116_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.7 Detailed Functional Requirements & State Logic · VF116 (Part 7/27)

[REQ_VF116_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.8 Detailed Functional Requirements & State Logic · VF116 (Part 8/27)

[REQ_VF116_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.9 Detailed Functional Requirements & State Logic · VF116 (Part 9/27)

[REQ_VF116_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.10 Detailed Functional Requirements & State Logic · VF116 (Part 10/27)

[REQ_VF116_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.11 Detailed Functional Requirements & State Logic · VF116 (Part 11/27)

[REQ_VF116_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.14 Detailed Functional Requirements & State Logic · VF116 (Part 12/27)

[REQ_VF116_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.15 Detailed Functional Requirements & State Logic · VF116 (Part 13/27)

[REQ_VF116_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.16 Detailed Functional Requirements & State Logic · VF116 (Part 14/27)

[REQ_VF116_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.17 Detailed Functional Requirements & State Logic · VF116 (Part 15/27)

[REQ_VF116_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.18 Detailed Functional Requirements & State Logic · VF116 (Part 16/27)

[REQ_VF116_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.19 Detailed Functional Requirements & State Logic · VF116 (Part 17/27)

[REQ_VF116_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.20 Detailed Functional Requirements & State Logic · VF116 (Part 18/27)

[REQ_VF116_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.21 Detailed Functional Requirements & State Logic · VF116 (Part 19/27)

[REQ_VF116_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.22 Detailed Functional Requirements & State Logic · VF116 (Part 20/27)

[REQ_VF116_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.23 Detailed Functional Requirements & State Logic · VF116 (Part 21/27)

[REQ_VF116_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.12 Indication Management

[REQ_VF116_IND] When T_DDD_WARN_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate DRIVER DROWSINESS ACTIVE.V1
IND_ROW | DRIVER DROWSINESS ACTIVE.V1 | When T_DDD_WARN_Sts == ACTIVE on CAN-FD network | No (Standard DRIVER

[REQ_VF116_IND] When T_DDD_WARN_FailSts == PRESENT, the IPC cluster shall activate DRIVER DROWSINESS FAIL.V1 on the display.
IND_ROW | DRIVER DROWSINESS FAIL.V1 | When T_DDD_WARN_FailSts == PRESENT | Yes - Check Driver Drowsiness Detec

[REQ_VF116_IND] When CAN node timeout > T_DDD_WARN_TIMEOUT, the IPC cluster shall activate DRIVER DROWSINESS RECOVERY.V1
IND_ROW | DRIVER DROWSINESS RECOVERY.V1 | When CAN node timeout > T_DDD_WARN_TIMEOUT | Yes - DRIVER DROWSINESS

25.25 Detailed Functional Requirements & State Logic · VF116 (Part 23/27)

[REQ_VF116_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.26 Detailed Functional Requirements & State Logic · VF116 (Part 24/27)

[REQ_VF116_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.27 Detailed Functional Requirements & State Logic · VF116 (Part 25/27)

[REQ_VF116_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

25.14 Configuration Parameters

25.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF116_01 | T_DDD_WARN_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF116_02 | T_DDD_WARN_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filter

PAR_ROW | PAR_VF116_03 | CFG_VF116_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF116_04 | T_BCM_VF116_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

25.29 Detailed Functional Requirements & State Logic · VF116 (Part 27/27)

[REQ_VF116_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF116_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF116_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF116_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF116_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF116_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF116_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF116_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF116_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF116_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF116_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF116_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF116_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF116_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF116_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF116_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF116_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF116_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF116_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF116_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF116_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF116_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF116_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF116_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF116_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF116_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF116_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26 VF117 - Traffic Sign Recognition (TSR) Display (VF117_V1_PJ3U)

Document Code: VF117_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

26.1 Purpose and Functional Overview

[REQ_VF117_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF117 - Traffic Sign Recognition (TSR) Display.

26.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF117_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF117_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF117_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF117_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF117_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF117_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF117_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF117_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF117_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF117_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF117_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF117_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF117_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF117_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF117_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF117_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF117_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

26.2 Detailed Functional Requirements & State Logic · VF117 (Part 2/27)

[REQ_VF117_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.3 Detailed Functional Requirements & State Logic · VF117 (Part 3/27)

[REQ_VF117_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.4 Detailed Functional Requirements & State Logic · VF117 (Part 4/27)

[REQ_VF117_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.5 Detailed Functional Requirements & State Logic · VF117 (Part 5/27)

[REQ_VF117_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.6 Detailed Functional Requirements & State Logic · VF117 (Part 6/27)

[REQ_VF117_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.7 Detailed Functional Requirements & State Logic · VF117 (Part 7/27)

[REQ_VF117_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.8 Detailed Functional Requirements & State Logic · VF117 (Part 8/27)

[REQ_VF117_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.9 Detailed Functional Requirements & State Logic · VF117 (Part 9/27)

[REQ_VF117_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.10 Detailed Functional Requirements & State Logic · VF117 (Part 10/27)

[REQ_VF117_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.11 Detailed Functional Requirements & State Logic · VF117 (Part 11/27)

[REQ_VF117_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.14 Detailed Functional Requirements & State Logic · VF117 (Part 12/27)

[REQ_VF117_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.15 Detailed Functional Requirements & State Logic · VF117 (Part 13/27)

[REQ_VF117_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.16 Detailed Functional Requirements & State Logic · VF117 (Part 14/27)

[REQ_VF117_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.17 Detailed Functional Requirements & State Logic · VF117 (Part 15/27)

[REQ_VF117_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.18 Detailed Functional Requirements & State Logic · VF117 (Part 16/27)

[REQ_VF117_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.19 Detailed Functional Requirements & State Logic · VF117 (Part 17/27)

[REQ_VF117_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.20 Detailed Functional Requirements & State Logic · VF117 (Part 18/27)

[REQ_VF117_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.21 Detailed Functional Requirements & State Logic · VF117 (Part 19/27)

[REQ_VF117_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.22 Detailed Functional Requirements & State Logic · VF117 (Part 20/27)

[REQ_VF117_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.23 Detailed Functional Requirements & State Logic · VF117 (Part 21/27)

[REQ_VF117_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.12 Indication Management

[REQ_VF117_IND] When T_TSR_HOLD_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate TRAFFIC SIGN ACTIVE.V1 on the di

IND_ROW | TRAFFIC SIGN ACTIVE.V1 | When T_TSR_HOLD_Sts == ACTIVE on CAN-FD network | No (Standard TRAFFIC SIGN

[REQ_VF117_IND] When T_TSR_HOLD_FailSts == PRESENT, the IPC cluster shall activate TRAFFIC SIGN FAIL.V1 on the display.

IND_ROW | TRAFFIC SIGN FAIL.V1 | When T_TSR_HOLD_FailSts == PRESENT | Yes - Check Traffic Sign Recognition (TS

[REQ_VF117_IND] When CAN node timeout > T_TSR_HOLD_TIMEOUT, the IPC cluster shall activate TRAFFIC SIGN RECOVERY.V1 on the dis

IND_ROW | TRAFFIC SIGN RECOVERY.V1 | When CAN node timeout > T_TSR_HOLD_TIMEOUT | Yes - TRAFFIC SIGN System Re

26.25 Detailed Functional Requirements & State Logic · VF117 (Part 23/27)

[REQ_VF117_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.26 Detailed Functional Requirements & State Logic · VF117 (Part 24/27)

[REQ_VF117_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.27 Detailed Functional Requirements & State Logic · VF117 (Part 25/27)

[REQ_VF117_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

26.14 Configuration Parameters

26.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF117_01 | T_TSR_HOLD_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF117_02 | T_TSR_HOLD_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filter

PAR_ROW | PAR_VF117_03 | CFG_VF117_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF117_04 | T_BCM_VF117_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

26.29 Detailed Functional Requirements & State Logic · VF117 (Part 27/27)

[REQ_VF117_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF117_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF117_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF117_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF117_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF117_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF117_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF117_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF117_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF117_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF117_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF117_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF117_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF117_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF117_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF117_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF117_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF117_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF117_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF117_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF117_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF117_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF117_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF117_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF117_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF117_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF117_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27 VF118 - Seat Belt Reminder (SBR) Front & Rear (VF118_V1_PJ3U)

Document Code: VF118_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

27.1 Purpose and Functional Overview

[REQ_VF118_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF118 - Seat Belt Reminder (SBR) Front & Rear.

27.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF118_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF118_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF118_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF118_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF118_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF118_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF118_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF118_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF118_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF118_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF118_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF118_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF118_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF118_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF118_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF118_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF118_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

27.2 Detailed Functional Requirements & State Logic · VF118 (Part 2/27)

[REQ_VF118_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.3 Detailed Functional Requirements & State Logic · VF118 (Part 3/27)

[REQ_VF118_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.4 Detailed Functional Requirements & State Logic · VF118 (Part 4/27)

[REQ_VF118_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.5 Detailed Functional Requirements & State Logic · VF118 (Part 5/27)

[REQ_VF118_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.6 Detailed Functional Requirements & State Logic · VF118 (Part 6/27)

[REQ_VF118_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.7 Detailed Functional Requirements & State Logic · VF118 (Part 7/27)

[REQ_VF118_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.8 Detailed Functional Requirements & State Logic · VF118 (Part 8/27)

[REQ_VF118_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.9 Detailed Functional Requirements & State Logic · VF118 (Part 9/27)

[REQ_VF118_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.10 Detailed Functional Requirements & State Logic · VF118 (Part 10/27)

[REQ_VF118_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.11 Detailed Functional Requirements & State Logic · VF118 (Part 11/27)

[REQ_VF118_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.14 Detailed Functional Requirements & State Logic · VF118 (Part 12/27)

[REQ_VF118_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.15 Detailed Functional Requirements & State Logic · VF118 (Part 13/27)

[REQ_VF118_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.16 Detailed Functional Requirements & State Logic · VF118 (Part 14/27)

[REQ_VF118_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.17 Detailed Functional Requirements & State Logic · VF118 (Part 15/27)

[REQ_VF118_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.18 Detailed Functional Requirements & State Logic · VF118 (Part 16/27)

[REQ_VF118_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.19 Detailed Functional Requirements & State Logic · VF118 (Part 17/27)

[REQ_VF118_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.20 Detailed Functional Requirements & State Logic · VF118 (Part 18/27)

[REQ_VF118_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.21 Detailed Functional Requirements & State Logic · VF118 (Part 19/27)

[REQ_VF118_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.22 Detailed Functional Requirements & State Logic · VF118 (Part 20/27)

[REQ_VF118_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.23 Detailed Functional Requirements & State Logic · VF118 (Part 21/27)

[REQ_VF118_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.12 Indication Management

[REQ_VF118_IND] When V_SBR_TH_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate SEAT BELT REMINDER ACTIVE.V1 on
IND_ROW | SEAT BELT REMINDER ACTIVE.V1 | When V_SBR_TH_Sts == ACTIVE on CAN-FD network | No (Standard SEAT BEL

[REQ_VF118_IND] When V_SBR_TH_FailSts == PRESENT, the IPC cluster shall activate SEAT BELT REMINDER FAIL.V1 on the display.
IND_ROW | SEAT BELT REMINDER FAIL.V1 | When V_SBR_TH_FailSts == PRESENT | Yes - Check Seat Belt Reminder (SBR)

[REQ_VF118_IND] When CAN node timeout > V_SBR_TH_TIMEOUT, the IPC cluster shall activate SEAT BELT REMINDER RECOVERY.V1 on
IND_ROW | SEAT BELT REMINDER RECOVERY.V1 | When CAN node timeout > V_SBR_TH_TIMEOUT | Yes - SEAT BELT REMINDER

27.25 Detailed Functional Requirements & State Logic · VF118 (Part 23/27)

[REQ_VF118_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.26 Detailed Functional Requirements & State Logic · VF118 (Part 24/27)

[REQ_VF118_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.27 Detailed Functional Requirements & State Logic · VF118 (Part 25/27)

[REQ_VF118_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

27.14 Configuration Parameters

27.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF118_01 | V_SBR_TH_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Pr

PAR_ROW | PAR_VF118_02 | V_SBR_TH_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filterin

PAR_ROW | PAR_VF118_03 | CFG_VF118_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF118_04 | T_BCM_VF118_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

27.29 Detailed Functional Requirements & State Logic · VF118 (Part 27/27)

[REQ_VF118_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF118_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF118_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF118_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF118_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF118_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF118_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF118_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF118_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF118_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF118_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF118_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF118_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF118_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF118_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF118_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF118_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF118_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF118_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF118_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF118_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF118_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF118_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF118_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF118_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF118_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF118_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28 VF120 - Doors, Hood and Trunk Open Status Graphic (VF120_V1_PJ3U)

Document Code: VF120_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

28.1 Purpose and Functional Overview

[REQ_VF120_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF120 - Doors, Hood and Trunk Open Status Graphic.

28.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF120_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF120_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF120_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF120_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF120_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF120_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF120_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF120_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF120_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF120_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF120_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF120_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF120_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF120_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF120_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF120_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF120_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

28.2 Detailed Functional Requirements & State Logic · VF120 (Part 2/27)

[REQ_VF120_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.3 Detailed Functional Requirements & State Logic · VF120 (Part 3/27)

[REQ_VF120_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.4 Detailed Functional Requirements & State Logic · VF120 (Part 4/27)

[REQ_VF120_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.5 Detailed Functional Requirements & State Logic · VF120 (Part 5/27)

[REQ_VF120_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.6 Detailed Functional Requirements & State Logic · VF120 (Part 6/27)

[REQ_VF120_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.7 Detailed Functional Requirements & State Logic · VF120 (Part 7/27)

[REQ_VF120_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.8 Detailed Functional Requirements & State Logic · VF120 (Part 8/27)

[REQ_VF120_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.9 Detailed Functional Requirements & State Logic · VF120 (Part 9/27)

[REQ_VF120_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.10 Detailed Functional Requirements & State Logic · VF120 (Part 10/27)

[REQ_VF120_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.11 Detailed Functional Requirements & State Logic · VF120 (Part 11/27)

[REQ_VF120_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.14 Detailed Functional Requirements & State Logic · VF120 (Part 12/27)

[REQ_VF120_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.15 Detailed Functional Requirements & State Logic · VF120 (Part 13/27)

[REQ_VF120_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.16 Detailed Functional Requirements & State Logic · VF120 (Part 14/27)

[REQ_VF120_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.17 Detailed Functional Requirements & State Logic · VF120 (Part 15/27)

[REQ_VF120_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.18 Detailed Functional Requirements & State Logic · VF120 (Part 16/27)

[REQ_VF120_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.19 Detailed Functional Requirements & State Logic · VF120 (Part 17/27)

[REQ_VF120_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.20 Detailed Functional Requirements & State Logic · VF120 (Part 18/27)

[REQ_VF120_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.21 Detailed Functional Requirements & State Logic · VF120 (Part 19/27)

[REQ_VF120_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.22 Detailed Functional Requirements & State Logic · VF120 (Part 20/27)

[REQ_VF120_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.23 Detailed Functional Requirements & State Logic · VF120 (Part 21/27)

[REQ_VF120_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.12 Indication Management

[REQ_VF120_IND] When V_DOOR_WARN_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate DOOR OPEN ACTIVE.V1 on the d

IND_ROW | DOOR OPEN ACTIVE.V1 | When V_DOOR_WARN_Sts == ACTIVE on CAN-FD network | No (Standard DOOR OPEN Tell

[REQ_VF120_IND] When V_DOOR_WARN_FailSts == PRESENT, the IPC cluster shall activate DOOR OPEN FAIL.V1 on the display.

IND_ROW | DOOR OPEN FAIL.V1 | When V_DOOR_WARN_FailSts == PRESENT | Yes - Check Doors, Hood and Trunk Open Sta

[REQ_VF120_IND] When CAN node timeout > V_DOOR_WARN_TIMEOUT, the IPC cluster shall activate DOOR OPEN RECOVERY.V1 on the d

IND_ROW | DOOR OPEN RECOVERY.V1 | When CAN node timeout > V_DOOR_WARN_TIMEOUT | Yes - DOOR OPEN System Recover

28.25 Detailed Functional Requirements & State Logic · VF120 (Part 23/27)

[REQ_VF120_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.26 Detailed Functional Requirements & State Logic · VF120 (Part 24/27)

[REQ_VF120_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.27 Detailed Functional Requirements & State Logic · VF120 (Part 25/27)

[REQ_VF120_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

28.14 Configuration Parameters

28.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF120_01 | V_DOOR_WARN_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF120_02 | V_DOOR_WARN_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filte

PAR_ROW | PAR_VF120_03 | CFG_VF120_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF120_04 | T_BCM_VF120_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

28.29 Detailed Functional Requirements & State Logic · VF120 (Part 27/27)

[REQ_VF120_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF120_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF120_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF120_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF120_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF120_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF120_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF120_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF120_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF120_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF120_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF120_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF120_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF120_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF120_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF120_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF120_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF120_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF120_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF120_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF120_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF120_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF120_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF120_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF120_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF120_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF120_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29 VF122 - External Lighting & Turn Signals Telltales (VF122_V1_PJ3U)

Document Code: VF122_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

29.1 Purpose and Functional Overview

[REQ_VF122_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF122 - External Lighting & Turn Signals Telltales.

29.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF122_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF122_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF122_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF122_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF122_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF122_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF122_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF122_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF122_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF122_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF122_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF122_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF122_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF122_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF122_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF122_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF122_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

29.2 Detailed Functional Requirements & State Logic · VF122 (Part 2/27)

[REQ_VF122_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.3 Detailed Functional Requirements & State Logic · VF122 (Part 3/27)

[REQ_VF122_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.4 Detailed Functional Requirements & State Logic · VF122 (Part 4/27)

[REQ_VF122_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.5 Detailed Functional Requirements & State Logic · VF122 (Part 5/27)

[REQ_VF122_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.6 Detailed Functional Requirements & State Logic · VF122 (Part 6/27)

[REQ_VF122_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.7 Detailed Functional Requirements & State Logic · VF122 (Part 7/27)

[REQ_VF122_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.8 Detailed Functional Requirements & State Logic · VF122 (Part 8/27)

[REQ_VF122_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.9 Detailed Functional Requirements & State Logic · VF122 (Part 9/27)

[REQ_VF122_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.10 Detailed Functional Requirements & State Logic · VF122 (Part 10/27)

[REQ_VF122_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.11 Detailed Functional Requirements & State Logic · VF122 (Part 11/27)

[REQ_VF122_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.14 Detailed Functional Requirements & State Logic · VF122 (Part 12/27)

[REQ_VF122_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.15 Detailed Functional Requirements & State Logic · VF122 (Part 13/27)

[REQ_VF122_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.16 Detailed Functional Requirements & State Logic · VF122 (Part 14/27)

[REQ_VF122_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.17 Detailed Functional Requirements & State Logic · VF122 (Part 15/27)

[REQ_VF122_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.18 Detailed Functional Requirements & State Logic · VF122 (Part 16/27)

[REQ_VF122_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.19 Detailed Functional Requirements & State Logic · VF122 (Part 17/27)

[REQ_VF122_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.20 Detailed Functional Requirements & State Logic · VF122 (Part 18/27)

[REQ_VF122_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.21 Detailed Functional Requirements & State Logic · VF122 (Part 19/27)

[REQ_VF122_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.22 Detailed Functional Requirements & State Logic · VF122 (Part 20/27)

[REQ_VF122_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.23 Detailed Functional Requirements & State Logic · VF122 (Part 21/27)

[REQ_VF122_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.12 Indication Management

[REQ_VF122_IND] When F_BLINK_RATE_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate TURN SIGNAL ACTIVE.V1 on the d

IND_ROW | TURN SIGNAL ACTIVE.V1 | When F_BLINK_RATE_Sts == ACTIVE on CAN-FD network | No (Standard TURN SIGNAL

[REQ_VF122_IND] When F_BLINK_RATE_FailSts == PRESENT, the IPC cluster shall activate TURN SIGNAL FAIL.V1 on the display.

IND_ROW | TURN SIGNAL FAIL.V1 | When F_BLINK_RATE_FailSts == PRESENT | Yes - Check External Lighting & Turn Si

[REQ_VF122_IND] When CAN node timeout > F_BLINK_RATE_TIMEOUT, the IPC cluster shall activate TURN SIGNAL RECOVERY.V1 on the d

IND_ROW | TURN SIGNAL RECOVERY.V1 | When CAN node timeout > F_BLINK_RATE_TIMEOUT | Yes - TURN SIGNAL System Re

29.25 Detailed Functional Requirements & State Logic · VF122 (Part 23/27)

[REQ_VF122_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.26 Detailed Functional Requirements & State Logic · VF122 (Part 24/27)

[REQ_VF122_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.27 Detailed Functional Requirements & State Logic · VF122 (Part 25/27)

[REQ_VF122_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

29.14 Configuration Parameters

29.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF122_01 | F_BLINK_RATE_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration

PAR_ROW | PAR_VF122_02 | F_BLINK_RATE_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filt

PAR_ROW | PAR_VF122_03 | CFG_VF122_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF122_04 | T_BCM_VF122_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

29.29 Detailed Functional Requirements & State Logic · VF122 (Part 27/27)

[REQ_VF122_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF122_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF122_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF122_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF122_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF122_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF122_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF122_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF122_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF122_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF122_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF122_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF122_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF122_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF122_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF122_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF122_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF122_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF122_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF122_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF122_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF122_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF122_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF122_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF122_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF122_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF122_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30 VF124 - High Beam & Auto High Beam Assist HMI (VF124_V1_PJ3U)

Document Code: VF124_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

30.1 Purpose and Functional Overview

[REQ_VF124_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF124 - High Beam & Auto High Beam Assist HMI.

30.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF124_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF124_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF124_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF124_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF124_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF124_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF124_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF124_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF124_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF124_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF124_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF124_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF124_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF124_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF124_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF124_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF124_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

30.2 Detailed Functional Requirements & State Logic · VF124 (Part 2/27)

[REQ_VF124_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.3 Detailed Functional Requirements & State Logic · VF124 (Part 3/27)

[REQ_VF124_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.4 Detailed Functional Requirements & State Logic · VF124 (Part 4/27)

[REQ_VF124_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.5 Detailed Functional Requirements & State Logic · VF124 (Part 5/27)

[REQ_VF124_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.6 Detailed Functional Requirements & State Logic · VF124 (Part 6/27)

[REQ_VF124_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.7 Detailed Functional Requirements & State Logic · VF124 (Part 7/27)

[REQ_VF124_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.8 Detailed Functional Requirements & State Logic · VF124 (Part 8/27)

[REQ_VF124_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.9 Detailed Functional Requirements & State Logic · VF124 (Part 9/27)

[REQ_VF124_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.10 Detailed Functional Requirements & State Logic · VF124 (Part 10/27)

[REQ_VF124_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.11 Detailed Functional Requirements & State Logic · VF124 (Part 11/27)

[REQ_VF124_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.14 Detailed Functional Requirements & State Logic · VF124 (Part 12/27)

[REQ_VF124_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.15 Detailed Functional Requirements & State Logic · VF124 (Part 13/27)

[REQ_VF124_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.16 Detailed Functional Requirements & State Logic · VF124 (Part 14/27)

[REQ_VF124_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.17 Detailed Functional Requirements & State Logic · VF124 (Part 15/27)

[REQ_VF124_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.18 Detailed Functional Requirements & State Logic · VF124 (Part 16/27)

[REQ_VF124_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.19 Detailed Functional Requirements & State Logic · VF124 (Part 17/27)

[REQ_VF124_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.20 Detailed Functional Requirements & State Logic · VF124 (Part 18/27)

[REQ_VF124_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.21 Detailed Functional Requirements & State Logic · VF124 (Part 19/27)

[REQ_VF124_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.22 Detailed Functional Requirements & State Logic · VF124 (Part 20/27)

[REQ_VF124_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.23 Detailed Functional Requirements & State Logic · VF124 (Part 21/27)

[REQ_VF124_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.12 Indication Management

[REQ_VF124_IND] When V_AHB_DEACT_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate HIGH BEAM ACTIVE.V1 on the disp

IND_ROW | HIGH BEAM ACTIVE.V1 | When V_AHB_DEACT_Sts == ACTIVE on CAN-FD network | No (Standard HIGH BEAM Tell

[REQ_VF124_IND] When V_AHB_DEACT_FailSts == PRESENT, the IPC cluster shall activate HIGH BEAM FAIL.V1 on the display.

IND_ROW | HIGH BEAM FAIL.V1 | When V_AHB_DEACT_FailSts == PRESENT | Yes - Check High Beam & Auto High Beam Ass

[REQ_VF124_IND] When CAN node timeout > V_AHB_DEACT_TIMEOUT, the IPC cluster shall activate HIGH BEAM RECOVERY.V1 on the disp

IND_ROW | HIGH BEAM RECOVERY.V1 | When CAN node timeout > V_AHB_DEACT_TIMEOUT | Yes - HIGH BEAM System Recover

30.25 Detailed Functional Requirements & State Logic · VF124 (Part 23/27)

[REQ_VF124_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.26 Detailed Functional Requirements & State Logic · VF124 (Part 24/27)

[REQ_VF124_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.27 Detailed Functional Requirements & State Logic · VF124 (Part 25/27)

[REQ_VF124_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

30.14 Configuration Parameters

30.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF124_01 | V_AHB_DEACT_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF124_02 | V_AHB_DEACT_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filte

PAR_ROW | PAR_VF124_03 | CFG_VF124_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF124_04 | T_BCM_VF124_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

30.29 Detailed Functional Requirements & State Logic · VF124 (Part 27/27)

[REQ_VF124_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF124_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF124_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF124_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF124_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF124_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF124_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF124_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF124_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF124_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF124_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF124_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF124_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF124_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF124_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF124_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF124_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF124_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF124_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF124_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF124_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF124_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF124_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF124_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF124_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF124_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF124_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31 VF126 - Front and Rear Fog Lights Indication (VF126_V1_PJ3U)

Document Code: VF126_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

31.1 Purpose and Functional Overview

[REQ_VF126_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF126 - Front and Rear Fog Lights Indication.

31.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF126_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF126_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF126_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF126_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF126_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF126_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF126_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF126_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF126_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF126_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF126_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF126_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF126_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF126_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF126_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF126_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF126_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

31.2 Detailed Functional Requirements & State Logic · VF126 (Part 2/27)

[REQ_VF126_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.3 Detailed Functional Requirements & State Logic · VF126 (Part 3/27)

[REQ_VF126_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.4 Detailed Functional Requirements & State Logic · VF126 (Part 4/27)

[REQ_VF126_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.5 Detailed Functional Requirements & State Logic · VF126 (Part 5/27)

[REQ_VF126_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.6 Detailed Functional Requirements & State Logic · VF126 (Part 6/27)

[REQ_VF126_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.7 Detailed Functional Requirements & State Logic · VF126 (Part 7/27)

[REQ_VF126_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.8 Detailed Functional Requirements & State Logic · VF126 (Part 8/27)

[REQ_VF126_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.9 Detailed Functional Requirements & State Logic · VF126 (Part 9/27)

[REQ_VF126_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.10 Detailed Functional Requirements & State Logic · VF126 (Part 10/27)

[REQ_VF126_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.11 Detailed Functional Requirements & State Logic · VF126 (Part 11/27)

[REQ_VF126_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.14 Detailed Functional Requirements & State Logic · VF126 (Part 12/27)

[REQ_VF126_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.15 Detailed Functional Requirements & State Logic · VF126 (Part 13/27)

[REQ_VF126_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.16 Detailed Functional Requirements & State Logic · VF126 (Part 14/27)

[REQ_VF126_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.17 Detailed Functional Requirements & State Logic · VF126 (Part 15/27)

[REQ_VF126_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.18 Detailed Functional Requirements & State Logic · VF126 (Part 16/27)

[REQ_VF126_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.19 Detailed Functional Requirements & State Logic · VF126 (Part 17/27)

[REQ_VF126_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.20 Detailed Functional Requirements & State Logic · VF126 (Part 18/27)

[REQ_VF126_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.21 Detailed Functional Requirements & State Logic · VF126 (Part 19/27)

[REQ_VF126_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.22 Detailed Functional Requirements & State Logic · VF126 (Part 20/27)

[REQ_VF126_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.23 Detailed Functional Requirements & State Logic · VF126 (Part 21/27)

[REQ_VF126_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.12 Indication Management

[REQ_VF126_IND] When T_FOG_FILTER_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate FOG LIGHT ACTIVE.V1 on the disp

IND_ROW | FOG LIGHT ACTIVE.V1 | When T_FOG_FILTER_Sts == ACTIVE on CAN-FD network | No (Standard FOG LIGHT Tel

[REQ_VF126_IND] When T_FOG_FILTER_FailSts == PRESENT, the IPC cluster shall activate FOG LIGHT FAIL.V1 on the display.

IND_ROW | FOG LIGHT FAIL.V1 | When T_FOG_FILTER_FailSts == PRESENT | Yes - Check Front and Rear Fog Lights Ind

[REQ_VF126_IND] When CAN node timeout > T_FOG_FILTER_TIMEOUT, the IPC cluster shall activate FOG LIGHT RECOVERY.V1 on the disp

IND_ROW | FOG LIGHT RECOVERY.V1 | When CAN node timeout > T_FOG_FILTER_TIMEOUT | Yes - FOG LIGHT System Recove

31.25 Detailed Functional Requirements & State Logic · VF126 (Part 23/27)

[REQ_VF126_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.26 Detailed Functional Requirements & State Logic · VF126 (Part 24/27)

[REQ_VF126_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.27 Detailed Functional Requirements & State Logic · VF126 (Part 25/27)

[REQ_VF126_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

31.14 Configuration Parameters

31.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | - | - | - | - | - | - | - | - | - | - | -

31.29 Detailed Functional Requirements & State Logic · VF126 (Part 27/27)

[REQ_VF126_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF126_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF126_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF126_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF126_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF126_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF126_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF126_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF126_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF126_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF126_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF126_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF126_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF126_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF126_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF126_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF126_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF126_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF126_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF126_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF126_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF126_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF126_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF126_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF126_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF126_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF126_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32 VF128 - Daytime Running Lights (DRL) Fault Warning (VF128_V1_PJ3U)

Document Code: VF128_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

32.1 Purpose and Functional Overview

[REQ_VF128_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF128 - Daytime Running Lights (DRL) Fault Warning.

32.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF128_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF128_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF128_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF128_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF128_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF128_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF128_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF128_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF128_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF128_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF128_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF128_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF128_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF128_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF128_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF128_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF128_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

32.2 Detailed Functional Requirements & State Logic · VF128 (Part 2/27)

[REQ_VF128_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.3 Detailed Functional Requirements & State Logic · VF128 (Part 3/27)

[REQ_VF128_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.4 Detailed Functional Requirements & State Logic · VF128 (Part 4/27)

[REQ_VF128_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.5 Detailed Functional Requirements & State Logic · VF128 (Part 5/27)

[REQ_VF128_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.6 Detailed Functional Requirements & State Logic · VF128 (Part 6/27)

[REQ_VF128_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.7 Detailed Functional Requirements & State Logic · VF128 (Part 7/27)

[REQ_VF128_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.8 Detailed Functional Requirements & State Logic · VF128 (Part 8/27)

[REQ_VF128_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.9 Detailed Functional Requirements & State Logic · VF128 (Part 9/27)

[REQ_VF128_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.10 Detailed Functional Requirements & State Logic · VF128 (Part 10/27)

[REQ_VF128_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.11 Detailed Functional Requirements & State Logic · VF128 (Part 11/27)

[REQ_VF128_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.14 Detailed Functional Requirements & State Logic · VF128 (Part 12/27)

[REQ_VF128_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.15 Detailed Functional Requirements & State Logic · VF128 (Part 13/27)

[REQ_VF128_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.16 Detailed Functional Requirements & State Logic · VF128 (Part 14/27)

[REQ_VF128_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.17 Detailed Functional Requirements & State Logic · VF128 (Part 15/27)

[REQ_VF128_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.18 Detailed Functional Requirements & State Logic · VF128 (Part 16/27)

[REQ_VF128_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.19 Detailed Functional Requirements & State Logic · VF128 (Part 17/27)

[REQ_VF128_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.20 Detailed Functional Requirements & State Logic · VF128 (Part 18/27)

[REQ_VF128_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.21 Detailed Functional Requirements & State Logic · VF128 (Part 19/27)

[REQ_VF128_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.22 Detailed Functional Requirements & State Logic · VF128 (Part 20/27)

[REQ_VF128_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.23 Detailed Functional Requirements & State Logic · VF128 (Part 21/27)

[REQ_VF128_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.12 Indication Management

[REQ_VF128_IND] When T_DRL_DEBOUNCE_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate DRL FAULT ACTIVE.V1 on the

IND_ROW | DRL FAULT ACTIVE.V1 | When T_DRL_DEBOUNCE_Sts == ACTIVE on CAN-FD network | No (Standard DRL FAULT T

[REQ_VF128_IND] When T_DRL_DEBOUNCE_FailSts == PRESENT, the IPC cluster shall activate DRL FAULT FAIL.V1 on the display.

IND_ROW | DRL FAULT FAIL.V1 | When T_DRL_DEBOUNCE_FailSts == PRESENT | Yes - Check Daytime Running Lights (DRL

[REQ_VF128_IND] When CAN node timeout > T_DRL_DEBOUNCE_TIMEOUT, the IPC cluster shall activate DRL FAULT RECOVERY.V1 on the

IND_ROW | DRL FAULT RECOVERY.V1 | When CAN node timeout > T_DRL_DEBOUNCE_TIMEOUT | Yes - DRL FAULT System Reco

32.25 Detailed Functional Requirements & State Logic · VF128 (Part 23/27)

[REQ_VF128_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.26 Detailed Functional Requirements & State Logic · VF128 (Part 24/27)

[REQ_VF128_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.27 Detailed Functional Requirements & State Logic · VF128 (Part 25/27)

[REQ_VF128_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

32.14 Configuration Parameters

32.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF128_01 | T_DRL_DEBOUNCE_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibratio

PAR_ROW | PAR_VF128_02 | T_DRL_DEBOUNCE_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Fi

PAR_ROW | PAR_VF128_03 | CFG_VF128_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF128_04 | T_BCM_VF128_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

32.29 Detailed Functional Requirements & State Logic · VF128 (Part 27/27)

[REQ_VF128_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF128_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF128_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF128_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF128_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF128_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF128_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF128_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF128_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF128_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF128_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF128_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF128_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF128_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF128_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF128_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF128_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF128_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF128_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF128_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF128_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF128_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF128_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF128_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF128_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF128_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF128_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33 VF130 - Alternator & Battery Charging System Warning (VF130_V1_PJ3U)

Document Code: VF130_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

33.1 Purpose and Functional Overview

[REQ_VF130_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF130 - Alternator & Battery Charging System Warning

33.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF130_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF130_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF130_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF130_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF130_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF130_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF130_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF130_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF130_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF130_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF130_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF130_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF130_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF130_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF130_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF130_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF130_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

33.2 Detailed Functional Requirements & State Logic · VF130 (Part 2/27)

[REQ_VF130_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.3 Detailed Functional Requirements & State Logic · VF130 (Part 3/27)

[REQ_VF130_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.4 Detailed Functional Requirements & State Logic · VF130 (Part 4/27)

[REQ_VF130_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.5 Detailed Functional Requirements & State Logic · VF130 (Part 5/27)

[REQ_VF130_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.6 Detailed Functional Requirements & State Logic · VF130 (Part 6/27)

[REQ_VF130_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.7 Detailed Functional Requirements & State Logic · VF130 (Part 7/27)

[REQ_VF130_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.8 Detailed Functional Requirements & State Logic · VF130 (Part 8/27)

[REQ_VF130_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.9 Detailed Functional Requirements & State Logic · VF130 (Part 9/27)

[REQ_VF130_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.10 Detailed Functional Requirements & State Logic · VF130 (Part 10/27)

[REQ_VF130_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.11 Detailed Functional Requirements & State Logic · VF130 (Part 11/27)

[REQ_VF130_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.14 Detailed Functional Requirements & State Logic · VF130 (Part 12/27)

[REQ_VF130_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.15 Detailed Functional Requirements & State Logic · VF130 (Part 13/27)

[REQ_VF130_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.16 Detailed Functional Requirements & State Logic · VF130 (Part 14/27)

[REQ_VF130_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.17 Detailed Functional Requirements & State Logic · VF130 (Part 15/27)

[REQ_VF130_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.18 Detailed Functional Requirements & State Logic · VF130 (Part 16/27)

[REQ_VF130_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.19 Detailed Functional Requirements & State Logic · VF130 (Part 17/27)

[REQ_VF130_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.20 Detailed Functional Requirements & State Logic · VF130 (Part 18/27)

[REQ_VF130_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.21 Detailed Functional Requirements & State Logic · VF130 (Part 19/27)

[REQ_VF130_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.22 Detailed Functional Requirements & State Logic · VF130 (Part 20/27)

[REQ_VF130_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.23 Detailed Functional Requirements & State Logic · VF130 (Part 21/27)

[REQ_VF130_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.12 Indication Management

[REQ_VF130_IND] When U_BATT_LOW_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate BATTERY CHARGE ACTIVE.V1 on t

IND_ROW | BATTERY CHARGE ACTIVE.V1 | When U_BATT_LOW_Sts == ACTIVE on CAN-FD network | No (Standard BATTERY CH

[REQ_VF130_IND] When U_BATT_LOW_FailSts == PRESENT, the IPC cluster shall activate BATTERY CHARGE FAIL.V1 on the display.

IND_ROW | BATTERY CHARGE FAIL.V1 | When U_BATT_LOW_FailSts == PRESENT | Yes - Check Alternator & Battery Charg

[REQ_VF130_IND] When CAN node timeout > U_BATT_LOW_TIMEOUT, the IPC cluster shall activate BATTERY CHARGE RECOVERY.V1 on t

IND_ROW | BATTERY CHARGE RECOVERY.V1 | When CAN node timeout > U_BATT_LOW_TIMEOUT | Yes - BATTERY CHARGE Syste

33.25 Detailed Functional Requirements & State Logic · VF130 (Part 23/27)

[REQ_VF130_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.26 Detailed Functional Requirements & State Logic · VF130 (Part 24/27)

[REQ_VF130_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.27 Detailed Functional Requirements & State Logic · VF130 (Part 25/27)

[REQ_VF130_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

33.14 Configuration Parameters

33.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF130_01 | U_BATT_LOW_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF130_02 | U_BATT_LOW_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filter

PAR_ROW | PAR_VF130_03 | CFG_VF130_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF130_04 | T_BCM_VF130_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

33.29 Detailed Functional Requirements & State Logic · VF130 (Part 27/27)

[REQ_VF130_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF130_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF130_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF130_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF130_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF130_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF130_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF130_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF130_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF130_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF130_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF130_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF130_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF130_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF130_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF130_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF130_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF130_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF130_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF130_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF130_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF130_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF130_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF130_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF130_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF130_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF130_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34 VF132 - Engine Oil Pressure & Level Warning (VF132_V1_PJ3U)

Document Code: VF132_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

34.1 Purpose and Functional Overview

[REQ_VF132_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF132 - Engine Oil Pressure & Level Warning.

34.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF132_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF132_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF132_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF132_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF132_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF132_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF132_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF132_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF132_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF132_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF132_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF132_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF132_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF132_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF132_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF132_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF132_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

34.2 Detailed Functional Requirements & State Logic · VF132 (Part 2/27)

[REQ_VF132_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.3 Detailed Functional Requirements & State Logic · VF132 (Part 3/27)

[REQ_VF132_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.4 Detailed Functional Requirements & State Logic · VF132 (Part 4/27)

[REQ_VF132_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.5 Detailed Functional Requirements & State Logic · VF132 (Part 5/27)

[REQ_VF132_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.6 Detailed Functional Requirements & State Logic · VF132 (Part 6/27)

[REQ_VF132_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.7 Detailed Functional Requirements & State Logic · VF132 (Part 7/27)

[REQ_VF132_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.8 Detailed Functional Requirements & State Logic · VF132 (Part 8/27)

[REQ_VF132_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.9 Detailed Functional Requirements & State Logic · VF132 (Part 9/27)

[REQ_VF132_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.10 Detailed Functional Requirements & State Logic · VF132 (Part 10/27)

[REQ_VF132_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.11 Detailed Functional Requirements & State Logic · VF132 (Part 11/27)

[REQ_VF132_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.14 Detailed Functional Requirements & State Logic · VF132 (Part 12/27)

[REQ_VF132_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.15 Detailed Functional Requirements & State Logic · VF132 (Part 13/27)

[REQ_VF132_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.16 Detailed Functional Requirements & State Logic · VF132 (Part 14/27)

[REQ_VF132_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.17 Detailed Functional Requirements & State Logic · VF132 (Part 15/27)

[REQ_VF132_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.18 Detailed Functional Requirements & State Logic · VF132 (Part 16/27)

[REQ_VF132_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.19 Detailed Functional Requirements & State Logic · VF132 (Part 17/27)

[REQ_VF132_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.20 Detailed Functional Requirements & State Logic · VF132 (Part 18/27)

[REQ_VF132_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.21 Detailed Functional Requirements & State Logic · VF132 (Part 19/27)

[REQ_VF132_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.22 Detailed Functional Requirements & State Logic · VF132 (Part 20/27)

[REQ_VF132_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.23 Detailed Functional Requirements & State Logic · VF132 (Part 21/27)

[REQ_VF132_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.12 Indication Management

[REQ_VF132_IND] When T_OIL_DELAY_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate OIL PRESSURE ACTIVE.V1 on the d

IND_ROW | OIL PRESSURE ACTIVE.V1 | When T_OIL_DELAY_Sts == ACTIVE on CAN-FD network | No (Standard OIL PRESSUR

[REQ_VF132_IND] When T_OIL_DELAY_FailSts == PRESENT, the IPC cluster shall activate OIL PRESSURE FAIL.V1 on the display.

IND_ROW | OIL PRESSURE FAIL.V1 | When T_OIL_DELAY_FailSts == PRESENT | Yes - Check Engine Oil Pressure & Level

[REQ_VF132_IND] When CAN node timeout > T_OIL_DELAY_TIMEOUT, the IPC cluster shall activate OIL PRESSURE RECOVERY.V1 on the d

IND_ROW | OIL PRESSURE RECOVERY.V1 | When CAN node timeout > T_OIL_DELAY_TIMEOUT | Yes - OIL PRESSURE System R

34.25 Detailed Functional Requirements & State Logic · VF132 (Part 23/27)

[REQ_VF132_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.26 Detailed Functional Requirements & State Logic · VF132 (Part 24/27)

[REQ_VF132_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.27 Detailed Functional Requirements & State Logic · VF132 (Part 25/27)

[REQ_VF132_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

34.14 Configuration Parameters

34.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF132_01 | T_OIL_DELAY_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF132_02 | T_OIL_DELAY_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filte

PAR_ROW | PAR_VF132_03 | CFG_VF132_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF132_04 | T_BCM_VF132_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

34.29 Detailed Functional Requirements & State Logic · VF132 (Part 27/27)

[REQ_VF132_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF132_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF132_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF132_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF132_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF132_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF132_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF132_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF132_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF132_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF132_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF132_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF132_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF132_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF132_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF132_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF132_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF132_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF132_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF132_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF132_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF132_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF132_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF132_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF132_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF132_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF132_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35 VF134 - MIL Check Engine (OBD) Telltale Management (VF134_V1_PJ3U)

Document Code: VF134_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

35.1 Purpose and Functional Overview

[REQ_VF134_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF134 - MIL Check Engine (OBD) Telltale Managemer

35.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF134_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF134_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF134_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF134_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF134_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF134_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF134_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF134_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF134_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF134_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF134_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF134_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF134_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF134_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF134_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF134_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF134_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

35.2 Detailed Functional Requirements & State Logic · VF134 (Part 2/27)

[REQ_VF134_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.3 Detailed Functional Requirements & State Logic · VF134 (Part 3/27)

[REQ_VF134_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.4 Detailed Functional Requirements & State Logic · VF134 (Part 4/27)

[REQ_VF134_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.5 Detailed Functional Requirements & State Logic · VF134 (Part 5/27)

[REQ_VF134_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.6 Detailed Functional Requirements & State Logic · VF134 (Part 6/27)

[REQ_VF134_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.7 Detailed Functional Requirements & State Logic · VF134 (Part 7/27)

[REQ_VF134_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.8 Detailed Functional Requirements & State Logic · VF134 (Part 8/27)

[REQ_VF134_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.9 Detailed Functional Requirements & State Logic · VF134 (Part 9/27)

[REQ_VF134_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.10 Detailed Functional Requirements & State Logic · VF134 (Part 10/27)

[REQ_VF134_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.11 Detailed Functional Requirements & State Logic · VF134 (Part 11/27)

[REQ_VF134_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.14 Detailed Functional Requirements & State Logic · VF134 (Part 12/27)

[REQ_VF134_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.15 Detailed Functional Requirements & State Logic · VF134 (Part 13/27)

[REQ_VF134_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.16 Detailed Functional Requirements & State Logic · VF134 (Part 14/27)

[REQ_VF134_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.17 Detailed Functional Requirements & State Logic · VF134 (Part 15/27)

[REQ_VF134_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.18 Detailed Functional Requirements & State Logic · VF134 (Part 16/27)

[REQ_VF134_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.19 Detailed Functional Requirements & State Logic · VF134 (Part 17/27)

[REQ_VF134_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.20 Detailed Functional Requirements & State Logic · VF134 (Part 18/27)

[REQ_VF134_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.21 Detailed Functional Requirements & State Logic · VF134 (Part 19/27)

[REQ_VF134_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.22 Detailed Functional Requirements & State Logic · VF134 (Part 20/27)

[REQ_VF134_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.23 Detailed Functional Requirements & State Logic · VF134 (Part 21/27)

[REQ_VF134_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.12 Indication Management

[REQ_VF134_IND] When T_MIL_BULBCHK_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate CHECK ENGINE MIL ACTIVE.V1
IND_ROW | CHECK ENGINE MIL ACTIVE.V1 | When T_MIL_BULBCHK_Sts == ACTIVE on CAN-FD network | No (Standard CHECK
[REQ_VF134_IND] When T_MIL_BULBCHK_FailSts == PRESENT, the IPC cluster shall activate CHECK ENGINE MIL FAIL.V1 on the display.
IND_ROW | CHECK ENGINE MIL FAIL.V1 | When T_MIL_BULBCHK_FailSts == PRESENT | Yes - Check MIL Check Engine (OBD
[REQ_VF134_IND] When CAN node timeout > T_MIL_BULBCHK_TIMEOUT, the IPC cluster shall activate CHECK ENGINE MIL RECOVERY.V1
IND_ROW | CHECK ENGINE MIL RECOVERY.V1 | When CAN node timeout > T_MIL_BULBCHK_TIMEOUT | Yes - CHECK ENGINE MI

35.25 Detailed Functional Requirements & State Logic · VF134 (Part 23/27)

[REQ_VF134_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.26 Detailed Functional Requirements & State Logic · VF134 (Part 24/27)

[REQ_VF134_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.27 Detailed Functional Requirements & State Logic · VF134 (Part 25/27)

[REQ_VF134_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

35.14 Configuration Parameters

35.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF134_01 | T_MIL_BULBCHK_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration

PAR_ROW | PAR_VF134_02 | T_MIL_BULBCHK_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Fil

PAR_ROW | PAR_VF134_03 | CFG_VF134_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF134_04 | T_BCM_VF134_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

35.29 Detailed Functional Requirements & State Logic · VF134 (Part 27/27)

[REQ_VF134_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF134_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF134_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF134_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF134_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF134_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF134_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF134_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF134_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF134_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF134_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF134_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF134_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF134_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF134_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF134_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF134_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF134_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF134_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF134_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF134_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF134_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF134_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF134_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF134_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF134_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF134_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36 VF136 - Diesel Particulate Filter (DPF) & AdBlue HMI (VF136_V1_PJ3U)

Document Code: VF136_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

36.1 Purpose and Functional Overview

[REQ_VF136_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF136 - Diesel Particulate Filter (DPF) & AdBlue HMI.

36.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF136_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF136_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF136_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF136_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF136_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF136_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF136_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF136_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF136_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF136_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF136_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF136_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF136_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF136_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF136_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF136_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF136_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

36.2 Detailed Functional Requirements & State Logic · VF136 (Part 2/27)

[REQ_VF136_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.3 Detailed Functional Requirements & State Logic · VF136 (Part 3/27)

[REQ_VF136_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.4 Detailed Functional Requirements & State Logic · VF136 (Part 4/27)

[REQ_VF136_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.5 Detailed Functional Requirements & State Logic · VF136 (Part 5/27)

[REQ_VF136_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.6 Detailed Functional Requirements & State Logic · VF136 (Part 6/27)

[REQ_VF136_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.7 Detailed Functional Requirements & State Logic · VF136 (Part 7/27)

[REQ_VF136_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.8 Detailed Functional Requirements & State Logic · VF136 (Part 8/27)

[REQ_VF136_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.9 Detailed Functional Requirements & State Logic · VF136 (Part 9/27)

[REQ_VF136_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.10 Detailed Functional Requirements & State Logic · VF136 (Part 10/27)

[REQ_VF136_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.11 Detailed Functional Requirements & State Logic · VF136 (Part 11/27)

[REQ_VF136_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.14 Detailed Functional Requirements & State Logic · VF136 (Part 12/27)

[REQ_VF136_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.15 Detailed Functional Requirements & State Logic · VF136 (Part 13/27)

[REQ_VF136_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.16 Detailed Functional Requirements & State Logic · VF136 (Part 14/27)

[REQ_VF136_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.17 Detailed Functional Requirements & State Logic · VF136 (Part 15/27)

[REQ_VF136_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.18 Detailed Functional Requirements & State Logic · VF136 (Part 16/27)

[REQ_VF136_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.19 Detailed Functional Requirements & State Logic · VF136 (Part 17/27)

[REQ_VF136_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.20 Detailed Functional Requirements & State Logic · VF136 (Part 18/27)

[REQ_VF136_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.21 Detailed Functional Requirements & State Logic · VF136 (Part 19/27)

[REQ_VF136_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.22 Detailed Functional Requirements & State Logic · VF136 (Part 20/27)

[REQ_VF136_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.23 Detailed Functional Requirements & State Logic · VF136 (Part 21/27)

[REQ_VF136_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.12 Indication Management

[REQ_VF136_IND] When L_ADBLUE_MIN_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate DPF REGENERATION ACTIVE.V1
IND_ROW | DPF REGENERATION ACTIVE.V1 | When L_ADBLUE_MIN_Sts == ACTIVE on CAN-FD network | No (Standard DPF RE
[REQ_VF136_IND] When L_ADBLUE_MIN_FailSts == PRESENT, the IPC cluster shall activate DPF REGENERATION FAIL.V1 on the display.
IND_ROW | DPF REGENERATION FAIL.V1 | When L_ADBLUE_MIN_FailSts == PRESENT | Yes - Check Diesel Particulate Fil
[REQ_VF136_IND] When CAN node timeout > L_ADBLUE_MIN_TIMEOUT, the IPC cluster shall activate DPF REGENERATION RECOVERY.V1
IND_ROW | DPF REGENERATION RECOVERY.V1 | When CAN node timeout > L_ADBLUE_MIN_TIMEOUT | Yes - DPF REGENERATION

36.25 Detailed Functional Requirements & State Logic · VF136 (Part 23/27)

[REQ_VF136_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.26 Detailed Functional Requirements & State Logic · VF136 (Part 24/27)

[REQ_VF136_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.27 Detailed Functional Requirements & State Logic · VF136 (Part 25/27)

[REQ_VF136_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

36.14 Configuration Parameters

36.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF136_01 | L_ADBLUE_MIN_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration

PAR_ROW | PAR_VF136_02 | L_ADBLUE_MIN_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filt

PAR_ROW | PAR_VF136_03 | CFG_VF136_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF136_04 | T_BCM_VF136_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

36.29 Detailed Functional Requirements & State Logic · VF136 (Part 27/27)

[REQ_VF136_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF136_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF136_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF136_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF136_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF136_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF136_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF136_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF136_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF136_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF136_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF136_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF136_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF136_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF136_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF136_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF136_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF136_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF136_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF136_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF136_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF136_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF136_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF136_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF136_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF136_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF136_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37 VF138 - Glow Plug Pre-Heating & Water in Fuel (VF138_V1_PJ3U)

Document Code: VF138_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

37.1 Purpose and Functional Overview

[REQ_VF138_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF138 - Glow Plug Pre-Heating & Water in Fuel.

37.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF138_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF138_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF138_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF138_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF138_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF138_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF138_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF138_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF138_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF138_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF138_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF138_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF138_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF138_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF138_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF138_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF138_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

37.2 Detailed Functional Requirements & State Logic · VF138 (Part 2/27)

[REQ_VF138_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.3 Detailed Functional Requirements & State Logic · VF138 (Part 3/27)

[REQ_VF138_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.4 Detailed Functional Requirements & State Logic · VF138 (Part 4/27)

[REQ_VF138_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.5 Detailed Functional Requirements & State Logic · VF138 (Part 5/27)

[REQ_VF138_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.6 Detailed Functional Requirements & State Logic · VF138 (Part 6/27)

[REQ_VF138_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.7 Detailed Functional Requirements & State Logic · VF138 (Part 7/27)

[REQ_VF138_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.8 Detailed Functional Requirements & State Logic · VF138 (Part 8/27)

[REQ_VF138_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.9 Detailed Functional Requirements & State Logic · VF138 (Part 9/27)

[REQ_VF138_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.10 Detailed Functional Requirements & State Logic · VF138 (Part 10/27)

[REQ_VF138_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.11 Detailed Functional Requirements & State Logic · VF138 (Part 11/27)

[REQ_VF138_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.14 Detailed Functional Requirements & State Logic · VF138 (Part 12/27)

[REQ_VF138_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.15 Detailed Functional Requirements & State Logic · VF138 (Part 13/27)

[REQ_VF138_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.16 Detailed Functional Requirements & State Logic · VF138 (Part 14/27)

[REQ_VF138_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.17 Detailed Functional Requirements & State Logic · VF138 (Part 15/27)

[REQ_VF138_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.18 Detailed Functional Requirements & State Logic · VF138 (Part 16/27)

[REQ_VF138_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.19 Detailed Functional Requirements & State Logic · VF138 (Part 17/27)

[REQ_VF138_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.20 Detailed Functional Requirements & State Logic · VF138 (Part 18/27)

[REQ_VF138_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.21 Detailed Functional Requirements & State Logic · VF138 (Part 19/27)

[REQ_VF138_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.22 Detailed Functional Requirements & State Logic · VF138 (Part 20/27)

[REQ_VF138_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.23 Detailed Functional Requirements & State Logic · VF138 (Part 21/27)

[REQ_VF138_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.12 Indication Management

[REQ_VF138_IND] When T_GLOW_MAX_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate GLOW PLUG ACTIVE.V1 on the dis

IND_ROW | GLOW PLUG ACTIVE.V1 | When T_GLOW_MAX_Sts == ACTIVE on CAN-FD network | No (Standard GLOW PLUG Tellt

[REQ_VF138_IND] When T_GLOW_MAX_FailSts == PRESENT, the IPC cluster shall activate GLOW PLUG FAIL.V1 on the display.

IND_ROW | GLOW PLUG FAIL.V1 | When T_GLOW_MAX_FailSts == PRESENT | Yes - Check Glow Plug Pre-Heating & Water i

[REQ_VF138_IND] When CAN node timeout > T_GLOW_MAX_TIMEOUT, the IPC cluster shall activate GLOW PLUG RECOVERY.V1 on the disp

IND_ROW | GLOW PLUG RECOVERY.V1 | When CAN node timeout > T_GLOW_MAX_TIMEOUT | Yes - GLOW PLUG System Recovery

37.25 Detailed Functional Requirements & State Logic · VF138 (Part 23/27)

[REQ_VF138_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.26 Detailed Functional Requirements & State Logic · VF138 (Part 24/27)

[REQ_VF138_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.27 Detailed Functional Requirements & State Logic · VF138 (Part 25/27)

[REQ_VF138_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

37.14 Configuration Parameters

37.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF138_01 | T_GLOW_MAX_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF138_02 | T_GLOW_MAX_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filter

PAR_ROW | PAR_VF138_03 | CFG_VF138_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF138_04 | T_BCM_VF138_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

37.29 Detailed Functional Requirements & State Logic · VF138 (Part 27/27)

[REQ_VF138_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF138_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF138_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF138_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF138_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF138_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF138_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF138_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF138_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF138_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF138_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF138_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF138_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF138_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF138_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF138_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF138_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF138_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF138_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF138_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF138_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF138_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF138_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF138_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF138_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF138_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF138_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38 VF139 - Airbag & Pretensioner Warning Management (VF139_V1_PJ3U)

Document Code: VF139_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

38.1 Purpose and Functional Overview

[REQ_VF139_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF139 - Airbag & Pretensioner Warning Management.

38.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF139_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF139_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF139_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF139_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF139_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF139_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF139_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF139_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF139_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF139_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF139_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF139_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF139_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF139_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF139_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF139_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF139_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

38.2 Detailed Functional Requirements & State Logic · VF139 (Part 2/27)

[REQ_VF139_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.3 Detailed Functional Requirements & State Logic · VF139 (Part 3/27)

[REQ_VF139_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.4 Detailed Functional Requirements & State Logic · VF139 (Part 4/27)

[REQ_VF139_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.5 Detailed Functional Requirements & State Logic · VF139 (Part 5/27)

[REQ_VF139_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.6 Detailed Functional Requirements & State Logic · VF139 (Part 6/27)

[REQ_VF139_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.7 Detailed Functional Requirements & State Logic · VF139 (Part 7/27)

[REQ_VF139_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.8 Detailed Functional Requirements & State Logic · VF139 (Part 8/27)

[REQ_VF139_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.9 Detailed Functional Requirements & State Logic · VF139 (Part 9/27)

[REQ_VF139_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.10 Detailed Functional Requirements & State Logic · VF139 (Part 10/27)

[REQ_VF139_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.11 Detailed Functional Requirements & State Logic · VF139 (Part 11/27)

[REQ_VF139_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.14 Detailed Functional Requirements & State Logic · VF139 (Part 12/27)

[REQ_VF139_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.15 Detailed Functional Requirements & State Logic · VF139 (Part 13/27)

[REQ_VF139_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.16 Detailed Functional Requirements & State Logic · VF139 (Part 14/27)

[REQ_VF139_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.17 Detailed Functional Requirements & State Logic · VF139 (Part 15/27)

[REQ_VF139_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.18 Detailed Functional Requirements & State Logic · VF139 (Part 16/27)

[REQ_VF139_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.19 Detailed Functional Requirements & State Logic · VF139 (Part 17/27)

[REQ_VF139_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.20 Detailed Functional Requirements & State Logic · VF139 (Part 18/27)

[REQ_VF139_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.21 Detailed Functional Requirements & State Logic · VF139 (Part 19/27)

[REQ_VF139_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.22 Detailed Functional Requirements & State Logic · VF139 (Part 20/27)

[REQ_VF139_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.23 Detailed Functional Requirements & State Logic · VF139 (Part 21/27)

[REQ_VF139_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.12 Indication Management

[REQ_VF139_IND] When tREC_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate AIR BAG ACTIVE.V1 on the display.

IND_ROW | AIR BAG ACTIVE.V1 | When tREC_Sts == ACTIVE on CAN-FD network | No (Standard AIR BAG Telltale) | AIR

[REQ_VF139_IND] When tREC_FailSts == PRESENT, the IPC cluster shall activate AIR BAG FAIL.V1 on the display.

IND_ROW | AIR BAG FAIL.V1 | When tREC_FailSts == PRESENT | Yes - Check Airbag & Pretensioner Warning Managemen

[REQ_VF139_IND] When CAN node timeout > tREC_TIMEOUT, the IPC cluster shall activate AIR BAG RECOVERY.V1 on the display.

IND_ROW | AIR BAG RECOVERY.V1 | When CAN node timeout > tREC_TIMEOUT | Yes - AIR BAG System Recovery | AIR BAG

38.25 Detailed Functional Requirements & State Logic · VF139 (Part 23/27)

[REQ_VF139_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.26 Detailed Functional Requirements & State Logic · VF139 (Part 24/27)

[REQ_VF139_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.27 Detailed Functional Requirements & State Logic · VF139 (Part 25/27)

[REQ_VF139_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

38.14 Configuration Parameters

38.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF139_01 | tREC_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Primar

PAR_ROW | PAR_VF139_02 | tREC_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filtering |

PAR_ROW | PAR_VF139_03 | CFG_VF139_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF139_04 | T_BCM_VF139_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

38.29 Detailed Functional Requirements & State Logic · VF139 (Part 27/27)

[REQ_VF139_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF139_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF139_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF139_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF139_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF139_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF139_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF139_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF139_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF139_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF139_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF139_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF139_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF139_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF139_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF139_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF139_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF139_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF139_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF139_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF139_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF139_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF139_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF139_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF139_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF139_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF139_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39 VF141 - Electric Power Steering (EPS) Fault Indication (VF141_V1_PJ3U)

Document Code: VF141_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

39.1 Purpose and Functional Overview

[REQ_VF141_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF141 - Electric Power Steering (EPS) Fault Indication

39.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF141_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF141_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF141_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF141_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF141_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF141_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF141_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF141_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF141_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF141_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF141_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF141_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF141_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF141_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF141_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF141_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF141_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

39.2 Detailed Functional Requirements & State Logic · VF141 (Part 2/27)

[REQ_VF141_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.3 Detailed Functional Requirements & State Logic · VF141 (Part 3/27)

[REQ_VF141_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.4 Detailed Functional Requirements & State Logic · VF141 (Part 4/27)

[REQ_VF141_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.5 Detailed Functional Requirements & State Logic · VF141 (Part 5/27)

[REQ_VF141_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.6 Detailed Functional Requirements & State Logic · VF141 (Part 6/27)

[REQ_VF141_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.7 Detailed Functional Requirements & State Logic · VF141 (Part 7/27)

[REQ_VF141_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.8 Detailed Functional Requirements & State Logic · VF141 (Part 8/27)

[REQ_VF141_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.9 Detailed Functional Requirements & State Logic · VF141 (Part 9/27)

[REQ_VF141_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.10 Detailed Functional Requirements & State Logic · VF141 (Part 10/27)

[REQ_VF141_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.11 Detailed Functional Requirements & State Logic · VF141 (Part 11/27)

[REQ_VF141_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.14 Detailed Functional Requirements & State Logic · VF141 (Part 12/27)

[REQ_VF141_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.15 Detailed Functional Requirements & State Logic · VF141 (Part 13/27)

[REQ_VF141_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.16 Detailed Functional Requirements & State Logic · VF141 (Part 14/27)

[REQ_VF141_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.17 Detailed Functional Requirements & State Logic · VF141 (Part 15/27)

[REQ_VF141_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.18 Detailed Functional Requirements & State Logic · VF141 (Part 16/27)

[REQ_VF141_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.19 Detailed Functional Requirements & State Logic · VF141 (Part 17/27)

[REQ_VF141_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.20 Detailed Functional Requirements & State Logic · VF141 (Part 18/27)

[REQ_VF141_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.21 Detailed Functional Requirements & State Logic · VF141 (Part 19/27)

[REQ_VF141_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.22 Detailed Functional Requirements & State Logic · VF141 (Part 20/27)

[REQ_VF141_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.23 Detailed Functional Requirements & State Logic · VF141 (Part 21/27)

[REQ_VF141_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.12 Indication Management

[REQ_VF141_IND] When T_EPS_FILTER_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate EPS STEERING ACTIVE.V1 on the
IND_ROW | EPS STEERING ACTIVE.V1 | When T_EPS_FILTER_Sts == ACTIVE on CAN-FD network | No (Standard EPS STEERI

[REQ_VF141_IND] When T_EPS_FILTER_FailSts == PRESENT, the IPC cluster shall activate EPS STEERING FAIL.V1 on the display.
IND_ROW | EPS STEERING FAIL.V1 | When T_EPS_FILTER_FailSts == PRESENT | Yes - Check Electric Power Steering (E

[REQ_VF141_IND] When CAN node timeout > T_EPS_FILTER_TIMEOUT, the IPC cluster shall activate EPS STEERING RECOVERY.V1 on the
IND_ROW | EPS STEERING RECOVERY.V1 | When CAN node timeout > T_EPS_FILTER_TIMEOUT | Yes - EPS STEERING System

39.25 Detailed Functional Requirements & State Logic · VF141 (Part 23/27)

[REQ_VF141_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.26 Detailed Functional Requirements & State Logic · VF141 (Part 24/27)

[REQ_VF141_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.27 Detailed Functional Requirements & State Logic · VF141 (Part 25/27)

[REQ_VF141_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

39.14 Configuration Parameters

39.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF141_01 | T_EPS_FILTER_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration

PAR_ROW | PAR_VF141_02 | T_EPS_FILTER_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filt

PAR_ROW | PAR_VF141_03 | CFG_VF141_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF141_04 | T_BCM_VF141_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

39.29 Detailed Functional Requirements & State Logic · VF141 (Part 27/27)

[REQ_VF141_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF141_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF141_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF141_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF141_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF141_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF141_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF141_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF141_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF141_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF141_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF141_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF141_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF141_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF141_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF141_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF141_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF141_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF141_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF141_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF141_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF141_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF141_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF141_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF141_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF141_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF141_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40 VF143 - Hand Brake & Electric Park Brake (EPB) HMI (VF143_V1_PJ3U)

Document Code: VF143_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

40.1 Purpose and Functional Overview

[REQ_VF143_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF143 - Hand Brake & Electric Park Brake (EPB) HMI.

40.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF143_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF143_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF143_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF143_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF143_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF143_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF143_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF143_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF143_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF143_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF143_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF143_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF143_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF143_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF143_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF143_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF143_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

40.2 Detailed Functional Requirements & State Logic · VF143 (Part 2/27)

[REQ_VF143_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.3 Detailed Functional Requirements & State Logic · VF143 (Part 3/27)

[REQ_VF143_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.4 Detailed Functional Requirements & State Logic · VF143 (Part 4/27)

[REQ_VF143_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.5 Detailed Functional Requirements & State Logic · VF143 (Part 5/27)

[REQ_VF143_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.6 Detailed Functional Requirements & State Logic · VF143 (Part 6/27)

[REQ_VF143_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.7 Detailed Functional Requirements & State Logic · VF143 (Part 7/27)

[REQ_VF143_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.8 Detailed Functional Requirements & State Logic · VF143 (Part 8/27)

[REQ_VF143_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.9 Detailed Functional Requirements & State Logic · VF143 (Part 9/27)

[REQ_VF143_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.10 Detailed Functional Requirements & State Logic · VF143 (Part 10/27)

[REQ_VF143_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.11 Detailed Functional Requirements & State Logic · VF143 (Part 11/27)

[REQ_VF143_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.14 Detailed Functional Requirements & State Logic · VF143 (Part 12/27)

[REQ_VF143_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.15 Detailed Functional Requirements & State Logic · VF143 (Part 13/27)

[REQ_VF143_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.16 Detailed Functional Requirements & State Logic · VF143 (Part 14/27)

[REQ_VF143_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.17 Detailed Functional Requirements & State Logic · VF143 (Part 15/27)

[REQ_VF143_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.18 Detailed Functional Requirements & State Logic · VF143 (Part 16/27)

[REQ_VF143_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.19 Detailed Functional Requirements & State Logic · VF143 (Part 17/27)

[REQ_VF143_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.20 Detailed Functional Requirements & State Logic · VF143 (Part 18/27)

[REQ_VF143_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.21 Detailed Functional Requirements & State Logic · VF143 (Part 19/27)

[REQ_VF143_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.22 Detailed Functional Requirements & State Logic · VF143 (Part 20/27)

[REQ_VF143_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.23 Detailed Functional Requirements & State Logic · VF143 (Part 21/27)

[REQ_VF143_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.12 Indication Management

[REQ_VF143_IND] When V_TH_HB_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate HAND BRAKE ACTIVE.V1 on the display.

IND_ROW | HAND BRAKE ACTIVE.V1 | When V_TH_HB_Sts == ACTIVE on CAN-FD network | No (Standard HAND BRAKE Tellta

[REQ_VF143_IND] When V_TH_HB_FailSts == PRESENT, the IPC cluster shall activate HAND BRAKE FAIL.V1 on the display.

IND_ROW | HAND BRAKE FAIL.V1 | When V_TH_HB_FailSts == PRESENT | Yes - Check Hand Brake & Electric Park Brake

[REQ_VF143_IND] When CAN node timeout > V_TH_HB_TIMEOUT, the IPC cluster shall activate HAND BRAKE RECOVERY.V1 on the display.

IND_ROW | HAND BRAKE RECOVERY.V1 | When CAN node timeout > V_TH_HB_TIMEOUT | Yes - HAND BRAKE System Recovery

40.25 Detailed Functional Requirements & State Logic · VF143 (Part 23/27)

[REQ_VF143_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.26 Detailed Functional Requirements & State Logic · VF143 (Part 24/27)

[REQ_VF143_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.27 Detailed Functional Requirements & State Logic · VF143 (Part 25/27)

[REQ_VF143_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

40.14 Configuration Parameters

40.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF143_01 | V_TH_HB_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Pri

PAR_ROW | PAR_VF143_02 | V_TH_HB_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filtering

PAR_ROW | PAR_VF143_03 | CFG_VF143_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF143_04 | T_BCM_VF143_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

40.29 Detailed Functional Requirements & State Logic · VF143 (Part 27/27)

[REQ_VF143_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF143_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF143_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF143_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF143_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF143_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF143_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF143_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF143_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF143_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF143_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF143_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF143_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF143_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF143_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF143_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF143_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF143_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF143_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF143_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF143_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF143_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF143_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF143_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF143_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF143_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF143_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41 VF145 - Low Brake Fluid & EBD Brake System Warning (VF145_V1_PJ3U)

Document Code: VF145_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

41.1 Purpose and Functional Overview

[REQ_VF145_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF145 - Low Brake Fluid & EBD Brake System Warnin

41.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF145_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF145_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF145_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF145_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF145_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF145_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF145_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF145_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF145_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF145_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF145_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF145_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF145_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF145_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF145_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF145_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF145_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

41.2 Detailed Functional Requirements & State Logic · VF145 (Part 2/27)

[REQ_VF145_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.3 Detailed Functional Requirements & State Logic · VF145 (Part 3/27)

[REQ_VF145_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.4 Detailed Functional Requirements & State Logic · VF145 (Part 4/27)

[REQ_VF145_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.5 Detailed Functional Requirements & State Logic · VF145 (Part 5/27)

[REQ_VF145_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.6 Detailed Functional Requirements & State Logic · VF145 (Part 6/27)

[REQ_VF145_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.7 Detailed Functional Requirements & State Logic · VF145 (Part 7/27)

[REQ_VF145_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.8 Detailed Functional Requirements & State Logic · VF145 (Part 8/27)

[REQ_VF145_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.9 Detailed Functional Requirements & State Logic · VF145 (Part 9/27)

[REQ_VF145_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.10 Detailed Functional Requirements & State Logic · VF145 (Part 10/27)

[REQ_VF145_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.11 Detailed Functional Requirements & State Logic · VF145 (Part 11/27)

[REQ_VF145_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.14 Detailed Functional Requirements & State Logic · VF145 (Part 12/27)

[REQ_VF145_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.15 Detailed Functional Requirements & State Logic · VF145 (Part 13/27)

[REQ_VF145_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.16 Detailed Functional Requirements & State Logic · VF145 (Part 14/27)

[REQ_VF145_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.17 Detailed Functional Requirements & State Logic · VF145 (Part 15/27)

[REQ_VF145_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.18 Detailed Functional Requirements & State Logic · VF145 (Part 16/27)

[REQ_VF145_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.19 Detailed Functional Requirements & State Logic · VF145 (Part 17/27)

[REQ_VF145_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.20 Detailed Functional Requirements & State Logic · VF145 (Part 18/27)

[REQ_VF145_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.21 Detailed Functional Requirements & State Logic · VF145 (Part 19/27)

[REQ_VF145_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.22 Detailed Functional Requirements & State Logic · VF145 (Part 20/27)

[REQ_VF145_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.23 Detailed Functional Requirements & State Logic · VF145 (Part 21/27)

[REQ_VF145_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.12 Indication Management

[REQ_VF145_IND] When T_LBF_FILTER_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate LOW BRAKE FLUID ACTIVE.V1 on

IND_ROW | LOW BRAKE FLUID ACTIVE.V1 | When T_LBF_FILTER_Sts == ACTIVE on CAN-FD network | No (Standard LOW BRA

[REQ_VF145_IND] When T_LBF_FILTER_FailSts == PRESENT, the IPC cluster shall activate LOW BRAKE FLUID FAIL.V1 on the display.

IND_ROW | LOW BRAKE FLUID FAIL.V1 | When T_LBF_FILTER_FailSts == PRESENT | Yes - Check Low Brake Fluid & EBD B

[REQ_VF145_IND] When CAN node timeout > T_LBF_FILTER_TIMEOUT, the IPC cluster shall activate LOW BRAKE FLUID RECOVERY.V1 on

IND_ROW | LOW BRAKE FLUID RECOVERY.V1 | When CAN node timeout > T_LBF_FILTER_TIMEOUT | Yes - LOW BRAKE FLUID S

41.25 Detailed Functional Requirements & State Logic · VF145 (Part 23/27)

[REQ_VF145_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.26 Detailed Functional Requirements & State Logic · VF145 (Part 24/27)

[REQ_VF145_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.27 Detailed Functional Requirements & State Logic · VF145 (Part 25/27)

[REQ_VF145_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

41.14 Configuration Parameters

41.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF145_01 | T_LBF_FILTER_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration

PAR_ROW | PAR_VF145_02 | T_LBF_FILTER_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filt

PAR_ROW | PAR_VF145_03 | CFG_VF145_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF145_04 | T_BCM_VF145_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

41.29 Detailed Functional Requirements & State Logic · VF145 (Part 27/27)

[REQ_VF145_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF145_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF145_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF145_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF145_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF145_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF145_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF145_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF145_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF145_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF145_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF145_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF145_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF145_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF145_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF145_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF145_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF145_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF145_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF145_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF145_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF145_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF145_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF145_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF145_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF145_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF145_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42 VF147 - ABS & ESC Stability Control Telltale Logic (VF147_V1_PJ3U)

Document Code: VF147_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

42.1 Purpose and Functional Overview

[REQ_VF147_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF147 - ABS & ESC Stability Control Telltale Logic.

42.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF147_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF147_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF147_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF147_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF147_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF147_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF147_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF147_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF147_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF147_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF147_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF147_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF147_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF147_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF147_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF147_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF147_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

42.2 Detailed Functional Requirements & State Logic · VF147 (Part 2/27)

[REQ_VF147_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.3 Detailed Functional Requirements & State Logic · VF147 (Part 3/27)

[REQ_VF147_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.4 Detailed Functional Requirements & State Logic · VF147 (Part 4/27)

[REQ_VF147_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.5 Detailed Functional Requirements & State Logic · VF147 (Part 5/27)

[REQ_VF147_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.6 Detailed Functional Requirements & State Logic · VF147 (Part 6/27)

[REQ_VF147_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.7 Detailed Functional Requirements & State Logic · VF147 (Part 7/27)

[REQ_VF147_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.8 Detailed Functional Requirements & State Logic · VF147 (Part 8/27)

[REQ_VF147_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.9 Detailed Functional Requirements & State Logic · VF147 (Part 9/27)

[REQ_VF147_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.10 Detailed Functional Requirements & State Logic · VF147 (Part 10/27)

[REQ_VF147_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.11 Detailed Functional Requirements & State Logic · VF147 (Part 11/27)

[REQ_VF147_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.14 Detailed Functional Requirements & State Logic · VF147 (Part 12/27)

[REQ_VF147_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.15 Detailed Functional Requirements & State Logic · VF147 (Part 13/27)

[REQ_VF147_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.16 Detailed Functional Requirements & State Logic · VF147 (Part 14/27)

[REQ_VF147_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.17 Detailed Functional Requirements & State Logic · VF147 (Part 15/27)

[REQ_VF147_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.18 Detailed Functional Requirements & State Logic · VF147 (Part 16/27)

[REQ_VF147_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.19 Detailed Functional Requirements & State Logic · VF147 (Part 17/27)

[REQ_VF147_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.20 Detailed Functional Requirements & State Logic · VF147 (Part 18/27)

[REQ_VF147_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.21 Detailed Functional Requirements & State Logic · VF147 (Part 19/27)

[REQ_VF147_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.22 Detailed Functional Requirements & State Logic · VF147 (Part 20/27)

[REQ_VF147_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.23 Detailed Functional Requirements & State Logic · VF147 (Part 21/27)

[REQ_VF147_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.12 Indication Management

[REQ_VF147_IND] When F_ESC_BLINK_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate ESC STABILITY ACTIVE.V1 on the d

IND_ROW | ESC STABILITY ACTIVE.V1 | When F_ESC_BLINK_Sts == ACTIVE on CAN-FD network | No (Standard ESC STABIL

[REQ_VF147_IND] When F_ESC_BLINK_FailSts == PRESENT, the IPC cluster shall activate ESC STABILITY FAIL.V1 on the display.

IND_ROW | ESC STABILITY FAIL.V1 | When F_ESC_BLINK_FailSts == PRESENT | Yes - Check ABS & ESC Stability Contro

[REQ_VF147_IND] When CAN node timeout > F_ESC_BLINK_TIMEOUT, the IPC cluster shall activate ESC STABILITY RECOVERY.V1 on the d

IND_ROW | ESC STABILITY RECOVERY.V1 | When CAN node timeout > F_ESC_BLINK_TIMEOUT | Yes - ESC STABILITY System

42.25 Detailed Functional Requirements & State Logic · VF147 (Part 23/27)

[REQ_VF147_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.26 Detailed Functional Requirements & State Logic · VF147 (Part 24/27)

[REQ_VF147_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.27 Detailed Functional Requirements & State Logic · VF147 (Part 25/27)

[REQ_VF147_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

42.14 Configuration Parameters

42.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF147_01 | F_ESC_BLINK_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF147_02 | F_ESC_BLINK_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filte

PAR_ROW | PAR_VF147_03 | CFG_VF147_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF147_04 | T_BCM_VF147_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

42.29 Detailed Functional Requirements & State Logic · VF147 (Part 27/27)

[REQ_VF147_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF147_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF147_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF147_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF147_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF147_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF147_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF147_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF147_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF147_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF147_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF147_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF147_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF147_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF147_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF147_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF147_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF147_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF147_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF147_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF147_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF147_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF147_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF147_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF147_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF147_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF147_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43 VF149 - Hill Holder & Hill Descent Control (HDC) HMI (VF149_V1_PJ3U)

Document Code: VF149_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

43.1 Purpose and Functional Overview

[REQ_VF149_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF149 - Hill Holder & Hill Descent Control (HDC) HMI.

43.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF149_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF149_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF149_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF149_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF149_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF149_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF149_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF149_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF149_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF149_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF149_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF149_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF149_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF149_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF149_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF149_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF149_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

43.2 Detailed Functional Requirements & State Logic · VF149 (Part 2/27)

[REQ_VF149_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.3 Detailed Functional Requirements & State Logic · VF149 (Part 3/27)

[REQ_VF149_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.4 Detailed Functional Requirements & State Logic · VF149 (Part 4/27)

[REQ_VF149_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.5 Detailed Functional Requirements & State Logic · VF149 (Part 5/27)

[REQ_VF149_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.6 Detailed Functional Requirements & State Logic · VF149 (Part 6/27)

[REQ_VF149_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.7 Detailed Functional Requirements & State Logic · VF149 (Part 7/27)

[REQ_VF149_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.8 Detailed Functional Requirements & State Logic · VF149 (Part 8/27)

[REQ_VF149_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.9 Detailed Functional Requirements & State Logic · VF149 (Part 9/27)

[REQ_VF149_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.10 Detailed Functional Requirements & State Logic · VF149 (Part 10/27)

[REQ_VF149_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.11 Detailed Functional Requirements & State Logic · VF149 (Part 11/27)

[REQ_VF149_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.14 Detailed Functional Requirements & State Logic · VF149 (Part 12/27)

[REQ_VF149_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.15 Detailed Functional Requirements & State Logic · VF149 (Part 13/27)

[REQ_VF149_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.16 Detailed Functional Requirements & State Logic · VF149 (Part 14/27)

[REQ_VF149_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.17 Detailed Functional Requirements & State Logic · VF149 (Part 15/27)

[REQ_VF149_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.18 Detailed Functional Requirements & State Logic · VF149 (Part 16/27)

[REQ_VF149_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.19 Detailed Functional Requirements & State Logic · VF149 (Part 17/27)

[REQ_VF149_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.20 Detailed Functional Requirements & State Logic · VF149 (Part 18/27)

[REQ_VF149_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.21 Detailed Functional Requirements & State Logic · VF149 (Part 19/27)

[REQ_VF149_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.22 Detailed Functional Requirements & State Logic · VF149 (Part 20/27)

[REQ_VF149_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.23 Detailed Functional Requirements & State Logic · VF149 (Part 21/27)

[REQ_VF149_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.12 Indication Management

[REQ_VF149_IND] When V_HDC_MAX_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate HILL HOLDER ACTIVE.V1 on the disp

IND_ROW | HILL HOLDER ACTIVE.V1 | When V_HDC_MAX_Sts == ACTIVE on CAN-FD network | No (Standard HILL HOLDER Te

[REQ_VF149_IND] When V_HDC_MAX_FailSts == PRESENT, the IPC cluster shall activate HILL HOLDER FAIL.V1 on the display.

IND_ROW | HILL HOLDER FAIL.V1 | When V_HDC_MAX_FailSts == PRESENT | Yes - Check Hill Holder & Hill Descent Con

[REQ_VF149_IND] When CAN node timeout > V_HDC_MAX_TIMEOUT, the IPC cluster shall activate HILL HOLDER RECOVERY.V1 on the disp

IND_ROW | HILL HOLDER RECOVERY.V1 | When CAN node timeout > V_HDC_MAX_TIMEOUT | Yes - HILL HOLDER System Recov

43.25 Detailed Functional Requirements & State Logic · VF149 (Part 23/27)

[REQ_VF149_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.26 Detailed Functional Requirements & State Logic · VF149 (Part 24/27)

[REQ_VF149_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.27 Detailed Functional Requirements & State Logic · VF149 (Part 25/27)

[REQ_VF149_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

43.14 Configuration Parameters

43.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF149_01 | V_HDC_MAX_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | P

PAR_ROW | PAR_VF149_02 | V_HDC_MAX_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filteri

PAR_ROW | PAR_VF149_03 | CFG_VF149_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF149_04 | T_BCM_VF149_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

43.29 Detailed Functional Requirements & State Logic · VF149 (Part 27/27)

[REQ_VF149_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF149_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF149_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF149_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF149_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF149_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF149_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF149_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF149_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF149_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF149_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF149_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF149_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF149_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF149_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF149_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF149_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF149_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF149_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF149_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF149_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF149_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF149_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF149_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF149_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF149_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF149_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44 VF150 - Wiper, Washer Fluid & Rain Sensor HMI (VF150_V1_PJ3U)

Document Code: VF150_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

44.1 Purpose and Functional Overview

[REQ_VF150_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF150 - Wiper, Washer Fluid & Rain Sensor HMI.

44.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF150_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF150_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF150_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF150_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF150_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF150_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF150_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF150_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF150_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF150_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF150_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF150_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF150_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF150_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF150_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF150_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF150_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

44.2 Detailed Functional Requirements & State Logic · VF150 (Part 2/27)

[REQ_VF150_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.3 Detailed Functional Requirements & State Logic · VF150 (Part 3/27)

[REQ_VF150_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.4 Detailed Functional Requirements & State Logic · VF150 (Part 4/27)

[REQ_VF150_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.5 Detailed Functional Requirements & State Logic · VF150 (Part 5/27)

[REQ_VF150_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.6 Detailed Functional Requirements & State Logic · VF150 (Part 6/27)

[REQ_VF150_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.7 Detailed Functional Requirements & State Logic · VF150 (Part 7/27)

[REQ_VF150_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.8 Detailed Functional Requirements & State Logic · VF150 (Part 8/27)

[REQ_VF150_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.9 Detailed Functional Requirements & State Logic · VF150 (Part 9/27)

[REQ_VF150_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.10 Detailed Functional Requirements & State Logic · VF150 (Part 10/27)

[REQ_VF150_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.11 Detailed Functional Requirements & State Logic · VF150 (Part 11/27)

[REQ_VF150_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.14 Detailed Functional Requirements & State Logic · VF150 (Part 12/27)

[REQ_VF150_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.15 Detailed Functional Requirements & State Logic · VF150 (Part 13/27)

[REQ_VF150_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.16 Detailed Functional Requirements & State Logic · VF150 (Part 14/27)

[REQ_VF150_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.17 Detailed Functional Requirements & State Logic · VF150 (Part 15/27)

[REQ_VF150_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.18 Detailed Functional Requirements & State Logic · VF150 (Part 16/27)

[REQ_VF150_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.19 Detailed Functional Requirements & State Logic · VF150 (Part 17/27)

[REQ_VF150_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.20 Detailed Functional Requirements & State Logic · VF150 (Part 18/27)

[REQ_VF150_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.21 Detailed Functional Requirements & State Logic · VF150 (Part 19/27)

[REQ_VF150_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.22 Detailed Functional Requirements & State Logic · VF150 (Part 20/27)

[REQ_VF150_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.23 Detailed Functional Requirements & State Logic · VF150 (Part 21/27)

[REQ_VF150_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.12 Indication Management

[REQ_VF150_IND] When T_WASHER_FILT_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate WASHER FLUID ACTIVE.V1 on t

IND_ROW | WASHER FLUID ACTIVE.V1 | When T_WASHER_FILT_Sts == ACTIVE on CAN-FD network | No (Standard WASHER FL

[REQ_VF150_IND] When T_WASHER_FILT_FailSts == PRESENT, the IPC cluster shall activate WASHER FLUID FAIL.V1 on the display.

IND_ROW | WASHER FLUID FAIL.V1 | When T_WASHER_FILT_FailSts == PRESENT | Yes - Check Wiper, Washer Fluid & Rai

[REQ_VF150_IND] When CAN node timeout > T_WASHER_FILT_TIMEOUT, the IPC cluster shall activate WASHER FLUID RECOVERY.V1 on th

IND_ROW | WASHER FLUID RECOVERY.V1 | When CAN node timeout > T_WASHER_FILT_TIMEOUT | Yes - WASHER FLUID System

44.25 Detailed Functional Requirements & State Logic · VF150 (Part 23/27)

[REQ_VF150_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.26 Detailed Functional Requirements & State Logic · VF150 (Part 24/27)

[REQ_VF150_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.27 Detailed Functional Requirements & State Logic · VF150 (Part 25/27)

[REQ_VF150_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

44.14 Configuration Parameters

44.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | - | - | - | - | - | - | - | - | - | - | - | -

44.29 Detailed Functional Requirements & State Logic · VF150 (Part 27/27)

[REQ_VF150_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF150_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF150_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF150_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF150_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF150_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF150_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF150_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF150_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF150_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF150_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF150_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF150_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF150_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF150_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF150_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF150_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF150_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF150_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF150_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF150_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF150_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF150_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF150_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF150_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF150_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF150_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45 VF155 - ParkSense Front & Rear Parking Sensors Graphic (VF155_V1_PJ3U)

Document Code: VF155_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

45.1 Purpose and Functional Overview

[REQ_VF155_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF155 - ParkSense Front & Rear Parking Sensors Gra

45.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF155_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF155_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF155_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF155_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF155_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF155_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF155_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF155_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF155_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF155_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF155_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF155_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF155_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF155_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF155_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF155_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF155_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

45.2 Detailed Functional Requirements & State Logic · VF155 (Part 2/27)

[REQ_VF155_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.3 Detailed Functional Requirements & State Logic · VF155 (Part 3/27)

[REQ_VF155_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.4 Detailed Functional Requirements & State Logic · VF155 (Part 4/27)

[REQ_VF155_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.5 Detailed Functional Requirements & State Logic · VF155 (Part 5/27)

[REQ_VF155_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.6 Detailed Functional Requirements & State Logic · VF155 (Part 6/27)

[REQ_VF155_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.7 Detailed Functional Requirements & State Logic · VF155 (Part 7/27)

[REQ_VF155_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.8 Detailed Functional Requirements & State Logic · VF155 (Part 8/27)

[REQ_VF155_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.9 Detailed Functional Requirements & State Logic · VF155 (Part 9/27)

[REQ_VF155_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.10 Detailed Functional Requirements & State Logic · VF155 (Part 10/27)

[REQ_VF155_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.11 Detailed Functional Requirements & State Logic · VF155 (Part 11/27)

[REQ_VF155_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.14 Detailed Functional Requirements & State Logic · VF155 (Part 12/27)

[REQ_VF155_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.15 Detailed Functional Requirements & State Logic · VF155 (Part 13/27)

[REQ_VF155_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.16 Detailed Functional Requirements & State Logic · VF155 (Part 14/27)

[REQ_VF155_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.17 Detailed Functional Requirements & State Logic · VF155 (Part 15/27)

[REQ_VF155_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.18 Detailed Functional Requirements & State Logic · VF155 (Part 16/27)

[REQ_VF155_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.19 Detailed Functional Requirements & State Logic · VF155 (Part 17/27)

[REQ_VF155_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.20 Detailed Functional Requirements & State Logic · VF155 (Part 18/27)

[REQ_VF155_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.21 Detailed Functional Requirements & State Logic · VF155 (Part 19/27)

[REQ_VF155_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.22 Detailed Functional Requirements & State Logic · VF155 (Part 20/27)

[REQ_VF155_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.23 Detailed Functional Requirements & State Logic · VF155 (Part 21/27)

[REQ_VF155_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.12 Indication Management

[REQ_VF155_IND] When D_PARK_BEEP_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate PARKSENSE ACTIVE.V1 on the dis

IND_ROW | PARKSENSE ACTIVE.V1 | When D_PARK_BEEP_Sts == ACTIVE on CAN-FD network | No (Standard PARKSENSE Tell

[REQ_VF155_IND] When D_PARK_BEEP_FailSts == PRESENT, the IPC cluster shall activate PARKSENSE FAIL.V1 on the display.

IND_ROW | PARKSENSE FAIL.V1 | When D_PARK_BEEP_FailSts == PRESENT | Yes - Check ParkSense Front & Rear Parking

[REQ_VF155_IND] When CAN node timeout > D_PARK_BEEP_TIMEOUT, the IPC cluster shall activate PARKSENSE RECOVERY.V1 on the dis

IND_ROW | PARKSENSE RECOVERY.V1 | When CAN node timeout > D_PARK_BEEP_TIMEOUT | Yes - PARKSENSE System Recover

45.25 Detailed Functional Requirements & State Logic · VF155 (Part 23/27)

[REQ_VF155_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.26 Detailed Functional Requirements & State Logic · VF155 (Part 24/27)

[REQ_VF155_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.27 Detailed Functional Requirements & State Logic · VF155 (Part 25/27)

[REQ_VF155_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

45.14 Configuration Parameters

45.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF155_01 | D_PARK_BEEP_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF155_02 | D_PARK_BEEP_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filte

PAR_ROW | PAR_VF155_03 | CFG_VF155_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF155_04 | T_BCM_VF155_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

45.29 Detailed Functional Requirements & State Logic · VF155 (Part 27/27)

[REQ_VF155_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF155_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF155_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF155_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF155_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF155_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF155_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF155_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF155_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF155_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF155_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF155_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF155_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF155_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF155_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF155_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF155_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF155_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF155_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF155_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF155_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF155_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF155_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF155_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF155_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF155_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF155_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46 VF160 - Tire Pressure Monitoring System (TPMS) (VF160_V1_PJ3U)

Document Code: VF160_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

46.1 Purpose and Functional Overview

[REQ_VF160_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF160 - Tire Pressure Monitoring System (TPMS).

46.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF160_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF160_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF160_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF160_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF160_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF160_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF160_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF160_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF160_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF160_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF160_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF160_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF160_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF160_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF160_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF160_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF160_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

46.2 Detailed Functional Requirements & State Logic · VF160 (Part 2/27)

[REQ_VF160_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.3 Detailed Functional Requirements & State Logic · VF160 (Part 3/27)

[REQ_VF160_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.4 Detailed Functional Requirements & State Logic · VF160 (Part 4/27)

[REQ_VF160_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.5 Detailed Functional Requirements & State Logic · VF160 (Part 5/27)

[REQ_VF160_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.6 Detailed Functional Requirements & State Logic · VF160 (Part 6/27)

[REQ_VF160_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.7 Detailed Functional Requirements & State Logic · VF160 (Part 7/27)

[REQ_VF160_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.8 Detailed Functional Requirements & State Logic · VF160 (Part 8/27)

[REQ_VF160_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.9 Detailed Functional Requirements & State Logic · VF160 (Part 9/27)

[REQ_VF160_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.10 Detailed Functional Requirements & State Logic · VF160 (Part 10/27)

[REQ_VF160_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.11 Detailed Functional Requirements & State Logic · VF160 (Part 11/27)

[REQ_VF160_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.14 Detailed Functional Requirements & State Logic · VF160 (Part 12/27)

[REQ_VF160_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.15 Detailed Functional Requirements & State Logic · VF160 (Part 13/27)

[REQ_VF160_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.16 Detailed Functional Requirements & State Logic · VF160 (Part 14/27)

[REQ_VF160_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.17 Detailed Functional Requirements & State Logic · VF160 (Part 15/27)

[REQ_VF160_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.18 Detailed Functional Requirements & State Logic · VF160 (Part 16/27)

[REQ_VF160_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.19 Detailed Functional Requirements & State Logic · VF160 (Part 17/27)

[REQ_VF160_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.20 Detailed Functional Requirements & State Logic · VF160 (Part 18/27)

[REQ_VF160_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.21 Detailed Functional Requirements & State Logic · VF160 (Part 19/27)

[REQ_VF160_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.22 Detailed Functional Requirements & State Logic · VF160 (Part 20/27)

[REQ_VF160_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.23 Detailed Functional Requirements & State Logic · VF160 (Part 21/27)

[REQ_VF160_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.12 Indication Management

[REQ_VF160_IND] When T_TPMS_BLINK_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate TPMS PRESSURE ACTIVE.V1 on

IND_ROW | TPMS PRESSURE ACTIVE.V1 | When T_TPMS_BLINK_Sts == ACTIVE on CAN-FD network | No (Standard TPMS PRES

[REQ_VF160_IND] When T_TPMS_BLINK_FailSts == PRESENT, the IPC cluster shall activate TPMS PRESSURE FAIL.V1 on the display.

IND_ROW | TPMS PRESSURE FAIL.V1 | When T_TPMS_BLINK_FailSts == PRESENT | Yes - Check Tire Pressure Monitoring

[REQ_VF160_IND] When CAN node timeout > T_TPMS_BLINK_TIMEOUT, the IPC cluster shall activate TPMS PRESSURE RECOVERY.V1 on t

IND_ROW | TPMS PRESSURE RECOVERY.V1 | When CAN node timeout > T_TPMS_BLINK_TIMEOUT | Yes - TPMS PRESSURE Syste

46.25 Detailed Functional Requirements & State Logic · VF160 (Part 23/27)

[REQ_VF160_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.26 Detailed Functional Requirements & State Logic · VF160 (Part 24/27)

[REQ_VF160_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.27 Detailed Functional Requirements & State Logic · VF160 (Part 25/27)

[REQ_VF160_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

46.14 Configuration Parameters

46.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF160_01 | T_TPMS_BLINK_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration

PAR_ROW | PAR_VF160_02 | T_TPMS_BLINK_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filt

PAR_ROW | PAR_VF160_03 | CFG_VF160_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF160_04 | T_BCM_VF160_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

46.29 Detailed Functional Requirements & State Logic · VF160 (Part 27/27)

[REQ_VF160_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF160_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF160_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF160_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF160_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF160_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF160_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF160_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF160_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF160_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF160_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF160_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF160_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF160_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF160_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF160_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF160_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF160_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF160_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF160_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF160_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF160_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF160_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF160_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF160_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF160_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF160_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47 VF165 - Drive Mode Selector (Sport / Eco / Auto) HMI (VF165_V1_PJ3U)

Document Code: VF165_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

47.1 Purpose and Functional Overview

[REQ_VF165_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF165 - Drive Mode Selector (Sport / Eco / Auto) HMI.

47.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF165_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF165_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF165_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF165_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF165_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF165_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF165_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF165_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF165_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF165_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF165_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF165_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF165_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF165_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF165_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF165_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF165_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

47.2 Detailed Functional Requirements & State Logic · VF165 (Part 2/27)

[REQ_VF165_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.3 Detailed Functional Requirements & State Logic · VF165 (Part 3/27)

[REQ_VF165_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.4 Detailed Functional Requirements & State Logic · VF165 (Part 4/27)

[REQ_VF165_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.5 Detailed Functional Requirements & State Logic · VF165 (Part 5/27)

[REQ_VF165_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.6 Detailed Functional Requirements & State Logic · VF165 (Part 6/27)

[REQ_VF165_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.7 Detailed Functional Requirements & State Logic · VF165 (Part 7/27)

[REQ_VF165_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.8 Detailed Functional Requirements & State Logic · VF165 (Part 8/27)

[REQ_VF165_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.9 Detailed Functional Requirements & State Logic · VF165 (Part 9/27)

[REQ_VF165_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.10 Detailed Functional Requirements & State Logic · VF165 (Part 10/27)

[REQ_VF165_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.11 Detailed Functional Requirements & State Logic · VF165 (Part 11/27)

[REQ_VF165_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.14 Detailed Functional Requirements & State Logic · VF165 (Part 12/27)

[REQ_VF165_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.15 Detailed Functional Requirements & State Logic · VF165 (Part 13/27)

[REQ_VF165_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.16 Detailed Functional Requirements & State Logic · VF165 (Part 14/27)

[REQ_VF165_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.17 Detailed Functional Requirements & State Logic · VF165 (Part 15/27)

[REQ_VF165_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.18 Detailed Functional Requirements & State Logic · VF165 (Part 16/27)

[REQ_VF165_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.19 Detailed Functional Requirements & State Logic · VF165 (Part 17/27)

[REQ_VF165_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.20 Detailed Functional Requirements & State Logic · VF165 (Part 18/27)

[REQ_VF165_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.21 Detailed Functional Requirements & State Logic · VF165 (Part 19/27)

[REQ_VF165_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.22 Detailed Functional Requirements & State Logic · VF165 (Part 20/27)

[REQ_VF165_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.23 Detailed Functional Requirements & State Logic · VF165 (Part 21/27)

[REQ_VF165_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.12 Indication Management

[REQ_VF165_IND] When T_MODE_BANNER_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate DRIVE MODE ACTIVE.V1 on th

IND_ROW | DRIVE MODE ACTIVE.V1 | When T_MODE_BANNER_Sts == ACTIVE on CAN-FD network | No (Standard DRIVE MODE

[REQ_VF165_IND] When T_MODE_BANNER_FailSts == PRESENT, the IPC cluster shall activate DRIVE MODE FAIL.V1 on the display.

IND_ROW | DRIVE MODE FAIL.V1 | When T_MODE_BANNER_FailSts == PRESENT | Yes - Check Drive Mode Selector (Sport

[REQ_VF165_IND] When CAN node timeout > T_MODE_BANNER_TIMEOUT, the IPC cluster shall activate DRIVE MODE RECOVERY.V1 on th

IND_ROW | DRIVE MODE RECOVERY.V1 | When CAN node timeout > T_MODE_BANNER_TIMEOUT | Yes - DRIVE MODE System Rec

47.25 Detailed Functional Requirements & State Logic · VF165 (Part 23/27)

[REQ_VF165_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.26 Detailed Functional Requirements & State Logic · VF165 (Part 24/27)

[REQ_VF165_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.27 Detailed Functional Requirements & State Logic · VF165 (Part 25/27)

[REQ_VF165_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

47.14 Configuration Parameters

47.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF165_01 | T_MODE_BANNER_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration

PAR_ROW | PAR_VF165_02 | T_MODE_BANNER_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Fil

PAR_ROW | PAR_VF165_03 | CFG_VF165_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF165_04 | T_BCM_VF165_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

47.29 Detailed Functional Requirements & State Logic · VF165 (Part 27/27)

[REQ_VF165_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF165_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF165_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF165_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF165_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF165_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF165_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF165_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF165_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF165_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF165_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF165_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF165_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF165_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF165_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF165_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF165_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF165_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF165_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF165_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF165_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF165_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF165_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF165_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF165_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF165_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF165_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48 VF170 - Service Interval & Oil Life Reset Management (VF170_V1_PJ3U)

Document Code: VF170_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

48.1 Purpose and Functional Overview

[REQ_VF170_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF170 - Service Interval & Oil Life Reset Management.

48.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF170_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF170_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF170_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF170_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF170_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF170_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF170_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF170_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF170_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF170_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF170_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF170_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF170_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF170_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF170_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF170_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF170_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

48.2 Detailed Functional Requirements & State Logic · VF170 (Part 2/27)

[REQ_VF170_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.3 Detailed Functional Requirements & State Logic · VF170 (Part 3/27)

[REQ_VF170_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.4 Detailed Functional Requirements & State Logic · VF170 (Part 4/27)

[REQ_VF170_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.5 Detailed Functional Requirements & State Logic · VF170 (Part 5/27)

[REQ_VF170_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.6 Detailed Functional Requirements & State Logic · VF170 (Part 6/27)

[REQ_VF170_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.7 Detailed Functional Requirements & State Logic · VF170 (Part 7/27)

[REQ_VF170_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.8 Detailed Functional Requirements & State Logic · VF170 (Part 8/27)

[REQ_VF170_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.9 Detailed Functional Requirements & State Logic · VF170 (Part 9/27)

[REQ_VF170_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.10 Detailed Functional Requirements & State Logic · VF170 (Part 10/27)

[REQ_VF170_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.11 Detailed Functional Requirements & State Logic · VF170 (Part 11/27)

[REQ_VF170_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.14 Detailed Functional Requirements & State Logic · VF170 (Part 12/27)

[REQ_VF170_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.15 Detailed Functional Requirements & State Logic · VF170 (Part 13/27)

[REQ_VF170_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.16 Detailed Functional Requirements & State Logic · VF170 (Part 14/27)

[REQ_VF170_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.17 Detailed Functional Requirements & State Logic · VF170 (Part 15/27)

[REQ_VF170_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.18 Detailed Functional Requirements & State Logic · VF170 (Part 16/27)

[REQ_VF170_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.19 Detailed Functional Requirements & State Logic · VF170 (Part 17/27)

[REQ_VF170_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.20 Detailed Functional Requirements & State Logic · VF170 (Part 18/27)

[REQ_VF170_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.21 Detailed Functional Requirements & State Logic · VF170 (Part 19/27)

[REQ_VF170_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.22 Detailed Functional Requirements & State Logic · VF170 (Part 20/27)

[REQ_VF170_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.23 Detailed Functional Requirements & State Logic · VF170 (Part 21/27)

[REQ_VF170_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.12 Indication Management

[REQ_VF170_IND] When D_SERVICE_WARN_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate SERVICE DUE ACTIVE.V1 on

IND_ROW | SERVICE DUE ACTIVE.V1 | When D_SERVICE_WARN_Sts == ACTIVE on CAN-FD network | No (Standard SERVICE D

[REQ_VF170_IND] When D_SERVICE_WARN_FailSts == PRESENT, the IPC cluster shall activate SERVICE DUE FAIL.V1 on the display.

IND_ROW | SERVICE DUE FAIL.V1 | When D_SERVICE_WARN_FailSts == PRESENT | Yes - Check Service Interval & Oil Li

[REQ_VF170_IND] When CAN node timeout > D_SERVICE_WARN_TIMEOUT, the IPC cluster shall activate SERVICE DUE RECOVERY.V1 on

IND_ROW | SERVICE DUE RECOVERY.V1 | When CAN node timeout > D_SERVICE_WARN_TIMEOUT | Yes - SERVICE DUE System

48.25 Detailed Functional Requirements & State Logic · VF170 (Part 23/27)

[REQ_VF170_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.26 Detailed Functional Requirements & State Logic · VF170 (Part 24/27)

[REQ_VF170_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.27 Detailed Functional Requirements & State Logic · VF170 (Part 25/27)

[REQ_VF170_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

48.14 Configuration Parameters

48.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF170_01 | D_SERVICE_WARN_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibratio

PAR_ROW | PAR_VF170_02 | D_SERVICE_WARN_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Fi

PAR_ROW | PAR_VF170_03 | CFG_VF170_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF170_04 | T_BCM_VF170_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

48.29 Detailed Functional Requirements & State Logic · VF170 (Part 27/27)

[REQ_VF170_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF170_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF170_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF170_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF170_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF170_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF170_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF170_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF170_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF170_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF170_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF170_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF170_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF170_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF170_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF170_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF170_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF170_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF170_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF170_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF170_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF170_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF170_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF170_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF170_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF170_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF170_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49 VF175 - Outside Temperature & Ice Warning Snowflake (VF175_V1_PJ3U)

Document Code: VF175_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

49.1 Purpose and Functional Overview

[REQ_VF175_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF175 - Outside Temperature & Ice Warning Snowflak

49.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF175_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF175_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF175_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF175_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF175_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF175_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF175_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF175_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF175_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF175_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF175_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF175_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF175_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF175_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF175_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF175_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF175_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

49.2 Detailed Functional Requirements & State Logic · VF175 (Part 2/27)

[REQ_VF175_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.3 Detailed Functional Requirements & State Logic · VF175 (Part 3/27)

[REQ_VF175_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.4 Detailed Functional Requirements & State Logic · VF175 (Part 4/27)

[REQ_VF175_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.5 Detailed Functional Requirements & State Logic · VF175 (Part 5/27)

[REQ_VF175_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.6 Detailed Functional Requirements & State Logic · VF175 (Part 6/27)

[REQ_VF175_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.7 Detailed Functional Requirements & State Logic · VF175 (Part 7/27)

[REQ_VF175_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.8 Detailed Functional Requirements & State Logic · VF175 (Part 8/27)

[REQ_VF175_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.9 Detailed Functional Requirements & State Logic · VF175 (Part 9/27)

[REQ_VF175_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.10 Detailed Functional Requirements & State Logic · VF175 (Part 10/27)

[REQ_VF175_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.11 Detailed Functional Requirements & State Logic · VF175 (Part 11/27)

[REQ_VF175_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.14 Detailed Functional Requirements & State Logic · VF175 (Part 12/27)

[REQ_VF175_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.15 Detailed Functional Requirements & State Logic · VF175 (Part 13/27)

[REQ_VF175_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.16 Detailed Functional Requirements & State Logic · VF175 (Part 14/27)

[REQ_VF175_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.17 Detailed Functional Requirements & State Logic · VF175 (Part 15/27)

[REQ_VF175_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.18 Detailed Functional Requirements & State Logic · VF175 (Part 16/27)

[REQ_VF175_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.19 Detailed Functional Requirements & State Logic · VF175 (Part 17/27)

[REQ_VF175_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.20 Detailed Functional Requirements & State Logic · VF175 (Part 18/27)

[REQ_VF175_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.21 Detailed Functional Requirements & State Logic · VF175 (Part 19/27)

[REQ_VF175_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.22 Detailed Functional Requirements & State Logic · VF175 (Part 20/27)

[REQ_VF175_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.23 Detailed Functional Requirements & State Logic · VF175 (Part 21/27)

[REQ_VF175_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.12 Indication Management

[REQ_VF175_IND] When T_ICE_TH_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate ICE WARNING ACTIVE.V1 on the displa

IND_ROW | ICE WARNING ACTIVE.V1 | When T_ICE_TH_Sts == ACTIVE on CAN-FD network | No (Standard ICE WARNING Tel

[REQ_VF175_IND] When T_ICE_TH_FailSts == PRESENT, the IPC cluster shall activate ICE WARNING FAIL.V1 on the display.

IND_ROW | ICE WARNING FAIL.V1 | When T_ICE_TH_FailSts == PRESENT | Yes - Check Outside Temperature & Ice Warni

[REQ_VF175_IND] When CAN node timeout > T_ICE_TH_TIMEOUT, the IPC cluster shall activate ICE WARNING RECOVERY.V1 on the displa

IND_ROW | ICE WARNING RECOVERY.V1 | When CAN node timeout > T_ICE_TH_TIMEOUT | Yes - ICE WARNING System Recove

49.25 Detailed Functional Requirements & State Logic · VF175 (Part 23/27)

[REQ_VF175_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.26 Detailed Functional Requirements & State Logic · VF175 (Part 24/27)

[REQ_VF175_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.27 Detailed Functional Requirements & State Logic · VF175 (Part 25/27)

[REQ_VF175_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

49.14 Configuration Parameters

49.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF175_01 | T_ICE_TH_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration | Pr

PAR_ROW | PAR_VF175_02 | T_ICE_TH_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filterin

PAR_ROW | PAR_VF175_03 | CFG_VF175_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF175_04 | T_BCM_VF175_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

49.29 Detailed Functional Requirements & State Logic · VF175 (Part 27/27)

[REQ_VF175_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF175_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF175_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF175_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF175_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF175_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF175_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF175_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF175_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF175_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF175_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF175_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF175_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF175_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF175_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF175_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF175_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF175_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF175_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF175_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF175_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF175_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF175_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF175_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF175_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF175_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF175_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50 VF180 - Immobilizer & Passive Entry Key Not Detected (VF180_V1_PJ3U)

Document Code: VF180_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

50.1 Purpose and Functional Overview

[REQ_VF180_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF180 - Immobilizer & Passive Entry Key Not Detected

50.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF180_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF180_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF180_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF180_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF180_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF180_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF180_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF180_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF180_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF180_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF180_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF180_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF180_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF180_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF180_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF180_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF180_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

50.2 Detailed Functional Requirements & State Logic · VF180 (Part 2/27)

[REQ_VF180_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.3 Detailed Functional Requirements & State Logic · VF180 (Part 3/27)

[REQ_VF180_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.4 Detailed Functional Requirements & State Logic · VF180 (Part 4/27)

[REQ_VF180_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.5 Detailed Functional Requirements & State Logic · VF180 (Part 5/27)

[REQ_VF180_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.6 Detailed Functional Requirements & State Logic · VF180 (Part 6/27)

[REQ_VF180_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.7 Detailed Functional Requirements & State Logic · VF180 (Part 7/27)

[REQ_VF180_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.8 Detailed Functional Requirements & State Logic · VF180 (Part 8/27)

[REQ_VF180_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.9 Detailed Functional Requirements & State Logic · VF180 (Part 9/27)

[REQ_VF180_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.10 Detailed Functional Requirements & State Logic · VF180 (Part 10/27)

[REQ_VF180_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.11 Detailed Functional Requirements & State Logic · VF180 (Part 11/27)

[REQ_VF180_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.14 Detailed Functional Requirements & State Logic · VF180 (Part 12/27)

[REQ_VF180_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.15 Detailed Functional Requirements & State Logic · VF180 (Part 13/27)

[REQ_VF180_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.16 Detailed Functional Requirements & State Logic · VF180 (Part 14/27)

[REQ_VF180_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.17 Detailed Functional Requirements & State Logic · VF180 (Part 15/27)

[REQ_VF180_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.18 Detailed Functional Requirements & State Logic · VF180 (Part 16/27)

[REQ_VF180_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.19 Detailed Functional Requirements & State Logic · VF180 (Part 17/27)

[REQ_VF180_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.20 Detailed Functional Requirements & State Logic · VF180 (Part 18/27)

[REQ_VF180_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.21 Detailed Functional Requirements & State Logic · VF180 (Part 19/27)

[REQ_VF180_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.22 Detailed Functional Requirements & State Logic · VF180 (Part 20/27)

[REQ_VF180_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.23 Detailed Functional Requirements & State Logic · VF180 (Part 21/27)

[REQ_VF180_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.12 Indication Management

[REQ_VF180_IND] When T_IMMO_POPUP_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate KEY NOT DETECTED ACTIVE.V1

IND_ROW | KEY NOT DETECTED ACTIVE.V1 | When T_IMMO_POPUP_Sts == ACTIVE on CAN-FD network | No (Standard KEY NO

[REQ_VF180_IND] When T_IMMO_POPUP_FailSts == PRESENT, the IPC cluster shall activate KEY NOT DETECTED FAIL.V1 on the display.

IND_ROW | KEY NOT DETECTED FAIL.V1 | When T_IMMO_POPUP_FailSts == PRESENT | Yes - Check Immobilizer & Passive

[REQ_VF180_IND] When CAN node timeout > T_IMMO_POPUP_TIMEOUT, the IPC cluster shall activate KEY NOT DETECTED RECOVERY.V1

IND_ROW | KEY NOT DETECTED RECOVERY.V1 | When CAN node timeout > T_IMMO_POPUP_TIMEOUT | Yes - KEY NOT DETECTED

50.25 Detailed Functional Requirements & State Logic · VF180 (Part 23/27)

[REQ_VF180_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.26 Detailed Functional Requirements & State Logic · VF180 (Part 24/27)

[REQ_VF180_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.27 Detailed Functional Requirements & State Logic · VF180 (Part 25/27)

[REQ_VF180_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

50.14 Configuration Parameters

50.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | - | - | - | - | - | - | - | - | - | - | -

50.29 Detailed Functional Requirements & State Logic · VF180 (Part 27/27)

[REQ_VF180_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF180_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF180_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF180_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF180_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF180_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF180_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF180_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF180_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF180_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF180_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF180_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF180_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF180_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF180_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF180_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF180_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF180_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF180_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF180_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF180_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF180_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF180_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF180_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF180_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF180_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF180_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51 VF185 - Acoustic Chime Priority & Arbitration Manager (VF185_V1_PJ3U)

Document Code: VF185_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

51.1 Purpose and Functional Overview

[REQ_VF185_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF185 - Acoustic Chime Priority & Arbitration Manager

51.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF185_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF185_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF185_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF185_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF185_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF185_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF185_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF185_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF185_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF185_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF185_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF185_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF185_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF185_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF185_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF185_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF185_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

51.2 Detailed Functional Requirements & State Logic · VF185 (Part 2/27)

[REQ_VF185_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.3 Detailed Functional Requirements & State Logic · VF185 (Part 3/27)

[REQ_VF185_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.4 Detailed Functional Requirements & State Logic · VF185 (Part 4/27)

[REQ_VF185_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.5 Detailed Functional Requirements & State Logic · VF185 (Part 5/27)

[REQ_VF185_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.6 Detailed Functional Requirements & State Logic · VF185 (Part 6/27)

[REQ_VF185_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.7 Detailed Functional Requirements & State Logic · VF185 (Part 7/27)

[REQ_VF185_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.8 Detailed Functional Requirements & State Logic · VF185 (Part 8/27)

[REQ_VF185_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.9 Detailed Functional Requirements & State Logic · VF185 (Part 9/27)

[REQ_VF185_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.10 Detailed Functional Requirements & State Logic · VF185 (Part 10/27)

[REQ_VF185_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.11 Detailed Functional Requirements & State Logic · VF185 (Part 11/27)

[REQ_VF185_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.14 Detailed Functional Requirements & State Logic · VF185 (Part 12/27)

[REQ_VF185_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.15 Detailed Functional Requirements & State Logic · VF185 (Part 13/27)

[REQ_VF185_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.16 Detailed Functional Requirements & State Logic · VF185 (Part 14/27)

[REQ_VF185_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.17 Detailed Functional Requirements & State Logic · VF185 (Part 15/27)

[REQ_VF185_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.18 Detailed Functional Requirements & State Logic · VF185 (Part 16/27)

[REQ_VF185_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.19 Detailed Functional Requirements & State Logic · VF185 (Part 17/27)

[REQ_VF185_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.20 Detailed Functional Requirements & State Logic · VF185 (Part 18/27)

[REQ_VF185_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.21 Detailed Functional Requirements & State Logic · VF185 (Part 19/27)

[REQ_VF185_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.22 Detailed Functional Requirements & State Logic · VF185 (Part 20/27)

[REQ_VF185_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.23 Detailed Functional Requirements & State Logic · VF185 (Part 21/27)

[REQ_VF185_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.12 Indication Management

[REQ_VF185_IND] When T_CHIME_GAP_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate CHIME ARBITRATION ACTIVE.V1 o

IND_ROW | CHIME ARBITRATION ACTIVE.V1 | When T_CHIME_GAP_Sts == ACTIVE on CAN-FD network | No (Standard CHIME

[REQ_VF185_IND] When T_CHIME_GAP_FailSts == PRESENT, the IPC cluster shall activate CHIME ARBITRATION FAIL.V1 on the display.

IND_ROW | CHIME ARBITRATION FAIL.V1 | When T_CHIME_GAP_FailSts == PRESENT | Yes - Check Acoustic Chime Priorit

[REQ_VF185_IND] When CAN node timeout > T_CHIME_GAP_TIMEOUT, the IPC cluster shall activate CHIME ARBITRATION RECOVERY.V1 o

IND_ROW | CHIME ARBITRATION RECOVERY.V1 | When CAN node timeout > T_CHIME_GAP_TIMEOUT | Yes - CHIME ARBITRATIO

51.25 Detailed Functional Requirements & State Logic · VF185 (Part 23/27)

[REQ_VF185_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.26 Detailed Functional Requirements & State Logic · VF185 (Part 24/27)

[REQ_VF185_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.27 Detailed Functional Requirements & State Logic · VF185 (Part 25/27)

[REQ_VF185_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

51.14 Configuration Parameters

51.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF185_01 | T_CHIME_GAP_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibration |

PAR_ROW | PAR_VF185_02 | T_CHIME_GAP_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Filte

PAR_ROW | PAR_VF185_03 | CFG_VF185_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF185_04 | T_BCM_VF185_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

51.29 Detailed Functional Requirements & State Logic · VF185 (Part 27/27)

[REQ_VF185_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF185_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF185_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF185_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF185_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF185_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF185_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF185_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF185_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF185_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF185_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF185_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF185_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF185_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF185_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF185_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF185_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF185_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF185_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF185_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF185_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF185_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF185_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF185_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF185_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF185_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF185_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52 VF190 - Display Brightness & Day/Night Dimming (VF190_V1_PJ3U)

Document Code: VF190_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

52.1 Purpose and Functional Overview

[REQ_VF190_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF190 - Display Brightness & Day/Night Dimming.

52.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver

CAN_ROW | STATUS_B_CAN_01 | VF190_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_02 | VF190_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_03 | VF190_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_04 | VF190_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_05 | VF190_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_06 | VF190_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_07 | VF190_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_08 | VF190_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_09 | VF190_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_10 | VF190_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_11 | VF190_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_12 | VF190_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_13 | VF190_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_14 | VF190_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_15 | VF190_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_16 | VF190_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC

CAN_ROW | STATUS_B_CAN_17 | VF190_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

52.2 Detailed Functional Requirements & State Logic · VF190 (Part 2/27)

[REQ_VF190_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.3 Detailed Functional Requirements & State Logic · VF190 (Part 3/27)

[REQ_VF190_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.4 Detailed Functional Requirements & State Logic · VF190 (Part 4/27)

[REQ_VF190_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.5 Detailed Functional Requirements & State Logic · VF190 (Part 5/27)

[REQ_VF190_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.6 Detailed Functional Requirements & State Logic · VF190 (Part 6/27)

[REQ_VF190_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.7 Detailed Functional Requirements & State Logic · VF190 (Part 7/27)

[REQ_VF190_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.8 Detailed Functional Requirements & State Logic · VF190 (Part 8/27)

[REQ_VF190_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.9 Detailed Functional Requirements & State Logic · VF190 (Part 9/27)

[REQ_VF190_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.10 Detailed Functional Requirements & State Logic · VF190 (Part 10/27)

[REQ_VF190_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.11 Detailed Functional Requirements & State Logic · VF190 (Part 11/27)

[REQ_VF190_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.14 Detailed Functional Requirements & State Logic · VF190 (Part 12/27)

[REQ_VF190_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.15 Detailed Functional Requirements & State Logic · VF190 (Part 13/27)

[REQ_VF190_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.16 Detailed Functional Requirements & State Logic · VF190 (Part 14/27)

[REQ_VF190_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.17 Detailed Functional Requirements & State Logic · VF190 (Part 15/27)

[REQ_VF190_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.18 Detailed Functional Requirements & State Logic · VF190 (Part 16/27)

[REQ_VF190_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.19 Detailed Functional Requirements & State Logic · VF190 (Part 17/27)

[REQ_VF190_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.20 Detailed Functional Requirements & State Logic · VF190 (Part 18/27)

[REQ_VF190_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.21 Detailed Functional Requirements & State Logic · VF190 (Part 19/27)

[REQ_VF190_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.22 Detailed Functional Requirements & State Logic · VF190 (Part 20/27)

[REQ_VF190_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.23 Detailed Functional Requirements & State Logic · VF190 (Part 21/27)

[REQ_VF190_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.12 Indication Management

[REQ_VF190_IND] When PWM_DAY_DEFAULT_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate DISPLAY DIMMING ACTIVE
IND_ROW | DISPLAY DIMMING ACTIVE.V1 | When PWM_DAY_DEFAULT_Sts == ACTIVE on CAN-FD network | No (Standard DISP

[REQ_VF190_IND] When PWM_DAY_DEFAULT_FailSts == PRESENT, the IPC cluster shall activate DISPLAY DIMMING FAIL.V1 on the display
IND_ROW | DISPLAY DIMMING FAIL.V1 | When PWM_DAY_DEFAULT_FailSts == PRESENT | Yes - Check Display Brightness &

[REQ_VF190_IND] When CAN node timeout > PWM_DAY_DEFAULT_TIMEOUT, the IPC cluster shall activate DISPLAY DIMMING RECOVERY.
IND_ROW | DISPLAY DIMMING RECOVERY.V1 | When CAN node timeout > PWM_DAY_DEFAULT_TIMEOUT | Yes - DISPLAY DIMMIN

52.25 Detailed Functional Requirements & State Logic · VF190 (Part 23/27)

[REQ_VF190_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.26 Detailed Functional Requirements & State Logic · VF190 (Part 24/27)

[REQ_VF190_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.27 Detailed Functional Requirements & State Logic · VF190 (Part 25/27)

[REQ_VF190_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

52.14 Configuration Parameters

52.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF190_01 | PWM_DAY_DEFAULT_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibrati

PAR_ROW | PAR_VF190_02 | PWM_DAY_DEFAULT_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal F

PAR_ROW | PAR_VF190_03 | CFG_VF190_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF190_04 | T_BCM_VF190_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

52.29 Detailed Functional Requirements & State Logic · VF190 (Part 27/27)

[REQ_VF190_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF190_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF190_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF190_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF190_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF190_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF190_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF190_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF190_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF190_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF190_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF190_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF190_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF190_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF190_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF190_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF190_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF190_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF190_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF190_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF190_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF190_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF190_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF190_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF190_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF190_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF190_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53 VF195 - Cluster Self-Test & Bulb Check Sequence (VF195_V1_PJ3U)

Document Code: VF195_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

53.1 Purpose and Functional Overview

[REQ_VF195_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF195 - Cluster Self-Test & Bulb Check Sequence.

53.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF195_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF195_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF195_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF195_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF195_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF195_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF195_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF195_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF195_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF195_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF195_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF195_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF195_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF195_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF195_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF195_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF195_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

53.2 Detailed Functional Requirements & State Logic · VF195 (Part 2/27)

[REQ_VF195_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.3 Detailed Functional Requirements & State Logic · VF195 (Part 3/27)

[REQ_VF195_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.4 Detailed Functional Requirements & State Logic · VF195 (Part 4/27)

[REQ_VF195_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.5 Detailed Functional Requirements & State Logic · VF195 (Part 5/27)

[REQ_VF195_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.6 Detailed Functional Requirements & State Logic · VF195 (Part 6/27)

[REQ_VF195_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.7 Detailed Functional Requirements & State Logic · VF195 (Part 7/27)

[REQ_VF195_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.8 Detailed Functional Requirements & State Logic · VF195 (Part 8/27)

[REQ_VF195_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.9 Detailed Functional Requirements & State Logic · VF195 (Part 9/27)

[REQ_VF195_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.10 Detailed Functional Requirements & State Logic · VF195 (Part 10/27)

[REQ_VF195_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.11 Detailed Functional Requirements & State Logic · VF195 (Part 11/27)

[REQ_VF195_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.14 Detailed Functional Requirements & State Logic · VF195 (Part 12/27)

[REQ_VF195_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.15 Detailed Functional Requirements & State Logic · VF195 (Part 13/27)

[REQ_VF195_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.16 Detailed Functional Requirements & State Logic · VF195 (Part 14/27)

[REQ_VF195_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.17 Detailed Functional Requirements & State Logic · VF195 (Part 15/27)

[REQ_VF195_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.18 Detailed Functional Requirements & State Logic · VF195 (Part 16/27)

[REQ_VF195_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.19 Detailed Functional Requirements & State Logic · VF195 (Part 17/27)

[REQ_VF195_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.20 Detailed Functional Requirements & State Logic · VF195 (Part 18/27)

[REQ_VF195_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.21 Detailed Functional Requirements & State Logic · VF195 (Part 19/27)

[REQ_VF195_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.22 Detailed Functional Requirements & State Logic · VF195 (Part 20/27)

[REQ_VF195_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.23 Detailed Functional Requirements & State Logic · VF195 (Part 21/27)

[REQ_VF195_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.12 Indication Management

[REQ_VF195_IND] When T_BULB_CHECK_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate BULB CHECK ACTIVE.V1 on the

IND_ROW | BULB CHECK ACTIVE.V1 | When T_BULB_CHECK_Sts == ACTIVE on CAN-FD network | No (Standard BULB CHECK T

[REQ_VF195_IND] When T_BULB_CHECK_FailSts == PRESENT, the IPC cluster shall activate BULB CHECK FAIL.V1 on the display.

IND_ROW | BULB CHECK FAIL.V1 | When T_BULB_CHECK_FailSts == PRESENT | Yes - Check Cluster Self-Test & Bulb Che

[REQ_VF195_IND] When CAN node timeout > T_BULB_CHECK_TIMEOUT, the IPC cluster shall activate BULB CHECK RECOVERY.V1 on the

IND_ROW | BULB CHECK RECOVERY.V1 | When CAN node timeout > T_BULB_CHECK_TIMEOUT | Yes - BULB CHECK System Reco

53.25 Detailed Functional Requirements & State Logic · VF195 (Part 23/27)

[REQ_VF195_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.26 Detailed Functional Requirements & State Logic · VF195 (Part 24/27)

[REQ_VF195_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.27 Detailed Functional Requirements & State Logic · VF195 (Part 25/27)

[REQ_VF195_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

53.14 Configuration Parameters

53.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | - | - | - | - | - | - | - | - | - | - | -

53.29 Detailed Functional Requirements & State Logic · VF195 (Part 27/27)

[REQ_VF195_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF195_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF195_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF195_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF195_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF195_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF195_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF195_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF195_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF195_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF195_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF195_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF195_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF195_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF195_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF195_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF195_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF195_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF195_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF195_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF195_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF195_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF195_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF195_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF195_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF195_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF195_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54 VF200 - CAN-FD Network Timeout & Node Recovery HMI (VF200_V1_PJ3U)

Document Code: VF200_V1_PJ3U | Target Subsystem: IPC - Instrument Panel Cluster 10 (CAN)

54.1 Purpose and Functional Overview

[REQ_VF200_0001] The IPC shall manage the visual, acoustic and diagnostic behavior for VF200 - CAN-FD Network Timeout & Node Recovery H

54.4 Input / Output CAN-FD Signals Table (Distractor Table)

CAN Message | Signal Name | Network | Period (ms) | Sender -> Receiver
CAN_ROW | STATUS_B_CAN_01 | VF200_SigSts_01 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_02 | VF200_SigSts_02 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_03 | VF200_SigSts_03 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_04 | VF200_SigSts_04 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_05 | VF200_SigSts_05 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_06 | VF200_SigSts_06 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_07 | VF200_SigSts_07 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_08 | VF200_SigSts_08 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_09 | VF200_SigSts_09 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_10 | VF200_SigSts_10 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_11 | VF200_SigSts_11 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_12 | VF200_SigSts_12 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_13 | VF200_SigSts_13 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_14 | VF200_SigSts_14 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_15 | VF200_SigSts_15 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_16 | VF200_SigSts_16 | CAN_FD_BH | 100 ms | BCM -> IPC
CAN_ROW | STATUS_B_CAN_17 | VF200_SigSts_17 | CAN_FD_BH | 100 ms | BCM -> IPC

54.2 Detailed Functional Requirements & State Logic · VF200 (Part 2/27)

[REQ_VF200_0201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_0202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_0203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_0204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_0205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_0206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_0207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_0208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_0209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_0210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_0211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_0212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_0213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_0214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_0215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_0216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_0217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_0218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_0219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_0220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_0221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_0222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_0223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_0224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_0225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_0226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_0227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.3 Detailed Functional Requirements & State Logic · VF200 (Part 3/27)

[REQ_VF200_0301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_0302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_0303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_0304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_0305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_0306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_0307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_0308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_0309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_0310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_0311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_0312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_0313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_0314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_0315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_0316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_0317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_0318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_0319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_0320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_0321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_0322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_0323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_0324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_0325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_0326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_0327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.4 Detailed Functional Requirements & State Logic · VF200 (Part 4/27)

[REQ_VF200_0401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_0402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_0403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_0404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_0405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_0406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_0407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_0408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_0409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_0410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_0411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_0412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_0413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_0414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_0415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_0416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_0417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_0418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_0419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_0420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_0421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_0422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_0423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_0424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_0425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_0426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_0427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.5 Detailed Functional Requirements & State Logic · VF200 (Part 5/27)

[REQ_VF200_0501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_0502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_0503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_0504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_0505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_0506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_0507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_0508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_0509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_0510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_0511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_0512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_0513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_0514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_0515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_0516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_0517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_0518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_0519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_0520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_0521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_0522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_0523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_0524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_0525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_0526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_0527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.6 Detailed Functional Requirements & State Logic · VF200 (Part 6/27)

[REQ_VF200_0601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_0602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_0603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_0604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_0605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_0606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_0607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_0608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_0609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_0610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_0611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_0612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_0613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_0614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_0615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_0616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_0617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_0618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_0619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_0620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_0621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_0622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_0623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_0624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_0625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_0626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_0627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.7 Detailed Functional Requirements & State Logic · VF200 (Part 7/27)

[REQ_VF200_0701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_0702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_0703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_0704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_0705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_0706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_0707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_0708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_0709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_0710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_0711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_0712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_0713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_0714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_0715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_0716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_0717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_0718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_0719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_0720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_0721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_0722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_0723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_0724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_0725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_0726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_0727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.8 Detailed Functional Requirements & State Logic · VF200 (Part 8/27)

[REQ_VF200_0801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_0802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_0803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_0804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_0805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_0806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_0807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_0808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_0809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_0810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_0811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_0812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_0813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_0814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_0815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_0816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_0817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_0818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_0819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_0820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_0821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_0822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_0823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_0824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_0825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_0826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_0827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.9 Detailed Functional Requirements & State Logic · VF200 (Part 9/27)

[REQ_VF200_0901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_0902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_0903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_0904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_0905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_0906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_0907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_0908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_0909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_0910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_0911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_0912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_0913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_0914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_0915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_0916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_0917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_0918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_0919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_0920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_0921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_0922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_0923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_0924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_0925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_0926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_0927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.10 Detailed Functional Requirements & State Logic · VF200 (Part 10/27)

[REQ_VF200_1001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.11 Detailed Functional Requirements & State Logic · VF200 (Part 11/27)

[REQ_VF200_1101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.14 Detailed Functional Requirements & State Logic · VF200 (Part 12/27)

[REQ_VF200_1201] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1202] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1203] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1204] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1205] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1206] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1207] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1208] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1209] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1210] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1211] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1212] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1213] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1214] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1215] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1216] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1217] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1218] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1219] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1220] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1221] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1222] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1223] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1224] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1225] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1226] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1227] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.15 Detailed Functional Requirements & State Logic · VF200 (Part 13/27)

[REQ_VF200_1301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.16 Detailed Functional Requirements & State Logic · VF200 (Part 14/27)

[REQ_VF200_1401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.17 Detailed Functional Requirements & State Logic · VF200 (Part 15/27)

[REQ_VF200_1501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.18 Detailed Functional Requirements & State Logic · VF200 (Part 16/27)

[REQ_VF200_1601] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1602] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1603] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1604] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1605] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1606] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1607] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1608] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1609] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1610] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1611] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1612] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1613] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1614] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1615] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1616] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1617] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1618] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1619] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1620] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1621] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1622] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1623] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1624] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1625] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1626] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1627] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.19 Detailed Functional Requirements & State Logic · VF200 (Part 17/27)

[REQ_VF200_1701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.20 Detailed Functional Requirements & State Logic · VF200 (Part 18/27)

[REQ_VF200_1801] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1802] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1803] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1804] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1805] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1806] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1807] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1808] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1809] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1810] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1811] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1812] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1813] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1814] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1815] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1816] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1817] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1818] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1819] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1820] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1821] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1822] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1823] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1824] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1825] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1826] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1827] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.21 Detailed Functional Requirements & State Logic · VF200 (Part 19/27)

[REQ_VF200_1901] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_1902] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_1903] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_1904] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_1905] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_1906] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_1907] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_1908] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_1909] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_1910] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_1911] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_1912] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_1913] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_1914] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_1915] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_1916] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_1917] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_1918] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_1919] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_1920] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_1921] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_1922] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_1923] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_1924] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_1925] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_1926] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_1927] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.22 Detailed Functional Requirements & State Logic · VF200 (Part 20/27)

[REQ_VF200_2001] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_2002] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_2003] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_2004] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_2005] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_2006] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_2007] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_2008] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_2009] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_2010] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_2011] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_2012] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_2013] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_2014] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_2015] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_2016] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_2017] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_2018] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_2019] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_2020] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_2021] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_2022] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_2023] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_2024] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_2025] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_2026] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_2027] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.23 Detailed Functional Requirements & State Logic · VF200 (Part 21/27)

[REQ_VF200_2101] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_2102] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_2103] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_2104] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_2105] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_2106] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_2107] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_2108] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_2109] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_2110] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_2111] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_2112] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_2113] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_2114] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_2115] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_2116] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_2117] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_2118] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_2119] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_2120] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_2121] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_2122] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_2123] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_2124] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_2125] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_2126] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_2127] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.12 Indication Management

[REQ_VF200_IND] When T_NODE_TIMEOUT_Sts == ACTIVE on CAN-FD network, the IPC cluster shall activate NETWORK RECOVERY ACTIV
IND_ROW | NETWORK RECOVERY ACTIVE.V1 | When T_NODE_TIMEOUT_Sts == ACTIVE on CAN-FD network | No (Standard NETW

[REQ_VF200_IND] When T_NODE_TIMEOUT_FailSts == PRESENT, the IPC cluster shall activate NETWORK RECOVERY FAIL.V1 on the displa
IND_ROW | NETWORK RECOVERY FAIL.V1 | When T_NODE_TIMEOUT_FailSts == PRESENT | Yes - Check CAN-FD Network Timeo

[REQ_VF200_IND] When CAN node timeout > T_NODE_TIMEOUT_TIMEOUT, the IPC cluster shall activate NETWORK RECOVERY RECOVER
IND_ROW | NETWORK RECOVERY RECOVERY.V1 | When CAN node timeout > T_NODE_TIMEOUT_TIMEOUT | Yes - NETWORK RECOVE

54.25 Detailed Functional Requirements & State Logic · VF200 (Part 23/27)

[REQ_VF200_2301] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_2302] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_2303] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_2304] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_2305] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_2306] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_2307] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_2308] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_2309] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_2310] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_2311] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_2312] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_2313] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_2314] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_2315] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_2316] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_2317] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_2318] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_2319] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_2320] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_2321] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_2322] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_2323] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_2324] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_2325] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_2326] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_2327] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.26 Detailed Functional Requirements & State Logic · VF200 (Part 24/27)

[REQ_VF200_2401] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_2402] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_2403] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_2404] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_2405] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_2406] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_2407] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_2408] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_2409] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_2410] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_2411] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_2412] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_2413] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_2414] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_2415] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_2416] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_2417] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_2418] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_2419] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_2420] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_2421] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_2422] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_2423] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_2424] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_2425] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_2426] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_2427] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.27 Detailed Functional Requirements & State Logic · VF200 (Part 25/27)

[REQ_VF200_2501] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_2502] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_2503] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_2504] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_2505] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_2506] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_2507] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_2508] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_2509] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_2510] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_2511] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_2512] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_2513] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_2514] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_2515] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_2516] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_2517] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_2518] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_2519] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_2520] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_2521] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_2522] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_2523] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_2524] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_2525] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_2526] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_2527] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.

54.14 Configuration Parameters

54.14.1 Configuration Parameters Table

ID | Parameter Name | First Trial Value | Range Value | Resolution | Unit | Component | Implementation | XCP | Impact | Description

PAR_ROW | PAR_VF200_01 | T_NODE_TIMEOUT_TH | 10,5 | 1,0÷50,0 | 0,5 | s | IPC | SUPPLIER EOL_2 | NO | HMI Calibratio

PAR_ROW | PAR_VF200_02 | T_NODE_TIMEOUT_DEBOUNCE | 2,0 | 0,5÷10,0 | 0,1 | s | IPC | SUPPLIER EOL_2 | NO | Signal Fi

PAR_ROW | PAR_VF200_03 | CFG_VF200_PROXI_EN | 1 | 0÷1 | 1 | - | IPC | PROXI | NO | Variant Coding | PROXI enable bi

PAR_ROW | PAR_VF200_04 | T_BCM_VF200_RAW | 100 | 10÷500 | 10 | ms | BCM | SUPPLIER EOL | YES | Input Acquisition |

54.29 Detailed Functional Requirements & State Logic · VF200 (Part 27/27)

[REQ_VF200_2701] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 1 executes.

[REQ_VF200_2702] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 2 executes.

[REQ_VF200_2703] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 3 executes.

[REQ_VF200_2704] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 4 executes.

[REQ_VF200_2705] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 5 executes.

[REQ_VF200_2706] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 6 executes.

[REQ_VF200_2707] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 7 executes.

[REQ_VF200_2708] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 8 executes.

[REQ_VF200_2709] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 9 executes.

[REQ_VF200_2710] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 10 executes.

[REQ_VF200_2711] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 11 executes.

[REQ_VF200_2712] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 12 executes.

[REQ_VF200_2713] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 13 executes.

[REQ_VF200_2714] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 14 executes.

[REQ_VF200_2715] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 15 executes.

[REQ_VF200_2716] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 16 executes.

[REQ_VF200_2717] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 17 executes.

[REQ_VF200_2718] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 18 executes.

[REQ_VF200_2719] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 19 executes.

[REQ_VF200_2720] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 20 executes.

[REQ_VF200_2721] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 21 executes.

[REQ_VF200_2722] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 22 executes.

[REQ_VF200_2723] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 23 executes.

[REQ_VF200_2724] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 24 executes.

[REQ_VF200_2725] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 25 executes.

[REQ_VF200_2726] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 26 executes.

[REQ_VF200_2727] When KeySts == KEY_ON and network voltage is within [9.0V .. 16.0V], subsystem state machine step 27 executes.