

# C200 PROGRAMMING ASSIGNMENT № 8: CLASSES, ALGORITHMS

---

**Dr. M.M. Dalkilic**

Computer Science

School of Informatics, Computing, and Engineering

Indiana University, Bloomington, IN, USA

April 14, 2022

## Introduction

In this homework, you'll work on translating critical thinking to programming. This homework is due on **Thursday, April, 21 at 10:59 PM EST**.

## Problem 1: Random Walk

A random walk is a *stochastic process*. A stochastic process is a series of values that are not determined functionally, but probabilistically. The random walk is supposed to describe an inebriated person who, starting from the bar, intends to walk home, but because of intoxication instead randomly takes single steps either forward or backward, left or right. The person has no memory of any steps taken, so theoretically, the person shouldn't move too far from where he or she starts. Random walks are used to model many phenomena, like the size of the web or changes in financial instruments. We will model a 2D random walk with two arrays  $x$  and  $y$  where  $x$  represents moving left or right and  $y$  represents forward or backward. The index  $i$  will represent the step and  $x[i], y[i]$  will represent the location at step  $i$ . So, for  $i=0$ , we have  $x[0], y[0]$  (starting place). Using random we choose from the list  $[1,2,3,4]$ . If the value is one then we move right from the previous  $x$  position:

---

```
1 x[i] = x[i-1] + 1
2 y[i] = y[i-1]
```

---

If the value is two, then we move left from the previous  $x$  position:

---

```
1 x[i] = x[i-1] - 1
2 y[i] = y[i-1]
```

---

If the value is three, we move up from the previous  $y$  position:

---

```
1 x[i] = x[i-1]
2 y[i] = y[i-1] + 1
```

---

And when the value is four, we move down from the previous  $y$  position:

---

```
1 x[i] = x[i-1]
2 y[i] = y[i-1] - 1
```

---

Here is another way to describe this:

$$step(0) = 0 \tag{1}$$

$$step_i(n) = \begin{cases} \text{right} & step(n-1), i=1 \\ \text{left} & step(n-1), i=2 \\ \text{up} & step(n-1), i=3 \\ \text{down} & step(n-1), i=4 \end{cases} \tag{2}$$

The random walk also describes investing in, say, stock.




Figure 1: The first few steps of a random walk.




Figure 2: The blue cross is where we started and the red cross is where we ended. Since each run is random, and we have 100,000 steps, your plot will not look similar to mine.

### Programming Problem 1: Random Walk

- Complete the step function.
- These are *random walks*; hence, the outputs will be different .

## Problem 2: Closest Pair

In this problem, you'll use write a *brute force* algorithm that, given a list of points in the 2D Euclidean plane,  $P = [(x_0, y_0), (x_1, y_1), \dots, (x_n, y_n)]$ , find the pair  $p_i = (x_i, y_i)$  and  $p_j = (x_j, y_j)$  such that the distance  $d$  between the two:

$$d(p_i, p_j) = \sqrt{(x_i - x_j)^2 + (y_i - y_j)^2} \quad (3)$$

is the smallest possible value of any possible distance  $d$  between any pair and  $P$  has at least two pairs. For example, say  $P = [(5, 1), (2, 2), (1, 1)]$ , then:

$$d(p_i, p_j) = \sqrt{(x_i - x_j)^2 + (y_i - y_j)^2} \quad (4)$$

$$d((5, 1), (2, 2)) = \sqrt{(5 - 2)^2 + (1 - 2)^2} = \sqrt{9 + 1} \approx 3.16 \quad (5)$$

$$d((2, 2), (1, 1)) = \sqrt{(2 - 1)^2 + (2 - 1)^2} = \sqrt{1 + 1} \approx 1.41 \quad (6)$$

$$d((5, 1), (1, 1)) = \sqrt{(5 - 1)^2 + (1 - 1)^2} = \sqrt{4} = 2 \quad (7)$$

So the closest pair is  $[(2, 2), (1, 1)]$ . Since  $d$  is commutative, it doesn't matter whether we choose  $p_i$  first or  $p_j$  first.

To make it easier for someone to use our code, the function will return  $[p1, p2, \text{distance}]$  where  $p1$  is the first point as a tuple,  $p2$  is the second point as a tuple, and distance is the distance between them, *i.e.*,  $d(p1, p2)$ . When this code is run:

```
1 x = [(rn.randint(1,50), rn.randint(1,50)) for _ in range(10)]
2 print(x)
3 print(brute(x))
```

this output was produced: When I ran this, my output was

```
1 [(34, 34), (28, 38), (24, 3), (18, 17), (33, 33),
2  (16, 1), (32, 45), (50, 24), (5, 35), (48, 30)]
3 [(34, 34), (33, 33), 1.4142135623730951]
```

### Deliverables for Problem 2

- Implement both functions.
- Observe that the function `brute(x)` takes a list of pairs of numbers and returns a list `[x,y,d]`, where `x` is the first pair, `y` is the second pair, and `d` is the smallest distance between `x` and `y`. An observation—`d` might not be necessarily unique—there might be two, or even several, ways to differently obtain this value.
- if you find that there are more than 1 pair with the same minimum distance then just return the first such pair.

## Problem 3: No Silver Bullet

Please read the *No Silver Bullet Essay* pushed to your git. This famous essay discusses the difficulty of designing and implementing software. Your task is two-fold with this problem. In the essay, the author describes a productivity function of two variables, time and number of people. Assume time is forty hours. The function then becomes dependent only on number of people. The task you have here is to complete the function. I have implemented the Newton-Raphson method to find roots (critical values) values shown in Fig. 3.

When I ran this, my output was, including the plot,

---

1 The maximum productivity is  $P(62) \sim 896$  person x hrs

---




Figure 3: Plotting the productivity function assuming time = 40 hrs/wk as a function of people.

### Deliverables for Problem 3

- Implement the 'productivity' function from the paper (the function specifically is given on page 9/13 but the essay is fun to read as well).
- Note that, we have already implemented the Newton() and fp() functions and these are used in the code to plot the graph.

## Problem 4: Permutations

In this problem you will take a list of numbers as input and return a list of lists that has all the permutations. For example,

---

```
1 print(permutation([1,2,3]))
```

---

returns

---

```
1 [[1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 3, 1], [3, 1, 2], [3, 2, 1]]
```

---

$3! = 6$  which is the number of permutations. To remind you, a permutation from some alphabet  $|A| = n$  means  $n!$  lists of every possible sequence. For example, if  $A = \{1, 2, 3\}$ , then there will be 6 lists (shown above). Adding one more makes 24:

---

```
1 print(permutation([1,2,3,4]))
```

---

gives

---

```
1 [1, 2, 3, 4], [1, 2, 4, 3], [1, 3, 2, 4],  
2 [1, 3, 4, 2], [1, 4, 2, 3], [1, 4, 3, 2],  
3 [2, 1, 3, 4], [2, 1, 4, 3], [2, 3, 1, 4],  
4 [2, 3, 4, 1], [2, 4, 1, 3], [2, 4, 3, 1],  
5 [3, 1, 2, 4], [3, 1, 4, 2], [3, 2, 1, 4],  
6 [3, 2, 4, 1], [3, 4, 1, 2], [3, 4, 2, 1],  
7 [4, 1, 2, 3], [4, 1, 3, 2], [4, 2, 1, 3],  
8 [4, 2, 3, 1], [4, 3, 1, 2], [4, 3, 2, 1]]
```

---

The order of the list itself isn't important – what's important is that every possible list is present. You are free to implement this non-recursively or recursively.

### Deliverable for Problem 4: Permutations

- Implement the permutation function – you cannot use any modules.
- Hint: Make small toy examples to find the pattern and then you can use that to basically make it work for list of any length.

## Problem 5: Vector Class

In this problem, you'll implement a mathematical vector class. While the vectors are depicted as a column, you'll use a tuple. A vector of size  $n \in \{1, 2, 3, \dots\}$  is a collection of real numbers:

$$\mathbf{x} = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix} \quad (8)$$

Given  $\mathbf{x}, \mathbf{y}$  are vectors of size  $n$  and  $z$  is a real number-we can define the following operations

$$\mathbf{x} + \mathbf{y} = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix} + \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix} = \begin{bmatrix} x_1 + y_1 \\ x_2 + y_2 \\ \vdots \\ x_n + y_n \end{bmatrix} \quad (9)$$

$$\mathbf{x} - \mathbf{y} = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix} - \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix} = \begin{bmatrix} x_1 - y_1 \\ x_2 - y_2 \\ \vdots \\ x_n - y_n \end{bmatrix} \quad (10)$$

$$\mathbf{x} \times \mathbf{y} = \sum_{i=1}^n x_i y_i \quad (11)$$

$$z \times \mathbf{x} = z \times \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix} = \begin{bmatrix} z \times x_1 \\ z \times x_2 \\ \vdots \\ z \times x_n \end{bmatrix} \quad (12)$$

$$-\mathbf{x} = \begin{bmatrix} -x_1 \\ -x_2 \\ \vdots \\ -x_n \end{bmatrix} \quad (13)$$

$$|\mathbf{x}| = \sqrt{\mathbf{x} \times \mathbf{x}} \quad (14)$$

$$(15)$$

Two vectors  $\mathbf{x}, \mathbf{y}$  are equal if  $x_i = y_i$  for  $1 \leq i \leq n$ . The class you'll build will work for any non-zero length vector. The class constructor is:

---

```
1 class Vector:
2     def __init__(self, *x):
3         self.__v = x
```

---

The \*x means you are making the arguments a tuple—further, a tuple can be sent if it has \*. For example,

---

```
1 w = Vector(*(10,10))
```

---

will send the tuple as a tuple—this makes arguments easier. For a vector  $x$  of length  $n$ , `print(x)` should display

---

```
1 <x1,x2,...,xn>
```

---

Here are instances and outputs:

---

```
1 x,y,w = Vector(1,2),Vector(3,-1),Vector(*(10,10))
2 z,a = Vector(0,3,2),Vector(-1,-1,-1)
3 print(x,y,z,a)
4 print(x+y,z+a)
5 print(x*y,z*a)
6 print(5*x,5*z)
7 print(abs(x),abs(z))
8 print(-x,-z)
9 print(x - y + y == x, 2 * z == z + z)
```

---

with output:

---

```
1 <1, 2> <3, -1> <0, 3, 2> <-1, -1, -1>
2 <4, 1> <-1, 2, 1>
3 1 -5
4 <5, 10> <0, 15, 10>
5 2.23606797749979 3.605551275463989
6 <-1, -2> <0, -3, -2>
7 True True
```

---

#### Deliverable for Problem 5: Vectors

- Complete the class—use a tuple to represent the mathematical vector.
- You can use Python's `sum` function.
- You are free to use any Python string class method.



## Paired Programming

For this assignment, here is your partner. If you find your partner is unresponsive, you are free to join another group.

mabdayem@iu.edu, shadoshi@iu.edu  
ahnabrah@iu.edu, bbacso@iu.edu  
adamsjf@iu.edu, raia@iu.edu  
dadeyeye@iu.edu, mattroac@iu.edu  
cmaguila@iu.edu, luilmill@iu.edu  
ahmedrr@iu.edu, gabradle@iu.edu  
malshama@iu.edu, timbogun@iu.edu  
olalbert@iu.edu, cbylciw@iu.edu  
nalemanm@iu.edu, linweix@iu.edu  
faysalza@iu.edu, asaokho@iu.edu  
rnameen@iu.edu, vramkum@iu.edu  
svamin@iu.edu, joecool@iu.edu  
jaygul@iu.edu, evewalsh@iu.edu  
rbajaj@iu.edu, akaushal@iu.edu  
cbalbuen@iu.edu, pheile@iu.edu  
ikbanist@iu.edu, sahmir@iu.edu  
zsbanks@iu.edu, dylomall@iu.edu  
mbarrant@iu.edu, johnslia@iu.edu  
tymbarre@iu.edu, jjwelp@iu.edu  
dcblakle@iu.edu, yangyuc@iu.edu  
mlboukal@iu.edu, anniye@iu.edu  
logbrads@iu.edu, kamdelmo@iu.edu  
lburrola@iu.edu, dazamora@iu.edu  
aidcarli@iu.edu, gillenj@iu.edu  
dcaspers@iu.edu, vimadhav@iu.edu  
mathchen@iu.edu, fraustom@iu.edu  
ccoriag@iu.edu, sowvemul@iu.edu  
gcruzcor@iu.edu, kjwalapu@iu.edu  
ddahodu@iu.edu, tymath@iu.edu  
rpdeady@iu.edu, ibnash@iu.edu  
cadelaga@iu.edu, yjan@iu.edu  
emdelph@iu.edu, yl181@iu.edu  
edepke@iu.edu, mvincen@iu.edu  
shrdesai@iu.edu, yudsingh@iu.edu  
eeconomo@iu.edu, eluthra@iu.edu  
ereilar@iu.edu, jpenrigh@iu.edu  
jaespin@iu.edu, gkarnuta@iu.edu

mfanous@iu.edu, rosavy@iu.edu  
jayfish@iu.edu, mschauss@iu.edu  
sydfoste@iu.edu, owenaj@iu.edu  
ethfrago@iu.edu, camitong@iu.edu  
nfrische@iu.edu, sothor@iu.edu  
gaoxinl@iu.edu, egmorley@iu.edu  
ggivan@iu.edu, silmudee@iu.edu  
bgloor@iu.edu, chlzhang@iu.edu  
noahgrah@iu.edu, jthurd@iu.edu  
halejd@iu.edu, ejharms@iu.edu  
ehallor@iu.edu, evtomak@iu.edu  
jchobbs@iu.edu, sj110@iu.edu  
binyhu@iu.edu, jk130@iu.edu  
srimmadi@iu.edu, chsand@iu.edu  
aj110@iu.edu, cl101@iu.edu  
gjarrold@iu.edu, hdwatter@iu.edu  
mjerrell@iu.edu, kevko@iu.edu  
yuljiao@iu.edu, actoney@iu.edu  
njindra@iu.edu, mdtanner@iu.edu  
cjohanns@iu.edu, gkyoung@iu.edu  
fkanmogn@iu.edu, mppan@iu.edu  
sskauvei@iu.edu, lancswar@iu.edu  
phklein@iu.edu, apoellab@iu.edu  
jtkrug@iu.edu, tclady@iu.edu  
jhlazar@iu.edu, ashankwi@iu.edu  
wlegear@iu.edu, bolabanj@iu.edu  
jleverty@iu.edu, remarche@iu.edu  
lopezis@iu.edu, jamoya@iu.edu  
mlumbant@iu.edu, ndvanbur@iu.edu  
pmanolis@iu.edu, rlmcdani@iu.edu  
mmansoo@iu.edu, eliserr@iu.edu  
mooralec@iu.edu, daparent@iu.edu  
jsm13@iu.edu, ryou@iu.edu  
hnasar@iu.edu, perkcaan@iu.edu  
apapaioa@iu.edu, nps1@iu.edu  
divpatel@iu.edu, powelchr@iu.edu  
shevphil@iu.edu, grtalley@iu.edu  
srpothir@iu.edu, vvictori@iu.edu  
sprabhak@iu.edu, cadwilco@iu.edu  
jwrohn@iu.edu, lzinn@iu.edu  
msronan@iu.edu, ssalama@iu.edu

sasaluja@iu.edu, astrouf@iu.edu  
ansiva@iu.edu, cy30@iu.edu  
amystaff@iu.edu, gtutton@iu.edu  
rwan@iu.edu, weidzhen@iu.edu