

Permutations with Square-Free Prefix Sums and OEIS Sequence A395620

Abstract

We study permutations of $\{1, 2, \dots, n\}$ whose prefix sums avoid perfect squares. This combinatorial constraint defines the OEIS sequence A395620. We provide a formal framework, a dynamic programming formulation for exact enumeration, complexity analysis, probabilistic heuristics, and several generalizations. We also discuss structural properties and open problems related to this class of restricted permutations.

1 Introduction

Let S_n denote the symmetric group on n elements. We consider permutations with a global additive constraint: no prefix sum is allowed to be a perfect square.

Such problems belong to the general family of permutation pattern avoidance problems with arithmetic constraints. Unlike classical pattern avoidance, the restriction here depends on cumulative structure rather than local order.

This construction corresponds to OEIS sequence A395620.

2 Definition

Definition 1. Let $\pi = (\pi_1, \pi_2, \dots, \pi_n)$ be a permutation of $\{1, 2, \dots, n\}$. Define prefix sums:

$$S_k = \sum_{i=1}^k \pi_i.$$

Let $\mathcal{A}_n$ be the set of permutations such that:

$$S_k \notin \{m^2 : m \in \mathbb{N}\}, \quad \forall k \in \{1, \dots, n\}.$$

We define:

$$a(n) = |\mathcal{A}_n|.$$

This sequence $(a(n))_{n \geq 1}$ is OEIS A395620.

3 First values

The initial values of $a(n)$ can be computed via exhaustive or DP-based enumeration for small n . These values are listed in OEIS A395620.

4 Combinatorial reformulation

We interpret the problem as a constrained path in a layered state space.

Each state corresponds to:

- a subset $U \subseteq \{1, \dots, n\}$ of used elements,
- a current sum $s = \sum_{i \in U} i$,

with transitions:

$$(U, s) \rightarrow (U \cup \{x\}, s + x)$$

for $x \notin U$, provided $s + x$ is not a perfect square.

Thus, valid permutations correspond to Hamiltonian paths in a directed acyclic state graph.

5 Dynamic programming algorithm

We define a DP over subsets:

$$DP[mask][s] = \text{number of ways to reach state } (mask, s).$$

Where: - $mask$ encodes used elements, - s is the current prefix sum.

Transition:

$$DP[mask \cup \{x\}][s + x] + = DP[mask][s]$$

if $s + x$ is not a perfect square.

5.1 Complexity

The naive complexity is:

$$O(n!).$$

The DP formulation reduces this to approximately:

$$O(2^n \cdot n \cdot S),$$

where $S = \frac{n(n+1)}{2}$ is the maximum possible sum.

Pruning invalid square states significantly reduces the effective state space in practice.

6 Heuristic probabilistic model

We consider a random permutation $\pi \in S_n$. The prefix sum S_k is approximately distributed around:

$$\mathbb{E}[S_k] = \frac{k(n+1)}{2}.$$

The density of perfect squares near x is approximately:

$$\sim \frac{1}{2\sqrt{x}}.$$

Thus, the probability that a random prefix sum hits a square is small for large x , suggesting that:

$$a(n) \approx n! \cdot \exp(-c\sqrt{n})$$

for some constant $c > 0$ (heuristic).

This suggests that although constraints are global, most permutations survive early stages, and failures concentrate at small prefix lengths.

7 Generalizations

We define several natural extensions:

7.1 Avoiding higher powers

Replace squares with k -th powers:

$$S_k \notin \{m^d : m \in \mathbb{N}\}.$$

7.2 Arbitrary forbidden sets

Let $F \subset \mathbb{N}$. Define:

$$S_k \notin F.$$

7.3 Modulo constraints

Require:

$$S_k \not\equiv r \pmod{m}.$$

7.4 Graph formulation

Let vertices represent partial sums; edges correspond to valid extensions. Then $a(n)$ counts Hamiltonian paths in a filtered state graph.

8 Open problems

We highlight several open directions:

- Does $a(n)$ admit a closed form or recurrence?
- What is the precise asymptotic growth rate of $a(n)$?
- Is the sequence log-concave or unimodal in any transformed sense?
- Can one characterize forbidden-prefix structures combinatorially?
- Is there a bijection to known permutation-avoidance classes?

9 Conclusion

We introduced and studied permutations with square-free prefix sums, corresponding to OEIS A395620. While exact enumeration is computationally expensive, the problem exhibits rich combinatorial structure and connects naturally to constrained path counting and additive combinatorics.

Further work includes asymptotic analysis and structural characterization of valid permutations.

References

- [1] OEIS Foundation Inc. *The On-Line Encyclopedia of Integer Sequences*, A395620.
- [2] R. P. Stanley, *Enumerative Combinatorics*, Vol. 1.