

# Missing Data Analysis

## High-Dimensional Imputation

Compiled by Kyle M. Lang

2019-10-21

The sources listed below represent an overview of the work on high-dimensional missing data imputation. This list is certainly not exhaustive—and may not be especially representative—but it should provide a good starting point for readers interested in learning about the current state-of-the-art in missing data imputation for high-dimensional problems.

Although most of these sources discuss/evaluate several different imputation methods, I have attempted to classify each paper by its primary focus.

### Overviews/Comparisons

- Drechsler, J., & Reiter, J. P. (2011). An empirical evaluation of easily implemented, nonparametric methods for generating synthetic datasets. *Computational Statistics and Data Analysis*, 55(12), 3232–3243. doi: 10.1016/j.csda.2011.06.006
- García-Laencina, P. J., Sancho-Gómez, J.-L., & Figueiras-Vidal, A. R. (2010). Pattern classification with missing data: A review. *Neural Computing & Applications*, 19(2), 263–282. doi: 10.1007/s00521-009-0295-6
- Junninen, H., Niska, H., Tuppurainen, K., Ruuskanen, J., & Kolehmainen, M. (2004). Methods for imputation of missing values in air quality data sets. *Atmospheric Environment*, 38(18), 2895–2907. doi: 10.1016/j.atmosenv.2004.02.026
- Lakshminarayan, K., Harp, S. A., & Samad, T. (1999). Imputation of missing data in industrial databases. *Applied Intelligence*, 11(3), 259–275. doi: 10.1023/A:1008334909089
- Saar-Tsechansky, M., & Provost, F. (2007). Handling missing values when applying classification models. *Journal of Machine Learning Research*, 8, 1217–1250.

### Single Imputation using Classification/Regression Trees

- Borgoni, R., & Berrington, A. (2013). Evaluating a sequential tree-based procedure for multivariate imputation of complex missing data structures. *Quality & Quantity*, 47(4), 1991–2008. doi: 10.1007/s11135-011-9638-3
- Conversano, C., & Siciliano, R. (2009). Incremental tree-based missing data imputation with lexicographic ordering. *Journal of Classification*, 26(3), 361–379. doi: 10.1007/s00357-009-9038-8

- D'Ambrosio, A., Aria, M., & Siciliano, R. (2012). Accurate tree-based missing data imputation and data fusion within the statistical learning paradigm. *Journal of Classification*, 29(2), 227–258. doi: 10.1007/s00357-012-9108-1
- Iacus, S. M., & Porro, G. (2007). Missing data imputation, matching and other applications of random recursive partitioning. *Computational Statistics & Data Analysis*, 52(2), 773–789. doi: 10.1016/j.csda.2006.12.036
- Nanni, L., Lumini, A., & Brahnam, S. (2012). A classifier ensemble approach for the missing feature problem. *Artificial Intelligence in Medicine*, 55(1), 37–50. doi: 10.1016/j.artmed.2011.11.006

## Single Imputation using K-Nearest Neighbors

- Brás, L. P., & Menezes, J. C. (2007). Improving cluster-based missing value estimation of dna microarray data. *Biomolecular engineering*, 24(2), 273–282.
- de Andrade Silva, J., & Hruschka, E. R. (2009). Eacimpute: an evolutionary algorithm for clustering-based imputation. In *2009 ninth international conference on intelligent systems design and applications* (pp. 1400–1406).
- de Andrade Silva, J., & Hruschka, E. R. (2013). An experimental study on the use of nearest neighbor-based imputation algorithms for classification tasks. *Data & Knowledge Engineering*, 84, 47–58. doi: 10.1016/j.datak.2012.12.006

The article compares 5 popular Nearest-Neighbour algorithms based on both their prediction accuracy and the classification bias. The results show that in a MCAR context, the Iterative KNNImpute algorithm proposed by Brás and Menezes (2007) outperforms all other methods, according to both the Normalised Root Mean Squared Error (NRMSE) and the Average Correct Classification Rate (ACCR) criterion. However, in a MAR scenario, the KNNI proposed by Troyanskaya et al 2001, the Sequential KNNI proposed by Kim et al (2004), and the EACI proposed by de Andrade Silva and Hruschka (2009) perform best.

One of the clearest contribution of the article is showing that better prediction accuracy does not necessarily imply a better modelling performance (i.e. an algorithm might “recover” the missing values better, but another algorithm might provide a better estimation of the relationship between attributes). This result motivates a departure from the exclusive use of the Normalised Root Mean Squared Error measure of prediction accuracy as the criteria to evaluate an imputation algorithm. It must be noted that this article is concerned exclusively with a classification task.

- García-Laencina, P. J., Sancho-Gómez, J.-L., Figueiras-Vidal, A. R., & Verleysen, M. (2009). K nearest neighbours with mutual information for simultaneous classification and missing data imputation. *Neurocomputing*, 72(7–9), 1483–1493. doi: 10.1016/j.neucom.2008.11.026

The authors introduce an improved version of the KNNImpute algorithm proposed by Troyanskaya *et al.* 2001. Their proposed strategy is called MI-KNNImpute, a somewhat confusing label: the “MI” portion does not refer to

“multiple imputation” but to the concept of Mutual Information (i.e. the reduction of the uncertainty of a variable when another one is known).

The authors show with different incomplete datasets that the performance of the classification task, performed by a KNN algorithm that uses a distance measure of Euclidian form and one that uses MI, is improved by first imputing the datasets with the MI-KNNImpute algorithm compared to the standard KNNImpute.

The improved performance is achieved by including some information regarding the classification task in the imputation phase, through the use of MI as a measure of distance between the target class variable and the other input attributes. The use of MI in the algorithm effectively weights the importance of each attribute for the imputation of the target class variable.

Kim, H., Golub, G. H., & Park, H. (2005). Missing value estimation for DNA microarray gene expression data: local least squares imputation. *Bioinformatics*, 21(2), 187–198. doi: 10.1093/bioinformatics/bth499

The authors developed the Local Least Square imputation (LLSImputation) method by which similar k-neighbour genes are selected, then used to estimate a prediction model which is finally employed to predict the missing values.

The article compares LLSImputation with the KNNImputation and SVDImputation proposed by Troyanskaya et al (2001), and the Bayesian PCA proposed by Oba *et al.* (2003). As the BPCA approach improves on the SVDImputation by incorporating Bayesian optimisation in a PC based method, LLSI improves on KNNI by combining the local similarity structure and the optimisation procedure of least squares.

Finally, the article directly confronts the issue of choosing the optimal number of k-nearest neighbours. In absence of clear theory, the authors propose to empirically identify on a case-by-case basis the value of  $k$  by repeatedly predicting some artificially imposed missing values and selecting the one that best recover the known fabricated missing values.

Kim, K.-Y., Kim, B.-J., & Yi, G.-S. (2004). Reuse of imputed data in microarray analysis increases imputation efficiency. *BMC bioinformatics*, 5(160). doi: 10.1186/1471-2105-5-160

Troyanskaya, O., Cantor, M., Sherlock, G., Brown, P., Hastie, T., Tibshirani, R., ... Altman, R. B. (2001). Missing value estimation methods for DNA microarrays. *Bioinformatics*, 17(6), 520–525. doi: 10.1093/bioinformatics/17.6.520

In the context of DNA microarray studies with missing data, the authors show the better performance of a k-nearest neighbour imputation method (KNNImpute), over an SVD-based regression imputation method (SVDImpute), and mean and zero imputation.

The KNNImpute algorithm outperforms all the other methods granting (1) less deterioration in performance with increasing percentage of missingness, (2) robustness to the type of data considered (time-series or not, noisy or not), (3) less sensitivity to the number of parameters used (the choice of  $k$ , the number of nearest neighbours considered for KNNImpute and the number of most significant eigengenes selected for SVDImpute).

The generalisability of these results is somewhat hindered by two methodological choices:

- the missing data mechanisms considered is MCAR;
- the metric used to identify the better method is the Root Mean Squared error, a standardised difference between the true data points values and the imputed ones. As many contributions have highlighted (see Rubin, 1996; de Andrade Silva *et al.*, 2013), the goal of missing data handling procedures is not necessarily recovering the true missing values but rather granting the statistical validity of the analyses performed on a dataset afflicted by missing data.

Wasito, I., & Mirkin, B. (2005). Nearest neighbour approach in the least-squares data imputation algorithms. *Information Sciences*, 169(1–2), 1–25. doi: 10.1016/j.ins.2004.02.014

The authors introduce the INImpute approach, an algorithm that combines an iterative SVD-based least-square imputation with a nearest neighbour approach. Missing values are imputed first globally (i.e. considering the entire dataset) through an Iterative Majorization Least Square algorithm (an SVD/PCR-based imputation method with 4 principal components,  $p=4$ ). Then, a kNN algorithm is used to select k-nearest-neighbours to an instance that had a missing value for a particular variable, and replaces the previously (globally) imputed value with a new one found with another IMLS run only among the nearest-neighbours (and with  $p=1$ ).

The theoretical properties of this approach are not discussed but the authors do show the superiority of INImpute to regular kNN and other ILS approaches in a variety of scenarios.

Wasito, I., & Mirkin, B. (2006). Nearest neighbour approach in the least-squares data imputation algorithms with different missing patterns. *Computational Statistics & Data Analysis*, 50(4), 926–949. doi: 10.1016/j.csda.2004.11.009

The authors extend the comparison of the different least-squares imputation techniques performed by Wasito and Mirkin (2005) to accommodate for different missing data mechanisms (MCAR, MNAR and a merged data missingness).

The results mainly show that all versions of Nearest-Neighbour-based least-squares imputations presented outperform the global versions. Furthermore, the global-local INI (IMLS-NN-IMLS) approach wins in almost all contexts except when only the local version (the NN-IMLS) wins. The article also includes a detailed description of a data generating process according to the Neural Network NetLab framework, and of the missing data patterns generation. Hence, it is a good reference for anyone planning a simulation study to test imputation methods.

Zhang, S. (2012). Nearest neighbor selection for iteratively kNN imputation. *The Journal of Systems and Software*, 85(11), 2541–2552. doi: 10.1016/j.jss.2012.05.073

The author introduces the Gray k-Nearest-Neighbour (GkNN) algorithm as an improvement to the traditional kNNImpute algorithm (see Troyanskaya *et al.*

2001). This new version uses a Gray Relation Grade measure of similarity, from Gray Relational Analysis, which easily accommodates for both numerical and categorical input variables. Furthermore, the GkNN is an iterative algorithm rooted in the EM framework, and the author claims that such feature makes the algorithm able to account for the uncertainty related to the imputation procedure. Finally, it uses all the information included in the dataset by including in the imputation of an instance  $i$ , the observed and imputed values of other instances that have missing values.

## Multiple Imputation

- Burgette, L. F., & Reiter, J. P. (2010). Multiple imputation for missing data via sequential regression trees. *American Journal of Epidemiology*, 172(9), 1070–1076. doi: 10.1093/aje/kwq260
- Deng, Y., Chang, C., Ido, M. S., & Long, Q. (2016). Multiple imputation for general missing data patterns in the presence of high-dimensional data. *Scientific reports*, 6, 21689. doi: 10.1038/srep21689
- He, R., & Belin, T. (2014). Multiple imputation for high-dimensional mixed incomplete continuous and binary data. *Statistics in Medicine*, 33(13), 2251–2262. doi: 10.1002/sim.6107
- Reiter, J. P. (2005). Using CART to generate partially synthetic, public use microdata. *Journal of Official Statistics*, 21(3), 7–30.
- Song, J., & Belin, T. R. (2004). Imputation for incomplete high-dimensional multivariate normal data using a common factor model. *Statistics in Medicine*, 23(18), 2827–2843. doi: 10.1002/sim.1867
- Wallace, M. L., Anderson, S. J., & Mazumdar, S. (2010). A stochastic multiple imputation algorithm for missing covariate data in tree-structured survival analysis. *Statistics in Medicine*, 29(29), 3004–3016. doi: 10.1002/sim.4079
- Zhao, Y., & Long, Q. (2016). Multiple imputation in the presence of high-dimensional data. *Statistical Methods in Medical Research*, 25(5), 2021–2035. doi: 10.1177/0962280213511027