

## Summary

### Signal Path1

Level and Gain

THD+N

PASSED

Signal to Noise Ratio

Crosstalk, One Channel Undriven
Interchannel Phase

Stepped Frequency Sweep

PASSED

PASSED

PASSED

### Sequence Result:



Signal Path1 : Level and Gain

Waveform: Sine

Generator Level: -0.000 dBFS
DC Offset: 0.000 D
Frequency: 1.00000 kHz

RMS Level (2015/10/20 14:14:39.520)

Ch1 566.4 mVrms Ch2 6.058 uVrms

Gain (2015/10/20 14:14:39.520)

Ch1 566.4 mVrms/FS Ch2 6.058 uVrms/FS

Peak Level (2015/10/20 14:14:39.520)

Ch1 803.4 mV Ch2 26.00 uV

10/20/2015 2:15 Page 2 of 16



Signal Path1: THD+N

Waveform: Sine

Generator Level: -0.000 dBFS
DC Offset: 0.000 D

Frequency: 1.00000 kHz

Low-pass Filter: 20 kHz

Weighting Filter: Signal Path

High-pass Filter: 20 Hz

Notch Tuning Mode: Measured Frequency

THD+N Ratio (2015/10/20 14:14:43.718)

Ch1 0.430453 %

Ch2 ---- %

THD+N Level (2015/10/20 14:14:43.718)

Ch1 2.443 mVrms Ch2 5.085 uVrms

THD Ratio (2015/10/20 14:14:43.718)

Ch1 0.406892 %

Ch2 ---- %

THD Level (2015/10/20 14:14:43.718)

Ch1 2.310 mVrms

Ch2 0.000 Vrms

Noise Ratio (2015/10/20 14:14:43.718)

Ch1 0.125323 %

Ch2 ---- %

Noise Level (2015/10/20 14:14:43.718)

Ch1 711.6 uVrms

Ch2 5.061 uVrms

Distortion Product Ratio (2015/10/20 14:14:43.718)

Distortion Product Ratio Parameters

Frequency Unit: Hz
Ratio Unit: dB

Distortion Product Level (2015/10/20 14:14:43.718)

**Distortion Product Level Parameters** 

10/20/2015 2:15 Page 3 of 16



Frequency Unit: Hz Level Unit: Vrms

Signal Path1 : Signal to Noise Ratio

Waveform: Sine

Generator Level: -0.000 dBFS
DC Offset: 0.000 D
Frequency: 1.00000 kHz

Low-pass Filter: 20 kHz
Weighting Filter: A-wt.
High-pass Filter: 20 Hz

Signal to Noise Ratio (2015/10/20 14:14:48.084)

Ch1 71.259 dB Ch2 0.882 dB

Signal Path1: Crosstalk, One Channel Undriven

Waveform: Sine

Generator Level: -0.000 dBFS
DC Offset: 0.000 D
Frequency: 10.0000 kHz

Crosstalk (2015/10/20 14:14:54.813)

Ch1 110.560 dB Ch2 -115.920 dB

Signal Path1: Interchannel Phase

Waveform: Sine

Generator Level: -0.000 dBFS
DC Offset: 0.000 D
Frequency: 1.00000 kHz

Reference Channel: Ch1

Meter Range: -90 -> 270 deg

Phase (2015/10/20 14:14:57.997)

Ch1 ---- deg Ch2 ---- deg

10/20/2015 2:15 Page 4 of 16



## Signal Path1 : Stepped Frequency Sweep


Generator Level: -0.000 dBFS
DC Offset: 0.000 D
EQ: None

Start Frequency: 20.0000 kHz
Stop Frequency: 20.0000 Hz
Step Type: Logarithmic

Number of Points: 31
Weighting Filter: A-wt.
High-pass Filter: 20 Hz
Phase Ref Channel: Ch1


Measured 1 2015/10/20 14:15:30


#### RMS Level (2015/10/20 14:15:30.858)



10/20/2015 2:15 Page 5 of 16







Result: V PASSED

Relative Level (1.00000 kHz) (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 6 of 16



Relative Level (1.00000 kHz) Parameters

Mode: Normalized at Reference

Ref Frequency: 1.00000 kHz

Deviation (20.0000 Hz - 20.0000 kHz) (2015/10/20 14:15:30.858)


Ch1 ±5.917 dB Ch2 ±0.197 dB

Deviation (20.0000 Hz - 20.0000 kHz) Parameters

Min: 20.0000 Hz Max: 20.0000 kHz

Phase (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 7 of 16



THD+N Ratio (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 8 of 16




THD+N Level (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 9 of 16



THD Ratio (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 10 of 16



THD Level (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 11 of 16



Distortion Product Ratio (H2) (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 12 of 16



Distortion Product Ratio (H2) Parameters

Harmonics: Single Harmonic

Harmonic Number: 2

Result: V PASSED

Distortion Product Level (H2) (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 13 of 16



Distortion Product Level (H2) Parameters

Harmonics: Single Harmonic

Harmonic Number: 2

Result: V PASSED

SINAD (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 14 of 16



Peak Level (2015/10/20 14:15:30.858)

10/20/2015 2:15 Page 15 of 16



10/20/2015 2:15 Page 16 of 16