



Guide to Kernel Driver Integration in Android for Huawei WCDMA & CDMA & LTE Modules

Issue	1.2.6
Date	2013-09-06

Huawei Technologies Co., Ltd. provides customers with comprehensive technical support and service. For any assistance, please contact our local office or company headquarters.

Huawei Technologies Co., Ltd.

Huawei Industrial Base, Bantian, Longgang, Shenzhen 518129, People's Republic of China

Tel: +86-755-28780808 Global Hotline: +86-755-28560808 Website: www.huawei.com

E-mail: mobile@huawei.com

Please refer color and shape to product. Huawei reserves the right to make changes or improvements to any of the products without prior notice.

Copyright © Huawei Technologies Co., Ltd. 2013. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

The product described in this manual may include copyrighted software of Huawei Technologies Co., Ltd and possible licensors. Customers shall not in any manner reproduce, distribute, modify, decompile, disassemble, decrypt, extract, reverse engineer, lease, assign, or sublicense the said software, unless such restrictions are prohibited by applicable laws or such actions are approved by respective copyright holders under licenses.

Trademarks and Permissions



HUAWEI

, HUAWEI



are trademarks or registered trademarks of Huawei Technologies Co., Ltd.

Other trademarks, product, service and company names mentioned are the property of their respective owners.

Notice

Some features of the product and its accessories described herein rely on the software installed, capacities and settings of local network, and may not be activated or may be limited by local network operators or network service providers, thus the descriptions herein may not exactly match the product or its accessories you purchase.

Huawei Technologies Co., Ltd reserves the right to change or modify any information or specifications contained in this manual without prior notice or obligation.

NO WARRANTY

THE CONTENTS OF THIS MANUAL ARE PROVIDED "AS IS". EXCEPT AS REQUIRED BY APPLICABLE LAWS, NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE MADE IN RELATION TO THE ACCURACY, RELIABILITY OR CONTENTS OF THIS MANUAL.

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO CASE SHALL HUAWEI TECHNOLOGIES CO., LTD BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, OR LOST PROFITS, BUSINESS, REVENUE, DATA, GOODWILL OR ANTICIPATED SAVINGS.

Import and Export Regulations

Customers shall comply with all applicable export or import laws and regulations and will obtain all necessary governmental permits and licenses in order to export, re-export or import the product mentioned in this manual including the software and technical data therein.



About This Document

Revision History

Document Version	Date	Chapter	Change Description
V1.0	2010-11-29		Completed the draft
V1.0.1	2011-05-03		Add the method of modifying the kernel files to support new PIDs and to enable the autosuspend feature
V1.2.1	2011-08-25		Add the method to solve upgrade problem in android system used by MC509
V1.2.3	2011-11-10		Enable zero Packet feature.
V1.2.4	2013-01-31		Update the comment scope
V1.2.6	2013-09-06	2	Updated Table 2-1 Linux kernel driver architecture supporting Huawei modules in Android
		All	Added the description related to the CDC ECM Driver
		All	Added the product scope of LTE
		5	Added chapter Appendix



Contents

1 Purpose	5
2 Scope	6
3 Overview	7
3.1 Linux Kernel Driver Architecture Supporting Huawei Modules in Android	7
4 Android's Linux Kernel Driver Integration Scheme	9
4.1 USB Serial Port Driver of Android Kernel	9
4.1.1 Revision on USB Serial Port Driver Integration	9
4.1.2 Configuration Procedures for USB Serial Port Driver Integration	18
4.2 Android's Linux Kernel CDC ECM Driver Integration	23
4.2.1 Revision on CDC ECM Driver Integration	23
4.2.2 Configuration Procedures for CDC ECM Driver Integration	24
5 Appendix	28
5.1 Checking Whether the Correct USB Serial Port Driver Exists in the Kernel	28
5.2 Checking Whether the Correct CDC ECM Driver Exists in the Kernel	28
5.3 Obtaining the Port Mapping Information of the Board	29



1 Purpose

This guide instructs the kernel driver integration development for Huawei modules based on Android operating system (OS). It is intended for the driver developers of the products based on Android OS.

2 Scope

This guide applies to:

- Embedded Linux with kernel version 2.6.35 or later^[1]
- Android 2.3 (Linux kernel 2.6.35) or later
- Huawei LTE, WCDMA and CDMA Modules

**NOTE**

[1]: If the host does not care power consumption of Huawei modules, the Linux can be integrated with kernel version 2.6.18 or later.


3 Overview

3.1 Linux Kernel Driver Architecture Supporting Huawei Modules in Android

Huawei modules communicate with Android mainly over Universal Serial Bus (USB) ports. Linux kernel of Android needs to load USB drivers according to the information about the USB device ports reported by Huawei modules. Huawei modules can work normally only after the correct USB drivers are loaded.

Figure 3-1 shows the Linux kernel driver architecture supporting Huawei modules in Android.

Figure 3-1 Linux kernel driver architecture supporting Huawei modules in Android





As shown in Figure 3-1 , in the USB driver architecture of Linux, the drivers related to Huawei modules are the USB serial port driver and CDC ECM driver.

- USB serial port driver: supports the ports such as the modem port and the AT command port. The code file (**option.c**) of this driver has been added into the source code of Linux kernel.
- CDC ECM driver: works as a standard ECM network port driver for USB and is used to transport network data.

4

Android's Linux Kernel Driver Integration Scheme

4.1 USB Serial Port Driver of Android Kernel

This integration scheme involves the following Linux kernel source code files:

- drivers/usb/serial/option.c
- drivers/usb/serial/usb_wwan.c

4.1.1 Revision on USB Serial Port Driver Integration

1. Linux kernels in version 2.6.35 or later versions have the selective suspend feature for USB serial port drivers. Therefore, enable this feature and the USB serial port drivers will support the selective suspend feature for power management.
2. To enable this feature, add the contents enclosed in the red rectangle in the following figure into the **option_attach ()** function in the **option.c** file in **/drivers/usb/serial/**. As the following figure illustrates, first add the macro of **#define HUAWEI_VENDOR_ID 0x12d1**.

```
if (serial->dev->descriptor.idVendor == HUAWEI_VENDOR_ID) {  
    if ( 0 != (serial->dev->config->desc.bmAttributes & 0x20)){  
        usb_enable_autosuspend(serial->dev);  
    }  
}  
  
data = serial->private = kzalloc(sizeof(struct usb_wwan_intf_private), GFP_KERNEL);  
  
if (!data)  
    return -ENOMEM;
```

Copy and paste the following contents:

```
if (serial->dev->descriptor.idVendor == HUAWEI_VENDOR_ID) {  
    if ( 0 != (serial->dev->config->desc.bmAttributes & 0x20)){  
        usb_enable_autosuspend(serial->dev);  
    }  
}
```

3. To invoke the **reset_resume** function, add the sentence enclosed in the red rectangle in the following figure. (If this operation is cancelled in some versions, the sentence enclosed in the red rectangle does not need to be added.)

```
static struct usb_driver option_driver = {
    .name      = "option",
    .probe     = usb_serial_probe,
    .disconnect = usb_serial_disconnect,
#ifdef CONFIG_PM
    .suspend   = usb_serial_suspend,
    .resume    = usb_serial_resume,
    .reset_resume = usb_serial_resume,
    .supports_autosuspend = 1,

```

Copy and paste the following contents:

```
.reset_resume = usb_serial_resume,
```

4. Add new supporting declarations for Huawei modules. Modifications are as follows:
 - Add the macro definition enclosed in the red rectangle in the following figure.

```
#include "usb-wwan.h"

/* Function prototypes */
static int option_probe(struct usb_serial *serial,
                        const struct usb_device_id *id);
static int option_send_setup(struct usb_serial_port *port);
static void option_instat_callback(struct urb *urb);

#define HW_USB_DEVICE_AND_INTERFACE_INFO(vend, cl, sc, pr) \
    .match_flags = USB_DEVICE_ID_MATCH_INT_INFO \
        | USB_DEVICE_ID_MATCH_VENDOR, \
    .idVendor = (vend), \
    .bInterfaceClass = (cl), \
    .bInterfaceSubClass = (sc), \
    .bInterfaceProtocol = (pr)
```

Copy and paste the following contents:

```
#define HW_USB_DEVICE_AND_INTERFACE_INFO(vend, cl, sc, pr) \
    .match_flags = USB_DEVICE_ID_MATCH_INT_INFO \
        | USB_DEVICE_ID_MATCH_VENDOR, \
    .idVendor = (vend), \
    .bInterfaceClass = (cl), \
    .bInterfaceSubClass = (sc), \
    .bInterfaceProtocol = (pr)
```

- Add the following sentences to the **static const struct usb_device_id option_ids[]** id list:

```
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0xff, 0xff) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x01) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x02) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x03) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x04) },
```

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]


```
{ HW_USB_DEVICE_AND_INTERFACE_INFO (HUAWEI_VENDOR_ID, 0xff, 0x06, 0x4C) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO (HUAWEI_VENDOR_ID, 0xff, 0x06, 0x4D) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO (HUAWEI_VENDOR_ID, 0xff, 0x06, 0x78) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO (HUAWEI_VENDOR_ID, 0xff, 0x06, 0x79) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO (HUAWEI_VENDOR_ID, 0xff, 0x06, 0x7A) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO (HUAWEI_VENDOR_ID, 0xff, 0x06, 0x7B) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO (HUAWEI_VENDOR_ID, 0xff, 0x06, 0x7C) },
{ HW_USB_DEVICE_AND_INTERFACE_INFO (HUAWEI_VENDOR_ID, 0xff, 0x06, 0x7D) },
```

5. Enable the zero packet feature to solve problems caused by module upgrades. The file to be modified is in the **drivers/usb/serial/usb_wwan.c** directory.

- Add the definition of the bcdUSB value (#define HW_bcdUSB 0x0110) and the definition of the Huawei vid value (#define HUAWEI_VENDOR_ID 0x12d1), as shown in the red rectangle in the following figure.

```
#include <linux/usb/serial.h>
#include "usb-wwan.h"
```

```
static int debug;
#define HW_bcdUSB 0x0110
#define HUAWEI_VENDOR_ID 0x12d1
```

```
void usb_wwan_dtr_rts(struct usb_serial_port *port, int on)
```

Copy and paste the following contents:

```
#define HW_bcdUSB 0x0110
#define HUAWEI_VENDOR_ID 0x12d1
```

- Add the definition of "struct usb_host_endpoint *ep" in the **usb_wwan_write** function. Then add the judgment of ZERO_PACKET in the **usb_wwan_write** function, as shown in the red rectangle in the following figure.

```
/* send the data */
memcpy(this_urb->transfer_buffer, buf, todo);
this_urb->transfer_buffer_length = todo;

if ((HUAWEI_VENDOR_ID == port->serial->dev->descriptor.idVendor)
    && (HW_bcdUSB != port->serial->dev->descriptor.bcdUSB)) {
    ep = usb_pipe_endpoint(this_urb->dev, this_urb->pipe);
    if (ep && (0 != this_urb->transfer_buffer_length)
        && (0 == this_urb->transfer_buffer_length % ep->desc.wMaxPacketSize)) {
        this_urb->transfer_flags |= URB_ZERO_PACKET;
    }
}
```

```
spin_lock_irqsave(&intfdata->susp_lock, flags);
```

Copy and paste the following contents:

```
if ((HUAWEI_VENDOR_ID == port->serial->dev->descriptor.idVendor)
    && (HW_bcdUSB != port->serial->dev->descriptor.bcdUSB)) {
    ep = usb_pipe_endpoint(this_urb->dev, this_urb->pipe);
    if (ep && (0 != this_urb->transfer_buffer_length)
        && (0 == this_urb->transfer_buffer_length % ep->desc.wMaxPacketSize)) {
        this_urb->transfer_flags |= URB_ZERO_PACKET;
    }
}
```

6. Modify the compilation configuration of Android kernel (in the **.config** file in the kernel root directory), and ensure that the following configuration options are enabled. For detailed configuration operations, see section 4.1.2 "Configuration Procedures for USB Serial Port Driver Integration."

- Configuration options related to USB power management:

```
CONFIG_USB_SUSPEND=y
```

- Configuration options related to the USB serial port driver:

```
CONFIG_USB_SERIAL=y
```

```
CONFIG_USB_SERIAL_OPTION=y
```

```
CONFIG_USB_SERIAL_WWAN=y
```

- Configuration options related to PPP dial-up connections:

```
CONFIG_PPP=y
```

```
CONFIG_PPP_MULTILINK=y
```

```
CONFIG_PPP_FILTER=y
```

```
CONFIG_PPP_ASYNC=y
```

```
CONFIG_PPP_SYNC_TTY=y
```


```
CONFIG_PPP_DEFLATE=y
```

```
CONFIG_PPP_BSDCOMP=y
```

4.1.2 Configuration Procedures for USB Serial Port Driver Integration

To configure USB serial port driver integration, perform the following steps:




- Step 1 Run the **Terminal** tool, enter the **kernel** directory (assume that the kernel is in the **/usr/src/myandroid/** directory, that is, **cd /usr/src/myandroid/kernel**), and then run the **make <configuration>** command (in this guide, assume that the standard **make menuconfig** command is used).



```
root@fangxz-desktop: /usr/src/mydroid/kernel
File Edit View Terminal Help
root@fangxz-desktop: /usr/src# cd mydroid/kernel/
root@fangxz-desktop: /usr/src/mydroid/kernel# make menuconfig
```

- Step 2 Select related configuration options.

1. Configuration options related to USB power management:



```

Device Drivers
Arrow keys navigate the menu. <Enter> selects submenus ---. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module <> module capable

^(-)
Character devices ---
<*> I2C support ---
[*] SPI support ---
  PPS support ---
  *- GPIO Support ---
  <> Dallas's 1-wire support ---
  <*> Power supply class support ---
  <> Hardware Monitoring support ---
  <> Generic Thermal sysfs driver ---
  [ ] Watchdog Timer Support ---
    Sonics Silicon Backplane ---
  Multifunction device drivers ---
  [*] Voltage and Current Regulator Support ---
  <*> Multimedia support ---
    Graphics support ---
  <> Sound card support ---
  [*] HID Devices ---
  [*] USB support ---
  <> Ultra Wideband devices (EXPERIMENTAL) ---
  <*> MMC/SD/SDIO card support ---
v(+)

<Select> < Exit > < Help >

```

```

USB support
Arrow keys navigate the menu. <Enter> selects submenus ---. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module <> module capable

^(-)
[ ] USB device class-devices (DEPRECATED)
[ ] Dynamic USB minor allocation
[*] USB selective suspend/resume and wakeup
[ ] Rely on DTG targeted Peripherals List
[ ] Disable external hubs
<*> USB Monitor
<> Enable Wireless USB extensions (EXPERIMENTAL)
<> Support WUSB Cable Based Association (CBA)
*** USB Host Controller Drivers ***
<> Cypress C67x00 HCD support
<> xHCI HCD (USB 3.0) support (EXPERIMENTAL)
<*> EHCI HCD (USB 2.0) support
  *- Root Hub Transaction Translators
    [ ] Improved Transaction Translator scheduling (EXPERIMENTAL)
  <> OXU210HP HCD support
  <> ISP116X HCD support
  <> ISP 1760 HCD support
  <> ISP1362 HCD support
  <> OHCI HCD support
  <> UHCI HCD (most Intel and VIA) support
v(+)

<Select> < Exit > < Help >

```

2. Configuration options related to the USB serial port driver:

```

Linux Kernel Configuration
Arrow keys navigate the menu. <Enter> selects submenus ---. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module <> module capable

General setup ---
[*] Enable loadable module support ---
[*] Enable the block layer ---
System Type ---
Bus support ---
Kernel Features ---
Boot options ---
CPU Power Management ---
Floating point emulation ---
Userspace binary formats ---
Power management options ---
[*] Networking support ---
  [*] Device Drivers ---
    File systems ---
    Kernel hacking ---
    Security options ---
    <> Cryptographic API ---
    Library routines ---
  ---
  Load an Alternate Configuration File
v(+)

<Select> < Exit > < Help >

```

```

Device Drivers
Arrow keys navigate the menu. <Enter> selects submenus ---. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module <> module capable

^(-)
Character devices ---
<*> I2C support ---
[*] SPI support ---
PPS support ---
-.*- GPIO Support ---
<> Dallas's 1-wire support ---
<*> Power supply class support ---
<> Hardware Monitoring support ---
<> Generic Thermal sysfs driver ---
[ ] Watchdog Timer Support ---
Sonics Silicon Backplane ---
Multifunction device drivers ---
[*] Voltage and Current Regulator Support ---
<*> Multimedia support ---
Graphics support ---
<> Sound card support ---
[*] HID Devices ---
[*] USB support ---
<> Ultra Wideband devices (EXPERIMENTAL) ---
<*> MMC/SD/SDIO card support ---

v(+)
<Select> < Exit > < Help >

```

```

USB support
Arrow keys navigate the menu. <Enter> selects submenus ---. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module <> module capable

^(-)
<> Olympus MAUSB-10/Fuji DPC-R1 support
<> Support OneTouch Button on Maxtor Hard Drives
<> Support for Rio Karma music player
<> SAT emulation on Cypress USB/ATA Bridge with ATACB
[ ] The shared table of common (or usual) storage devices
*** USB Imaging devices ***
<> USB Mustek MDC800 Digital Camera support
<> Microtek X6USB scanner support
*** USB port drivers ***
<*> USB Serial Converter support ---
*** USB Miscellaneous drivers ***
<> EMI 6/2m USB Audio interface support
<> EMI 2/6 USB Audio interface support
<> ADU devices from Ontrak Control Systems
<> USB 7-Segment LED Display
<> USB Diamond Rio500 support
<> USB Lego Infrared Tower support
<> USB LCD driver support
<> USB BlackBerry recharge support
<> USB LED driver support

v(+)
<Select> < Exit > < Help >

```

```




USB Serial Converter support
Arrow keys navigate the menu. <Enter> selects submenus ---. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module <> module capable

^(-)
<> USB Moschip 7720 Serial Driver (NEW)
<> USB Moschip 7840/7820 USB Serial Driver (NEW)
<> USB Motorola Phone modem driver (NEW)
<> USB Navman GPS device (NEW)
<> USB Prolific 2303 Single Port Serial Driver (NEW)
<> USB Qualcomm Serial modem (NEW)
<> USB SPCP8x5 USB To Serial Driver (NEW)
<> USB HP4x Calculators support (NEW)
<> USB Safe Serial (Encapsulated) Driver (NEW)
<> USB Siemens MPI driver (NEW)
<> USB Sierra Wireless driver (NEW)
<> USB Symbol Barcode driver (serial mode) (NEW)
<> USB TI 3410/5052 Serial Driver (NEW)
<> USB REINER SCT cyberJack pinpad/e-com chipcard reader (NEW)
<> USB Xircom / Entegre Single Port Serial Driver (NEW)
<*> USB driver for GSM and CDMA modems
<> USB ZyXEL omni.net LCD Plus Driver (NEW)
<> USB Opticon Barcode driver (serial mode) (NEW)
<> USB Debugging Device (NEW)


<Select> < Exit > < Help >

```

3. Configuration options related to PPP dial-up connections:



- Step 3 Select **Exit** to exit all configuration screens. Then, in the window for saving the configuration, select **<Yes>** to exit and save the configuration.



- Step 4 After the configuration is completed, run the **make** command to compile the revised kernel version.

----End

4.2 Android's Linux Kernel CDC ECM Driver Integration

This integration scheme involves the following Linux kernel source code file:

drivers/net/usb/usbnet.c.

4.2.1 Revision on CDC ECM Driver Integration

To enable this feature, add the contents enclosed in the red rectangle in the following figure into the **usbnet_probe ()** function in the **usbnet.c** file in **drivers/net/usb/**. As shown in the following figure, first add the macro of **#define HUAWEI_VENDOR_ID 0x12d1**.

```
usb_set_intfdata (udev, dev);

if(xdev->descriptor.idVendor == HUAWEI_VENDOR_ID){
    if( 0 != (xdev->config->desc.bmAttributes & 0x20)){
        usb_enable_autosuspend(xdev);
    }
}

netif_device_attach (net);

if (dev->driver_info->flags & FLAG_LINK_INTR)
    netif_carrier_off(net);

return 0;
```

Copy and paste the following contents:

```
if(xdev->descriptor.idVendor == HUAWEI_VENDOR_ID){
    if( 0 != (xdev->config->desc.bmAttributes & 0x20)){
```

```
        usb_enable_autosuspend(xdev);  
    }  
}
```

4.2.2 Configuration Procedures for CDC ECM Driver Integration

To configure CDC ECM driver integration, perform the following steps:


- Step 1 Modify the compilation configuration of Android kernel (in the **.config** file in the kernel root directory), and ensure that the following configuration options are enabled.

Relevant configuration options related to CND ECM driver integration:

```
CONFIG_USB_USBNET=y  
CONFIG_NETDEVICES=y  
CONFIG_USB_NET_CDCETHER=y
```

- Step 2 Specific operations are as follows:

1. Run the **Terminal** tool, enter the **kernel** directory (assume that the kernel is in the **/usr/src/myandroid/** directory, that is, **cd /usr/src/myandroid/kernel**), and then run the **make <configuration>** command (in this guide, assume that the standard **make menuconfig** command is used).



```
root@fangxz-desktop: /usr/src/mydroid/kernel  
File Edit View Terminal Help  
root@fangxz-desktop: /usr/src# cd mydroid/kernel/  
root@fangxz-desktop: /usr/src/mydroid/kernel# make menuconfig
```

2. Configure the CDC ECM driver configuration options, as shown in the following figures.


```
.config - Linux/i386 3.8.0-rc2 Kernel Configuration

Linux/i386 3.8.0-rc2 Kernel Configuration
Arrow keys navigate the menu. <Enter> selects submenus --->.
Highlighted letters are hotkeys. Pressing <Y> includes, <N> excludes,
<M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </>
for Search. Legend: [*] built-in [ ] excluded <M> module < >

General setup --->
[*] Enable loadable module support --->
-- Enable the block layer --->
Processor type and features --->
Power management and ACPI options --->
Bus options (PCI etc.) --->
Executable file formats / Emulations --->
-- Networking support --->
  [*] Device Drivers --->
    Firmware Drivers --->
v(+)

<Select> < Exit > < Help >
```

```
.config - Linux/i386 3.8.0-rc2 Kernel Configuration

Device Drivers
Arrow keys navigate the menu. <Enter> selects submenus --->.
Highlighted letters are hotkeys. Pressing <Y> includes, <N> excludes,
<M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </>
for Search. Legend: [*] built-in [ ] excluded <M> module < >

^(-)
[*] Multiple devices driver support (RAID and LVM) --->
<M> Generic Target Core Mod (TCM) and ConfigFS Infrastructure --
[*] Fusion MPT device support --->
IEEE 1394 (FireWire) support --->
< > I2O device support --->
[*] Macintosh device drivers --->
-- Network device support --->
  Input device support --->
  Character devices --->
  {M} I2C support --->
v(+)

<Select> < Exit > < Help >
```

```
.config - Linux/i386 3.8.0-rc2 Kernel Configuration

Network device support
Arrow keys navigate the menu. <Enter> selects submenus --->.
Highlighted letters are hotkeys. Pressing <Y> includes, <N> excludes,
<M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </>
for Search. Legend: [*] built-in [ ] excluded <M> module < >

^ (-)
<M>   PPP over L2TP (EXPERIMENTAL)
<M>   PPP support for async serial ports
<M>   PPP support for sync tty ports
<M>   SLIP (serial line) support
[*]   CSLIP compressed headers
[*]   Keepalive and linefill
[ ]   Six bit SLIP encapsulation
[*]   USB Network Adapters --->
[*]   Wireless LAN --->
      WiMAX Wireless Broadband devices --->
v(+)


<Select>    < Exit >    < Help >
```

```
.config - Linux/i386 3.8.0-rc2 Kernel Configuration


USB Network Adapters
Arrow keys navigate the menu. <Enter> selects submenus --->.
Highlighted letters are hotkeys. Pressing <Y> includes, <N> excludes,
<M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </>
for Search. Legend: [*] built-in [ ] excluded <M> module < >

<M> USB CATC NetMate-based Ethernet device support (EXPERIMENTAL)
<M> USB KLSI KL5USB101-based ethernet device support
<M> USB Pegasus/Pegasus-II based ethernet device support
<M> USB RTL8150 based ethernet device support (EXPERIMENTAL)
[*] Multi-purpose USB Networking Framework
<M>   ASIX AX88xxx Based USB 2.0 Ethernet Adapters
[*]   CDC Ethernet support (smart devices such as cable modems)
<M>   CDC EEM support
{M}   CDC NCM support
<M>   CDC MBIM support
v(+)

<Select>    < Exit >    < Help >
```



- Step 3 Select **Exit** to exit all configuration screens. Then, in the window for saving the configuration, select **<Yes>** to exit and save the configuration.



- Step 4 After the configuration is completed, run the **make** command to compile the revised kernel version.

----End

5 Appendix

5.1 Checking Whether the Correct USB Serial Port Driver Exists in the Kernel

Run the following command to check the kernel log information:

```
dmesg
```

If the following information (or similar information) exists in the kernel log, the correct USB serial port driver has been integrated into the kernel.

```
[ 1.755889] usb usb1: New USB device strings: Mfr=3, Product=2, SerialNumber=1
[ 1.755893] usb usb1: Product: EHCI Host Controller
[ 1.755897] usb usb1: Manufacturer: Linux 2.6.36.3 ehci_hcd
[ 1.755900] usb usb1: SerialNumber: 0000:00:1a.0
[ 1.755994] hub 1-0:1.0: USB hub found
[ 1.755998] hub 1-0:1.0: 3 ports detected
[ 1.756049] ehci_hcd 0000:00:1d.0: PCI INT A -> GSI 23 (level, low) -> IRQ 23
[ 1.756061] ehci_hcd 0000:00:1d.0: EHCI Host Controller
[ 1.756066] ehci_hcd 0000:00:1d.0: new USB bus registered, assigned bus number 2
[ 1.756085] ehci_hcd 0000:00:1d.0: debug port 2
[ 1.760048] ehci_hcd 0000:00:1d.0: irq 23, io mem 0xfe526000
[ 1.769818] ehci_hcd 0000:00:1d.0: USB 2.0 started, EHCI 1.00
[ 1.769854] usb usb2: New USB device found, idVendor=1d6b, idProduct=0002
[ 1.769858] usb usb2: New USB device strings: Mfr=3, Product=2, SerialNumber=1
[ 1.769862] usb usb2: Product: EHCI Host Controller
[ 1.769866] usb usb2: Manufacturer: Linux 2.6.36.3 ehci_hcd
[ 1.769869] usb usb2: SerialNumber: 0000:00:1d.0
[ 1.769951] hub 2-0:1.0: USB hub found
[ 1.769953] hub 2-0:1.0: 3 ports detected
[ 1.770011] usbcore: registered new interface driver usbserial
[ 1.770018] USB Serial support registered for generic
[ 1.770025] usbcore: registered new interface driver usbserial_generic
[ 1.770026] usbserial: USB Serial Driver core
[ 1.770032] USB Serial support registered for GSM modem (1-port)
[ 1.770044] usbcore: registered new interface driver option
```

5.2 Checking Whether the Correct CDC ECM Driver Exists in the Kernel

Run the following command to check the kernel log information:

`dmesg`

If the information in the red rectangle in the following figure exists in the kernel log, the correct CDC ECM driver has been integrated into the kernel.

```
226.168555] usb 2-1.2: USB disconnect, device number 3
226.170773] cdc_ether 2-1.2:2.0 eth0: unregister 'cdc_ether' usb-0000:00:1d:0
226.177183] option1 ttyUSB0: GSM modem (1-port) converter now disconnected fr
226.177198] option 2-1.2:2.2: device disconnected
257.419920] usb 2-1.2: new high-speed USB device number 4 using ehci-pci
257.536485] usb 2-1.2: New USB device found, idVendor=12d1, idProduct=1573
257.536489] usb 2-1.2: New USB device strings: Mfr=2, Product=3, SerialNumber
257.536493] usb 2-1.2: Product: HUAWEI Mobile
257.536496] usb 2-1.2: Manufacturer: HUAWEI Technology
257.536498] usb 2-1.2: SerialNumber: 0123456712ABCA17
257.595410] cdc_ether 2-1.2:2.0 eth0: register 'cdc_ether' at usb-0000:00:1d:
257.608340] option 2-1.2:2.2: GSM modem (1-port) converter detected
257.608735] usb 2-1.2: GSM modem (1-port) converter now attached to ttyUSB0
```

5.3 Obtaining the Port Mapping Information of the Board

Run the `dmesg` command to check whether the driver for Huawei modules has been loaded successfully. If the information in the red rectangle in the following figure exists in the kernel log, the correct driver has been loaded successfully. (The value of `idProduct` varies with the actual product.)

```
226.168555] usb 2-1.2: USB disconnect, device number 3
226.170773] cdc_ether 2-1.2:2.0 eth0: unregister 'cdc_ether' usb-0000:00:1d:0
226.177183] option1 ttyUSB0: GSM modem (1-port) converter now disconnected fr
226.177198] option 2-1.2:2.2: device disconnected
257.419920] usb 2-1.2: new high-speed USB device number 4 using ehci-pci
257.536485] usb 2-1.2: New USB device found, idVendor=12d1, idProduct=1573
257.536489] usb 2-1.2: New USB device strings: Mfr=2, Product=3, SerialNumber
257.536493] usb 2-1.2: Product: HUAWEI Mobile
257.536496] usb 2-1.2: Manufacturer: HUAWEI Technology
257.536498] usb 2-1.2: SerialNumber: 0123456712ABCA17
257.595410] cdc_ether 2-1.2:2.0 eth0: register 'cdc_ether' at usb-0000:00:1d:
257.608340] option 2-1.2:2.2: GSM modem (1-port) converter detected
257.608735] usb 2-1.2: GSM modem (1-port) converter now attached to ttyUSB0
```

To query the device file names of Huawei modules' ports (such as the modem and pcui ports), run the following command:

```
ls /dev/ttyUSB*
```

```
# ls /dev/ttyU*
/dev/ttyUSB0
/dev/ttyUSB1
/dev/ttyUSB2
/dev/ttyUSB3
/dev/ttyUSB4
```