AppoTech
卓荣集成

CW6611A

Bluetooth Audio Player Microcontroller

Product Spec

[CW6611A-PS-EN]

Versions: 1.1.0

Release Date: 2016/9/23

Unit705-707,7/F IC Development Centre,
No.6 Science Park West Ave,
Hong Kong Science Apark,
Shation,N.T.,HongKong.
香港新界沙田香港科学园科技大道西6号
集成电路开发中心7楼705-707室

Tel 电话: (852)26074090
Fax传真: (852)26074096
info@appotech.com

www.appotech.com www.buildwin.com

Table of content

Table of content II
1 Product Overview 1
1.1 Outline 1
1.2 Features 1
2 Pin Definitions 2
2.1 CW6611A 2
2.1.1 Package 2
2.1.2 Pin Assignment 2
2.1.3 Pin Desciption 2
3 Characteristics 5
3.1 PMU Parameters 5
3.2 CORE PLL Parameters 5
3.3 General purpose I/O Parameters 5
3.4 Audio ADDA Parameters 6
3.5 RF Analog Blocks 6
4 Package Outline Dimensions 8
4.1 SSOP28 8
Revision History i

1 Product Overview

1.1 Outline

CW6611A is an MCS-51™ Compatible high performance mixed signal microcontroller. It integrates advanced digital and analog peripherals to suit for BT audio playback and BT Communicate applications.

1.2 Features

- CPU Compatible with MCS-51TM instruction set;
- Compliant to Bluetooth 4.2 + EDR, backward-compatible with BT1.2, 2.0, 2.1,3.0 and 4.1
- Support SCMS-T content protection method;
- Support HFP v1.6, HSP v1.2, A2DP 1.3, AVCTP 1.4, AVDTP 1.3 and AVRCP 1.5;
- Class 2 power level, RF Performance: Tx:0dBm, Rx: -85dBm;
- Support simple pairing and auto reconnection function;
- Support MP3/SBC decoder;
- Support two pairs of AUX;
- Six Channels 10-bit SARADC;
- support 16bit Mono DAC with >90dB SNR, embedded with four class A/B headphone amplifier
- 16bit Mono ADC with >90dB DR
- Support Audio record function to MIC ADPCM;
- Support Audio playback from SD
- Two 8-bit timers, support Capture and PWM mode;
- Two 16-bit timers, support Capture and PWM mode;
- Watchdog Timer with on-chip RC oscillator;
- Support full-duplex UART, SPI, SD interface;
- Support IIC interface for FM function;
- 2 channels 16 levels Low Voltage Detector;
- Power on Reset
- Internal crystal oscillator support 26M crystal
- Internal LDO regulator:4.2V to 1.35V, 4.2V to 3.3V

2 Pin Definitions

2.1 CW6611A

2.1.1 Package

SSOP28

2.1.2 Pin Assignment

Figure 2-1 shows the pin assignments of SSOP28 package.



Figure 2-1 Pin Assignment of CW6611A

2.1.3 Pin Desciption

Table 2-1 shows the pin description of CW6611A.

Table 2-1 Pin Description of CW6611A

Pin No.SSOP28	Name	Type	Function
1	P21	I/O	GPIO AUXR2 ADC1 SDCLK EMIDAT1 LCD_D1
2	MICN	A	MIC Negative input
3	MICP/VCM	A	MIC Positive input DAC VCM output
4	AVSS	GND	Analog GND
5	VDDHP	PWR	Headphone power
6	DACR	A	DAC right output GPIO input
7	P01/VCM_BUF	I/O	GPIO AUXR0 UARTTX1 PORT INT/WKUP0 SDDAT2 DAC VCM buffer
8	P00	I/O	GPIO AUXL0 UARTRX1 SDDAT1 SPI0DIN2
9	P13	I/O	GPIO ADC5
10	P31	I/O	GPIO SDCMD SPI0DIN3
11	P32	I/O	GPIO SDDAT0 SPI0DOUT3/DIN3
12	P30	I/O	GPIO ADC4 SDCLK SPI0CLK3
13	P04	I/O	GPIO SPI1DOUT/DIN1
14	P05	I/O	GPIO SPI1CLK
15	P36	I/O	GPIO
16	PAD_VCC_IF	PWR	Power VCC

Pin No.SSOP28	Name	Type	Function
	VCC_RF VCC_PA		RF/PA Power VCC
17	RXTX	A	RF Rx and Tx pin
18	GND_ANT1	GND	RF GND
19	VCC_VCO VCC_XO/ PAD_VDDQ	PWR	Power VCC Power VCC/VDDQ
20	XO_P	A	BT 26MHz XOSC Positive Pin
21	XO_N	A	BT 26MHz XOSC Negative Pin
22	BVIN	PWR	PMU Power input Pin 4.2V(typ)
23	VOUT1V5	PWR	Power LVD output
24	VDDLDO	PWR	LDO power input 4.2V(typ)
25	VDDIO/AVDD	PWR	Power output VDDIO 3.3V
26	P10	I/O	GPIO
27	P11	I/O	GPIO
28	P20	I/O	GPIO

3 Characteristics

3.1 PMU Parameters

Table 3-1 PMU Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
BVIN	Buck input voltage	2.8	4.2	4.6	V	
VDDLDO	VDDLDO input voltage	2.8	4.2	4.6	V	
VOUT1V5	Power LDO output voltage	1.15	1.35	1.6	V	
VDDHP	Audio LDO output voltage	2.8	3.0	3.3	V	
VCM	Audio VCM output voltage	1.15	1.35	1.6	V	
VDDIO	3.3V output voltage	3.0	3.3	3.6	V	

3.2 CORE PLL Parameters

Table 3-2 PLL Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
F_{I1}	Frequency input	-	32.768	-	KHz	Low frequency OSC
F_{I2}	Frequency input	1	12	15	MHz	High frequency OSC
F_{OUT1}	Frequency output	-	48	-	MHz	
T_{LOCK1}	PLL locked time	-	2	-	ms	Use low frequency OSC as input reference
T_{LOCK2}	PLL locked time	-	0.1	-	ms	Use high frequency OSC as input reference

3.3 General purpose I/O Parameters

Table 3-3 I/O Parameters

Symbol	Description	Min	Typ	Max	Units	Conditions
V_{IL}	Low-Level input voltage	-	-	30% * VDDIO	V	VDDIO = 3.3V
V_{IH}	High-level input voltage	70% * VDDIO	-	-	V	VDDIO = 3.3V
R_{PUP0}	Internal pull-up resister 0	-	10	-	KΩ	
R_{PUP1}	Internal pull-up resister 1	-	200	-	KΩ	
R_{PUP2}	Internal pull-up resister 2	-	0.5	-	KΩ	
R_{PDN0}	Internal pull-down resister 0	-	10	-	KΩ	
R_{PDN1}	Internal pull-down resister 1	-	0.33	-	KΩ	
R_{PDN2}	Internal pull-down resister 2	-	0.5	-	KΩ	
I_{LEVEL1}	Level1 current driving	8	-	-	mA	For PORT1
I_{LEVEL2}	Level2 current driving	24	-	-	mA	For Port1.1

3.4 **Audio ADDA Parameters**

Table 3-4 Audio DAC Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
DAC SNR&DR		-	90	-	dB	48PIN
DAC SNR&DR		-	90	-	dB	28PIN & 20 PIN
DAC THD+N		-	-80	-	dB	10Kohm loading
PWR_{AB}	ClassAB AMP power output	-	-	16	mW	32ohm loading
V_{PP}	Maximum output voltage	-	-	2.6	V	10Kohm loading
ADC SNR/DR			93		dB	In Voice Band
ADC THD+N			89		dB	In Voice Band

3.5 **RF Analog Blocks**

Table 3-5 Frequency Synthesizer Parameters

Parameter	Condition		MIN	typ	max	Unit
Synthesizer						
Synthesizer settling time	Within +/- 25 KHz accuracy		-	70	-	us
Phase Noise	Fc=2.4GHz	ΔF=1 MHz	-	-110	-	dBc/Hz
		ΔF=2 MHz	-	-118	-	dBc/Hz
		ΔF≥3 MHz	-	-123	-	dBc/Hz
XTAL Oscillator						
Frequency range			-	26	-	MHz
Frequency Trimming Range	6 bits		-1	-	+1	kHz

Table 3-6 Receive path Parameters

Parameter	Condition		MIN	typ	max	Unit
Receiver Channel						
Minimum Usable Signal	RX sensitivity		-	-85	-	dBm
LNA						
Gain		High Gain	-	25	-	dB
		Mid Gain	-	15	-	dB
		Low Gain	-	5	-	dB
Mixer						
Conversion Gain			-	0	-	dB
Ifamp						
Gain	5/9/12/15/18 dB		-	12	-	
Complex BPF						
Band pass -3 dB BW	Figure 1.		-	2	-	MHz

Parameter	Condition	MIN	typ	max	Unit
Image Rejection		-	30	-	dB
VGA					
Gain Range		-6	-	+68	dB
Gain Step		-	+1/+6	-	dB
ADMOD					
SNDR	Freq = +- BW	-	>50	-	dB

Table 3-7 Transmit path Parameters

Parameter	Condition		MIN	typ	max	Unit
Transmit Channel						
Available output power			-2	0	1.5	dBm
Side Band Suppression			-	-30	-	dBm
LPF						
Low pass -3 dB BW	Figure 2.		-	1	-	MHz
TXVGA						
Gain Step			-7	-	7	dB
PA						
Gain Range	Set paPWR[2:0] of Control Register #16	GFSK	-12	-	4	dBm
		DPSK	-15	-	1	dBm

4 Package Outline Dimensions

4.1 SSOP28



SYMBOL	COMMON DIMENSION MILLIMETERS			COMMON DIMENSION INCH		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A			2.0			0.079
A1	0.05			0.002		
A2	1.65	1.75	1.85	0.065	0.069	0.073
b	0.22		0.38	0.009		0.015
b1	0.22	0.30	0.33	0.009	0.012	0.013
c	0.09		0.25	0.004		0.010
c1	0.09	0.15	0.21	0.004	0.006	0.008
E	7.50	7.80	8.10	0.295	0.307	0.319
E1	5.00	5.30	5.60	0.197	0.209	0.220
e	0.65 BSC			0.0256 BSC		
L	0.55	0.75	0.95	0.021	0.030	0.037
L1	1.25 REF.			0.050 REF.		
R1	0.09			0.004		
θ	0°	4°	8°	0°	4°	8°

N	20	28
D ±0.20	7.20	10.20
JEDEC NO.	MO-150 AE	MO-150 AH



Figure 4-1 SSOP28 Package Outline Dimension

Revision History

Date	Version	Comments	Revised by
2016/7/19	0.0.1	Initial version	YX
2016/7/22	0.0.2	Modify	GAO
2016/7/26	1.0.0	Released	YX
2016/9/23	1.0.1	Modify work voltage	YX
2016/9/23	1.1.0	Release	YX