# Oracle® Database Oracle True Cache User's Guide





Oracle Database Oracle True Cache User's Guide, 23ai

F77385-02

Copyright © 2024, Oracle and/or its affiliates.

Primary Authors: J. True, J.-F. VERRIER

Contributors: P. Chandiramani, D. Chen, S. Datta, J. De Lavarene, K. Fekete, M. Girkar, W. Hu, S. Krishnaswamy, A. Lee, B. Lee, Y. Li, R. Mallegowda, M. Malvezzi, C. Ruiz, P. Saini, V. Senapati, A. Srivastava, M. Stalin, J. Stamos, D. Surber, T. Thathachary

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

## Contents

	rc	٠£.	_	_	_
$\mathbf{r}$	I (-	11	н		=

Convention	ns .	vi
Overvie	w of Oracle True Cache	
1.1 Abo	ut Oracle True Cache	1-1
1.2 Ben	efits of Oracle True Cache	1-2
1.3 How	True Cache Works	1-2
1.4 Con	siderations for Using True Cache	1-2
1.5 Appl	ication Usage Models	1-3
1.6 Lock	z-Free Concurrency Control	1-3
Configu	ring True Cache	
2.1 Ove	rview of the True Cache Configuration	2-1
2.1.1	Uniform Configuration	2-2
2.1.2	Partitioned Configuration	2-2
2.1.3	True Cache Configuration Process Overview	2-2
2.1.4	Best Practices for Database Application Services	2-2
2.1.5	Best Practices for Maximum Availability Architecture (MAA) with True Cache	2-2
	figuring True Cache with Oracle DBCA	2-3
2.2 Con	Prerequisites	2-3
2.2 Con 2.2.1	Toroquiolico	
	Creating True Cache with DBCA	2-4
2.2.1	·	2-4 2-5
2.2.1 2.2.2	Creating True Cache with DBCA	
2.2.1 2.2.2 2.2.3 2.2.4	Creating True Cache with DBCA Configuring True Cache Database Application Services with DBCA	2-5
2.2.1 2.2.2 2.2.3 2.2.4 2.2.4	Creating True Cache with DBCA Configuring True Cache Database Application Services with DBCA Oracle DBCA Commands and Parameters for True Cache	2-5 2-8
2.2.1 2.2.2 2.2.3 2.2.4 2.2.4	Creating True Cache with DBCA Configuring True Cache Database Application Services with DBCA Oracle DBCA Commands and Parameters for True Cache 2.4.1 configureDatabase	2-5 2-8 2-8
2.2.1 2.2.2 2.2.3 2.2.4 2.2.4	Creating True Cache with DBCA Configuring True Cache Database Application Services with DBCA Oracle DBCA Commands and Parameters for True Cache 2.4.1 configureDatabase 2.4.2 createTrueCache	2-5 2-8 2-8 2-9
2.2.1 2.2.2 2.2.3 2.2.4 2.2 2.3 2.3 Con	Creating True Cache with DBCA Configuring True Cache Database Application Services with DBCA Oracle DBCA Commands and Parameters for True Cache 2.4.1 configureDatabase 2.4.2 createTrueCache figuring True Cache Manually	2-5 2-8 2-8 2-9 2-11
2.2.1 2.2.2 2.2.3 2.2.4 2.2 2.3 Con 2.3.1 2.3.2	Creating True Cache with DBCA Configuring True Cache Database Application Services with DBCA Oracle DBCA Commands and Parameters for True Cache 2.4.1 configureDatabase 2.4.2 createTrueCache figuring True Cache Manually Prerequisites	2-5 2-8 2-8 2-9 2-11 2-12



		Cache Node	2-15
	2.3.2.4		2-16
		5 Create and Start True Cache	2-18
		onfiguring True Cache Database Application Services Manually	2-18
	2.3.3.1		2-19
	2.3.3.2	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	2-20
	2.3.3.3		2-20
2.4		g True Cache for an Oracle RAC Primary Database	2-21
2.5		the True Cache Configuration	2-22
		rifying That True Cache Is Working as Expected	2-22
		rifying the Remote Listener Configuration	2-23
		rifying the True Cache and Primary Database Application Services	2-23
2.6		DML Redirection	2-24
De	ploying	True Cache in Containers	
Sh	uttina D	own and Starting True Cache	
		own and Starting True Cache	<i>1</i> _1
Sh 4.1 4.2	Shutting	Own and Starting True Cache  Down True Cache  True Cache	4-1 4-1
4.1	Shutting	Down True Cache	
4.1 4.2	Shutting Starting	Down True Cache	
4.1 4.2	Shutting Starting	Down True Cache True Cache	
4.1 4.2 Mo	Shutting Starting  onitoring  Monitorin	Down True Cache True Cache  True Cache	4-1
4.1 4.2 Mo	Shutting Starting onitoring Monitorir 5.1.1 V\$	Down True Cache True Cache  True Cache  Ing True Cache with the V\$TRUE_CACHE View	5-1
4.1 4.2 Mo 5.1	Shutting Starting  onitoring  Monitorir 5.1.1 V\$  Using the	Down True Cache True Cache  True Cache  Ing True Cache with the V\$TRUE_CACHE View  ITRUE_CACHE Columns	5-1 5-2
4.1 4.2 MC 5.1	Shutting Starting Onitoring Monitorin 5.1.1 V\$ Using the	Down True Cache True Cache  True Cache  Ing True Cache with the V\$TRUE_CACHE View ITRUE_CACHE Columns Ite Automatic Workload Repository for True Cache	5-1 5-2
4.1 4.2 Mo 5.1 5.2	Shutting Starting Onitoring Monitorin 5.1.1 V\$ Using the	Down True Cache  True Cache  True Cache  Ing True Cache with the V\$TRUE_CACHE View  ITRUE_CACHE Columns  It Automatic Workload Repository for True Cache  Cle True Cache in Your Applications	5-1 5-2 5-2
4.1 4.2 MC 5.1 5.2 US 6.1	Shutting Starting Onitoring Monitorir 5.1.1 V\$ Using the onitoring Methods Sample	Down True Cache True Cache  True Cache  Ing True Cache with the V\$TRUE_CACHE View ITRUE_CACHE Columns Ite Automatic Workload Repository for True Cache  Cle True Cache in Your Applications  for Connecting to True Cache	5-1 5-2 5-2
4.1 4.2 5.1 5.2 US 6.1 6.2	Shutting Starting  Onitoring  Monitorin  5.1.1 V\$  Using the  Methods  Sample of	Down True Cache True Cache  True Cache  Ing True Cache with the V\$TRUE_CACHE View ITRUE_CACHE Columns It Automatic Workload Repository for True Cache  Cle True Cache in Your Applications  for Connecting to True Cache  Java Code Using the JDBC Thin Driver	5-1 5-2 5-2 6-1 6-2
4.1 4.2 5.1 5.2 6.1 6.2 6.3 6.4	Shutting Starting Onitoring Monitorin 5.1.1 V\$ Using the Methods Sample	Down True Cache True Cache  True Cache  Ing True Cache with the V\$TRUE_CACHE View ITRUE_CACHE Columns It Automatic Workload Repository for True Cache  Cle True Cache in Your Applications  for Connecting to True Cache Java Code Using the JDBC Thin Driver Java Code for Applications Using a Native Connection to the Database	5-1 5-2 5-2 6-1 6-4
4.1 4.2 Mo 5.1 5.2 US 6.1 6.2 6.3 6.4	Shutting Starting Starting Monitoring Monitorin 5.1.1 V\$ Using the Methods Sample Sample Sample Methods	Down True Cache  True Cache  Ing True Cache with the V\$TRUE_CACHE View  ITRUE_CACHE Columns  It Automatic Workload Repository for True Cache  Cle True Cache in Your Applications  for Connecting to True Cache  Java Code Using the JDBC Thin Driver  Java Code for Applications Using a Native Connection to the Database citices for Load Balancing in a Uniform Configuration  entary Caching Features	5-1 5-2 5-2 6-1 6-4 6-5
4.1 4.2 5.1 5.2 US 6.1 6.2 6.3 6.4 CO 7.1	Shutting Starting Starting Monitoring Monitorir 5.1.1 V\$ Using the ing Orac Methods Sample a Sample a Best Pra mpleme	Down True Cache  True Cache with the V\$TRUE_CACHE View  TRUE_CACHE Columns  Automatic Workload Repository for True Cache  Cle True Cache in Your Applications  for Connecting to True Cache  Java Code Using the JDBC Thin Driver  Java Code for Applications Using a Native Connection to the Database ctices for Load Balancing in a Uniform Configuration  Entary Caching Features  Side Result Set Cache	5-1 5-2 5-2 5-2 7-1
4.1 4.2 5.1 5.2 US 6.1 6.2 6.3 6.4	Shutting Starting Starting Monitoring Monitoring 5.1.1 V\$ Using the Methods Sample of	Down True Cache  True Cache with the V\$TRUE_CACHE View  TRUE_CACHE Columns  Automatic Workload Repository for True Cache  Cle True Cache in Your Applications  for Connecting to True Cache  Java Code Using the JDBC Thin Driver  Java Code for Applications Using a Native Connection to the Database ctices for Load Balancing in a Uniform Configuration  Entary Caching Features  Side Result Set Cache  Uffer Pool	5-1 5-2 5-2 6-1 6-4 6-5 7-1
4.1 4.2 5.1 5.2 6.1 6.2 6.3 6.4 Co	Shutting Starting Starting Monitoring Monitoring 5.1.1 V\$ Using the Methods Sample of	Down True Cache  True Cache with the V\$TRUE_CACHE View  TRUE_CACHE Columns  Automatic Workload Repository for True Cache  Cle True Cache in Your Applications  Tor Connecting to True Cache  Java Code Using the JDBC Thin Driver  Java Code for Applications Using a Native Connection to the Database  ctices for Load Balancing in a Uniform Configuration  Entary Caching Features  Side Result Set Cache  Uffer Pool  Perview of Using the KEEP Buffer Pool with True Cache	5-1 5-2 5-2 5-2 7-1



	7.2.3 Assigning Objects to the KEEP Buffer Pool for True Cache	7-3
	7.2.3.1 TRUE_CACHE_KEEP Procedure	7-3
	7.2.4 Removing an Object's KEEP Buffer Pool Assignment for True Cache	7-4
	7.2.4.1 TRUE_CACHE_UNKEEP Procedure	7-4
	7.2.5 Viewing a List of KEEP Objects on True Cache	7-5
	7.2.5.1 V\$TRUE_CACHE_KEEPOBJ Columns	7-6
	7.3 Database Smart Flash Cache	7-6
8	Deleting True Cache	
	8.1 Using Oracle DBCA to Delete True Cache	8-1
	8.1.1 Cleaning Up the True Cache Services from the Primary Database	8-1
	8.1.2 Deleting True Cache from the True Cache Node	8-1
	8.2 Deleting True Cache Manually	8-2
Α	True Cache Error Messages	
В	Licensing for True Cache	
С	Troubleshooting True Cache	
	C.1 Rerunning Oracle DBCA	C-1
	C.1.1 Rerunning Oracle DBCA After Creating True Cache	C-1
	C.1.2 Rerunning Oracle DBCA After Configuring True Cache Database Application Services	C-1



## **Preface**

This guide provides a single location with everything you need to know about configuring and using True Cache.

- Documentation Accessibility
- Related Documents
   The following documents contain information that may be of use when configuring and using True Cache.
- Conventions

## **Documentation Accessibility**

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

#### **Access to Oracle Support**

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

## Related Documents

The following documents contain information that may be of use when configuring and using True Cache.

- Oracle True Cache Technical Architecture
- Oracle Data Guard Concepts and Administration
- Oracle Database Administrator's Guide
- Oracle Database Container Images
- Oracle Database Error Messages
- Oracle Database Performance Tuning Guide
- Oracle Database PL/SQL Packages and Types Reference
- Oracle Database Reference
- Oracle Database JDBC Developer's Guide
- Oracle Multitenant Administrator's Guide
- Oracle Real Application Clusters Administration and Deployment Guide
- Oracle Database SQL Language Reference
- Oracle Universal Connection Pool Developer's Guide
- Java™ Platform, Standard Edition 7 API Specification



## Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
italic	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.



1

## Overview of Oracle True Cache

Oracle True Cache is an in-memory, consistent, and automatically managed SQL and key-value (object or JSON) cache for Oracle Database.

For an interactive tour, see Oracle True Cache Technical Architecture.

- About Oracle True Cache
   True Cache is an in-memory, read-only cache in front of an Oracle database.
- Benefits of Oracle True Cache
   Oracle True Cache provides several business benefits related to application development
   and performance.
- How True Cache Works
   At a high level, here's how Oracle True Cache works.
- Considerations for Using True Cache
   Consider these points when deciding whether to use Oracle True Cache.
- Application Usage Models
   Applications can use True Cache in two ways.
- Lock-Free Concurrency Control
   For applications that work with JSON documents, Oracle extends HTTP entity tag (ETAG) support to implement lock-free, optimistic concurrency control.

## 1.1 About Oracle True Cache

True Cache is an in-memory, read-only cache in front of an Oracle database.

Like Oracle Active Data Guard, True Cache is a fully functional, read-only replica of the primary database, except that it's mostly diskless.

Modern applications often require a high number of connections and fast, low-latency access to the data. A popular approach is to place caches in front of the database because applications typically perform many more reads than updates, and they can read from the cache without affecting the database performance. For example, an airline reservation system reads data frequently as people shop for flights, and it's okay if the data isn't the most current compared to what's in the database. The application only needs to access the most current data when someone reserves a flight.

Unlike conventional caches, True Cache automatically keeps the most frequently accessed data in the cache, and it keeps the cache consistent with the primary database, other objects in the same cache, and other caches. It caches all Oracle Database objects and data types, including JSON.

Because True Cache implements Oracle Database security policies, you can control access to the cache. This enables you to cache sensitive data, like private personal information, that you might not ordinarily cache.

## 1.2 Benefits of Oracle True Cache

Oracle True Cache provides several business benefits related to application development and performance.

- Improves scalability and performance by offloading queries from the primary database.
- Reduces application response time and network latency by deploying True Cache closer to the application. This especially benefits situations where a database is in a different location than the application due to data residency requirements.
- Creates a large, in-memory storage area by dividing data across multiple True Caches.
   The total size of the cached data across all True Caches can be much larger than it would be for a single primary database or cache.
- Automatically maintains the cache contents.
- Simplifies development and maintenance by being transparent to the application.

## 1.3 How True Cache Works

At a high level, here's how Oracle True Cache works.

- An application decides whether to query data from True Cache or the primary database.
   For details on how this works, see Application Usage Models.
- True Cache satisfies queries by using data that's cached in its memory. When the data isn't in the cache, True Cache fetches the data from the primary database.
- True Cache is empty when it starts up, so it reads large chunks of data to populate the
  cache. After a block is cached, it's updated automatically through redo apply from the
  primary database. This is similar to the update mechanism used in Oracle Active Data
  Guard.
- A query to True Cache returns only committed data, and the data is always consistent.
- Like all caches, the True Cache data might not be the most current data as it exists in the primary database.
- If multiple True Caches exist and serve the same database application service, the listener automatically distributes and load balances sessions to each cache.

## 1.4 Considerations for Using True Cache

Consider these points when deciding whether to use Oracle True Cache.

- You need to configure enough memory for True Cache so your most frequently accessed data will stay in memory.
- True Cache only needs a small amount of storage for the standby redo log files.
   Configuration files like control files, the SPFILE, and temporary data files are automatically created.
- True Cache is a read-only cache, so you can't directly update the cache, but you can use DML redirection to indirectly update the cache.



#### **Related Topics**

Enabling DML Redirection

True Cache is a read-only cache, so you can't directly update the cache, but you can use DML redirection to indirectly update the cache.

## 1.5 Application Usage Models

Applications can use True Cache in two ways.

• The application maintains *two physical connections*: one to the primary database and one to True Cache. Each connection has a database application service, and the application chooses which connection to use based on whether it's reading or writing. You can use this model with any existing client drivers and any programming language.

The application sends queries that don't need to see the most current data to True Cache through a True Cache database application service. The application sends other queries and updates to the primary database through the primary database application service.

 The application maintains one logical connection that uses the database application service for the primary database. The JDBC Thin driver (starting with Oracle Database 23ai) maintains physical connections to the primary database and True Cache. This model only works with Java applications.

The application switches between the primary database and True Cache without having to specify an instance name. The application uses special calls to flag the logical connection as read-only or read-write. If it's read-only, the query is sent to True Cache. Otherwise, it's sent to the primary database.

#### **Related Topics**

Using Oracle True Cache in Your Applications
 When True Cache is configured, applications must decide whether to query data from True Cache or the primary database.

## 1.6 Lock-Free Concurrency Control

For applications that work with JSON documents, Oracle extends HTTP entity tag (ETAG) support to implement lock-free, optimistic concurrency control.

A database GET request to True Cache automatically computes the ETAG and inserts it into the returned document. When the modified document is PUT back into the primary database, the following occurs:

- The database verifies that the underlying document rows still match the ETAG that was computed by the GET request.
- 2. If the rows match the ETAG, the rows are atomically updated.
- 3. If there's not a match, another user has changed the data and the PUT request is rejected.
- The PUT request can be retried using the new data.



## **Configuring True Cache**

You can configure True Cache using the Oracle Database Configuration Assistant (Oracle DBCA) or you can configure it manually.



True Cache for Oracle Database Free has a simplified configuration process. Get started with the *Oracle Database Free Installation Guide* for your platform. See Configuring True Cache on Oracle Database Free (Linux).

- Overview of the True Cache Configuration
  - A True Cache environment can have a uniform or partitioned configuration.
- Configuring True Cache with Oracle DBCA
   The simplest way to configure a True Cache environment is to use Oracle Database
   Configuration Assistant (Oracle DBCA).
- Configuring True Cache Manually
   Follow these steps to set up a True Cache environment manually if you're not using the
   Oracle Database Configuration Assistant (Oracle DBCA).
- Deploying True Cache for an Oracle RAC Primary Database
   This section summarizes the configuration requirements for deploying True Cache for a primary database in an Oracle Real Application Clusters (Oracle RAC) environment. These requirements are also included in context within the detailed configuration steps.
- Verifying the True Cache Configuration
   Verify that True Cache and the database application services are working as expected.
- Enabling DML Redirection
   True Cache is a read-only cache, so you can't directly update the cache, but you can use DML redirection to indirectly update the cache.

## 2.1 Overview of the True Cache Configuration

A True Cache environment can have a uniform or partitioned configuration.

- Uniform Configuration
  - In a uniform configuration, you can deploy multiple, identical True Caches that use the same True Cache database application service.
- Partitioned Configuration
  - In a partitioned configuration, the data is divided across multiple True Caches, which each cache a different subset of the data.
- True Cache Configuration Process Overview
   At a high level, creating a True Cache configuration involves the following steps.
- Best Practices for Database Application Services
   Associate each primary database application service with a corresponding True Cache database application service.

Best Practices for Maximum Availability Architecture (MAA) with True Cache
 Follow these best practices for maximum availability with True Cache.

## 2.1.1 Uniform Configuration

In a uniform configuration, you can deploy multiple, identical True Caches that use the same True Cache database application service.

Client sessions are evenly distributed among True Caches, which all cache the same set of data.

See the following technical architecture diagram for details and an example of a uniform configuration:

True Cache Uniform Configuration

## 2.1.2 Partitioned Configuration

In a partitioned configuration, the data is divided across multiple True Caches, which each cache a different subset of the data.

The total size of the cached data across all True Caches can be much larger than it would be for a single primary database or a single cache in a uniform configuration.

See the following technical architecture diagrams for details and examples of partitioned configurations:

- True Cache Configuration with colocation\_tag
- True Cache Partitioned Configuration with Multiple Services

## 2.1.3 True Cache Configuration Process Overview

At a high level, creating a True Cache configuration involves the following steps.

- Configure the network for True Cache and the primary database, and optionally create a remote listener for high availability.
- Create True Cache.
- 3. Create and start the True Cache database application services.

## 2.1.4 Best Practices for Database Application Services

Associate each primary database application service with a corresponding True Cache database application service.

To distinguish the True Cache database application services, it's a good practice to use the primary service name followed by  $\, \mathbb{T}C$ .

For example, if the primary service is SALES, the True Cache service would be SALES TC.

Also, only start the True Cache services on True Caches, and make sure they're read-only.

## 2.1.5 Best Practices for Maximum Availability Architecture (MAA) with True Cache

Follow these best practices for maximum availability with True Cache.



- Configure True Cache for high availability with two identical True Caches per dataset using the uniform configuration architecture. To learn more, see Uniform Configuration.
- Use the JDBC 23ai UCP connection configuration for the application to ensure minimal impact on the application if one True Cache becomes unavailable.
- Before enabling the database application service for True Cache, populate the cache by running critical workload queries. To learn more about how data is cached, see How True Cache Works.
- Before shutting down True Cache for planned maintenance, stop the database application service on True Cache.
- Partition or design True Caches to minimize fetches from the primary database.

## 2.2 Configuring True Cache with Oracle DBCA

The simplest way to configure a True Cache environment is to use Oracle Database Configuration Assistant (Oracle DBCA).

Oracle DBCA is an assistant tool that comes with Oracle Database to simplify the process of creating, configuring, and managing Oracle databases and True Caches.



True Cache for Oracle Database Free has a simplified configuration process. Get started with the *Oracle Database Free Installation Guide* for your platform. See Configuring True Cache on Oracle Database Free (Linux).

- Prerequisites
   Before configuring True Cache, complete the following prerequisites.
- Creating True Cache with DBCA
   Follow these steps to create True Cache with Oracle DBCA.
- Configuring True Cache Database Application Services with DBCA
   To use True Cache with the JDBC Thin driver, for each primary database application service that you want to cache, create a corresponding True Cache database application service.
- Oracle DBCA Commands and Parameters for True Cache
   Use the following Oracle DBCA commands and parameters to configure True Cache.

## 2.2.1 Prerequisites

Before configuring True Cache, complete the following prerequisites.

- Set up a network path to access the primary (source) database with an Easy Connect (EZConnect) string from the True Cache node.
- Install the Oracle Database software on the True Cache nodes.
- Ensure that a primary database is running on the primary node in archive logging (ARCHIVELOG) mode.

The primary database must be in ARCHIVELOG mode to ship redo log files to the True Cache node. Oracle DBCA verifies that the primary database is in ARCHIVELOG mode.



If the primary database is not in ARCHIVELOG mode, restart it in mount mode, run the ALTER DATABASE ARCHIVELOG command, and open the primary database again.

• Don't set LOG\_ARCHIVE\_CONFIG and LOG\_ARCHIVE\_DEST\_n on the primary database. True Cache automatically configures these for the primary database.

## 2.2.2 Creating True Cache with DBCA

Follow these steps to create True Cache with Oracle DBCA.

- Copy the password file, and optionally the Transparent Data Encryption (TDE) wallet, from the primary database to the True Cache node. You can use either of the following methods:
  - Manually copy the primary database's password file (and optional TDE wallet) to any location on the True Cache node.
  - Run a DBCA command on the primary database to package the password file (and optional TDE wallet) into a configuration BLOB file. Then copy the file to the True Cache node and ensure that the file is owned by the Oracle Home user.

Use the following command to prepare the configuration BLOB file on the primary database:

```
ORACLE_HOME/bin/dbca -configureDatabase -prepareTrueCacheConfigFile -sourceDB primary_db_sid_or_db_unique_name -trueCacheBlobLocation primary db config blob path -silent
```

#### Example:

```
$ORACLE_HOME/bin/dbca -configureDatabase -prepareTrueCacheConfigFile -
sourceDB primdbli -trueCacheBlobLocation /tmp/blob loc2 -silent
```

For descriptions of the parameters, see configureDatabase.

2. On the True Cache node, run the -createTrueCache command to complete the True Cache configuration and start True Cache.

Choose one of the following command formats, depending on the method that you used to copy the primary database's password file (and optional TDE wallet) to the True Cache node in step 1.

If you manually copied the password file (and optional TDE wallet), use this command:

```
ORACLE_HOME/bin/dbca -createTrueCache -gdbName true_cache_global_name -sid true_cache_sid -sourceDBConnectionString
primary_db_easy_connect_string -passwordFileFromSourceDB
password_file_path -sgaTargetInMB sga_memory_size -
pgaAggregateTargetInMB pga memory size -silent
```

#### Example using a password file:

\$ORACLE\_HOME/bin/dbca -createTrueCache -gdbName tcdb1 -sid tcdb1 -sourceDBConnectionString primary.example.com:1522/primdb1i.example.com -passwordFileFromSourceDB /tmp/password\_loc2/orapwddbmc1 -sgaTargetInMB 20000 -pgaAggregateTargetInMB 4000 -silent



If you created the configuration BLOB file, use this command:

```
ORACLE_HOME/bin/dbca -createTrueCache -gdbName true_cache_global_name -sid true_cache_sid -sourceDBConnectionString
primary_db_easy_connect_string -trueCacheBlobFromSourceDB
true_cache_config_blob_path -sgaTargetInMB sga_memory_size -
pgaAggregateTargetInMB pga_memory_size -tdeWalletLoginType AUTO_LOGIN -
listeners listener name -silent
```

#### Example using a TDE wallet:

\$ORACLE\_HOME/bin/dbca -createTrueCache -gdbName tcdb1 -sid tcdb1 sourceDBConnectionString primary.example.com:1522/primdb1i.example.com trueCacheBlobFromSourceDB /tmp/blob\_loc2/blob.tar.gz -sgaTargetInMB
20000 -pgaAggregateTargetInMB 4000 -tdeWalletLoginType AUTO\_LOGIN listeners LISTENER -silent

For descriptions of the parameters, see createTrueCache.



For Oracle RAC primary databases, set the -sourceDBConnectionString parameter to SCAN:port/service name.

#### **Related Topics**

Rerunning Oracle DBCA After Creating True Cache
 If you need to rerun Oracle DBCA after creating True Cache, clean up the True Cache node first.

## 2.2.3 Configuring True Cache Database Application Services with DBCA

To use True Cache with the JDBC Thin driver, for each primary database application service that you want to cache, create a corresponding True Cache database application service.

This makes it easy for applications to switch an existing JDBC connection from a primary database to True Cache without having to change the JDBC connection URL. This is possible with the 23ai JDBC Thin driver by setting the <code>ReadOnly</code> parameter of the connection to <code>TRUE</code> or <code>FALSE</code>.

On the primary database, complete the following steps:

Configure the remote listener.



Check to see if Valid Node Checking for Registration (VNCR) is configured for the listener. If so, add True Cache to the

REGISTRATION\_INVITED\_NODES\_LISTENER parameter in the listener.ora file of the remote listener.



#### Note:

For Oracle RAC primary databases, add the True Cache node to the invited node list for the SCAN listener by using the srvctl command line utility. (Don't manually edit the listener.ora file as the grid owner user.)

For example:

```
srvctl modify scan_listener -invitednodes true_cache_host -
endpoints TCP:port
```

2. Create and start a primary database application service to use with the True Cache service, and then verify that the service is running.

Choose one of the following options based on the primary database configuration:

 For single instance primary databases, use the DBMS\_SERVICE PL/SQL package. For services that are specific to a pluggable database (PDB), connect to the specific PDB, or set the correct PDB container in your session before starting the service using DBMS\_SERVICE.

Here's an example using the <code>DBMS\_SERVICE</code> package for a single instance primary database:

```
BEGIN

DBMS_SERVICE.CREATE_SERVICE('SALES', 'SALES');

DBMS_SERVICE.START_SERVICE('SALES');

END;

PL/SQL procedure successfully completed.

SELECT service_id, name, true_cache_service FROM v$active_services
WHERE name='SALES';

SERVICE_ID NAME TRUE_CACHE_SERVICE

6 SALES

// TRUE_CACHE_SERVICE will be filled in by this (dbca - configureTrueCacheInstanceService) command
```

• For Oracle RAC primary databases, use the <code>srvctl</code> command line utility with the <code>true\_cache\_service</code> option. Start the service on the primary instance. Use <code>srvctl</code> only for clusterware-managed instances.

```
srvctl add service -db primary_db_unique_name -service
primary_db_service_name -preferred primary_db_instance_list -pdb
primary_pdb_name -true_cache_service true_cache_service_name
```



#### For example:

```
srvctl add service -db primdb1i -service sales -preferred
primdb1i1,primdb1i2 -pdb sales pdb -true cache service sales tc
```

 Run the dbca -configureDatabase command with the configureTrueCacheInstanceService parameter to configure True Cache.

This configures the True Cache database application service on the primary database and then starts the True Cache service on True Cache. Run this command for each True Cache database application services.



The primary database application service must already exist before you run this command.

#### Note:

For a uniform True Cache configuration with multiple True Caches serving the same service, DBCA starts the service on the first True Cache and then you manually start the service on the other True Caches.

ORACLE\_HOME/bin/dbca -configureDatabase -configureTrueCacheInstanceService -sourceDB primary\_db\_sid\_or\_db\_unique\_name -trueCacheConnectString true\_cache\_easy\_connect\_string -trueCacheServiceName true\_cache\_service\_name -serviceName primary\_db\_service\_name -pdbName primary\_pdb\_name -silent

#### Example:

```
$ORACLE_HOME/bin/dbca -configureDatabase -
configureTrueCacheInstanceService -sourceDB primdbli -
trueCacheConnectString tc.example.com:1522/tcdb1.example.com -
trueCacheServiceName sales_tc -serviceName sales -pdbName sales_pdb -silent
```

For descriptions of the parameters, see configureDatabase.

4. After the database application service starts on True Cache, use the lsnrctl command to validate the remote listener services for the True Cache service registration.

See Verifying the Remote Listener Configuration.

5. For a uniform True Cache configuration with multiple True Caches serving the same service, start the service on all additional True Caches. For example:

```
EXEC DBMS SERVICE.START SERVICE('SALES TC');
```

#### **Related Topics**

- CREATE SERVICE Procedure
- MODIFY\_SERVICE Procedure



- srvctl modify scan listener
- Uniform Configuration

In a uniform configuration, you can deploy multiple, identical True Caches that use the same True Cache database application service.

Rerunning Oracle DBCA After Configuring True Cache Database Application Services
If you need to rerun Oracle DBCA after configuring True Cache database application
services, you might need to delete the True Cache service from the primary pluggable
database (PDB) using the DBMS\_Service package.

#### 2.2.4 Oracle DBCA Commands and Parameters for True Cache

Use the following Oracle DBCA commands and parameters to configure True Cache.

#### configureDatabase

The configureDatabase command configures the primary database for True Cache. Run this command on the primary database.

#### createTrueCache

The createTrueCache command configures True Cache. Run this command on the True Cache node.

## 2.2.4.1 configure Database

The configureDatabase command configures the primary database for True Cache. Run this command on the primary database.

#### **Parameters**

For True Cache, use the dbca -configureDatabase command with the following syntax.



This table lists the <code>configureDatabase</code> parameters that are specific to True Cache. For the full syntax and parameters, see configureDatabase in the Oracle Multitenant Administrator's Guide.

Table 2-1 configureDatabase Parameters

Parameter	Required/ Optional	Description
prepareTrueCacheConfigFile	Required for True Cache	Use this option to prepare a configuration BLOB file that contains the primary database's password file or wallet.  Enter the following additional parameters for this option:
		<ul> <li>-sourceDB: Enter the primary database system identifier (SID) or database unique name (DB_UNIQUE_NAME).</li> <li>-tdeWalletPassword: If the primary database uses a Transparent Data Encryption (TDE) wallet, enter the password for the wallet. This parameter is optional.</li> <li>-trueCacheBlobLocation: Enter the path where you want to save the configuration BLOB file on the primary database. This parameter is optional.</li> </ul>



Table 2-1 (Cont.) configureDatabase Parameters

Parameter	Required/ Optional	Description
- configureTrueCacheInstanceServ ice	Required for True Cache	Use this option to configure the True Cache database application service on the primary database and start the service on True Cache.
		Enter the following additional parameters for this option:
		<ul> <li>-serviceName: Enter the primary database application service name.</li> <li>-sourceDB: Enter the primary database SID or database</li> </ul>
		<ul> <li>unique name (DB_UNIQUE_NAME).</li> <li>-trueCacheConnectString: Enter the Easy Connect (EZConnect) string to connect to True Cache.</li> </ul>
		<pre>Example: host:port/service name</pre>
		<ul> <li>-trueCacheServiceName: Enter a name for the True</li> <li>Cache database application service.</li> </ul>
		<ul> <li>-pdbName: Enter the primary pluggable database (PDB) name. This parameter is optional.</li> </ul>
- cleanupTrueCacheInstanceServic e	Required for True Cache	Use this option to remove the True Cache database application services from the primary database configuration if, for example, you delete True Cache.
		Enter the following additional parameters for this option:
		<ul> <li>-serviceName: Enter the primary database application service name.</li> </ul>
		<ul> <li>-sourceDB: Enter the primary database SID or database unique name (DB_UNIQUE_NAME).</li> </ul>
		<ul> <li>-trueCacheConnectString: Enter the Easy Connect (EZConnect) string to connect to True Cache.</li> </ul>
		<pre>Example: host:port/service_name</pre>

#### 2.2.4.2 createTrueCache

The createTrueCache command configures True Cache. Run this command on the True Cache node.

#### **Syntax and Parameters**

Use the dbca -createTrueCache command with the following syntax:



```
[-sgaTargetInMB sga_memory_size]
[-sid true_cache_sid]
[-sourceTdeWalletPassword primary_db_wallet_password]
[-tdeWalletLoginType {PASSWORD | AUTO_LOGIN | LOCAL_AUTO_LOGIN}]
[-tdeWalletRoot tde_wallet_root_init_parameter]
[-useWalletForDBCredentials {true | false}
    -dbCredentialsWalletLocation wallet_files_directory
    [-dbCredentialsWalletPassword wallet_account_password]]
```

Table 2-2 createTrueCache Parameters

Parameter	Required/ Optional	Description
-dbUniqueName  true_cache_unique_name  or	Required	Enter either the unique name for this True Cache or the global database name.
-gdbName true_cache_global_name		
-sourceDBConnectionString primary_db_easy_connect_string	Required	Enter the Easy Connect (EZConnect) string to connect to the primary database.
		<pre>Example: host:port/service_name</pre>
		Note: For Oracle RAC primary databases, set the - sourceDBConnectionString parameter to SCAN:port/ service_name.
-trueCacheBlobFromSourceDB	Required	Enter one of the following:
<pre>true_cache_config_blob_path or -passwordFileFromSourceDB</pre>	·	<ul> <li>The full path and file name for the configuration BLOB file that contains the primary database's password file or wallet. This is the path where the file is located on the True Cache node.</li> </ul>
password_file_path		<ul> <li>The path to the primary database's password file that was copied to the True Cache node.</li> </ul>
		If you use -passwordFileFromSourceDB, you can also enter the following additional parameter:
		-tdeWalletFromSourceDB: Enter the path to the primary database's Transparent Data Encryption (TDE) wallet file that was copied to the True Cache node. You can copy and use the TDE wallet file only if the primary (source) database has TDE enabled. Otherwise, the wallet file isn't required.
-createListener new_database_listener	Optional	Enter a new database listener to be created and to register the database in the form <i>LISTENER_NAME:PORT</i> .
-datafileDestination true cache control file path	Optional	Enter the location where the True Cache control file, standby redo log groups, and temporary data files are to be stored.
		If Oracle Automatic Storage Management (ASM) storage is used for True Cache, enter the disk group name for – datafileDestination and use the following additional parameter:
		<ul><li>-useOMF: Enter true to use Oracle-Managed Files (OMF).</li><li>Otherwise, enter false.</li></ul>

Table 2-2 (Cont.) createTrueCache Parameters

Parameter	Required/ Optional	Description
-initParams	Optional	Enter a comma-separated list of name=value pairs with additional initialization parameter values for this True Cache.
<pre>initialization_parameters_list</pre>		You can also provide the -initParamsEscapeChar parameter for using a specific escape character between multiple values of an initialization parameter. If an escape character is not specified, backslash (\) is used as the default escape character.
-listeners	Optional	If one or more listeners already exist, enter a comma-separated
listeners_list		list of existing listeners that the database can be configured with. If you don't specify the existing listeners, DBCA creates a new listener.
-pgaAggregateTargetInMB	Optional	Enter a value in MB for the target aggregate Program Global
pga_memory_size		Area (PGA) memory to make available to all server processes that are attached to this True Cache.
-sgaTargetInMB	Optional	Enter a value in MB for the System Global Area (SGA) memory
sga_memory_size		size for this True Cache.
-sid	Optional	Enter the system identifier (SID) for this True Cache.
true_cache_sid		
-sourceTdeWalletPassword	Optional	If the primary database uses a TDE wallet, enter the password
primary_db_wallet_password		for the wallet.
-tdeWalletLoginType	Optional	Oracle recommends the AUTO_LOGIN or LOCAL_AUTO_LOGIN
{PASSWORD   AUTO_LOGIN   LOCAL AUTO LOGIN}		wallet for True Cache to avoid having to manually open a password wallet for each True Cache startup.
100112_11010_100111,		To learn more about wallet types, see About Oracle Database Wallets
-tdeWalletRoot	Optional	Enter the location for the True Cache TDE wallet root
tde_wallet_root_init_parameter		initialization parameter, which specifies where to place the wallet for True Cache.
-useWalletForDBCredentials	Optional	If the primary database uses Oracle Wallet for database credentials, enter true. The default is false.
{true   false}		If you enter true, also enter the following additional parameters:
		<ul> <li>-dbCredentialsWalletLocation: Enter the path of the directory that contains the Oracle Wallet files.</li> </ul>
		<ul> <li>-dbCredentialsWalletPassword: Enter the password for the Oracle Wallet account to open the wallet with autologin disabled. This parameter is optional.</li> </ul>

#### **Related Topics**

createTrueCache

## 2.3 Configuring True Cache Manually

Follow these steps to set up a True Cache environment manually if you're not using the Oracle Database Configuration Assistant (Oracle DBCA).

Prerequisites
 Before configuring True Cache, complete the following steps.

Creating True Cache Manually

Follow these steps to create True Cache manually.

Configuring True Cache Database Application Services Manually
 To use True Cache with the JDBC Thin driver, for each primary database application
 service that you want to cache, create a corresponding True Cache database application
 service.

## 2.3.1 Prerequisites

Before configuring True Cache, complete the following steps.

- Install the Oracle Database software on the True Cache nodes.
- Ensure that a primary database is running on the primary node in archive logging (ARCHIVELOG) mode.

The primary database must be in ARCHIVELOG mode to ship redo log files to the True Cache node. To see if the primary database is in ARCHIVELOG mode, enter the following SQL query:

```
SELECT log_mode FROM v$database;

LOG_MODE

ARCHIVELOG
```

If the primary database is not in ARCHIVELOG mode, restart it in mount mode, run the ALTER DATABASE ARCHIVELOG command, and open the primary database again.

• Don't set LOG\_ARCHIVE\_CONFIG and LOG\_ARCHIVE\_DEST\_n on the primary database. True Cache automatically configures these for the primary database.

## 2.3.2 Creating True Cache Manually

Follow these steps to create True Cache manually.

- Edit the tnsnames.ora File for True Cache and the Primary Database

  Configure the database network connections by editing the tnsnames.ora file on both True

  Cache and the primary database.
- Configure and Start the Local Listener on the True Cache Node
   Configure and start the local listener to enable the True Cache node to receive redo from
   the primary database.
- Copy the Password File or Wallet from the Primary Database to the True Cache Node
  To provide authentication for redo transport sessions, copy the primary database's
  password file or wallet to the True Cache node.
- Prepare a PFILE for True Cache
   For each True Cache, prepare a PFILE with the following parameters.
- Create and Start True Cache
   Follow these steps to create and start True Cache for the first time.



## 2.3.2.1 Edit the tnsnames.ora File for True Cache and the Primary Database

Configure the database network connections by editing the tnsnames.ora file on both True Cache and the primary database.

On most Linux platforms, you find the tnsnames.ora file in the \$ORACLE\_HOME/network/admin directory.

You can create this file manually or by using Oracle Net Configuration Assistant (NETCA).

Add the following information to all primary database and True Cache tnsnames.ora files if the information isn't already present:

- Network names for the primary database and all True Caches. These are needed to send redo to True Cache, and they enable redo shipping to work even if the database application services are not yet created.
- All primary database and True Cache database application service names. One True Cache can support multiple database application services that are started simultaneously.
- All participating listener network aliases, if you're using a remote listener.

Here are examples of the entries in the tnsnames.ora files for True Cache and the primary database:

```
# True Cache network name
tcdb1i =
  (DESCRIPTION =
    (ADDRESS LIST =
      (ADDRESS = (PROTOCOL = TCP) (HOST = true cache host) (PORT = 1521))
    (CONNECT DATA =
      (SID = tcdb1i)
    )
  )
# True Cache database application service name
sales tc =
  (DESCRIPTION =
    (ADDRESS LIST =
      (ADDRESS = (PROTOCOL = TCP) (HOST = true_cache_host) (PORT = 1521))
    (CONNECT DATA =
      (SERVICE NAME = sales tc)
# Primary database network name
primdb1i =
  (DESCRIPTION =
    (ADDRESS LIST =
      (ADDRESS = (PROTOCOL = TCP) (HOST = primary database host) (PORT = 1521))
```

## 2.3.2.2 Configure and Start the Local Listener on the True Cache Node

Configure and start the local listener to enable the True Cache node to receive redo from the primary database.

1. Create the listener.ora file manually or by using NETCA.

Here's an example of listener.ora on a True Cache node:

2. In a command window, ensure that the <code>ORACLE\_HOME</code> and <code>ORACLE\_SID</code> environment variables are set properly.

#### See Configuring the Operating System Environment Variables.

- 3. Ensure that the <code>\$ORACLE HOME/bin directory</code> is in your PATH environment variable.
- 4. Start the listener and verify that it started correctly.

lsnrctl start
lsnrctl status

## 2.3.2.3 Copy the Password File or Wallet from the Primary Database to the True Cache Node

To provide authentication for redo transport sessions, copy the primary database's password file or wallet to the True Cache node.

True Cache uses Oracle Net to transport redo data and control messages between the members of a True Cache configuration. These redo transport sessions are authenticated using a password file, so every True Cache in the configuration needs an up-to-date copy of the password file from the primary database.

Copy the primary database's password file to the appropriate directory on the True Cache node. You can find the password file in the V\$PASSWORDFILE\_INFO view, and on Linux the file is usually in \$ORACLE HOME/dbs/orapwSID.

In the examples in this documentation, the primary database's password file is <code>\$ORACLE\_HOME/dbs/orapwprimdbli</code> and would be copied to a True Cache node and renamed to <code>\$ORACLE\_HOME/dbs/orapwtcdbli</code>.

You need to recopy the password file in the following situations:

- Whenever an administrative privilege (SYSDG, SYSOPER, SYSDBA, and so on) is granted or revoked.
- After the password of any user with administrative privileges is changed.

Copy the wallet instead of the password file in the following situations:

- If the primary database uses TLS certificate authentication instead of a password file.
- If the primary database configures Transparent Data Encryption (TDE). Include only the ROOT container's master key in the copy for True Cache, which is used to decrypt encrypted redo that's shipped from the primary database.

#### Note:

When using a TDE wallet, Oracle recommends configuring an auto-login or local auto-login wallet for True Cache. For auto-login wallets, you an create the wallet on the primary database and copy both the password wallet (ewallet.p12) and auto-login wallet (cwallet.sso) to True Cache. Local auto-login wallets are host-specific, so you can't copy them to another node. Instead, for local auto-login wallets, copy the password wallet to True Cache, open it on True Cache, and create the local auto-login wallet there with the wallet password. The local auto-login wallet offers more security because it prevents someone from copying both wallets and using them without knowing the wallet password. To learn more about wallet types, see About Oracle Database Wallets. To learn more about wallet types, see About Oracle Database Wallets



## 2.3.2.4 Prepare a PFILE for True Cache

For each True Cache, prepare a  $\mbox{\tt PFILE}$  with the following parameters.

**Table 2-3 Initialization Parameters** 

Parameter	Description
TRUE CACHE=TRUE	This tells the server that this is a True Cache.
DB_NAME	Enter the same value as the one for the primary database.
DB_UNIQUE_NAME	Specify a unique name for this True Cache.
DB_FILES	Enter the same value as the one for the primary database.
SGA_TARGET	Enter the SGA memory size of this True Cache.
REMOTE_LISTENER	Enter the primary database listener. This is not needed for the CREATE TRUE CACHE command, but it's needed to use JDBC.
	<b>Note:</b> For Oracle RAC primary databases, set the REMOTE_LISTENER parameter to SCAN:port.
	Note: Check to see if Valid Node Checking for Registration (VNCR) is configured for the listener. If so, add True Cache to the REGISTRATION_INVITED_NODES_LISTENER parameter in the listener.ora file of the remote listener. (In the example following this table, this is the primary database's listener.ora file.)
	Note: To simplify configuration and avoid connection issues, you can use the LISTENER_NETWORKS parameter instead of specifying REMOTE_LISTENER and LOCAL_LISTENER separately. All listeners within the same network_name will cross-register. For example:
	LISTENER_NETWORKS='((NAME=network_name) (LOCAL_LISTENER=(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=true_cache_host)(PORT=1521)))) (REMOTE_LISTENER=primary_database_host:1521))'
	For more information, see Best Practices for Load

Balancing in a Uniform Configuration.



Table 2-3 (Cont.) Initialization Parameters

Parameter	Description
FAL_SERVER	Enter the network name for the primary database.
	<b>Note:</b> For Oracle RAC primary databases, set the FAL_SERVER parameter to SCAN:port/service name.
	If you have standby databases that could become a primary after a primary-standby switchover, True Cache automatically adds the existing standby databases to the FAL_SERVER list. However, if you add a new standby database after configuring True Cache, you need to append the new standby database to the FAL_SERVER parameter for True Cache. To do this, use the following command with a comma-separated list of databases:
	ALTER SYSTEM SET  FAL_SERVER='existing_databases,new_st  andby_database' SCOPE=BOTH
FAL_CLIENT	Enter the True Cache network name. When you start True Cache, it automatically adds that network name to the corresponding primary database LOG_ARCHIVE_DEST_n initialization parameter so that the primary database knows where to send online redo log blocks.
DB_CREATE_FILE_DEST	Enter a directory to store the internal True Cache files (for example, control files and temp files).
DB_DOMAIN	This might be necessary if the primary database also sets <code>DB_DOMAIN</code> . Set this to the domain where the True Cache node resides.
WALLET_ROOT and TDE_CONFIGURATION	If the primary database configures TDE with the recommended WALLET_ROOT and TDE_CONFIGURATION parameters, configure them accordingly on this True Cache.

For example, the following PFILE is named  $init\_tcdb1i.ora$  and stored in the  $ORACLE\ HOME/dbs/$  directory on the True Cache node:

true\_cache=true
db\_name=primaryd
db\_unique\_name=tcdb1
db\_files=200
sga\_target=20G
fal\_server=primdb1i
fal\_client=tcdb1i
instance\_name=tcdb1i
db\_create\_file\_dest=local\_directory\_on\_true\_cache\_node
local\_listener=listener
remote\_listener=listener\_primary

The preceding example assumes that the primary database's <code>DB\_UNIQUE\_NAME</code> initialization parameter is set to <code>primarydb</code> and <code>DB\_FILES</code> is set to <code>200</code>.

#### **Related Topics**

- TRUE\_CACHE
- Initialization Parameters

#### 2.3.2.5 Create and Start True Cache

Follow these steps to create and start True Cache for the first time.

Start up True Cache in NOMOUNT mode using SQL\*Plus.

```
export ORACLE_SID=tcdb1i
sqlplus / as SYSDBA
STARTUP NOMOUNT PFILE=$ORACLE HOME/dbs/init tcdb1i.ora;
```

2. Verify that the password file points to the right file.

3. Create and start True Cache.

```
CREATE TRUE CACHE;
```

4. To verify that True Cache is working, see Verifying That True Cache Is Working as Expected.

When you create True Cache, it automatically creates standby redo logs with the appropriate size, control files, temp files (when needed), and an internal SPFILE based on the first PFILE that you created. This SPFILE is used automatically on later STARTUP commands without the need to specify any PFILE values.

At this point, your applications can use separate physical connections to the primary database and True Cache and choose which connection to use based on whether it's reading or writing.

To use True Cache with the JDBC Thin driver, continue to the next topic to configure the database application services for True Cache.

## 2.3.3 Configuring True Cache Database Application Services Manually

To use True Cache with the JDBC Thin driver, for each primary database application service that you want to cache, create a corresponding True Cache database application service.

This makes it easy for applications to switch an existing JDBC connection from a primary database to True Cache without having to change the JDBC connection URL. This is possible with the 23ai JDBC Thin driver by setting the <code>ReadOnly</code> parameter of the connection to <code>TRUE</code> or <code>FALSE</code>.

- Create Database Application Services on the Primary Database
   From the primary database, create or modify the True Cache and primary database services using one of the following methods.
- Verify That the Database Application Services Are Created
   After you create services on the primary database, True Cache automatically inherits their definitions. Using SQL\*Plus, make sure that you can see the same results on both the primary database and True Cache.
- Start the Database Application Services
   Using SQL\*Plus, start the database application services on both the primary database and True Cache.

### 2.3.3.1 Create Database Application Services on the Primary Database

From the primary database, create or modify the True Cache and primary database services using one of the following methods.

- For True Cache and single instance primary databases, use the DBMS\_SERVICE PL/SQL package. For services that are specific to a pluggable database (PDB), connect to the specific PDB, or set the correct PDB container in your session before starting the service using DBMS\_SERVICE.
- For Oracle RAC primary databases, use the srvctl command line utility with the true\_cache\_service option. Start the service on the primary instance. Use srvctl only for clusterware-managed instances.

```
srvctl add service -db primary_db_unique_name -service
primary_db_service_name -preferred primary_db_instance_list -pdb
primary_pdb_name -true_cache_service true_cache_service_name
```

#### For example:

```
srvctl add service -db primdb1i -service sales -preferred
primdb1i1,primdb1i2 -pdb sales pdb -true cache service sales tc
```

You can associate one primary database service with one True Cache service.

Here's an example of creating these two services using the <code>DBMS\_SERVICE</code> package for a single instance primary database:

```
DECLARE

db_params dbms_service.svc_parameter_array;

BEGIN

-- create a database application service for True Cache called SALES_TC using SALES_TC tnsname

DBMS_SERVICE.CREATE_SERVICE('SALES_TC', 'SALES_TC', db_params);

-- create a database application service SALES for primary database using SALES tnsname and associate it to the SALES_TC service name using TRUE_CACHE_SERVICE attribute

db_params('true_cache_service') := 'SALES_TC';

DBMS_SERVICE.CREATE_SERVICE('SALES', 'SALES', db_params);

-- or, modify an already existing primary database application service called SALES to associate it to the SALES_TC service name using the TRUE CACHE SERVICE attribute
```

```
db_params('true_cache_service') := 'SALES_TC';
DBMS_SERVICE.MODIFY_SERVICE('SALES', db_params);
END;
```

#### **Related Topics**

- CREATE\_SERVICE Procedure
- MODIFY\_SERVICE Procedure
- Server Control Utility Reference

## 2.3.3.2 Verify That the Database Application Services Are Created

After you create services on the primary database, True Cache automatically inherits their definitions. Using SQL\*Plus, make sure that you can see the same results on both the primary database and True Cache.

#### For example:

## 2.3.3.3 Start the Database Application Services

Using SQL\*Plus, start the database application services on both the primary database and True Cache.

#### Example 2-1 True Cache

```
connect / as SYSDBA

SELECT database_role FROM v$database;

DATABASE_ROLE
______
TRUE CACHE

EXEC DBMS_SERVICE.START_SERVICE('SALES_TC');

SELECT service_id, name FROM v$active_services WHERE name='SALES_TC';

SERVICE ID NAME
```

```
28 SALES TC
```

#### **Example 2-2 Primary Database**

#### **Related Topics**

- Verify That the Database Application Services Are Created
   After you create services on the primary database, True Cache automatically inherits their definitions. Using SQL\*Plus, make sure that you can see the same results on both the primary database and True Cache.
- START\_SERVICE Procedure
- V\$ACTIVE\_SERVICES
- V\$DATABASE

## 2.4 Deploying True Cache for an Oracle RAC Primary Database

This section summarizes the configuration requirements for deploying True Cache for a primary database in an Oracle Real Application Clusters (Oracle RAC) environment. These requirements are also included in context within the detailed configuration steps.



All of this information also appears in the context of the configuration steps for Configuring True Cache with Oracle DBCA and Configuring True Cache Manually.

- True Cache needs to be able to access each instance in the Oracle RAC environment. To
  do this, use the single client access name (SCAN) listener when configuring True Cache.
  - If you're configuring True Cache with DBCA, set the -sourceDBConnectionString parameter to SCAN:port/service name.

- If you're manually configuring True Cache, use the following settings when preparing the PFILE for True Cache:
  - \* Set the REMOTE LISTENER parameter to SCAN: port.
  - \* Set the FAL\_SERVER parameter to SCAN:port/service\_name.
- Add the True Cache node to the invited node list for the SCAN listener by using the srvctl command line utility. (Don't manually edit the listener.ora file as the grid owner user.)

#### For example:

```
srvctl modify scan_listener -invited
nodes true\_cache\_host -endpoints TCP: port
```

• When creating the database application services on the primary database, use the srvctl command line utility with the -true\_cache\_service option. Start the service on the primary instance.

```
srvctl add service -db primary_db_unique_name -service
primary_db_service_name -preferred primary_db_instance_list -pdb
primary pdb name -true cache service true cache service name
```

#### For example:

```
srvctl add service -db primdb1i -service sales -preferred
primdb1i1,primdb1i2 -pdb sales pdb -true cache service sales tc
```

#### **Related Topics**

srvctl modify scan\_listener

## 2.5 Verifying the True Cache Configuration

Verify that True Cache and the database application services are working as expected.

- Verifying That True Cache Is Working as Expected
   To verify that True Cache is applying redo and making progress, check the following queries on True Cache.
- Verifying the Remote Listener Configuration
   After the database application service starts on True Cache, use the lsnrctl command to validate the remote listener services for the True Cache service registration.
- Verifying the True Cache and Primary Database Application Services
   Verify that all database application services are active on both the primary database and True Cache.

## 2.5.1 Verifying That True Cache Is Working as Expected

To verify that True Cache is applying redo and making progress, check the following queries on True Cache.

1. Run SQL\*Plus on the True Cache.

```
sqlplus / as SYSDBA
```



#### 2. Enter the following query:

```
SELECT database role, open mode FROM v$database;
```

#### The output should look like this:

```
DATABASE_ROLE OPEN_MODE
TRUE CACHE READ ONLY WITH APPLY
```

If OPEN\_MODE is READ ONLY WITH APPLY, it means that the True Cache redo apply is actively working.

3. Enter the following query multiple times:

```
SELECT current scn FROM v$database;
```

If  ${\tt CURRENT\_SCN}$  is advancing over time, it means that True Cache is moving forward as expected.

4. To find the size of each log file, enter the following query:

```
SELECT THREAD#, SEQUENCE#, BYTES FROM v$standby log;
```

## 2.5.2 Verifying the Remote Listener Configuration

After the database application service starts on True Cache, use the <code>lsnrctl</code> command to validate the remote listener services for the True Cache service registration.

#### Note:

For Oracle RAC primary databases, before using the <code>lsnrctl</code> command, set your <code>\$ORACLE\_HOME</code> environment variable to the path for the Oracle Grid Infrastructure home (Grid home).

The following example shows two True Caches registered with the SCAN listener for an Oracle RAC primary database:

REMOTE SERVER
(ADDRESS=(PROTOCOL=TCP) (HOST=tc2.example.com) (PORT=1521))



If the True Cache service is not registered with the remote listener, validate the remote listener invited nodes and the True Cache initialization parameters for REMOTE\_LISTENER or LISTENER\_NETWORKS.

## 2.5.3 Verifying the True Cache and Primary Database Application Services

Verify that all database application services are active on both the primary database and True Cache.

#### **True Cache**

1. Run SQL\*Plus on True Cache.

```
sqlplus / as SYSDBA
```

2. Enter the following query:

```
SELECT service_id, name FROM v$active_services WHERE
name='true cache service name';
```

#### For example:

#### **Primary Database**

1. Run SQL\*Plus on the primary database.

```
sqlplus / as SYSDBA
```

2. Enter the following query:

```
SELECT service_id, name, true_cache_service FROM v$active_services WHERE name='primary_db_service_name';
```

#### For example:

```
SELECT service_id, name, true_cache_service FROM v$active_services WHERE name='SALES';

SERVICE_ID NAME TRUE_CACHE_SERVICE
```



29 SALES SALES TC

#### **Related Topics**

- Configuring True Cache Database Application Services Manually
   To use True Cache with the JDBC Thin driver, for each primary database application
   service that you want to cache, create a corresponding True Cache database application
   service.
- V\$ACTIVE\_SERVICES

## 2.6 Enabling DML Redirection

True Cache is a read-only cache, so you can't directly update the cache, but you can use DML redirection to indirectly update the cache.

DML redirection writes data to the primary database and then that data is automatically updated in the cache. This is similar to how Oracle Active Data Guard works. Because DML redirection uses more resources, it's not recommended for update-intensive applications.

To enable and use DML redirection, set the <code>ADG\_REDIRECT\_DML</code> initialization parameter to <code>TRUE</code> on True Cache.

✓ Note:

If the user logs in to True Cache with OS authentication, the user can't enable <code>ADG\_REDIRECT\_DML</code>. This is because the True Cache database administrator might not actually have the <code>SYSDBA</code> password but is allowed to use OS authentication to manage True Cache as <code>SYSDBA</code>. If the user can set <code>ADG\_REDIRECT\_DML</code>, then that user can update primary data as <code>SYSDBA</code> without knowing the <code>SYSDBA</code> password.

For more on enabling DML redirection, see Managing Physical and Snapshot Standby Databases.



## Deploying True Cache in Containers

Containers can simplify the deployment of True Cache configurations.

You can use the scripts that are provided in the True Cache container image to automatically create a True Cache configuration. The scripts complete the following configuration tasks:

- Create the primary database and True Cache containers.
- Create and start True Cache.
- Create and start the database application services for the primary database and True Cache.

See the complete instructions for downloading the images and creating the containers in the Oracle Database Container Images README.md.

Create a separate container for each True Cache. Assign different container names, Oracle SIDs, and database application service names, as needed.



4

## Shutting Down and Starting True Cache

You can shut down and start an existing True Cache.

- Shutting Down True Cache
  To shut down True Cache, use the SHUTDOWN command.
- Starting True Cache
  To start an existing True Cache, use the STARTUP command.

### 4.1 Shutting Down True Cache

To shut down True Cache, use the SHUTDOWN command.



Before shutting down True Cache for planned maintenance, stop the database application service on True Cache.

```
connect / as SYSDBA;
SHUTDOWN;
```

When you shut down True Cache, the cached content is lost. When you restart True Cache, it fetches the content again from the primary database.

## 4.2 Starting True Cache

To start an existing True Cache, use the STARTUP command.

```
connect / as SYSDBA;
STARTUP;
```

Work is automatically routed to True Cache when it declares that it's ready to support the True Cache service.

## Monitoring True Cache

You can monitor True Cache with the V\$TRUE\_CACHE view, and you can use the Automatic Workload Repository (AWR) to gather performance statistics for True Cache.

- Monitoring True Cache with the V\$TRUE\_CACHE View
   Use the V\$TRUE\_CACHE view to monitor the overall relationship and health of a True Cache configuration.
- Using the Automatic Workload Repository for True Cache
  You can use the Automatic Workload Repository (AWR) to gather performance statistics
  for True Cache.

## 5.1 Monitoring True Cache with the V\$TRUE\_CACHE View

Use the V\$TRUE\_CACHE view to monitor the overall relationship and health of a True Cache configuration.

You can query the V\$TRUE\_CACHE view on the primary database and True Cache. On True Cache, the view displays a single row for the primary database that it connects to. On the primary database, the view shows one row for each True Cache that's connected to the primary database. Each row displays the status for the True Cache.

To use this view, enter the following guery:

```
SELECT * FROM v$true cache;
```

The following example shows output on True Cache:

The following example shows output on a primary database:

#### V\$TRUE\_CACHE Columns

The following table describes the columns in the V\$TRUE CACHE view.

### 5.1.1 V\$TRUE\_CACHE Columns

The following table describes the columns in the V\$TRUE\_CACHE view.

Table 5-1 V\$TRUE\_CACHE Columns

Oalima	Paramintian
Column	Description
MY_DG_ID	The Data Guard ID (DGID) that uniquely identifies the True Cache or primary database in the True Cache configuration.
REMOTE_DG_ID	On True Cache, this is the primary database's DGID. On the primary database, it's the True Cache DGID.
DEST_ID	On True Cache, this is always 0. On the primary database, it's the corresponding destination ID (n) of the LOG_ARCHIVE_DEST_n initialization parameter. The LOG_ARCHIVE_DEST_n initialization parameter specifies the network name of the True Cache so that the primary database knows where to send online redo log blocks.
TRUE_CACHE_NAME	The unique name of the True Cache (DB_UNIQUE_NAME in the PFILE).
PRIMARY_NAME	The unique name of the primary database (DB_UNIQUE_NAME in the PFILE).
STATUS	Describes the current status of the True Cache. If no issues are found, it displays HEALTHY. Otherwise, it displays an error description. For example: ORA-01034: The Oracle instance is not available for use. Start the instance.
REMOTE_VERSION	On True Cache, this is the database version of the primary database. On the primary database, this is the database version of the True Cache.
CON_ID	The root container ID.

#### **Related Topics**

V\$TRUE\_CACHE

## 5.2 Using the Automatic Workload Repository for True Cache

You can use the Automatic Workload Repository (AWR) to gather performance statistics for True Cache.

You can run these steps on the primary database or on True Cache.

 Enable the AWR snapshot service for True Cache by entering the following SQL commands:

```
alter session set container = CDB$ROOT;

BEGIN
   dbms workload repository.enable snapshot service(
```

```
dbid => NULL,
    snap_type => 'WORKLOAD',
    snap_action => 'CREATE');
END;
```

2. Generate the AWR snapshot report by going to the <code>\$ORACLE\_HOME</code> directory and running the following script:

```
@?/rdbms/admin/awrrpti.sql
```

3. Specify whether you want an HTML or a text report. For example:

```
Enter value for report_type: text
```

The output displays a list of available database identifiers and instance numbers.

**4.** Enter the database identifier (dbid) and instance number (inst\_num) for True Cache. For example:

```
Enter value for dbid: 3309173529
Using 3309173529 for database Id
Enter value for inst num: 1
```

5. Specify the number of days for which you want to list snapshot IDs. For example:

```
Enter value for num days: 2
```

The output displays a list of existing snapshots for the specified time range.

6. Specify beginning and ending snapshot IDs for the workload repository report. For example:

```
Enter value for begin_snap: 150
Enter value for end snap: 160
```

7. Enter a report name or accept the default report name. For example:

```
Enter value for report_name:
Using the report name awrrpt 1 150 160
```

#### **Related Topics**

- Automatic Workload Repository (AWR)
- Generating an AWR Report Using the Command-Line Interface
- DBMS\_WORKLOAD\_REPOSITORY



## Using Oracle True Cache in Your Applications

When True Cache is configured, applications must decide whether to query data from True Cache or the primary database.

- Methods for Connecting to True Cache
   Applications can use True Cache in two ways.
- Sample Java Code Using the JDBC Thin Driver
   The JDBC method is illustrated by the following Java code using the JDBC Thin driver.
- Sample Java Code for Applications Using a Native Connection to the Database
   The following Java code illustrates how to use True Cache with applications that use an object-relational mapping (ORM) framework.
- Best Practices for Load Balancing in a Uniform Configuration
   If multiple True Caches exist and serve the same database application service, the listener automatically distributes and load balances sessions to each cache. In a uniform configuration, the listener picks a True Cache randomly or based on load, and all True Caches cache the same data.

## 6.1 Methods for Connecting to True Cache

Applications can use True Cache in two ways.

- The application maintains two physical connections: one to the primary database and one
  to True Cache. Each connection has a database application service, and the application
  chooses which connection to use based on whether it's reading or writing. You can use this
  model with any existing client drivers and any programming language.
  - The application sends queries that don't need to see the most current data to True Cache through a True Cache database application service. The application sends other queries and updates to the primary database through the primary database application service.
- The application maintains *one logical connection* that uses the database application service for the primary database. The JDBC Thin driver (starting with Oracle Database 23ai) maintains physical connections to the primary database and True Cache. This model only works with Java applications.

The application switches between the primary database and True Cache without having to specify an instance name. The application uses special calls to flag the logical connection as read-only or read-write. If it's read-only, the query is sent to True Cache. Otherwise, it's sent to the primary database.

To enable the True Cache functionality for Java applications, set the value of the oracle.jdbc.useTrueCacheDriverConnection property to true. After you enable True Cache, the JDBC Thin driver uses the standard

java.sql.Connection.setReadOnly(boolean) and java.sql.Connection.isReadOnly() methods to mark a connection as read-only. By default, the read-only mode is false for a connection.

See the following technical architecture diagram for details and examples:

True Cache Application

#### **Related Topics**

- Support for Oracle True Cache
- setReadOnly(boolean) method
- isReadOnly() method

## 6.2 Sample Java Code Using the JDBC Thin Driver

The JDBC method is illustrated by the following Java code using the JDBC Thin driver.



#### **WARNING:**

Do not use this code in a production environment.

The core of this basic code is in the test1 function, which does the following:

- Creates a connection to the primary database by using the JDBC Thin driver with either a
  default user name and password or values that are specified on the command line when
  invoking the program.
- 2. Prints some basic information about the primary database connection to verify that the application is connected to the database.
- 3. Changes the isReadOnly connection parameter to TRUE to automatically switch the connection to True Cache and verify that it's connected to it.

```
import java.sql.*;
import java.io.*;
import java.util.*;
import java.util.logging.FileHandler;
import java.util.logging.Level;
import java.util.logging.Logger;
import oracle.jdbc.driver.OracleLog;
import oracle.jdbc.pool.OracleDataSource;
public class TrueCache {
  static String url primary = "jdbc:oracle:thin:@primary database host:1521/
SALES";
  static String user = "username";
  static String password = "password";
  public static void main(String args[]) {
     TrueCache t = new TrueCache();
      if(args != null && args.length >0 ) {
       url primary = args[0];
       user = args[1];
        password = args[2];
     t.test1();
    } catch (Exception e) {
      e.printStackTrace();
```

```
public void test1() throws SQLException {
    show ("Basic test to connect to primary and True Cache");
     show("Get Connection from True Cache instance using primary db and
properties");
     OracleDataSource ods1 = new OracleDataSource();
      show("URL = " + url_primary);
     ods1.setURL(url primary);
     ods1.setUser(user);
     ods1.setPassword(password);
     ods1.setConnectionProperty("oracle.jdbc.useTrueCacheDriverConnection",
"true");
     Connection conn1 = ods1.getConnection();
     show("isReadonly " + conn1.isReadOnly());
     verifyConnection(conn1); // This is connected to Primary
     conn1.setReadOnly(true);
     show("isReadonly " + conn1.isReadOnly());
     verifyConnection(conn1); // This is connected to True Cache
     conn1.close();
    } catch (SQLException sqex) {
     show("test1 -- failed" + sqex.getMessage()+":"+sqex.getCause());
     sqex.printStackTrace();
   show("The end");
 public void verifyConnection(Connection conn) {
     Statement statement = conn.createStatement();
     ResultSet rs = statement.executeQuery("SELECT database role from
v$database");
     ResultSetMetaData rsmd = rs.getMetaData();
     int columnsNumber = rsmd.getColumnCount();
     show("Database role : " + rs.getString(1));
     rs.close();
     ResultSet resultSet = statement.executeQuery("SELECT
SYS CONTEXT('userenv', 'instance name') as instance name"
         + ", SYS_CONTEXT('userenv', 'server_host')" + " as server_host" +
", SYS CONTEXT('userenv', 'service name')"
         + " as service name" + ", SYS CONTEXT('USERENV', 'db unique name')"
+ " as db unique name" + " from sys.dual");
      resultSet.next();
     show("instance name : " + resultSet.getString("instance name"));
      show("server host : " + resultSet.getString("server host"));
     show("service name : " + resultSet.getString("service name"));
     show("db_unique_name : " + resultSet.getString("db_unique_name"));
     resultSet.close();
     statement.close();
    } catch (SQLException sqex) {
```

```
show("verifyConnection failed " + sqex.getMessage());
}

public void show(String msg) {
   System.out.println(msg);
}
```

# 6.3 Sample Java Code for Applications Using a Native Connection to the Database

The following Java code illustrates how to use True Cache with applications that use an object-relational mapping (ORM) framework.

This is another example of maintaining only one logical connection to a database application service running on the primary database and letting the driver handle the underlying physical connections. It shows how to get the underlying connections from the framework so you can set the necessary parameter.

#### **WARNING:**

Do not use this code in a production environment.

- Add the oracle.jdbc.useTrueCacheDriverConnection=true connection property to the connection URL in the persistence.xml file.
- 2. In the methods that need to use a True Cache connection, unwrap the session, use the dowork method to retrieve the underlying JDBC connection, and set the necessary read-only parameter for the connection. For example:

```
Session session = em.unwrap(Session.class);
session.doWork(new Work() {
   @Override
   public void execute(Connection con) throws SQLException {
      // if it is connected to primary, I want the connection to switch to
true cache now
      if(!con.isReadOnly()) {
         // The below code demonstrates the connection is to primary
now
         System.out.println("Query getting executed on:");
         Statement statement = con.createStatement();
         ResultSet rs = statement.executeQuery("SELECT database role from
v$database");
         System.out.println("Database role : " + rs.getString(1));
         rs.close();
         // Now switching the connections to true cache
         con.setReadOnly(true);
         // The below code demonstrates the connection is to true cache
```

## 6.4 Best Practices for Load Balancing in a Uniform Configuration

If multiple True Caches exist and serve the same database application service, the listener automatically distributes and load balances sessions to each cache. In a uniform configuration, the listener picks a True Cache randomly or based on load, and all True Caches cache the same data.

A uniform configuration uses runtime connection load balancing (CLB), which routes requests to the True Cache that offers the best performance. For this to work, all True Caches' REMOTE\_LISTENER parameters should point to the same listener, which is also the primary database's listener (whether it's single instance primary database's local listener or an Oracle RAC primary database's SCAN listener).

The application's JDBC URL should point to the primary database. Then the JDBC Thin driver creates one logical connection and multiple physical connections to the primary database and to each True Cache. Setting the <code>setReadOnly(true)</code> flag in the Java code reroutes connections to the True Caches automatically. The True Caches are registered with the primary database listener, and they also send their load statistics to the primary database listener. You should see an even distribution between True Caches.

To simplify configuration and avoid connection issues, consider using the LISTENER\_NETWORKS initialization parameter instead of specifying REMOTE\_LISTENER and LOCAL\_LISTENER separately. With LISTENER\_NETWORKS, all listeners within the same network name will cross-register. For example:

For more about configuring remote listeners and listener networks, see Prepare a PFILE for True Cache.

#### **Related Topics**

About Run-Time Connection Load Balancing



7

## Complementary Caching Features

True Cache can be combined with other Oracle Database features to improve performance.

#### Server-Side Result Set Cache

The server-side result cache is used to cache the results of the current queries, query fragments, and PL/SQL functions in memory. The cached results are used in future uses of the query, query fragment, or PL/SQL function.

#### KEEP Buffer Pool

You can use the KEEP buffer pool to keep frequently accessed tables persistent in the buffer pool.

Database Smart Flash Cache

If the data that you want to cache doesn't fit in memory, you can expand the capacity of True Cache by adding flash devices. You do this by configuring Database Smart Flash Cache.

### 7.1 Server-Side Result Set Cache

The server-side result cache is used to cache the results of the current queries, query fragments, and PL/SQL functions in memory. The cached results are used in future uses of the query, query fragment, or PL/SQL function.

The cached results stay in the result cache memory part of the SGA. A cached result is automatically invalidated whenever a database object used in its creation is successfully changed. See Tuning the Result Cache for more information about configuring the server-side result set cache.

To enable the server-side result cache on True Cache, issue the following command on the primary database:

```
ALTER TABLE table name RESULT CACHE (STANDBY ENABLE);
```

Support for server-side result set caching is available for both JDBC Thin and JDBC Oracle Call Interface (JDBC OCI) drivers.

#### **Related Topics**

Using the Result Cache on Physical Standby Databases

### 7.2 KEEP Buffer Pool

You can use the KEEP buffer pool to keep frequently accessed tables persistent in the buffer pool.

- Overview of Using the KEEP Buffer Pool with True Cache
  You can assign different objects to the KEEP buffer pool on different True Caches.
- Configuring DB\_KEEP\_CACHE\_SIZE on True Cache
   To configure the KEEP buffer pool on True Cache, set the DB\_KEEP\_CACHE\_SIZE initialization
   parameter to a large size (such as 10 GB).

- Assigning Objects to the KEEP Buffer Pool for True Cache
   After configuring the KEEP buffer pool, assign the object to the KEEP buffer pool for True
   Cache.
- Removing an Object's KEEP Buffer Pool Assignment for True Cache
   You can use DBMS\_CACHEUTIL.TRUE\_CACHE\_UNKEEP() to remove objects from the KEEP
   buffer pool.
- Viewing a List of KEEP Objects on True Cache
  Use the V\$TRUE\_CACHE\_KEEPOBJ view to see which objects are assigned to the KEEP buffer cache for True Cache.

### 7.2.1 Overview of Using the KEEP Buffer Pool with True Cache

You can assign different objects to the  $\mathtt{KEEP}$  buffer pool on different True Caches.

At a high level, this involves the following steps:

- 1. Configure DB\_KEEP\_CACHE\_SIZE on True Cache.
- 2. Assign objects on True Cache to the KEEP buffer pool.

As with the primary database, when an object is assigned to the KEEP buffer pool on True Cache, the object's blocks are loaded for a query and then kept in the KEEP buffer pool. When new data is inserted into the object on the primary database, that new data is automatically propagated to the KEEP buffer pool on True Cache through the redo apply mechanism.

To propagate direct load data to True Cache, specify the LOGGING clause in the corresponding DDL or DML, or alter the corresponding object property to LOGGING. The LOGGING clause lets you specify whether certain operations will be logged in the redo log file (LOGGING) or not (NOLOGGING).

How True Cache Works with the Primary Database Buffer Cache
 By default, marking something KEEP on the primary database also marks it KEEP on True Cache.

#### **Related Topics**

- Configuring the KEEP Pool
- logging\_clause

### 7.2.1.1 How True Cache Works with the Primary Database Buffer Cache

By default, marking something KEEP on the primary database also marks it KEEP on True Cache.

To prevent objects that are intended to be KEEP objects only on the primary database from filling up the True Cache KEEP buffer pool, you can use the DBMS\_CACHEUTIL.TRUE\_CACHE\_KEEP procedure to mark objects as KEEP on True Cache. DBMS\_CACHEUTIL.TRUE\_CACHE\_KEEP takes precedence and overrides objects that are marked as KEEP on the primary database.

Also consider the following points:

- ALTER TABLE KEEP assignments on the primary database are persistent because ALTER TABLE is a DDL. The DBMS\_CACHEUTIL.TRUE\_CACHE\_KEEP procedure isn't persistent when True Cache restarts.
- You can't use the DBMS\_CACHEUTIL.TRUE\_CACHE\_UNKEEP procedure to unkeep a primary ALTER TABLE KEEP assignment. Instead, either don't configure DB\_KEEP\_CACHE\_SIZE on



True Cache or assign a different object with <code>DBMS\_CACHEUTIL.TRUE\_CACHE\_KEEP</code> on True Cache.

• All scans on True Cache use the CACHE path instead of the direct (NOCACHE) path, except temporary tables that are local to True Cache.

### 7.2.2 Configuring DB\_KEEP\_CACHE\_SIZE on True Cache

To configure the KEEP buffer pool on True Cache, set the DB\_KEEP\_CACHE\_SIZE initialization parameter to a large size (such as 10 GB).

#### For example:

```
ALTER SYSTEM SET DB KEEP CACHE SIZE=size SCOPE=BOTH;
```

#### **Related Topics**

- DB\_KEEP\_CACHE\_SIZE
- Setting or Changing Initialization Parameter Values

### 7.2.3 Assigning Objects to the KEEP Buffer Pool for True Cache

After configuring the KEEP buffer pool, assign the object to the KEEP buffer pool for True Cache.

To do this, call the DBMS CACHEUTIL.TRUE CACHE KEEP() procedure on True Cache.

#### **Example: Nonpartitioned Object**

```
EXECUTE DBMS CACHEUTIL.TRUE CACHE KEEP('SYS', 'TABLE1');
```

#### **Example: Partition of a Partitioned Object**

```
EXECUTE DBMS CACHEUTIL.TRUE CACHE KEEP('SYS', 'TABLE2', 'TABLE2 PART1');
```

TRUE\_CACHE\_KEEP Procedure

When you call this procedure on True Cache, it assigns the object to the  $\mathtt{KEEP}$  buffer pool on that cache.

### 7.2.3.1 TRUE\_CACHE\_KEEP Procedure

When you call this procedure on True Cache, it assigns the object to the KEEP buffer pool on that cache.

To use this procedure, the <code>DB\_KEEP\_CACHE\_SIZE</code> initialization parameter must be configured on True Cache.

#### **Syntax**

```
DBMS_CACHEUTIL.TRUE_CACHE_KEEP(
schema IN VARCHAR2,
obj IN VARCHAR2,
partition IN VARCHAR2 := NULL);
```



#### **Parameters**

Table 7-1 TRUE CACHE KEEP Procedure Parameters

Parameter	Description
schema	The name of the schema for the object.
obj	The name of the object.
partition	<ul> <li>If the object is not partitioned, then this is NULL.</li> <li>If the object is partitioned, use the name of the partition segment.</li> <li>If it's a composited partitioned object, use the name of the subpartition segment.</li> </ul>

#### **Related Topics**

TRUE\_CACHE\_KEEP Procedure

### 7.2.4 Removing an Object's KEEP Buffer Pool Assignment for True Cache

You can use <code>DBMS\_CACHEUTIL.TRUE\_CACHE\_UNKEEP()</code> to remove objects from the <code>KEEP</code> buffer pool.

Note that the block is not removed immediately. Instead, it will be naturally aged out as new blocks for other objects are brought into the KEEP buffer pool. Also, the KEEP buffer pool assignment on True Cache is only remembered while True Cache is up.

#### **Example: Nonpartitioned Object**

```
EXECUTE DBMS CACHEUTIL.TRUE CACHE UNKEEP('SYS', 'TABLE1');
```

#### **Example: Partition of a Partitioned Object**

```
EXECUTE DBMS CACHEUTIL.TRUE CACHE UNKEEP('SYS', 'TABLE2', 'TABLE2 PART1');
```

#### TRUE\_CACHE\_UNKEEP Procedure

When an object on True Cache no longer needs to be in the KEEP buffer pool, use this procedure to remove the object's KEEP assignment.

### 7.2.4.1 TRUE\_CACHE\_UNKEEP Procedure

When an object on True Cache no longer needs to be in the KEEP buffer pool, use this procedure to remove the object's KEEP assignment.

#### **Syntax**

```
DBMS_CACHEUTIL.TRUE_CACHE_UNKEEP(
schema IN VARCHAR2,
obj IN VARCHAR2,
partition IN VARCHAR2 := NULL);
```



#### **Parameters**

Table 7-2 TRUE\_CACHE\_UNKEEP Procedure Parameters

Parameter	Description
schema	The name of the schema for the object.
obj	The name of the object.
partition	<ul> <li>If the object is not partitioned, then this is NULL.</li> <li>If the object is partitioned, use the name of the partition segment.</li> <li>If it's a composited partitioned object, use the name of the subpartition segment.</li> </ul>

#### **Related Topics**

TRUE\_CACHE\_UNKEEP Procedure

### 7.2.5 Viewing a List of KEEP Objects on True Cache

Use the V\$TRUE\_CACHE\_KEEPOBJ view to see which objects are assigned to the KEEP buffer cache for True Cache.

#### Example 1

```
SELECT * FROM v$true_cache_keepobj;

TS_NUMBER DATA_OBJECT_ID CON_ID

5 72948 3
5 72950 3
```

#### Example 2

V\$TRUE\_CACHE\_KEEPOBJ Columns

The following table describes the columns in the V\$TRUE CACHE KEEPOBJ view.



### 7.2.5.1 V\$TRUE\_CACHE\_KEEPOBJ Columns

The following table describes the columns in the V\$TRUE CACHE KEEPOBJ view.

Column	Description
TS_NUMBER	The tablespace number.
DATA_OBJECT_ID	The dictionary object number of the segment that contains the object.
CON_ID	The root container ID.

### 7.3 Database Smart Flash Cache

If the data that you want to cache doesn't fit in memory, you can expand the capacity of True Cache by adding flash devices. You do this by configuring Database Smart Flash Cache.

To enable Database Smart Flash Cache, see Configuring Database Smart Flash Cache.



When configuring Database Smart Flash Cache on True Cache, spilling TDE encrypted data to local flash devices is not supported. If a data block is TDE encrypted on the primary database, it stays in the DRAM buffer cache on True Cache.



## **Deleting True Cache**

You can delete True Cache with Oracle DBCA or manually.

- Using Oracle DBCA to Delete True Cache
   You can use Oracle DBCA to clean up the True Cache services and delete True Cache.
- Deleting True Cache Manually
   To delete True Cache manually, use the following commands.

## 8.1 Using Oracle DBCA to Delete True Cache

You can use Oracle DBCA to clean up the True Cache services and delete True Cache.

- Cleaning Up the True Cache Services from the Primary Database
   To delete True Cache, you need to clean up its corresponding services on the primary database.
- Deleting True Cache from the True Cache Node
   Run the following command to delete True Cache from the True Cache node.

### 8.1.1 Cleaning Up the True Cache Services from the Primary Database

To delete True Cache, you need to clean up its corresponding services on the primary database.

Run the following command on the primary database to delete all the services that correspond to the True Cache that you're planning to delete.

```
ORACLE_HOME/bin/dbca -configureDatabase -cleanupTrueCacheInstanceService -sourceDB primary_sid_or_db_unique_name -trueCacheConnectString true_cache_easy_connect_string -serviceName primary_service_name -silent
```

#### Example:

```
$ORACLE_HOME/bin/dbca -configureDatabase -cleanupTrueCacheInstanceService -
sourceDB primdbli -trueCacheConnectString tc.example.com:1522/
tcdbl.example.com -serviceName sales -silent
```

For descriptions of the parameters, see configureDatabase.

### 8.1.2 Deleting True Cache from the True Cache Node

Run the following command to delete True Cache from the True Cache node.

ORACLE\_HOME/bin/dbca -deleteDatabase -sourceDB primary\_sid\_or\_db\_unique\_name - silent

#### Example:

\$ORACLE HOME/bin/dbca -deleteDatabase -sourceDB tcdb1 -silent

## 8.2 Deleting True Cache Manually

To delete True Cache manually, use the following commands.

```
connect / as SYSDBA;
shutdown immediate;
startup mount exclusive restrict;
drop database;
```

#### Note:

This does *not* drop the primary database. It deletes the True Cache SPFILE; drops the True Cache control, standby log, and temporary files; and removes LOG\_ARCHIVE\_DEST entries from the primary database.



A

## True Cache Error Messages

View error messages that you might encounter when using True Cache.

Select an error message to read the full description in the Error Help Portal.

- ORA-61850, Oracle version mismatch between primary database and True Cache.
- ORA-61851, True Cache instance does not allow string operation.
- ORA-61852, CREATE TRUE CACHE failed.
- ORA-61853 Cannot start True Cache.
- ORA-61854 Cannot start True Cache with non True Cache control file.
- ORA-61855 Invalid TRUE\_CACHE\_CONFIG attribute.
- ORA-61856 True Cache requires a valid parameter value for string.
- ORA-61857 Communication with the primary failed.
- ORA-61858 Unable to translate FAL\_SERVER initialization parameter string.
- ORA-61859 There was an error when executing a remote procedure call (op: string-stringstring) at primary server string.
- ORA-61860 True Cache instance is being shutdown because it has been disconnected from the primary for too long.
- ORA-61861 Unable to receive redo since standby redo log is not available.
- ORA-61862 String is not configured as a multitenant database.
- ORA-61863 True Cache could not be started because there was a configuration parameter mismatch with the primary. Restart the database.
- ORA-61864 True Cache failed to read metadata from the primary.
- ORA-61865 The TNS alias string could not be translated.
- ORA-61866 Some static parameters (string) differed from the value in the primary database. These parameters have been fixed and the database will be shut down.
- ORA-61867 Oracle True Cache failed to restart. Shutting down.
- ORA-61868 True Cache entry corresponding to the hash ID string not found in a LOG\_ARCHIVE\_DEST\_n parameter.
- ORA-61869 Unable to connect to True Cache.
- ORA-61870 True Cache requires ARCHIVELOG mode to be enabled at the primary database.
- ORA-61871 Cannot fetch data block from the primary database (file # string, block # string).
- ORA-61872 The string command in pluggable database string failed because some process is keeping a lock on it for too long. True cache will be restarted.
- ORA-61873 True Cache could not be started because the system parameter 'string' is different in the PRIMARY database. Remove the parameter from the True Cache initialization file.

- ORA-61874 Cannot fetch data block from the primary database (file # string, block # string).
- ORA-61875 There was a failure adding the system parameter LOG\_ARCHIVE\_DEST\_n at the primary database. True Cache database cannot be opened without it.
- ORA-61876 Failed to open True Cache because the primary database is configured for shared server.
- ORA-61877 True Cache recovery lags too far behind, exceeding string seconds.
- ORA-61878 PDB (con\_id:string) is not open on the primary database.
- ORA-61879 db\_keep\_cache\_size is not configured on True Cache.
- ORA-61880 This operation (string) is only allowed on True Cache instance.
- ORA-61881 Failed to open True Cache because there has been an error reading metadata (string) from the primary database string.



B

## Licensing for True Cache

True Cache licensing is based on the edition of Oracle Database that you're using for both the primary database and True Cache.

See Permitted Features, Options, and Management Packs by Oracle Database Offering in the Oracle Database Licensing Information User Manual.



C

## Troubleshooting True Cache

Follow these recommendations if you run into issues when configuring or using True Cache.

Rerunning Oracle DBCA
 If you run into issues when configuring True Cache with Oracle DBCA, you need to clean up the True Cache node and then rerun DBCA.

## C.1 Rerunning Oracle DBCA

If you run into issues when configuring True Cache with Oracle DBCA, you need to clean up the True Cache node and then rerun DBCA.

- Rerunning Oracle DBCA After Creating True Cache
   If you need to rerun Oracle DBCA after creating True Cache, clean up the True Cache node first.
- Rerunning Oracle DBCA After Configuring True Cache Database Application Services
  If you need to rerun Oracle DBCA after configuring True Cache database application
  services, you might need to delete the True Cache service from the primary pluggable
  database (PDB) using the DBMS\_Service package.

### C.1.1 Rerunning Oracle DBCA After Creating True Cache

If you need to rerun Oracle DBCA after creating True Cache, clean up the True Cache node first.

If you don't do the cleanup, DBCA might say that the instance already exists.

- Shut down True Cache if it was started during the creation. See Shutting Down True Cache.
- 2. Remove any newly created files in the <code>\$ORACLE\_HOME/dbs</code> directory for True Cache. File names contain the True Cache name.
- 3. If you used a Transparent Data Encryption (TDE) auto-login wallet, delete the wallet and auto-login file in the <code>\$ORACLE BASE/admin/true cache name/wallet root/tde/directory.</code>
- 4. Create True Cache again. See Creating True Cache with DBCA.

# C.1.2 Rerunning Oracle DBCA After Configuring True Cache Database Application Services

If you need to rerun Oracle DBCA after configuring True Cache database application services, you might need to delete the True Cache service from the primary pluggable database (PDB) using the DBMS\_Service package.

Example error message:

[DBT-19958] Database service 'trueCacheServiceName'

- 1. For services that are specific to a PDB, connect to the specific PDB, or set the correct PDB container in your session.
- 2. Connect to True Cache and stop the True Cache service on True Cache if it's running.

```
EXEC DBMS_SERVICE.STOP_SERVICE('trueCacheServiceName');
```

3. Delete the service on the primary database using DBMS SERVICE. DELETE SERVICE.

```
EXEC DBMS_SERVICE.DELETE_SERVICE('trueCacheServiceName');
```

 Configuration the True Cache application service again. See Configuring True Cache Database Application Services with DBCA.

