


Dynamic Memory Allocation

- Programmers use *dynamic memory allocators* (such as `malloc`) to assign VM at run time.

- For data structures whose size is only known at runtime.

- Dynamic memory allocators manage an area of process virtual memory known as the *heap*.



Dynamic Memory Allocation

- Allocator maintains heap as collection of variable sized *blocks*, which are either *allocated* or *free*
- Types of allocators
 - *Explicit allocator*
 - E.g., `malloc`
 - *Implicit allocator*
 - E.g. garbage collection in Python and Lisp
- Will discuss simple explicit memory allocation today

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

The malloc Package

```
#include <stdlib.h>
```

```
void *malloc(size_t size)
```

- Successful:
 - Returns a pointer to a memory block of at least **size** bytes (typically) aligned to 8-byte boundary
 - If **size** =

- Unsuccessful: r

```
void free(void *p)
```

- Returns the block pointed at by **p** to pool of available memory
- **p** must come from a previous call to **malloc** or **realloc**

Other functions

- **calloc**: Version of **malloc** that initializes allocated block to zero.
- **realloc**: Changes the size of a previously allocated block.
- **sbrk**: Used internally by allocators to grow or shrink the heap

malloc Example

```
void foo(int n, int m) {  
    int i, *p;  
  
    /* Allocate a block of n ints */  
    p = (int *) malloc(n * sizeof(int));  
    if (p == NULL) {  
        perror("malloc");  
        exit(0);  
    }  
  
    /* Initialize allocated block  
    for (i=0; i<n; i++)  
        p[i] = i;  
  
    /* Return p to the heap */  
    free(p);  
}
```

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro