

Implicit List: Freeing a Block


■ Simplest implementation:

- Need only clear the “allocated” flag

```
void free_block(ptr p) { *p = *p & -2 }
```

Assignment Project Exam Help


- But can lead to “false fragmentation”



There is enough free space, but the allocator won't be able to find it

Implicit List: Coalescing

- Join (*coalesce*) with next/previous blocks, if they are free
 - Coalescing with next block



```
void free_block(ptr p) {
    *p = *p & -2;           // clear allocated flag
    next = p + *p;           // find next block
    if ((*next & 1) == 0)
        *p = *p + *next;    // add to this block if
                             // not allocated
}
```


- But how do we coalesce with *previous* block?

Implicit List: Bidirectional Coalescing

■ **Boundary tags** [Knuth73]


- Replicate size/allocated word at “bottom” (end) of free blocks
- Allows us to traverse the “list” backwards, but requires extra space
- Important and general technique!

Assignment Project Exam Help



Add WeChat edu_assist_pro

*Format of
allocated and
free blocks*




a = 1: Allocated block
a = 0: Free block

Size: Total block size


Payload: Application data
(allocated blocks only)

Constant Time Coalescing




Add WeChat edu_assist_pro

Constant Time Coalescing (Case 1)



Constant Time Coalescing (Case 2)




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Constant Time Coalescing (Case 3)



Constant Time Coalescing (Case 4)

m1	0
m1	0
n	
n	
m2	0
m2	0

n+m1+m2	0
n+m1+m2	0

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro