



Outlines

Overview

Introduction

Linear Algebra

Probability

Linear Regression

Linear Regression

Linear Classification 1

Linear Classification 2

Kernel Methods

Sparse Kernel Methods

Structure Models and EM 1

Structure Models and EM 2

Neural Networks 1

Neural Networks 2

Deep Component Analysis

Generators

Graphical Models 1

Graphical Models 2

Graphical Models 3

Sampling

Sequential Data 1

Sequential Data 2

Statistical Machine Learning

Assignment Project Exam Help

Christian Walder

<https://eduassistpro.github.io>

College of Engineering and Computer Science
The Australian National University

Add WeChat edu_assist_pro

Canberra

Semester One, 2020.

(Many figures from C. M. Bishop, "Pattern Recognition and Machine Learning")



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Bayesian Approximation
Logistic Regression

Assignment Project Exam Help

Part VI

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

Three Models for Decision Problems



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Bayesian Approximation

Bayesian Logistic
Regression

In increasing order of complexity

- Find a discriminant function $f(\mathbf{x})$ which maps each input directly onto a class label.
- Discriminative Models

①

②

<https://eduassistpro.github.io>

- Generative Models

③

Solve the inference problem of determining the class-conditional probabilities $p(\mathbf{x} | C_k)$

④

Also, infer the prior class probabilities

⑤

Use Bayes' theorem to find the posterior $p(C_k | \mathbf{x})$.

⑥

Alternatively, model the joint distribution $p(\mathbf{x}, C_k)$ directly.

⑦

Use decision theory to assign each new \mathbf{x} to one of the classes.

Add WeChat edu_assist_pro



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Bayesian Approximation

Bayesian Logistic
Regression

Given:

- class prior $p(\mathbf{t})$
- class-conditional $p(\mathbf{x} | \mathbf{t})$

to generate

1. Sample \mathbf{t} from $p(\mathbf{t})$
2. Sample \mathbf{x} from $p(\mathbf{x} | \mathbf{t})$

distribution $p(\mathbf{x} | \mathbf{t})$.

(more about sampling later — this is called

Thinking about the data generating process is a useful modelling step, especially when we have more prior knowledge.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro



- Generative approach: model class-conditional densities $p(\mathbf{x} | \mathcal{C}_k)$ and *class* priors (not parameter priors!) $p(\mathcal{C}_k)$ to calculate the posterior probability for class \mathcal{C}_1

$$p(\mathcal{C}_1 | \mathbf{x}) = \frac{p(\mathbf{x} | \mathcal{C}_1)p(\mathcal{C}_1)}{p(\mathbf{x} | \mathcal{C}_1)p(\mathcal{C}_1) + p(\mathbf{x} | \mathcal{C}_2)p(\mathcal{C}_2)}$$

<https://eduassistpro.github.io>

where a and the **logistic sigmoid** function

Add WeChat [edu_assist_pro](#)

$$\sigma(a) = \frac{1}{1 + \exp(-a)}.$$

- One point of this re-writing: we may learn $a(\mathbf{x})$ directly as e.g. a deep neural network.

Logistic Sigmoid



Probabilistic Generative Models

Continuous Input

Discrete Features

Probabilistic Discriminative Models

Logistic Regression

Active Reweighted Least Squares

Bayesian Approximation

Logistic Regression

- The **logistic sigmoid** function is called a “squashing function” because it squashes the real axis into a finite interval $(0, 1)$.


- Well known properties (derive them):

- Symmetry: $\sigma(-a) = 1 - \sigma(a)$


•

- Inv

<https://eduassistpro.github.io>



$$\text{Sigmoid } \sigma(a) = \frac{1}{1 + \exp(-a)}$$



$$\text{Logit } a(\sigma) = \ln \left(\frac{\sigma}{1 - \sigma} \right)$$



- The normalised exponential is given by

$$p(C_k | \mathbf{x}) = \frac{p(\mathbf{x} | C_k) p(C_k)}{p(\mathbf{x} | j) p(j)} = \frac{\exp(a_k)}{\exp(a_j)}$$

wh

<https://eduassistpro.github.io>

- Usually called the softmax function as it is a smooth version of the arg max function, in particular

Add WeChat edu_assist_pro

$$a_k \gg a_j \forall j \neq k \Rightarrow (p(C_k | \mathbf{x}) \approx 1 \wedge$$

- So, softargmax is a more descriptive though less common name.

- Assume class-conditional probabilities are Gaussian, with the **same covariance** and different mean:

Assignment Project Exam Help

<https://eduassistpro.github.io>

- Let's characterise the posterior probabilities.
- We may separate the quadratic and linear term in

Add WeChat edu_assist_pro

$$p(\mathbf{x} | C_k) = \frac{1}{(2\pi)^{D/2}} \frac{1}{|\Sigma|^{1/2}} \exp \left\{ -\frac{1}{2} (\mathbf{x} - \boldsymbol{\mu}_k)^T \Sigma^{-1} (\mathbf{x} - \boldsymbol{\mu}_k) \right\}$$

$$= \frac{1}{(2\pi)^{D/2}} \frac{1}{|\Sigma|^{1/2}} \exp \left\{ -\frac{1}{2} \mathbf{x}^T \Sigma^{-1} \mathbf{x} + \boldsymbol{\mu}_k^T \Sigma^{-1} \mathbf{x} - \frac{1}{2} \boldsymbol{\mu}_k^T \Sigma^{-1} \boldsymbol{\mu}_k \right\}$$



Probabil. Generative Model - Continuous Input



- For two classes

$$p(\mathcal{C}_1 | \mathbf{x}) = \sigma(a(\mathbf{x}))$$

and $a(\mathbf{x})$ is linear because the quadratic terms in \mathbf{x} cancel
(c.f. the previous slide):

<https://eduassistpro.github.io>

$$\frac{\exp \left(\mu_2^T \Sigma^{-1} \mathbf{x} - \frac{1}{2} \mu_2^T \Sigma^{-1} \mu \right)}{p(\mathcal{C}_2)}$$

- Therefore

$$p(\mathcal{C}_1 | \mathbf{x}) = \sigma(\mathbf{w}^T \mathbf{x} + w_0)$$

where

$$\mathbf{w} = \Sigma^{-1}(\mu_1 - \mu_2)$$

$$w_0 = -\frac{1}{2} \mu_1^T \Sigma^{-1} \mu_1 + \frac{1}{2} \mu_2^T \Sigma^{-1} \mu_2 + \ln \frac{p(\mathcal{C}_1)}{p(\mathcal{C}_2)}$$

Add WeChat edu_assist_pro



Assignment Project Exam Help

Class-conditional densities for two classes (left). Posterior probability $p(C_1 | \mathbf{x})$ (right). Note the logistic sigmoid of a linear function of \mathbf{x} .

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

General Case - K Classes, Shared Covariance



- Use the normalised exponential

$$p(C_k | \mathbf{x}) = \frac{p(\mathbf{x} | C_k) p(C_k)}{\sum_j p(\mathbf{x} | C_j) p(C_j)} = \frac{\exp(a_k)}{\sum_j \exp(a_j)}$$

wh

- to get

$$a_k(\mathbf{x}) = \mathbf{w}_k^T \mathbf{x} + w_{k0}.$$



where

$$\mathbf{w}_k = \Sigma^{-1} \boldsymbol{\mu}_k$$

$$w_{k0} = -\frac{1}{2} \boldsymbol{\mu}_k^T \Sigma^{-1} \boldsymbol{\mu}_k + p(C_k).$$

General Case - K Classes, Different Covariance

- If the class-conditional distributions have different covariances, the quadratic terms $-\frac{1}{2}\mathbf{x}^T \Sigma^{-1} \mathbf{x}$ do not cancel out.
- We get a quadratic discriminant.



- Given the functional form of the class-conditional densities $p(\mathbf{x} | \mathcal{C}_k)$, how can we determine the parameters μ and Σ and the class prior?

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro





Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Bayesian Approximation

Bayesian Logistic
Regression

- Given the functional form of the class-conditional densities $p(\mathbf{x} | \mathcal{C}_k)$, how can we determine the parameters μ and Σ and the class prior?

- Simplest is maximum likelihood.

- Given
code

$t_n =$

- Assume

with the same covariance, but different mean.

- Denote the prior probability $p(\mathcal{C}_1) = \pi$, and $p(\mathcal{C}_2) = 1 - \pi$.

- Then

$$p(\mathbf{x}_n, \mathcal{C}_1) = p(\mathcal{C}_1)p(\mathbf{x}_n | \mathcal{C}_1) = \pi \mathcal{N}(\mathbf{x}_n | \mu_1, \Sigma)$$

$$p(\mathbf{x}_n, \mathcal{C}_2) = p(\mathcal{C}_2)p(\mathbf{x}_n | \mathcal{C}_2) = (1 - \pi) \mathcal{N}(\mathbf{x}_n | \mu_2, \Sigma)$$

Maximum Likelihood Solution



- Thus the likelihood for the whole data set \mathbf{X} and \mathbf{t} is given by

$$p(\mathbf{t} | \mathbf{X}; \pi, \mu_1, \Sigma_1, \mu_2, \Sigma_2) \\ = \prod_{n=1}^N [\pi \mathcal{N}(\mathbf{x}_n | \mu_1, \Sigma_1)]^{t_n} [(1 - \pi) \mathcal{N}(\mathbf{x}_n | \mu_2, \Sigma_2)]^{1-t_n}$$

- Maximize
- The log-likelihood

<https://eduassistpro.github.io>

Add WeChat [edu_assist_pro](#)

- which is maximal for (derive it)

$$\pi = \frac{1}{N} \sum_{n=1}^N t_n = \frac{N_1}{N} = \frac{N_1}{N_1 + N_2}$$

where N_1 is the number of data points in class \mathcal{C}_1 .



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Bayesian Approximation

Bayesian Logistic
Regression

Assignment Project Exam Help

- Similarly, we can maximise the likelihood $p(\mathbf{t}, \mathbf{X} | \pi, \mu_1, \mu_2, \Sigma)$ w.r.t. the means μ_1 and μ_2 , to get

<https://eduassistpro.github.io>

$$\mu_2 = \frac{1}{N_2} \sum_{n=1}^N (1 - t_n)$$

- For each class, this are the means of all input vect assigned to this class.

Add WeChat edu_assist_pro



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

active Reweighted
st Squares

approximation

Logistic
ression

Assignment Project Exam Help

- Finally, the log likelihood $\ln p(\mathbf{t}, \mathbf{X} | \pi, \mu_1, \mu_2, \Sigma)$ can be
ma

<https://eduassistpro.github.io>

$$\mathbf{S}_k = \frac{1}{N_k} \sum_{n \in \mathcal{C}_k} (\mathbf{x}_n - \mu_k)(\mathbf{x}_n$$

Add WeChat edu_assist_pro



- Assume the input space consists of discrete features, in the simplest case $x_i \in \{0, 1\}$.

- For a D -dimensional input space, a general distribution would be represented by a table with 2^D entries.

- To
ind

- Gro

- The Naïve Bayes assumption is that, given the class k , the features are independent of each other:

$$\begin{aligned} p(\mathbf{x} | C_k) &= \prod_{i=1}^D p(x_i | C_k) \\ &= \prod_{i=1}^D \mu_{ki}^{x_i} (1 - \mu_{ki})^{1-x_i} \end{aligned}$$



- With the naïve Bayes

$$p(\mathbf{x} | \mathcal{C}_k) = \prod_{i=1}^D \mu_{ki}^{x_i} (1 - \mu_{ki})^{1-x_i}$$

- we can express

$$p(\mathcal{C}_k | \mathbf{x}) = \frac{p(\mathbf{x} | \mathcal{C}_k)p(\mathcal{C}_k)}{\sum_j p(\mathbf{x} | \mathcal{C}_j)p(\mathcal{C}_j)} = \frac{p(\mathcal{C}_k) \prod_{i=1}^D \mu_{ki}^{x_i} (1 - \mu_{ki})^{1-x_i}}{\sum_j p(\mathcal{C}_j) \prod_{i=1}^D \mu_{ji}^{x_i} (1 - \mu_{ji})^{1-x_i}}$$

- as a linear function of the x_i

$$a_k(\mathbf{x}) = \sum_{i=1}^D \{x_i \ln \mu_{ki} + (1 - x_i) \ln(1 - \mu_{ki})\} + \ln p(\mathcal{C}_k).$$

Three Models for Decision Problems



In increasing order of complexity

- Find a discriminant function $f(\mathbf{x})$ which maps each input directly onto a class label.

- Discriminative Models

①

②

<https://eduassistpro.github.io>

- Generative Models

③

Solve the inference problem of determining the class-conditional probabilities $p(\mathbf{x} | C_k)$

④

Also, infer the prior class probabilities

⑤

Use Bayes' theorem to find the posterior $p(C_k | \mathbf{x})$.

⑥

Alternatively, model the joint distribution $p(\mathbf{x}, C_k)$ directly.

⑦

Use decision theory to assign each new \mathbf{x} to one of the classes.

Probabilistic Generative Models

Continuous Input

Discrete Features

Probabilistic Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Bayesian Approximation

Logistic
Regression

Add WeChat edu_assist_pro



- **Discriminative** training: learn only to discriminate between the classes.

- Maximise a likelihood function defined through the conditional distribution $p(C_k | \mathbf{x})$ directly.

- Ty

- As we be b
class-conditional density assumptions $p(\mathbf{x} | C_k)$ poorly approximate the true distributions.

- But: discriminative models can not create syn
as $p(\mathbf{x})$ is not modelled.

- As an aside: *certain theoretical analyses show that generative models converge faster to their — albeit worse — asymptotic classification performance and are superior in some regimes.*



Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

Original Input versus Feature Space



- So far in classification, we used direct input \mathbf{x} .
- All classification algorithms work also if we first apply a fixed nonlinear transformation of the inputs using a vector of basis functions $\phi(\mathbf{x})$.
- Example: Use two Gaussian basis functions centered at the \mathbf{g}



Original Input versus Feature Space



- Linear decision boundaries in the feature space generally correspond to nonlinear boundaries in the input space.
- Classes which are NOT linearly separable in the input space may become linearly separable in the feature space:



- If classes overlap in input space, they will also overlap in feature space — nonlinear features $\phi(\mathbf{x})$ can not remove the overlap; but they may increase it.



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Bayesian Approximation

Bayesian Logistic
Regression

Assignment Project Exam Help

- Fixed basis functions do not adapt to the data and therefore have important limitations (see discussion in Lin
- Un eas instead of the original input space.
- Some applications use fixed features success avoiding the limitations.
- We will therefore use ϕ instead of \mathbf{x} fro

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro



- Two classes where the posterior of class \mathcal{C}_1 is a logistic sigmoid $\sigma(\cdot)$ acting on a linear function of the input:

$$p(\mathcal{C}_1 | \phi) = y(\phi) = \sigma(\mathbf{w}^T \phi)$$

- $p(\mathcal{C}$
- Mo
spa
- Compare this to fitting two Gaussians, which has a quadratic number of parameters in M :

$$\underbrace{2M}_{\text{means}} + \underbrace{M(M+1)/2}_{\text{shared covariance}}$$

- For larger M , the logistic regression model has a clear advantage.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

active Reweighted
st Squares

approximation

Logistic
ression

- Determine the parameter via maximum likelihood for data $(\phi_n, t_n), n = 1, \dots, N$ where $\phi_n = \phi(\mathbf{x}_n)$. The class membership is coded as $t_n \in \{0, 1\}$.

- Likelihood function

<https://eduassistpro.github.io>

where $y_n = p(C_1 | \phi_n)$.

- Error function: negative log likelihood resulting in cross-entropy error function

$$E(\mathbf{w}) = -\ln p(\mathbf{t} | \mathbf{w}) = -\sum_{n=1}^N \{t_n \ln y_n + (1 - t_n) \ln(1 - y_n)\}$$



- Error function (cross-entropy loss)

$$L(\mathbf{w}) = - \sum_{n=1}^N \{ t_n \ln y_n + (1 - t_n) \ln (1 - y_n) \}$$

- y_n

- We
rule

<https://eduassistpro.github.io>

$$\nabla E(\mathbf{w}) = \sum_{n=1}^N (y_n - t_n)$$


Add WeChat edu_assist_pro

- for each data point error is product of deviation $y_n - t_n$ and basis function ϕ_n .
- We can now use gradient descent.
- We may easily modify this to reduce over-fitting by using regularised error or MAP (how?).




- Given a continuous distribution $p(x)$ which is not Gaussian, can we approximate it by a Gaussian $q(x)$?

- Need to find a mode of $p(x)$. Try to find a Gaussian with the same mode:



p.d.f. of :
Non-Gaussian (yellow) and
Gaussian approximation (red).



negative log p.d.f. of :
Non-Gaussian (yellow) and
Gaussian approximation. (red).



- Cheap and nasty but sometimes effective.
- Assume $p(x)$ can be written as

$$p(z) = \frac{1}{Z} f(z)$$

- We want to approximate $p(z)$ with a Gaussian distribution $q(z)$.
- A mode of $p(z)$ is at a point z_0 where p'
- Taylor expansion of $\ln f(z)$ at z_0

$$\ln f(z) \simeq \ln f(z_0) - \frac{1}{2} A (z - z_0)^2$$

where

$$A = - \frac{d^2}{dz^2} \ln f(z) \big|_{z=z_0}$$



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Laplace Approximation

Logistic
Regression

- Exponentiating

$$\ln f(z) \simeq \ln f(z_0) - \frac{1}{2} A (z - z_0)^2$$

- we get

<https://eduassistpro.github.io>

- And after normalisation we get the Laplace app

Add WeChat edu_assist_pro

$$q(z) = \left(\frac{A}{2\pi}\right)^{1/2} \exp\left\{-\frac{A}{2}(z - z_0)^2\right\}$$

- Only defined for precision $A > 0$ as only then $p(z)$ has a maximum.



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Laplace Approximation

Logistic
Regression

- Approximate $p(\mathbf{z})$ for $\mathbf{z} \in \mathbb{R}^M$

Assignment Project Exam Help

- we get the Taylor expansion

<https://eduassistpro.github.io>

- where the Hessian \mathbf{A} is defined as

Add WeChat [edu_assist_pro](https://eduassistpro.github.io)

- The Laplace approximation of $p(\mathbf{z})$ is th

$$q(\mathbf{z}) \propto \exp \left\{ -\frac{1}{2}(\mathbf{z} - \mathbf{z}_0)^T \mathbf{A}(\mathbf{z} - \mathbf{z}_0) \right\}$$
$$\Rightarrow q(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{z}_0, \mathbf{A}^{-1})$$



Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

active Reweighted
st Squares

Approximation

st Logistic
ression

Assignment Project Exam Help

- Exact Bayesian inference for the logistic regression is intractable.

- Wh
and l
sig

- Eva

- Therefore we will use the Laplace approximation

- The predictive distribution remains intractable
the Laplace approximation to the posterior distribution
it can be approximated.

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro



Assignment Project Exam Help

- Assume a Gaussian prior

$$p(\mathbf{w}) = \mathcal{N}(\mathbf{w} | \mathbf{m}_0, \mathbf{S}_0)$$

for fi

- Hy con
- For a set of training data (\mathbf{x}_n, t_n) , where posterior is given by

$$p(\mathbf{w} | \mathbf{t}) \propto p(\mathbf{w})p(\mathbf{t} | \mathbf{w})$$

where $\mathbf{t} = (t_1, \dots, t_N)^T$.

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro



- Using our previous result for the cross-entropy function

$$E(\mathbf{w}) = -\ln p(\mathbf{t} | \mathbf{w}) = - \sum_{n=1}^N \{t_n \ln y_n + (1 - t_n) \ln(1 - y_n)\}$$

we can

<https://eduassistpro.github.io>

using the notation $y_n = \sigma(\mathbf{w}^T \phi_n)$ as

$$\begin{aligned} \ln p(\mathbf{w} | \mathbf{t}) = & - \frac{1}{2} (\mathbf{w} - \mathbf{m}_0)^T \mathbf{S}_0^{-1} (\mathbf{w} \\ & + \sum_{n=1}^N \{t_n \ln y_n + (1 - t_n) \ln(1 - y_n)\} \end{aligned}$$

Add WeChat edu_assist_pro



Probabilistic Generative Models

Continuous Input

Discrete Features

Probabilistic Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Bayesian Approximation

Bayesian Logistic
Regression

- To obtain a Gaussian approximation to

$$\ln p(\mathbf{w} | \mathbf{t}) = -\frac{1}{2}(\mathbf{w} - \mathbf{m}_0)^T \mathbf{S}_0^{-1}(\mathbf{w} - \mathbf{m}_0) + \sum_{n=1}^N \{t_n \ln y_n + (1 - t_n) \ln(1 - y_n)\}$$

- 1 <https://eduassistpro.github.io>

nonlinear function in \mathbf{w} because $y_n = \sigma(\mathbf{w}^T \mathbf{x}_n)$

- 2 Calculate the second derivative of the negative log-likelihood to get the inverse covariance of the Laplace approximation

$$\mathbf{S}_N = -\nabla \nabla \ln p(\mathbf{w} | \mathbf{t}) = \mathbf{S}_0^{-1} + \sum_{n=1}^N \mathbf{x}_n \mathbf{x}_n^T y_n (1 - y_n)$$

Nowadays the gradient and Hessian would be computed with automatic differentiation; one need only implement $\ln p(\mathbf{w} | \mathbf{t})$.



Assignment Project Exam Help

- The approximated Gaussian (via Laplace approximation) of the posterior distribution is now

<https://eduassistpro.github.io>

wh

$$S_N = -\nabla \nabla \ln p(\mathbf{w} | \mathbf{t}) = S_0^{-1} + \sum_{n=1}^N$$

Add WeChat edu_assist_pro

Probabilistic Generative
Models

Continuous Input

Discrete Features

Probabilistic
Discriminative Models

Logistic Regression

Active Reweighted
Least Squares

Laplace Approximation

Bayesian Logistic
Regression