



Outlines

Overview

Introduction

Linear Algebra

Probability

Linear Regression

Linear Regression

Linear Classification 1

Linear Classification 2

Kernel Methods

Sparse Kernel Methods

Structure Models and EM 1

Structure Models and EM 2

Neural Networks 1

Neural Networks 2

Deep Component Analysis

Generators

Graphical Models 1

Graphical Models 2

Graphical Models 3

Sampling

Sequential Data 1

Sequential Data 2

Statistical Machine Learning

Assignment Project Exam Help

Christian Walder

<https://eduassistpro.github.io>

College of Engineering and Computer Science
The Australian National University

Add WeChat edu_assist_pro

Canberra

Semester One, 2020.

(Many figures from C. M. Bishop, "Pattern Recognition and Machine Learning")



Assignment Project Exam Help

Part IX

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis



Assignment Project Exam Help

Empirical observations - pre 2006:

- Deep architectures get stuck in local minima or plateaus
- As a
- Har
- 1 or 2 hidden layers seem to perform better
- 2006: Unsupervised pre-training of each layer possible
 - Usually based on auto-encoders (tomorrow)
 - Similar in spirit to PCA (today's lecture)

Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

<https://eduassistpro.github.io>
Add WeChat edu_assist_pr



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

Given a dataset of numerical features:

- Lo
- Hig
- Dim
 - Enables visualisation
 - The new basis may yield insights
 - Aside: can simplify/speed up subsequent regression

<https://eduassistpro.github.io>
Add WeChat edu_assist_pro



Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

- Given are pairs of data $x_i \in \mathcal{X}$ and target t_i in the form (x_i, t_i) , where $i = 1 \dots N$.
- Learn a mapping between the data X and the target t which generalises well to new data.

Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

- Given only the data $x_i \in \mathcal{X}$.
- Discover (=learn) some interesting structure inherent in the data X .



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

- Given only the data $x_i \in \mathcal{X}$.
- Discover (=learn) some interesting structure inherent in the data.

Testing - Supervised versus Unsupervised Learning

Statistical Machine Learning

© 2020

Ong & Walder & Webers
Data61 \ CSIRO
The Australian National University



Motivation

Eigenvectors


Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help



<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

Recall: Fisher's Linear Discriminant



Motivation

Eigenvectors


Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Samples from two classes in a two-dimensional input space and their histogram when projected to two different one-dimensional spaces.





Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

- Every square matrix $A \in \mathbb{R}^{n \times n}$ has an Eigenvector decomposition.

$$Ax = \lambda x$$

wh

- Exa

<https://eduassistpro.github.io>

$$\begin{bmatrix} -1 & 0 \\ 0 & 1 \end{bmatrix}$$

Add WeChat edu_assist_pr

$$\lambda \in \{-1, 1\}$$
$$x = \left\{ \begin{bmatrix} 1 \\ 1 \end{bmatrix}, \begin{bmatrix} -1 \\ 1 \end{bmatrix} \right\}$$



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

- How many eigenvalue/eigenvector pairs?

-

is eq

$$(A - \lambda I)x = 0$$

- Has only non-trivial solution for $\det \{A - \lambda I\} = 0$
- polynomial of n th order; at most n distinct

<https://eduassistpro.github.io>
Add WeChat: edu_assist_pro



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

- How can we enforce real eigenvalues?

- Let'

- Tra

$n \quad n$

<https://eduassistpro.github.io>

$$5 + i6 \quad 7 + i8 \quad = \quad 3 - i4 \quad 7$$

- Denote the complex conjugate of a complex number λ .

Add WeChat edu_assist_pro



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- How can we enforce real eigenvalues?
- Let's assume $A \in \mathbb{C}^{n \times n}$, Hermitian ($A^H = A$).

- Calculate

$$x^H A x = \lambda x^H x$$

for an eigenvector $x \in \mathbb{C}^n$ of A .

- An

<https://eduassistpro.github.io>

$$= (x^H A x)^H \quad (\text{reverse order})$$

$$= (\lambda x^H x)^H$$

$$= \bar{\lambda} x^H x$$

Add WeChat [edu_assist_pro](https://eduassistpro.github.io)

- and therefore

$$\lambda = \bar{\lambda} \quad (\lambda \text{ is real}).$$

- If A is Hermitian, then all eigenvalues are real.
- Special case: If A has only real entries and is symmetric, then all eigenvalues are real.



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Assignment Project Exam Help

Every matrix
three matrices

$n \times p$

where U

$U^T U = I$ and $V^T V = I$), and $\Sigma \in \mathbb{R}^{n \times p}$ has n
numbers on the diagonal.

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro



Assignment Project Exam Help

$N = 10$


<https://eduassistpro.github.io>

$$t_i \in \mathbb{R} \quad i = 1, \dots, N$$

$$y(x, \mathbf{w}) = w_1 x + w_0$$

$$\mathbf{x} \equiv \begin{bmatrix} x & 1 \end{bmatrix}$$

$$\mathbf{w}^* = (X^T X)^{-1} X^T \mathbf{t}$$



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- Assume a full rank symmetric real matrix A .
- Then $A = U^T \Lambda U$ where
- Λ is a diagonal matrix with real eigenvalues
- U is

$$A^{-1} = (U^T \Lambda U)^{-1}$$

$$= U^{-1} \Lambda^{-1} U^{-T}$$

inverse of

$$= U^T \Lambda^{-1} U$$

- The inverse of a diagonal matrix is the inverse of its elements.

Dimensionality Reduction



Motivation

Eigenvectors


Singular Value
Decomposition

Principal Component
Analysis

Principal Component
Analysis (PCA)

Independent Component
Analysis

- Main goal of Principal Component Analysis: **dimensionality reduction**
- Many applications in visualisation, feature extraction, signal processing, data compression, ...
- Example: Use hand-written digits (binary data) and place the and t
- Dat
- But rotation angle).
- FYI only: this manifold is not linear and requires bl edge models like capsule networks (Hinton 2015) can locally approximate with PCA.



Principal Component Analysis (PCA)



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)


Independent Component
Analysis

- Idea: Linearly project the data points onto a lower dimensional subspace such that
 - the variance of the projected data is maximised, or
 - the distortion error from the projection is minimised
- Both formulations lead to the same result.
- Ne

prin

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr



Principal Component Analysis (PCA)

Statistical Machine
Learning

© 2020

Ong & Walder & Webers
Data61 \ CSIRO
The Australian National
University



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis


Principal Component
Analysis (PCA)

Independent Component
Analysis

- Given N observations $\mathbf{x}_n \in \mathbb{R}^D$, $n = 1, \dots, N$.
- Project onto a space with dimensionality $M < D$ while maximising the variance.
- More advanced : How to calculate M from the data.

The
Co
vec

<https://eduassistpro.github.io>



Add WeChat: edu_assist_pro



- Each data point \mathbf{x}_n is then projected onto a scalar value $\mathbf{u}_1^T \mathbf{x}_n$.

- The mean of the projected data is $\mathbf{u}_1^T \bar{\mathbf{x}}$ where $\bar{\mathbf{x}}$ is the sample mean

N

- The

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

with the covariance matrix

$$\mathbf{S} = \frac{1}{N} \sum_{n=1}^N (\mathbf{x}_n - \bar{\mathbf{x}})(\mathbf{x}_n - \bar{\mathbf{x}})^T.$$



Assignment Project Exam Help

Maximising $\mathbf{u}_1^T \mathbf{S} \mathbf{u}_1$ under the constraint $\mathbf{u}_1^T \mathbf{u}_1 = 1$ (why do we need to bound \mathbf{u}_1 ?) leads to the Lagrange equation

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis



Assignment Project Exam Help

Maximising $\mathbf{u}_1^T \mathbf{S} \mathbf{u}_1$ under the constraint $\mathbf{u}_1^T \mathbf{u}_1 = 1$ (why do we need to bound \mathbf{u}_1 ?) leads to the Lagrange equation

Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

whi <https://eduassistpro.github.io>

Add WeChat edu_assist_pr



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

Maximising $\mathbf{u}_1^T \mathbf{S} \mathbf{u}_1$ under the constraint $\mathbf{u}_1^T \mathbf{u}_1 = 1$ (why do we need to bound \mathbf{u}_1 ?) leads to the Lagrange equation

whi
wit

λ_1

$$\mathbf{S} \mathbf{u}_1 = \lambda_1 \mathbf{u}_1.$$

- The variance is then $\mathbf{u}_1^T \mathbf{S} \mathbf{u}_1 = \lambda_1$.
- Variance is maximised if \mathbf{u}_1 is the eigenv covariance \mathbf{S} with the largest eigenvalue.

Add WeChat edu_assist_pr



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

- Continue maximising the variance amongst all possible directions orthogonal to those already considered.
- The for v_i eig corresponding to the M largest eigenvalues $\lambda_1, \dots, \lambda_M$.
- Is this subspace always uniquely defined?
- Not if $\lambda_M = \lambda_{M+1}$.

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

PCA - Minimise Distortion Error



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- The distortion between data points \mathbf{x}_n and their projection

$\tilde{\mathbf{x}}_n$

$$J = \frac{1}{N} \sum_{n=1}^N \|\mathbf{x}_n - \tilde{\mathbf{x}}_n\|^2$$

is mi

- The

<https://eduassistpro.github.io>

$$J = \sum_{i=M+1}^D \lambda_i$$

where $\lambda_i, i = M + 1, \dots, D$ are the **smalle**
the covariance matrix \mathbf{S} .

- In signal processing we speak of the **signal space** (principal subspace) and the **noise space** (orthogonal to the principal subspace).

Add WeChat edu_assist_pr



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- The eigenvectors of the covariance matrix are elements of the original vector space $u_i \in \mathbb{R}^D$.

- If the input data are images, the eigenvectors are also images.

Assignment Project Exam Help

<https://eduassistpro.github.io>



Add WeChat edu_assist_pr

The mean and the first four eigenvectors u_1, \dots, u_4 of a set of handwritten digits of 'three'.

Blue corresponds to positive values, white is zero and yellow corresponds to negative values.



Motivation

Eigenvectors


Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- The eigenvalues of the covariance matrix express the variance of the data set in the direction of the corresponding eigenvectors.



Plot of the eigenvalue spectrum for the digits of three data set.



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)


Independent Component
Analysis

- The sum of the eigenvalues of the covariance matrix of the discarded directions express the distortion error.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr



Plot of the distortion error versus the number of dimension of the subspace considered for projection.



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- The approximated data vector $\tilde{\mathbf{x}}_n$ can be written in the form

$$\tilde{\mathbf{x}}_n = \bar{\mathbf{x}} + \sum_{i=1}^M (\mathbf{u}_i^T (\mathbf{x}_n - \bar{\mathbf{x}})) \mathbf{u}_i$$

- Co
- Co

<https://eduassistpro.github.io>



Reconstruction of an image retaining M principal components.



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- Standardise certain features of a data set (for instance as a preprocessing step to subsequent algorithms expecting these features).

- Usually, individual standardisation: each variable (dimension) has zero mean and unit variance. But vari

- PC
- the

- Wri

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

$$S\mathbf{U} = \mathbf{U}\mathbf{L}$$

where \mathbf{L} is the diagonal matrix of (positive!) ei

- Transform the original data by

$$\mathbf{y}_n = \mathbf{L}^{-1/2} \mathbf{U}^T (\mathbf{x}_n - \bar{\mathbf{x}})$$

- The set $\{\mathbf{y}_n\}$ has mean zero and covariance given by the identity.



Motivation

Eigenvectors

Singular Value Decomposition

Principal Component Analysis (PCA)

Principal Component Analysis (PCA)

Independent Component Analysis

- Transform the original data by

$$\mathbf{y}_n = \mathbf{L}^{-1/2} \mathbf{U}^T (\mathbf{x}_n - \bar{\mathbf{x}})$$

- Mean of the set $\{\mathbf{y}_n\}$

$$\frac{1}{N} \sum_{n=1}^N \mathbf{y}_n = \frac{1}{N} \sum_{n=1}^N \mathbf{L}^{-1/2} \mathbf{U}^T (\mathbf{x}_n - \bar{\mathbf{x}})$$

<https://eduassistpro.github.io>

- Covariance of the set $\{\mathbf{y}_n\}$

$$\begin{aligned} \frac{1}{N} \sum_{n=1}^N \mathbf{y}_n \mathbf{y}_n^T &= \frac{1}{N} \sum_{n=1}^N \mathbf{L}^{-1/2} \mathbf{U}^T (\mathbf{x}_n - \bar{\mathbf{x}}) (\mathbf{x}_n - \bar{\mathbf{x}})^T \mathbf{U} \mathbf{L}^{-1/2} \\ &= \mathbf{L}^{-1/2} \mathbf{U}^T \mathbf{S} \mathbf{U} \mathbf{L}^{-1/2} \\ &= \mathbf{L}^{-1/2} \mathbf{U}^T \mathbf{U} \mathbf{L} \mathbf{U}^T \mathbf{U} \mathbf{L}^{-1/2} \\ &= \mathbf{I} \end{aligned}$$


Add WeChat edu_assist_pro

PCA - The Effect of Whitening




- Compare standardising and whitening of a data set.


- (b) also shows the principal axis of the normalised data set plotted as red lines over the range $\pm \lambda_i^{1/2}$.



Original data
(note the different
axis).



Standardising to
zero mean and unit
variance.



Whitening to
achieve unit
covariance.

Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

Assignment Project Exam Help

- Kernel PCA

- Use $\Phi(x)$ as features, and express in terms of kernel matrix

-

- Pro

- Explicitly model latent variable $\mathbf{z} \sim \mathcal{N}(\mu, \sigma^2)$
- Mean value of observed variable is given by
- Conditional distribution of observed variable

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

$$\mathbf{x} \sim \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \mu, \sigma^2)$$

Independence versus Uncorrelatedness



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

dependent Component
analysis

- Independence

$$p(x_1, x_2) = p(x_1) p(x_2)$$

- Uncorrelatedness (defined via a zero covariance)

$$\mathbb{E}[x_1 x_2] - \mathbb{E}[x_1] \mathbb{E}[x_2] = 0$$

- Ind

- BU

- Exa

the set $\{(0, 1), (0, -1), (1, 0), (-1, 0)\}$.

- Then x_1 and x_2 are uncorrelated because

$$\mathbb{E}[x_1] = \mathbb{E}[x_2] = \mathbb{E}[x_1 x_2] = 0.$$

- But x_1 and x_2 are NOT independent

$$p(x_1 = 0, x_2 = -1) = \frac{1}{4}$$

$$p(x_1 = 0) p(x_2 = -1) = \frac{1}{2} \times \frac{1}{4}$$

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

Independent Component Analysis - Overview

Statistical Machine
Learning

© 2020

Ong & Walder & Webers
Data61 | CSIRO
The Australian National
University



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- Assume we have K signals and K recordings, each recording containing a mixture of the signals.

- 'Cocktail party' problem : K people speak at the same time in a room, and K microphones pickup a mixture of what they say.

- Give
mixture

<https://eduassistpro.github.io>

=

- Can we recover the original signals (Blind Source Separation)?
- Yes, under the assumption that
 - at most one of the signals is Gaussian distributed.
 - we don't care for the amplitude (including the sign).
 - we don't care for the order of the recovered signals.
 - we have at least as many observed mixtures as signals, the matrix \mathbf{A} has full rank and can be inverted.

Add WeChat edu_assist_pro



Motivation

Eigenvectors

Singular Value
Decomposition

Principal Component
Analysis (PCA)

Principal Component
Analysis (PCA)

Independent Component
Analysis

- Uncorrelated variables are not necessarily independent.
- ICA maximises the statistical independence of the estimated components.
- Fin

<https://eduassistpro.github.io>

are maximally independent.

- Several definitions for statistical independence
- Central Limit Theorem. The distribution of a sum of independent random variables tends toward a normal distribution (under certain conditions).
- FastICA algorithm.

Add WeChat edu_assist_pro