

15-213/513/613: Assignment Project Exam Help

<https://eduassistpro.github.io/>

Kashish & Ishita Add WeChat edu_assist_pro

Final Exam Logistics

- Cheat sheets - 2 double sided 8.5 x 11 in.
 - Join Zoom, turn on video AND microphone.
 - Show ID and eo.
 - You will receive <https://eduassistpro.github.io/> to the zoom call, the exam time, and more details soon.
- Add WeChat edu_assist_pro
- 8 categories of questions:
 - Malloc, VM, Processes, Signals, IO, Threads, ThreadSync, Multiple Choice (pre-midterm)

Virtual Memory

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Virtual Memory

Virtual Address - 18 Bits

Physical Address - 12 Bits

Page Size - 512 Bytes

TLB is 8-way set associative

Cache is 2-way set associative

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

TLB			
Index	Tag	PPN	Valid
0	55	6	0
	48	F	1
	00	A	0
	32	9	1
	6A	3	1
	56	1	0
	60	4	1
	78	9	0
1	71	5	1
	31	A	1
	53	F	0
	87	8	0
	51	D	0
	39	E	1
	43	B	0
	73	2	1

Final S-02 (#5)

Lecture 18: VM - Systems

2-way Set Associative Cache												
Index	Tag	Valid	Byte 0	Byte 1	Byte 2	Byte 3	Tag	Valid	Byte 0	Byte 1	Byte 2	Byte 3
0	7A	1	09	EE	12	64	00	0	99	04	03	48
1	02	0	60	17	18	19	7F	1	FF	BC	0B	37
2	55	1	30	EB	C2	0D	0B	0	8F	E2	05	BD
3	07	1	03	04	05	06	5D	1	7A	08	03	22

Virtual Memory


Label the following:

- (A) VPO: Virtual Page Offset
- (B) VPN: Virtual Page Number
- (C) TLBI: TLB Invalidate
- (D) TLBT: TLB Tag

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Virtual Memory

Label the following:

- (A) VPO: Virtual Page Offset
 (B) VPN: Virtual Page Number
 (C) TLBI: TLB Ind

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Cache

17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

B	B	B	B	B	B	B	B	B	A	A	A	A	A	A	A	A	A
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

TLBI

Virtual Memory

Label the following:

- (A) VPO: Virtual Page Offset
 (B) VPN: Virtual Page Number
 (C) TLBI: TLB Ind
 (D) TLBT: TLB Ta

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

B	B	B	B	B	B	B	B	B	A	A	A	A	A	A	A	A	A
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

TLBT

TLBI

Virtual Memory


Label the following:

- (A) PPO: Physical Page Offset
- (B) PPN: Physical Page Number
- (C) CO: Cache Of
- (D) CI: Cache Ind
- (E) CT: Cache Tag

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Virtual Memory


Label the following:

- (A) PPO: Physical Page Offset - Same as VPO
(B) PPN: Physical Page Number - Everything Else
(C) CO: Cache Of

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Virtual Memory


Label the following:

- (A) *PPO*: Physical Page Offset - Same as VPO
- (B) *PPN*: Physical Page Number - Everything Else
- (C) *CO*: Cache Of
- (D) *CI*: Cache Ind

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro




Virtual Memory

Label the following:

- (A) PPO: Physical Page Offset - Same as VPO
- (B) PPN: Physical Page Number - Everything Else
- (C) CO: Cache Of
- (D) CI: Cache Ind

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Virtual Memory


Label the following:

- (A) PPO: Physical Page Offset - Same as VPO
 (B) PPN: Physical Page Number - Everything Else
 (C) CO: Cache Of
 (D) CI: Cache Ind
 (E) CT: Cache Tag Everything

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation

1 = 0001

A =

1

4 = 0100

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	0	1	0	1	0	0	1	1	1	1	1	0	1	0	0

Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation
2. Extract Information

VPN: 0

BT: 0x??

TLB Hit: Y/N? Page Fault: : 0x??

Add WeChat edu_assist_pro

17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	0	1	0	1	0	0	1	1	1	1	1	0	1	0	0

Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation
2. Extract Information

VPN: 0

BT: 0x??

TLB Hit: Y/N?

Page Fault:

: 0x??

Add WeChat edu_assist_pro

17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	0	1	0	1	0	0	1	1	1	1	1	0	1	0	0

Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation
2. Extract Information

VPN: 0

BT: 0x??

TLB Hit: Y/N?

Page Fault:

: 0x??

17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	0	1	0	1	0	0	1	1	1	1	1	0	1	0	0

Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation
2. Extract Information

VPN: 0

<https://eduassistpro.github.io/>

BT: 0x6A

TLB Hit: Y/N? Page Fault: : 0x??

Add WeChat edu_assist_pro

TLB			
Index	Tag	PPN	Valid
0	55	6	0
	48	F	1
	00	A	0
	32	9	1
	6A	3	1
	56	1	0
	60	4	1
	78	9	0
1	71	5	1
	31	A	1
	53	F	0
	87	8	0
	51	D	0
	39	E	1
	43	B	0
	73	2	1

17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

0	1	1	0	1	0	1	0	0	1	1	1	1	1	0	1	0	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation
2. Extract Information

VPN: 0

TLB Hit: Y! Page Fault: Y

BT: 0x6A

x??

TLB			
Index	Tag	PPN	Valid
0	55	6	0
	48	F	1
	00	A	0
	32	9	1
	6A	3	1
	56	1	0
	60	4	1
	78	9	0
1	71	5	1
	31	A	1
	53	F	0
	87	8	0
	51	D	0
	39	E	1
	43	B	0
	73	2	1

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

0	1	1	0	1	0	1	0	0	1	1	1	1	1	1	0	1	0	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation
2. Extract Information

VPN: 0

TLB Hit: Y! Page Fault: ??

BT: 0x6A

TLB			
Index	Tag	PPN	Valid
0	55	6	0
	48	F	1
	00	A	0
	32	9	1
	6A	3	1
	56	1	0
	60	4	1
	78	9	0
1	71	5	1
	31	A	1
	53	F	0
	87	8	0
	51	D	0
	39	E	1
	43	B	0
	73	2	1

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

0	1	1	0	1	0	1	0	0	1	1	1	1	1	0	1	0	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation
2. Extract Information

VPN: 0

<https://eduassistpro.github.io/>

BT: 0x6A

TLB Hit: Y! Page Fault: 3

Add WeChat edu_assist_pro

TLB			
Index	Tag	PPN	Valid
0	55	6	0
	48	F	1
	00	A	0
	32	9	1
	6A	3	1
	56	1	0
	60	4	1
	78	9	0
1	71	5	1
	31	A	1
	53	F	0
	87	8	0
	51	D	0
	39	E	1
	43	B	0
	73	2	1

17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

0	1	1	0	1	0	1	0	0	1	1	1	1	1	0	1	0	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Virtual Memory

Now to the actual question!

Q) Translate the following address: 0x1A9F4

1. Write down bit representation

2. Extract Information

3. Put it all together:

4

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	1	1	1	0	1	0	0

Virtual Memory

Q) What is the value of the address?

Assignment Project Exam Help

CO: 0x?? CI: 0x?? /N? Value:0x??

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	1	1	1	0	1	0	0

Virtual Memory

Q) What is the value of the address?

1. Extract more information

Assignment Project Exam Help

CO: 0x00 CI: 0x?? /N? Value: 0x??

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	1	1	1	0	1	0	0

Virtual Memory

Q) What is the value of the address?

1. Extract more information

Assignment Project Exam Help

CO: 0x00 CI: 0x01

/N? Value:0x??

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	1	1	1	0	1	0	0

Virtual Memory

Q) What is the value of the address?

1. Extract more information

2. Go to Cache Table

CO: 0x00 CI: 0x01

/N? Value: 0x??

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	1	1	1	0	1	0	0

Virtual Memory

Q) What is the value of the address?

1. Extract more information

2. Go to Cache Table

CO: 0x00 CI: 0x01

Value: 0x??

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	1	1	1	0	1	0	0

Virtual Memory

Q) What is the value of the address?

1. Extract more information
2. Go to Cache Table

CO: 0x00 CI: 0x01

Value: 0xFF

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	1	1	1	0	1	0	0

Virtual Memory

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Threads

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Threads

Given this code, what variables do you think are shared?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Threads (Contd.)

Which variables can be shared by multiple threads simultaneously in this program?

Assignment Project Exam Help

- (A) i
- (B) balance
- (C) instance
- (D) cnt
- (E) None of the above

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Threads (Contd.)

Which variables can be shared by multiple threads simultaneously in this program?

Assignment Project Exam Help

- (A) i
 - (B) balance
 - (C) instance
 - (D) cnt
 - (E) None of the above
- <https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Answer: B

Threads (Contd.)

(A) i is a local variable so it isn't shared.

(B) balance is a global variable so it's shared.

(C) cnt is a static variable, so it retains its value even outside the scope in which it was defined, so it isn't shared.

(D) cnt is a static variable, so it retains its value even outside the scope in which it was defined, so it isn't shared.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Threads (Contd.)

Given the withdraw() and deposit() functions, what are the possible outputs? (balance = 10 initially)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
int deposit(int amt) {  
    balance = balance + amt;  
    sleep(2);  
    return 0;  
}
```

Threads (Contd.)

What can be the value of balance?

- (A) balance: 0
- (B) balance: -3
- (C) balance: 1
- (D) balance: 6
- (E) balance: 17
- (F) balance: 4

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Threads (Contd.)

What can be printed at the indicated line?

- Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro
- (A) balance: 0
 - (B) balance: -3
 - (C) balance: 1
 - (D) balance: 6
 - (E) balance: 17
 - (F) balance: 4

Answer: ABDF

Threads (Contd.)

The following is one interleaving that leads to output 0:

- Thread A executes deposit(4), balance = 14
- Thread B executes deposit(4), balance = 8
- Thread B executes deposit(4), balance = 11
- Thread A executes withdraw(4), balance = 0
- Thread B executes withdraw(7), balance = 0

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WhatsApp [edu_assist_pro](https://eduassistpro.github.io/)

Threads (Contd.)

The following is one interleaving that leads to output -3:

- Thread A executes `deposit(4)`, `balance = 14`
- Thread A starts `withdraw(11)` and enters the `if`
- Thread B executes `withdraw(8)`
- Thread A computes RHS for `withdraw(11) = -3`
- Thread B executes `deposit(3)`, `balance = 11`
- Thread A completes `withdraw(11)`, `balance = -3`
- Thread B executes `withdraw(7)`, `balance = -3`

Threads (Contd.)

The following is one interleaving that leads to output 6:

- Thread A executes deposit(4), balance = 14
- Thread A e balance = 3
- Thread B e
- Thread B executes deposit(2), balance = 6
- Thread B executes withdraw(7), balance = 6

Threads (Contd.)

The following is one interleaving that leads to output 4:

- Thread B executes withdraw(6), balance = 4
- Thread A executes deposit(8), balance = 8
- Thread A executes deposit(8), balance = 8
- Thread B executes deposit(7), balance = 11
- Thread B executes withdraw(7), balance = 4

Synchronization

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Thread Synchronization

How many potential deadlock situations are present?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
sem_t add_sem;  
sem_t rem_sem;
```

Thread Synchronization (Contd.)

Situation 1:

tid1 executes $V(&add_sem)$ and $V(&rem_sem)$. Then, tid2 executes $P(&add_sem)$. In this situation, tid1 can't execute $P(&rem_sem)$ since the value of add_sem is 0. As a result, there's a deadlock, since after the execution of thread 2, thread 1 can't resume. Thus, there's a deadlock.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Thread Synchronization (Contd.)

Situation 2:

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

tid1 executes V(&add_sem) and V(&rem_sem). Then,
tid2 executes P(&add_sem). Th P(&add_sem)
but it can't since add_sem has value 1. tid1 wants
to execute P(&rem_sem) but it can't since rem_sem has
value 0. Thus, there's a deadlock.

Thread Synchronization (Contd.)

For lengths 0-6, indicate the number of outcomes of that length that can be produced.

```
sem_t add_sem;  
sem_t rem_sem;
```

```
void add() {  
    printf("A");  
}
```

```
void remove() {  
    printf("R");  
}
```

```
void *thread2(void *vargp) {  
    P(&rem_sem);  
    P(&add_sem);  
  
    add();  
    remove();  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Thread Synchronization (Contd.)

Response length 0: None

Assignment Project Exam Help

This is because at least 'R' must get printed due to the
a deadlock, remove() in
before any that state
sort of deadlock from the above

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Thread Synchronization (Contd.)

Response length 1: 1 (R)

Assignment Project Exam Help

In the deadlock scenario 2, where thread 1 executes `P(&add_sem)` and neither of the three print statements are executed in point. The only print statement that gets executed is due to the call to `remove()` before the calls to `P()` in thread 1.

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Thread Synchronization (Contd.)

Response length 2: None

We noticed that 'R' due to the call to remove() in
the cleanup() gets pri
notice that it's not her print
statement to get executed

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Thread Synchronization (Contd.)

Response length 3: 2 (RAR, ARR)

Assignment Project Exam Help

This happens due to deadlock scenario 1 above, where
 thread2() execute
 after execute P(&add_

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- RAR: Thread 1 executes remove(), followed by thread 2 executing add() and remove().
- ARR: Thread 2 executes add(), followed by any ordering of the 2 calls to remove() by threads 1 and 2.

Thread Synchronization (Contd.)

Response length 4: None

Assignment Project Exam Help
For any length greater than 3, it means that there was no
operation and lock, since the thread could get
which the thread could get
would run to completion as well. edu_assist_pro
length greater than 3 and less than 6 are possible.

<https://eduassistpro.github.io/>
Add WeChat: edu_assist_pro

Thread Synchronization (Contd.)

Response length 5: None

For any length greater than 3, it means that there was no
deadlock, since the thread could get the lock and finish its
execution. It could get the lock and finish its execution
before the other thread starts. For response lengths of
length greater than 3 and less than 6 are possible.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Thread Synchronization (Contd.)

Response length 6: 4

(RARAAR, RARARA, RAARRA, RAARAR)

Assignment Project Exam Help

Since there are n

calls to V() and P()

and 'A' definitely get printed. After calls to V() get

executed by thread 1 and then, thread 2 can execute its

calls to P(). After this, based on the interleavings

between the threads, there are 4 possible outputs.

<https://eduassistpro.github.io/>

Add WhatsApp [edu_assist_pro](https://eduassistpro.github.io/)

Thread Synchronization (Contd.)

- RARAAR: Thread 1 executes remove(), threads 1 and 2 execute the add() statements in any order, and then thread 2 executes remove().
- RARARA: Thread 1 executes add(), thread 2 executes add(), thread 1 executes remove(), thread 2 executes remove(), thread 1 executes add(), and thread 2 executes add().

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Thread Synchronization (Contd.)

- RAARRA: Thread 2 executes add(), threads 1 and 2 execute the remove() statements in any order, and then thread 1 executes add().
- RAARAR: Thread 1 executes remove() and add(), then thread 2 executes remove().

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Good luck!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Processes

1. Logical control flow
2. Private address space

<https://eduassistpro.github.io/>

Important system calls

1. Fork
2. Execve
3. Wait
4. Waitpid

Add WeChat edu_assist_pro

Processes

Draw a Process Graph!!!

Assignment Project Exam Help

(it does not have to be like mine)

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Processes

```
int main() {  
    int count = 1;  
    int pid1 = fork();  
    int pid2 = fork();  
  
    if(pid1 == 0)  
        count++;  
    else{  
        if(pid2 == 0)  
            count--;  
        else  
            count += 2;  
    }  
    printf("%d", count);  
}
```

What is printed?

Assignment Project Exam Help

Assume printf is atomic,
system calls

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Processes

```
int main() {  
    int count = 1;  
    int pid1 = fork();  
    int pid2 = fork();  
  
    if(pid1 == 0)  
        count++;  
    else{  
        if(pid2 == 0)  
            count--;  
        else  
            count += 2;  
    }  
    printf("%d", count);  
}
```

How many processes?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Processes

```
int main() {
    int count = 1;
    int pid1 = fork();
    int pid2 = fork();

    if(pid1 == 0)
        count++;
    else{
        if(pid2 == 0)
            count--;
        else
            count += 2;
    }
    printf("%d", count);
}
```

How many processes?

Assignment Project Exam Help

Parent: forks child

<https://eduassistpro.github.io/>

nd child each fork
child

Add WeChat edu_assist_pro
cesses

Processes

```
int main() {  
    int count = 1;  
    int pid1 = fork();  
    int pid2 = fork();  
  
    if(pid1 == 0)  
        count++;  
    else{  
        if(pid2 == 0)  
            count--;  
        else  
            count += 2;  
    }  
    printf("%d", count);  
}
```

What does the process diagram look like?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Processes

```
int main() {  
    int count = 1;  
    int pid1 = fork();  
    int pid2 = fork();  
  
    if(pid1 == 0)  
        count++;  
    else{  
        if(pid2 == 0)  
            count--;  
        else  
            count += 2;  
    }  
    printf("%d", count);  
}
```

What does the process diagram look like?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Processes

```

int main() {
    int count = 1;
    int pid1 = fork();
    int pid2 = fork();
    if (pid1 != 0)
        count++;
    if (pid2 != 0)
        count++;
    else if (pid2 == 0)
        count--;
    else
        count += 2;
    printf("%d", count);
}

```

What does count look like?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: [edu_assist_pro](#)

Processes

```

int main() {
    int count = 1;
    int pid1 = fork();
    int pid2 = fork();
    if (pid1 == 0)
        count++;
    else if (pid2 == 0)
        count--;
    else
        count += 2;
    printf("%d", count);
}

```

What does count look like?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

- count = 0
Child2: pid1 == 0 and pid2 == 0
- count = 2
Grandchild: pid1 == 0 and pid2 == 0

Processes

```
int main() {  
    int count = 1;  
    int pid1 = fork();  
    int pid2 = fork();  
  
    if(pid1 == 0)  
        count++;  
    else{  
        if(pid2 == 0)  
            count--;  
        else  
            count += 2;  
    }  
    printf("%d", count);  
}
```

Given the process diagram, what are the different permutations that can be printed out?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Processes

Given the process diagram, what are the different permutations that can be printed out?

```
int main() {  
    int count = 1;  
    int pid1 = fork();  
    int pid2 = fork();  
  
    if(pid1 == 0)  
        count++;  
    else{  
        if(pid2 == 0)  
            count--;  
        else  
            count += 2;  
    }  
    printf("%d", count);  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Math!

$4! / 2 = 12$ different possible outcomes

Processes

Remember:

- Processes can occur in any order
 - Watch out for a `wait` or `waitpid`!
 - What if I included a `wait(NULL)` before I printed out count?
- Good luck!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro`

File IO

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

How the Unix Kernel Represents Open Files

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

File IO

Main ideas:

- How does read offset?
- How does dup2 work?
- What is the order of arguments?
d3 share offset with fd2?

foo.txt: abcdefgh...xyz

```
int main() {  
    int fd1, fd2, fd3;  
    char c;  
    pid_t pid;  
    fd1 = open("foo.txt", O_RDONLY);  
    fd2 = open("foo.txt",  
    fd3 = open("foo.txt",  
    read(fd1, &c, sizeof(  
    read(fd2, &c, sizeof(c));           // c = ?  
    dup2(fd2, fd3);  
    read(fd3, &c, sizeof(c));           // c = ?  
    read(fd2, &c, sizeof(c));           // c = ?  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

File IO

```
foo.txt: abcdefgh...xyz
```

```
int main() {
    int fd1, fd2, fd3;
    char c;
    pid_t pid;
    fd1 = open("foo.txt", O_RDONLY);
    fd2 = open("foo.txt",
    fd3 = open("foo.txt",
    read(fd1, &c, sizeof(
    read(fd2, &c, sizeof(c));           // c = a
    dup2(fd2, fd3);
    read(fd3, &c, sizeof(c));           // c = b
    read(fd2, &c, sizeof(c));           // c = c
```

- How does read offset?
 - Incremented by number of bytes

- How does dup2 work?

ad/write from fd3 now

in from fd2

sets are shared

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

File IO

```
read(fd1, &c, sizeof(c)); // a
read(fd2, &c, sizeof(c)); // a
dup2(fd2, fd3);
read(fd3, &c, sizeof(c)); // b
read(fd2, &c, sizeof(c)); // c
```

```
pid = fork();
if (pid==0) {
    read(fd1, &c,
    printf("c = %c\n", c);
    dup2(fd1, fd2);
    read(fd3, &c, sizeof(c));
    printf("c = %c\n", c);
}
read(fd2, &c, sizeof(c));
printf("c = %c\n", c);
read(fd1, &c, sizeof(c));
printf("c = %c\n", c);
```

Main ideas:

- How are fd shared between processes?
- How does dup2 work from parent

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

File IO

```
read(fd1, &c, sizeof(c)); // a
read(fd2, &c, sizeof(c)); // a
dup2(fd2, fd3);
read(fd3, &c, sizeof(c)); // b
read(fd2, &c, sizeof(c)); // c
```

Assignment Project Exam Help

What would this program print?

```
pid = fork();
if (pid==0) {
    read(fd1, &c, sizeof(c));
    printf("c = %c\n", c);
    dup2(fd1, fd2);
    read(fd3, &c, sizeof(c));
    printf("c = %c\n", c);
}
read(fd2, &c, sizeof(c));
printf("c = %c\n", c);
read(fd1, &c, sizeof(c));
printf("c = %c\n", c);
```

<https://eduassistpro.github.io/>

possible outcomes due

to i

try two simple cases :

Add WeChat edu_assist_pro

1. First child executes to the end
2. First parent executes to the end.

File IO

```
read(fd1, &c, sizeof(c)); // a
read(fd2, &c, sizeof(c)); // a
dup2(fd2, fd3);
read(fd3, &c, sizeof(c)); // b
read(fd2, &c, sizeof(c)); // c
```

Possible output 1:

c = b // in child

c = a // in child

```
pid = fork();
if (pid==0) {
    read(fd1, &c,
    printf("c = %c\n", c);
    dup2(fd1, fd2);
    read(fd3, &c, sizeof(c));
    printf("c = %c\n", c);
}
read(fd2, &c, sizeof(c));
printf("c = %c\n", c);
read(fd1, &c, sizeof(c));
printf("c = %c\n", c);
```

child

child

parent

parent

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

File IO

```
read(fd1, &c, sizeof(c)); // a
read(fd2, &c, sizeof(c)); // a
dup2(fd2, fd3);
read(fd3, &c, sizeof(c)); // b
read(fd2, &c, sizeof(c)); // c
```

Possible output 2:

c = d // in parent

c = b // in parent

hild from fd1

```
pid = fork();
```

```
if (pid==0) {
```

```
    read(fd1, &c,
```

```
    printf("c = %c\n", c);
```

```
    dup2(fd1, fd2);
```

```
    read(fd3, &c, sizeof(c));
```

```
    printf("c = %c\n", c);
```

```
}
```

```
read(fd2, &c, sizeof(c));
```

```
printf("c = %c\n", c);
```

```
read(fd1, &c, sizeof(c));
```

```
printf("c = %c\n", c);
```

hild from fd3

d

d

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

File IO

```
.  
.br/>pid = fork();  
if (pid==0) {  
    read(fd1, &c, sizeof(c));  
    printf("c = %c", c);  
    dup2(fd1, fd2);  
    read(fd3, &c, sizeof(c));  
    printf("c = %c\n", c);  
}  
if (pid!=0) waitpid(-1, NULL, 0);  
read(fd2, &c, sizeof(c));  
printf("c = %c\n", c);  
read(fd1, &c, sizeof(c));  
printf("c = %c\n", c);  
return 0;  
}
```

Assignment Project Exam Help

he possible outputs now?

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

File IO

Possible output:

```

.
.
pid = fork();
if (pid==0) {
    read(fd1, &c, sizeof(c));
    printf("c = %c\n", c);
    dup2(fd1, fd2);
    read(fd3, &c, sizeof(c));
    printf("c = %c\n", c);
}
if (pid!=0) waitpid(-1, NULL, 0);
read(fd1, &c, sizeof(c));
printf("c = %c\n", c);
read(fd2, &c, sizeof(c));
printf("c = %c\n", c);
return 0;
}

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

c = b // in child
 c = d // in child
 hild
 hild
 ent
 ent

File IO

```
read(fd1, &c, sizeof(c)); // a
read(fd2, &c, sizeof(c)); // a
dup2(fd2, fd3);
read(fd3, &c, sizeof(c)); // b
read(fd2, &c, sizeof(c)); // c
```

```
pid = fork();
if (pid==0) {
    read(fd1, &c,
    dup2(fd1, fd2);
    read(fd3, &c, sizeof(c));
}
if (pid!=0) waitpid(-1, NULL, 0);
read(fd2, &c, sizeof(c));
read(fd1, &c, sizeof(c));
```

- Child creates a copy of the parent fd table

- dup2/open/close in parent affect the child

open/close in child do

affect the parent

- rs across process

the file offset.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc

- Fit algorithms - first/next/best/good
- Fragmentation
 - Internal - inside blocks
 - External -
- Organization
 - Implicit
 - Explicit
 - Segregated

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)						
b = malloc(16)						
c = malloc(16)						
free(a)						
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)						
c = malloc(16)						
free(a)						
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)						
free(a)						
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
free(a)						
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
free(a)						
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f[0]	48a		
free(a)						
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f[0]	48a		
free(a)	4		2f[1]	48a		
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48a		32f [1]	48a		
e = malloc(16)	48a	32a	32f [0]	48a		
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48a		32f [1]	48a		
e = malloc(16)	48a	32a	32f [0]	48a		
free(d)	48a	32a	80f [0]			
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48a		32f [1]	48a		
e = malloc(16)	48a	32a	32f [0]	48a		
free(d)	48a	32a	80f [0]			
f = malloc(48)	48a	32a	80a			
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48a		32f [1]	48a		
e = malloc(16)	48a	32a	32f [0]	48a		
free(d)	48a	32a	80f [0]			
f = malloc(48)	48a	32a	80a			
free(b)	48a	32f [0]	80a			

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size
- fragmentation?
 - internal?

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
d = free(a)	48a		32f [1]	48a		
e = malloc(16)	48a	32a	32f [0]	48a		
free(d)	48a	32a	80f [0]			
f = malloc(48)	48a	32a	80a			
free(b)	48a	32f [0]	80a			

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size
- fragmentation?
 - internal
 - $(48-16) + (80-48) = 64$
 - external?

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48a		32f [1]	48a		
e = malloc(16)	48a	32a	32f [0]	48a		
free(d)	48a	32a	80f [0]			
f = malloc(48)	48a	32a	80a			
free(b)	48a	32f [0]	80a			

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - First fit

- 16 byte align
- coalesced
- footerless
- 32 min size
- fragmentation?
 - internal
 - $(48-16) + (80-48) = 64$
 - external
 - 32

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48a		32f [1]	48a		
e = malloc(16)	48a	32a	32f [0]	48a		
free(d)	48a	32a	80f [0]			
f = malloc(48)	48a	32a	80a			
free(b)	48a	32f [0]	80a			

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)						
b = malloc(16)						
c = malloc(16)						
free(a)						
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f[0]	48a		
free(a)	14		2f[1]	48a		
e = malloc(16)						
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48f [0]	32a	32f [1]	48a		
e = malloc(16)	48f [0]	32a	32a	48a		
free(d)						
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48f [0]	32a	32f [1]	48a		
e = malloc(16)	48f [0]	32a	32a	48a		
free(d)	48f [1]	32a	32a	48f [0]		
f = malloc(48)						
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48f [0]	32a	32f [1]	48a		
e = malloc(16)	48f [0]	32a	32a	48a		
free(d)	48f [1]	32a	32a	48f [0]		
f = malloc(48)	48f [0]	32a	32a	64a		
free(b)						

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48f [0]		32f [1]	48a		
e = malloc(16)	48f [0]	32a	32a	48a		
free(d)	48f [1]	32a	32a	48f [0]		
f = malloc(48)	48f [0]	32a	32a	64a		
free(b)	80f [0]		32a	64a		

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size
- fragmentation?
 - internal?

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48f [0]		32f [1]	48a		
e = malloc(16)	48f [0]	32a	32a	48a		
free(d)	48f [1]	32a	32a	48f [0]		
f = malloc(48)	48f [0]	32a	32a	64a		
free(b)	80f [0]		32a	64a		

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size
- fragmentation?
 - internal
 - $(32-16) + (64-48) = 32$
 - external?

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48f [0]		32f [1]	48a		
e = malloc(16)	48f [0]	32a	32a	48a		
free(d)	48f [1]	32a	32a	48f [0]		
f = malloc(48)	48f [0]	32a	32a	64a		
free(b)	80f [0]		32a	64a		

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Malloc - Best fit

- 16 byte align
- coalesced
- footerless
- 32 min size
- fragmentation?
 - internal
 - $(32-16) + (64-48) = 32$
 - external
 - 80

	#1	#2	#3	#4	#5	#6
a = malloc(32)	48a					
b = malloc(16)	48a	32a				
c = malloc(16)	48a	32a	32a			
			32a	48a		
			32f [0]	48a		
free(a)	48f [0]		32f [1]	48a		
e = malloc(16)	48f [0]	32a	32a	48a		
free(d)	48f [1]	32a	32a	48f [0]		
f = malloc(48)	48f [0]	32a	32a	64a		
free(b)	80f [0]		32a	64a		

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Signals

who would win?

Assignment Project Exam Help

several hundre

ynchronous boi

tshlab c <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```

7 void
6 exec_cmdline(char *cmdline, char **argv, sigset_t *set,
5             int bg, int fd_in, int fd_out)
4 {
3     pid_t pid = 0;
2     if ((pid = Fork()) == 0) {
1         // Child process; restore mask and execute job.
314 |     Sigprocmask(SIG_SETMASK, set, NULL);

```

Signals

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Signals (Contd.)

- Sending the same signal to the parent in all the calls to kill() may print 1 since there would be no queuing of signals.
- We can guarantee precisely one SIGUSR1 and one SIGUSR2
- We can print 1-4 depending on the manner in which signals are sent and received.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

And WeChat edu_assist_pro