

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

14-513

18-613

Linking

Assignment Project Exam Help

15-213/18-213/14-513/15-513/18-613:

Introduction to Com

14th Lecture, Octobe

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Today

■ Linking

- Motivation
- What it does
- How it works
- Dynamic linking

■ Case study: Libr

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

**Understanding linking can help you avoid nasty errors
and make you a better programmer.**

Example C Program

```
int sum(int *a, int n);
```

```
int array[2] = {1, 2};
```

```
int main(int argc,  
{
```

```
    int val = sum(array, 2);
```

```
    return val;
```

```
}
```

main.c

```
int sum(int *a, int n)
```

```
{
```

```
    int i, s = 0;
```

```
    for (i = 0; i < n; i++) {
```

```
        s += a[i];
```

```
    }
```

```
}
```

sum.c

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Linking

■ Programs are translated and linked using a *compiler driver*:

- `linux> gcc -Og -o prog main.c sum.c`
- `linux> ./prog`



Why Linkers?

■ Reason 1: Modularity

- Program can be written as a collection of smaller source files, rather than one monolithic mass.
- Can build libraries (on this later)
 - e.g., Math library, standard C li

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Why Linkers? (cont)

■ Reason 2: Efficiency

- Time: Separate compilation. How does that save time?
 - Change one source file, compile, and then relink.
 - No need to recompile other source files.
 - Can compile
- Space: Libraries.
 - Common functions can be aggregated into a single file...
 - **Option 1: *Static Linking***
 - Executable files and running memory images contain only the library code they actually use
 - **Option 2: *Dynamic linking***
 - Executable files contain no library code
 - During execution, single copy of library code can be shared across all executing processes

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

What Do Linkers Do?

■ Step 1: Symbol resolution

- Programs define and reference *symbols* (global variables and functions):

Assignment Project Exam Help
<https://eduassistpro.github.io/>
 Add WeChat edu_assist_pro

```

  ▪ void swap() {...} /* define symbol swap */
  ▪ swap(); /* reference symbol swap */
  ▪ int *xp = 1; /* reference x */
  
```

- Symbol definitions are stored in object (e.g., `obj.o`) in *symbol table*.
 - Symbol table is an array of entries
 - Each entry includes name, size, and location of symbol.

- During symbol resolution step, the linker associates each symbol reference with exactly one symbol definition.

Symbols in Example C Program

Definitions

```
int sum(int *a, int n);
```

```
int array[2] = {1, 2};
```

```
int main(int argc,
```

```
{
    int val = sum(array, 2);
    return val;
}
```

main.c

```
int sum(int *a, int n)
{
```

```
    int i, s = 0;
```

```
    for (i = 0; i < n; i++) {
        s += a[i];
    }
```

sum.c

Reference

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

What Do Linkers Do? (cont)

■ Step 2: Relocation

- Merges separate code and data sections into single sections

Assignment Project Exam Help

- Relocates symbols in the .o files to their final absolute addresses.

<https://eduassistpro.github.io/>

- Updates all references to these symbols to their new positions.

Add WeChat edu_assist_pro

Let's look at these two steps in more detail....

Three Kinds of Object Files (Modules)

■ Relocatable object file (. o file)

- Contains code and data in a form that can be combined with other relocatable object files to form executable object file.
 - Each . o file is produced from exactly one source (. c) file

■ Executable object file (. exe file)

- Contains code and data in a form that can be loaded directly into memory and then executed.

■ Shared object file (. so file)

- Special type of relocatable object file that can be loaded into memory and linked dynamically, at either load time or run-time.
- Called *Dynamic Link Libraries* (DLLs) by Windows

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Executable and Linkable Format (ELF)

- Standard binary format for object files

- One unified format for

- Relocatable object files (.o),
- Executable object files (a.out),
- Shared object files (so)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Generic name: ELF binaries

ELF Object File Format

■ Elf header

- Word size, byte ordering, file type (.o, exec, .so), machine type, etc.

■ Segment header table

- Page size, virtual address memory segments (sections), segment sizes

■ .text section

- Code

■ .rodata section


- Read only data: jump tables, string constants

■ .data section

- Initialized global variables

■ .bss section

- Uninitialized global variables
- “Block Started by Symbol”
- “Better Save Space”
- Has section header but occupies no space




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

ELF Object File Format (cont.)

- **.symtab section**
 - Symbol table
 - Procedure and static variable names
 - Section names and locations
- **.rel.text section**
 - Relocation info for .text section
 - Addresses of instructions modified in the executable
 - Instructions for modifying instructions
- **.rel.data section**
 - Relocation info for .data section
 - Addresses of pointer data that will need to be modified in the merged executable
- **.debug section**
 - Info for symbolic debugging (`gcc -g`)
- **Section header table**
 - Offsets and sizes of each section



0

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Linker Symbols

■ Global symbols

- Symbols defined by module m that can be referenced by other modules.
- E.g.: non-**static** C functions and non-**static** global variables.

Assignment Project Exam Help

■ External symbol

- Global symbols <https://eduassistpro.github.io/> m but defined by some other module.

Add WeChat edu_assist_pro

■ Local symbols

- Symbols that are defined and referenced exclusively by module m .
- E.g.: C functions and global variables defined with the **static** attribute.
- **Local linker symbols are *not* local program variables**

Step 1: Symbol Resolution

...that's defined here

Referencing
a global...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
int sum(int *a, int n);

int array[2] = {1, 2};

int main(int argc, char **argv)
{
    int val = sum(array, 2);
    return val;
}
```

main.c

```
int sum(int *a, int n)
{
    int s = 0;
    for (int i = 0; i < n; i++) {
        s += *a[i];
    }
    return s;
}
```

sum.c

Defining
a global

Linker knows
nothing of val

Referencing
a global...

...that's defined here

Linker knows
nothing of i or s

Symbol Identification

Which of the following names will be in the symbol table of `symbols.o`?

Names:

`symbols.c`:

```
int incr = 1;
static int foo(int a) {
    int b = a + incr;
    return b;
}

int main(int argc,
          char* argv[]) {
    printf("%d\n", foo(5));
    return 0;
}
```

Assignment Project Exam Help

Add WeChat edu_assist_pro

- `incr`

- `printf`

- `"%d\n"`

Can find this with `readelf`:

```
linux> readelf -s symbols.o
```

Local Symbols

■ Local non-static C variables vs. local static C variables

- local non-static C variables: stored on the stack
- local static C variables: stored in either `.bss`, or `.data`

```
static int x = 15;
```

```
int f() {
    static int x
    return x++;
}
```

```
int g() {
    static int x = 19;
    return x += 14;
}
```

```
int h() {
    return x += 27;
}
```

static-local.c

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Com each space in `.data` for `x`

Creates local symbols in the symbol table with unique names, e.g., `x`, `x.1721` and `x.1724`.

How Linker Resolves Duplicate Symbol Definitions

■ Program symbols are either *strong* or *weak*

- **Strong**: procedures and initialized globals

- **Weak**: uninitialized globals

- Or ones dec



Linker's Symbol Rules

■ Rule 1: Multiple strong symbols are not allowed

- Each item can be defined only once
- Otherwise: Linker error

Assignment Project Exam Help

■ Rule 2: Given a strong symbol and one or more weak symbols, choose the strong symbol

- References to the weak symbol resolve to the strong symbol

■ Rule 3: If there are multiple weak symbols, pick an arbitrary one

- Can override this with `gcc -fno-common`

■ Puzzles on the next slide

Linker Puzzles

```
int x;
p1() {}
```

```
p1() {}
```

Link time error: two strong symbols (**p1**)

```
int x;
p1() {}
```

```
int x;
p2() {}
```

References to **x** will refer to the same uninitialized int. Is this what you really want?

```
int x;
int y;
p1() {}
```

```
double
p2() {}
```

<https://eduassistpro.github.io/> it overwrites **y**!

Evil!

Add WeChat **edu_assist_pro**

```
int x=7;
int y=5;
p1() {}
```

```
double x;
p2() {}
```

Writes to **x** in **p2** might overwrite **y**!
Nasty!

```
int x=7;
p1() {}
```

```
int x;
p2() {}
```

References to **x** will refer to the same initialized variable.

Important: Linker does not do type checking.

Type Mismatch Example

```
long int x; /* Weak symbol */
```

```
int main(int argc,  
         char *argv[]) {  
    printf("%ld\n",  
    return 0;  
}
```

mismatch-main.c

```
/* Global strong symbol */
```

```
double x = 3.14;
```

mismatch-variable.c

- Compiles without any errors or warnings
- What gets printed?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Global Variables

- Avoid if you can

- Otherwise

- Use **static** if you can
- Initialize if you do
- Use **extern** if
 - Treated as weak symbol
 - But also causes linker error if not defined in some file

Assignment Project Exam Help

<https://eduassistpro.github.io/>
al variable

Add WeChat edu_assist_pro

Use of extern in .h Files (#1)

c1.c

```
#include "global.h"

int f() {
    return g+1;
}
```

global.h

```
extern int g;
int f();
```

Assignment Project Exam Help

c2.c

```
#include <stdio.h>
#include "global.h"

int g = 0;

int main(int argc, char argv[]) {
    int t = f();
    printf("Calling f yields %d\n", t);
    return 0;
}
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Linking Example

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
int sum(int *a, int n);
```

```
int array[2] = {1,
```

```
int main(int argc, char **argv)
```

```
{
```

```
    int val = sum(array, 2);
```

```
    return val;
```

```
}
```

main.c

```
int sum(int *a, int n)
```

```
{
    int s = 0;
```

```
    for (int i = 0; i < n; i++) {
```

```
        a[i];
```

```
    }
```


```
    return s;
```

```
}
```


sum.c

Step 2: Relocation


Relocatable Object Files




`main.o`



`sum.o`



Executable Object File



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Relocation Entries

```
int array[2] = {1, 2};

int main(int argc, char**
argv)
{
    int val = sum(array, 2);
    return val;
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

0000000000000000 <main>:

0:	48 83 ec 08	sub		
4:	be 02 00 00 00	mov		
9:	bf 00 00 00 00	mov	\$0x0,%edi	# %edi = &array
		a: R_X86_64_32	array	# Relocation entry
e:	e8 00 00 00 00	callq	13 <main+0x13>	# sum()
		f: R_X86_64_PC32	sum-0x4	# Relocation entry
13:	48 83 c4 08	add	\$0x8,%rsp	
17:	c3	retq		

main.o

Relocated .text section

```

00000000004004d0 <main>:
  4004d0:      48 83 ec 08          sub     $0x8,%rsp
  4004d4:      be 02 00 00 00      mov     $0x2,%esi
  4004d9:      bf 18 10 60 00      mov     $0x601018,%edi    # %edi = &array
  4004de:      e8 05 00 00 00      callq   4004e8 <sum>      # sum()
  4004e3:      48 83 c4 08          add     $0x8,%rsp
  4004e7:      c3

```

```

00000000004004e8 <sum>
  4004e8:      b8 00 00 00 00          0,%eax
  4004ed:      ba 00 00 00 00          0,%edx
  4004f2:      eb 09                  4fd <sum+0x15>
  4004f4:      48 63 ca              movslq  %edx,%rcx
  4004f7:      03 04 8f              add     (%rdi,%rcx,4),%eax
  4004fa:      83 c2 01              add     $0x1,%edx
  4004fd:      39 f2                cmp     %esi,%edx
  4004ff:      7c f3                jl      4004f4 <sum+0xc>
  400501:      f3 c3              repz retq

```

`callq` instruction uses PC-relative addressing for `sum()`:


$$0x4004e8 = 0x4004e3 + 0x5$$

Source: `objdump -d prog`

Loading Executable Object Files

Executable Object File

0	ELF header
	Program header table (required for executables)
	.init section
	.text section
	.rodata section
	.data section
	.bss section
	.symtab
	.debug
	.line
	.strtab
	Section header table (required for relocatables)



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Quiz Time!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Check out:

Add WeChat edu_assist_pro

<https://canvas.cmu.edu/courses/10968>

Libraries: Packaging a Set of Functions

■ How to package functions commonly used by programmers?

- Math, I/O, memory management, string manipulation, etc.

■ Awkward, given the linker framework so far:

- **Option 1:** Put all ^{file} _{programs}
 - Programmer
 - Space and time inefficient
- **Option 2:** Put each function in a separate source file
 - Programmers explicitly link appropriate binaries into their programs
 - More efficient, but burdensome on the programmer

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Old-fashioned Solution: Static Libraries

■ **Static libraries** (.a archive files)

- Concatenate related relocatable object files into a single file with an index (called an *archive*).


Assignment Project Exam Help

- Enhance linker s lved external references
by looking for th <https://eduassistpro.github.io/> ives.

Add WeChat edu_assist_pro

- If an archive member file resolves r it into the executable.

Creating Static Libraries



- Archiver allows incremental updates
- Recompile function that changes and replace .o file in archive.

Commonly Used Libraries

`libc.a` (the C standard library)

- 4.6 MB archive of 1496 object files.
- I/O, memory allocation, signal handling, string handling, data and time, random numbers, integer math

`libm.a` (the C math library)

- 2 MB archive of 44
- floating point math

Assignment Project Exam Help

<https://eduassistpro.github.io/>

```
% ar -t /usr/lib/libc.a | sort
```

```
...
fork.o
...
fprintf.o
fpu_control.o
fputc.o
freopen.o
fscanf.o
fseek.o
fstab.o
...
```

```
/lib/libm.a | sort
```

```
e_acos.o
e_acosf.o
e_acosh.o
e_acoshf.o
e_acoshl.o
e_acosl.o
e_asin.o
e_asinf.o
e_asinl.o
...
```

Add WeChat `edu_assist_pro`

Linking with Static Libraries

```
#include <stdio.h>
#include "vector.h"

int x[2] = {1, 2};
int y[2] = {3, 4};
int z[2];

int main(int argc, char** argv)
{
    addvec(x, y, z, 2);
    printf("z = [%d %d]\n",
           z[0], z[1]);
    return 0;
}
```

main2.c

libvector.a

```
void addvec(int *x, int *y,
            int *z, int n) {
    int i;
    for (i = 0; i < n; i++)
        x[i] + y[i];
}
```

addvec.c

```
void multvec(int *x, int *y,
             int *z, int n)
{
    int i;
    for (i = 0; i < n; i++)
        z[i] = x[i] * y[i];
}
```


multvec.c

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Linking with Static Libraries



"c" for "compile-time"

Using Static Libraries

■ Linker's algorithm for resolving external references:

- Scan `.o` files and `.a` files in the command line order.
- During the scan, keep a list of the current unresolved references.
- As each new `.o` or `.a` file, `obj`, is encountered, try to resolve each unresolved reference in the list against the symbols defined in `obj`.
- If any entries in the list remain unresolved, then error.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

■ Problem: Add WeChat edu_assist_pro

- Command line order matters!
- Moral: put libraries at the end of the command line.

```
unix> gcc -static -o prog2c -L. -lvector main2.o  
main2.o: In function `main':  
main2.c:(.text+0x19): undefined reference to `addvec'  
collect2: error: ld returned 1 exit status
```

Modern Solution: Shared Libraries

■ Static libraries have the following disadvantages:

- Duplication in the stored executables (every function needs libc)
- Duplication in the running executables
- Minor bug fixes of system libraries require each application to explicitly relink
 - Rebuild every application
 - <https://security.googleblog.com/2015-7547-glibc-getaddrinfo-stack.html>

■ Modern solution: Shared Libraries

- Object files that contain code and data that are loaded and linked into an application *dynamically*, at either *load-time* or *run-time*
- Also called: dynamic link libraries, DLLs, `.so` files

Shared Libraries (cont.)

- **Dynamic linking can occur when executable is first loaded and run (load-time linking).**
 - Common case for Linux, handled automatically by the dynamic linker (`ld-linux.so`).
 - Standard C library is dynamically linked.
- **Dynamic linking (run-time linking)**
 - In Linux, this is done by calls to the `dlopen()` interface.
 - Distributing software.
 - High-performance web servers.
 - Runtime library interpositioning.
- **Shared library routines can be shared by multiple processes.**
 - More on this when we learn about virtual memory

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

ram has begun

What dynamic libraries are required?

■ .interp section

- Specifies the dynamic linker to use (i.e., `ld-linux.so`)

■ .dynamic section

- Specifies the names, etc of the dynamic libraries to use
- Follow an exam

(NEEDED)

<https://eduassistpro.github.io/> [libm.so.6]

■ Where are the libraries found?


- Use “`ldd`” to find out:

```
unix> ldd prog
linux-vdso.so.1 => (0x00007ffcf2998000)
libc.so.6 => /lib/x86_64-linux-gnu/libc.so.6 (0x00007f99ad927000)
/lib64/ld-linux-x86-64.so.2 (0x00007f99adcef000)
```

Assignment Project Exam Help

Add WeChat edu_assist_pro

Dynamic Library Example




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Dynamic Linking at Load-time



Dynamic Linking at Run-time

```
#include <stdio.h>
#include <stdlib.h>
#include <dlfcn.h>
```

```
int x[2] = {1, 2};
int y[2] = {3, 4};
int z[2];
```

```
int main(int argc, c
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
void *handle;
void (*addvec)(int *, int *, int
char *error;
```

```
/* Dynamically load the shared library that contains addvec() */
```

```
handle = dlopen("./libvector.so", RTLD_LAZY);
```

```
if (!handle) {
    fprintf(stderr, "%s\n", dlerror());
    exit(1);
}
```

```
. . .
```

d11.c

Dynamic Linking at Run-time (cont)

```
...
```

```
/* Get a pointer to the addvec() function we just loaded */
addvec = dlsym(handle, "addvec");
if ((error = dlerror()) != NULL) {
    fprintf(stderr, "%s\n", error);
    exit(1);
}
```

```
/* Now we can call addvec() just the function */
addvec(x, y, z, 2);
printf("z = [%d %d]\n", z[0], z[1]);
```

```
/* Unload the shared library */
if (dlclose(handle) < 0) {
    fprintf(stderr, "%s\n", dlerror());
    exit(1);
}
return 0;
```

```
}
```


dll.c

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Dynamic Linking at Run-time



Linking Summary

- Linking is a technique that allows programs to be constructed from multiple object files.
- Linking can happen at different times in a program's lifetime:
 - Compile time (when a program is compiled)
 - Load time (when a program is loaded into memory)
 - Run time (while a program is executing)
- Understanding linking can help you avoid nasty errors and make you a better programmer.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Today

- Linking
- **Case study: Library interpositioning**

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Case Study: Library Interpositioning

- Documented in Section 7.13 of book
- Library interpositioning : powerful linking technique that allows programmers to intercept calls to arbitrary functions
- Interpositioning can occur at:
 - Compile time:
 - Link time: When <https://eduassistpro.github.io/> statically linked to form an executable object file
 - Load/run time: When an executable object file is loaded into memory, dynamically linked, and then executed.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Some Interpositioning Applications

■ Security

- Confinement (sandboxing)
- Behind the scenes encryption

■ Debugging **Assignment Project Exam Help**

- In 2014, two Facebook engineers reached a 1-year old bug in their iOS code in the SPDY networking stack the wrong location
- Solved by intercepting calls to Posix write functions (write, writev, pwrite)

Source: Facebook engineering blog post at:

<https://code.facebook.com/posts/313033472212144/debugging-file-corruption-on-ios/>

Some Interpositioning Applications (cont)

■ Monitoring and Profiling

- Count number of calls to functions
- Characterize call sites and arguments to functions
- Malloc tracing

- Detecting m

- **Generating** <https://eduassistpro.github.io/>

■ Error Checking **Add WeChat edu_assist_pro**

- C Programming Lab used customized versions of malloc/free to do careful error checking
- Other labs (malloc, shell, proxy) also use interpositioning to enhance checking capabilities

Example program

```
#include <stdio.h>
#include <malloc.h>
#include <stdlib.h>

int main(int argc,
        char *argv[])
{
    int i;
    for (i = 1; i < a
        void *p =
            malloc(atoi(argv[i]));
        free(p);
    }
    return(0);
}
```

int.c

- Goal: trace the addresses and sizes of the allocated and freed blocks, without breaking the program, and not modifying the code.
- Three solutions: interpose on the library malloc and free functions at compile time, link time, and load/run time.

Compile-time Interpositioning

```
#ifdef COMPILETIME
#include <stdio.h>
#include <malloc.h>

/* malloc wrapper function */
void *mymalloc(size_t size)
{
    void *ptr = malloc(size);
    printf("malloc %p\n", ptr);
    return ptr;
}

/* free wrapper function */
void myfree(void *ptr)
{
    free(ptr);
    printf("free(%p) \n", ptr);
}
#endif
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

mymalloc.c

Compile-time Interpositioning

```
#define malloc(size) mymalloc(size)
#define free(ptr) myfree(ptr)
```

```
void *mymalloc(size_t size);
void myfree(void *ptr);
```

Assignment Project Exam Help

malloc.h

```
linux> make intc
gcc -Wall -DCOMPIL
gcc -Wall -I. -o intc int.c myma
```

```
linux> make runc
./intc 10 100 1000
malloc(10)=0x1ba7010
free(0x1ba7010)
malloc(100)=0x1ba7030
free(0x1ba7030)
malloc(1000)=0x1ba70a0
free(0x1ba70a0)
linux>
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Search for <malloc.h> leads to
/usr/include/malloc.h

Search for <malloc.h> leads to

Link-time Interpositioning

```

#ifdef LINKTIME
#include <stdio.h>

void *__real_malloc(size_t size);
void __real_free(void *ptr);

/* malloc wrapper function */
void *__wrap_malloc(size_t size)
{
    void *ptr = __real_malloc(size);
    printf("malloc(%d) = %p\n", size, ptr);
    return ptr;
}

/* free wrapper function */
void __wrap_free(void *ptr)
{
    __real_free(ptr); /* Call libc free */
    printf("free(%p)\n", ptr);
}
#endif

```

Assignment Project Exam Help
<https://eduassistpro.github.io/>
 Add WeChat edu_assist_pro

mymalloc.c

Link-time Interpositioning

```
linux> make intl
```

```
gcc -Wall -DLINKTIME -c mymalloc.c
```

```
gcc -Wall -c int.c
```

```
gcc -Wall -Wl,--wrap,malloc -Wl,--wrap,free -o intl \
```

```
int.o mymalloc.o
```

```
linux> make runl
```

```
./intl 10 100 1000
```

```
malloc(10) = 0x91a
```

```
free(0x91a010)
```

```
. . .
```

Search for `<malloc.h>` leads to
`/usr/include/malloc.h`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- The “`-Wl`” flag passes argument to linker, replacing each comma with a space.
- The “`--wrap,malloc`” arg instructs linker to resolve references in a special way:
 - Refs to `malloc` should be resolved as `__wrap_malloc`
 - Refs to `__real_malloc` should be resolved as `malloc`

Load/Run-time Interpositioning

```
#ifdef RUNTIME
#define _GNU_SOURCE
#include <stdio.h>
#include <stdlib.h>
#include <dlfcn.h>
```

Observe that DON'T have
#include <malloc.h>

```
/* malloc wrapper function */
```

```
void *malloc(size_t size)
```

```
{
```

```
    void *(*mallocp) (size_t)
```

```
    char *error;
```

```
    mallocp = dlsym(RTLD_NEXT, "malloc"); /* Call libc malloc */
```

```
    if ((error = dlerror()) != NULL) {
```

```
        fputs(error, stderr);
```

```
        exit(1);
```

```
    }
```

```
    char *ptr = mallocp(size); /* Call libc malloc */
```

```
    printf("malloc(%d) = %p\n", (int)size, ptr);
```

```
    return ptr;
```

```
}
```

mymalloc.c

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Load/Run-time Interpositioning

```

/* free wrapper function */
void free(void *ptr)
{
    void (*freep)(void *) = NULL;
    char *error;

    if (!ptr)
        return;

    freep = dlsym(RTLD_NEXT, "free");
    if ((error = dlerror()) != NULL) {
        fputs(error, stderr);
        exit(1);
    }
    freep(ptr); /* Call libc free */
    printf("free(%p)\n", ptr);
}
#endif

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

mymalloc.c

Load/Run-time Interpositioning

```
linux> make intr
gcc -Wall -DRUNTIME -shared -fpic -o mymalloc.so mymalloc.c -ldl
gcc -Wall -o intr int.c
linux> make runr
(LD_PRELOAD="./mymalloc.so" ./intr 10 100 1000)
malloc(10) = 0x91a010
free(0x91a010)
. . .
linux>
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

<malloc.h> leads to
include/malloc.h

Add WeChat edu_assist_pro

- The `LD_PRELOAD` environment variable tells the dynamic linker to resolve unresolved refs (e.g., to `malloc`) by looking in `mymalloc.so` first.
- Type into (some) shells as:

```
env LD_PRELOAD=./mymalloc.so ./intr 10 100 1000)
```

Interpositioning Recap

■ Compile Time

- Apparent calls to **malloc/free** get macro-expanded into calls to **mymalloc/myfree**
- Simple approach. Must have access to source & recompile

■ Link Time

- Use linker trick to <https://eduassistpro.github.io/>
 - `malloc` → `__wrap_malloc`
 - `__real_malloc` → `malloc`

■ Load/Run Time

- Implement custom version of **malloc/free** that use dynamic linking to load library **malloc/free** under different names
- Can use with ANY dynamically linked binary

```
env LD_PRELOAD=./mymalloc.so gcc -c int.c)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Linking Recap

- **Usually: Just happens, no big deal**

- **Sometimes: Strange errors**

- Bad symbol resolution
- Ordering dependence of linked .o, .a, and .so files

- **For power users**

- Interpositioning

Assignment Project Exam Help

<https://eduassistpro.github.io/>
out source

Add WeChat edu_assist_pro