

Graphs

Assignment Project Exam Help

Dr Timothy Kimber

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Introduction

Graphs are fundamental to much of computer science

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

- We have already seen how trees are used as data structures
- All sorts of problems can be modelled using graphs
- Networks, images, programs, anything involving **related objects**

Graph Terminology

Assignment Project Exam Help

<https://eduassistpro.github.io>

Definition

A **graph** G is a pair (V, E) where V is a finite set of vertices and E is a binary relation on V . Elements of V are called **vertices** and elements of E are called **edges**.

- E is a set of pairs of vertices: $\{u, v\}$ such that there is an edge between u and v
- Vertices u and v are **adjacent** if there is an edge $\{u, v\}$

Graph Terminology

Assignment Project Exam Help

<https://eduassistpro.github.io>

- A **path** from v_1 to v_n , written $v_1 \rightsquigarrow v_n$, is such that there is an edge $\{v_i, v_{i+1}\}$ for $i = 1, \dots, n-1$.
- A **cycle** exists if there is a path from a vertex to itself, for some vertex v .
- Vertex v is **reachable** from vertex u if $u = v$, or if there is a path $u \rightsquigarrow v$.
- A **connected component** (also just called a component) is a set of vertices all reachable from each other.

Graph Representation

Question

How should a graph be represented as a data structure?

- A gra
- Goi

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Graph Representation

Two common ways:

- Adjacency List (S): $adj[u]$ contains v if there is an edge $\{u, v\}$
- Adjacency Matrix: $adj_{uv} = 1$ if there is an edge u, v , else 0

Adjacen

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Graph Search

Question

Why **search** a graph?

- Searching a graph is like iterating through an ordered structure
- Wa

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Graph Search Actions

Searching a graph has two actions:

- Find adjacent vertices
- Visit vertices not found before

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

- Visiting means using the vertex: includes finding further vertices
- Vertices are visited in the order they are first found
- Vertices are coloured when they are first found/visited

Breadth-First Search

Question

What is a breadth-first search of a graph?

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Breadth-First Search

In **breadth-first** search

- Visit a vertex v (starting with **source vertex** s)
- Find all vertices adjacent to v before visiting another
- Result: search proceeds gradually down every path at the same rate

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

BFS Procedure

Question

How would you implement BFS?

- Inputs are graph g and vertex s
- $g.a$
- $g.v$
- Obj

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Breadth-First Search

BFS (Input: graph g , vertex s)

```
found = new boolean[g.vertices]
```

```
q = new Queue(s) // FIFO queue
```

```
wh
```

```
if not found[v] // avoid loops
```

```
found[v] = true
```

```
q.add(v)
```

- The use of a (FIFO) queue is characteristic of BFS
- By convention only search from given s

Shortest Paths

BFS searches all paths at the same rate, so ...

Question

Assignment Project Exam Help

How would you modify the BFS procedure to find the length (number of edges) of th

BFS (Inpu

```
found = new boolean[g.vertices]
q = new Queue(s)           // FIFO queue
while q is not empty
    u = q.remove()
    for v in g.adj[u]
        if not found[v]           // avoid loops
            found[v] = true
            q.add(v)
```

Shortest Paths

BFS (Input: graph g , vertex s)

```

q = new Queue(s)
dist = new int[g.vertices]
dist.fill(-1)
di
wh
for v in g.adj[u]
    if dist[v] == -1          // not found
        dist[v] = dist[u] + 1
        q.add(v)

```

- The distance is recorded when a vertex is (first) found
- Arrays of size $|V|$ like *dist* are also common in graph search
- Unreachable vertices have $\text{dist}[v] = -1$

Time

Question

For a connected graph with V vertices and E edges, how long does BFS take?

BFS (Impl)

```
for
q = new Queue(s)
while q is not empty
    u = q.remove()
    for v in g.adj[u]
        if not found[v]
            found[v] = true
            q.add(v)
```

BFS Time Complexity

- Each vertex is added and removed from the queue exactly once
- Each adjacency list is used exactly once
- Each edge contributes exactly two vertices to the adjacency lists
- Time

BFS (Input)

```

found = new boolean[g.vertices]
q = new Queue(s)
while q is not empty
    u = q.remove()           runs once per vertex
    for v in g.adj[u]
        if not found[v]     runs twice per edge
            found[v] = true
            q.add(v)

```


Depth-First Search

Question

What is a depth-first search of a graph?

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Depth-First Search

In **depth-first** search

- **Visit** every vertex as soon as it is found
- i.e. start the next visit before completing current visit
- Result: search follows a single path as far as possible and then
back

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

DFS Procedure

Question

How would you implement DFS?

- Input is graph g
- Ass
- Obj

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Depth-First Search

DepthFirstSearch (Input: graph g)

```
found = new boolean[g.vertices]
for v in g
    if not found[v]
```

DFS (Inp

```
found[s] = true
for v in g.adj[s]
    if not found[v]
        DFS(g, v, found)
```

- DFS can use call stack instead of explicit queue
- Restart until whole graph searched (or not)

An Application

Assignment Project Exam Help

- Program checks if (whole) graph is acyclic
- Returns true or false

DepthFi

```
pa
parent.fill(-1)          // nothing found
for v in g
    if parent[v] == -1    // not found
        parent[v] = -2   // found, no parent
        if not DFSAcyclic(g, v, parent)
            return false
return true
```

Depth-First Search

```
DFSAcyclic (Input: graph  $g$ , vertex  $u$ , array parent)
```

```
  for  $v$  in  $g.adj[u]$ 
    if parent[ $v$ ] == -1           // not found
```

```
      return false
  return true
```

- A cycle exists if v was already found, unless u
- Since u was just found, and not from v , the edge $\{u, v\}$ completes an alternative path to u from the source

Time

Assignment Project Exam Help

Question

For a `conne`
take?

FS

DFS (Inp

```
found[s] = true
for v in g.adj[s]
  if not found[v]
    DFS(g, v, found)
```

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

DFS Time Complexity

Assignment Project Exam Help

- DFS is called exactly once per vertex
- Each adjacency list is used exactly once
- Eac
- Tim

<https://eduassistpro.github.io>

DFS (Input: graph g , vertex s , array found)

```

found[s] = true           runs V times
for v in g.adj[s]
    if not found[v]        runs 2E times
        DFS(g, v, found)
  
```