BU CS 332 – Theory of Computation

Lecture 2:

- Parts of a Th
  Computatio
- Sets, Strings, and Languag

Reading:

- Sipser Ch 0

Mark Bun

January 27, 2021

What makes a good theory?

- General ideas that apply to many different systems
- Expressed simply, abstractly, and precisely

Parts of a Theory

- Models for machines (computers)
- Models for the problems machines can be used to solve
- Theorems about what kinds of machines can solve what kinds of problems, and at what cost

What is a (Computational) Problem?

For us: A problem will be the task of recognizing whether a *string* is in a *language*

- **Alphabet**: A finite set Σ Ex. $\Sigma = \{a, b\}$
- **String:** A finite c https://eduassistpro.github.io/ het symbols

  Ex. bba, ababb

  ε denotes empty string, l

  Σ^* = set of all strings using symbols from Σ

  Ex. $\{a, b\}^* = \{\varepsilon, a, b, aa, ab, ba, bb, \dots\}$

- **Language:** A set $L \subseteq \Sigma^*$ of strings

Examples of Languages

Parity: Given a string consisting of a's and b's, does it contain an even number of a's?

Σ = L =

Primality: Given a resented in binary), is

Σ = L =

Halting Problem: Given a C program, can it ever get stuck in an infinite loop?

Σ = L =

Machine Models

Computation is the processing of information by the **unlimited application** of a **finite set** of operations or rules



Abstraction: We don't care how the control is implemented. We just require it to have a finite number of states, and to transition between states using fixed rules.

Machine Models

- Finite Automata (FAs): Machine with a finite amount of unstructured memory



Control scans left-to-right

k simple patterns

rform unlimited counting

Useful for modeling chips, simple control systems, choose-your-own adventure games…

Machine Models

- Turing Machines (TMs): Machine with unbounded, unstructured memory



Control can scan in both directions an both read and write

Model for general sequential computation

Church-Turing Thesis: Everything we intuitively think of as "computable" is computable by a Turing Machine

What theorems would we like to prove?

We will define classes of languages based on which machines can recognize them

Inclusion: Every language recognizable by a FA is also recognizable by a

Non-inclusion: There exist lang gnizable by TMs which are not recognizable by

Completeness: Identify a "hardest" language in a class

Robustness: Alternative definitions of the same class

Ex. Languages recognizable by FAs = regular expressions

Why study theory of computation?

- You'll learn how to formally reason about computation
- You'll learn the technology-independent foundations of CS

Philosophically in

- Are there well-defined proble[illegible] not be solved by computers?

- Can we always find the solution to a puzzle faster than trying all possibilities?
- Can we say what it means for one problem to be "harder" than another?

Why study theory of computation?

- You'll learn how to formally reason about computation
- You'll learn the technology-independent foundations of CS

Connections to ot

- Finite automata arise in compi ng, chemistry

https://cstheory.stackexchange. 8

- Hard problems are essential to cryptography
- Computation occurs in cells/DNA, the brain, economic systems, physical systems, social networks, etc.

What appeals to you about the theory of computation?



1. I want to learn new ways of thinking about computation
2. I like math and want to see how it's used in computer science
3. I'm excited abo estions about computation
4. I want to practice problem so lgorithmic thinking
5. I want to develop a "computational perspective" on other areas of math/science
6. I actually wanted to take CS 320 or 350 but they were full

Why study theory of computation?

Practical knowledge for developers

"Boss, I can't find an efficient algorithm. I guess I'm just too dumb."

"B n efficient algorithm because no such algorithm exists."

Will you be asked about this material on job interviews?

No promises, but a true story…

More about strings and languag

String Theory



- **Symbol:** Ex. $a, b, 0, 1$
- **Alphabet**: A finite set Σ Ex. $\Sigma = \{a, b\}$
- **String:** A finite c bet symbols

  Ex. bba, ab

  ε denotes empty string, l

  Σ^* = set of all strings using symbols from Σ

  Ex. $\{a, b\}^* = \{\varepsilon, a, b, aa, ab, ba, bb, \ldots\}$
- **Language:** A set $L \subseteq \Sigma^*$ of strings

String Theory



- **Length** of a string, written $|x|$, is the number of symbols

Ex. $|\text{abba}| =$ $|\varepsilon| =$

- **Concatenation** of strings x and y, written xy, is the symbols from x ols from y

Ex. $x = \text{ab}, y = \text{b}$

$x = \text{ab}, y = \varepsilon \Rightarrow$

- **Reversal** of string x, written x^R, consists of the symbols of x written backwards

Ex. $x = \text{aab}$ $\Rightarrow$ $x^R =$

Fun with String Operations



What is $(xy)^R$?

Ex. $x = \text{aba}, y = \text{bba}$ $\Rightarrow$ $xy =$

$\Rightarrow$ $(xy)^R =$

1. $x^R y^R$
2. $y^R x^R$
3. $(yx)^R$
4. xy^R

Fun Proofs with String Operations

Claim: $(xy)^R =$

Proof: Let $x = x_1 x_2 \ldots x_n$ and $y = y_1 y_2 \ldots y_m$

Then $(xy)^R =$

Not even the most formal way to do this:

1. Define string length recursively
2. Prove by induction on $|y|$

Languages

A language L is a set of strings over an alphabet Σ

i.e., $L \subseteq \Sigma^*$

Languages = com roblems

Input: String $x \in$

Output: Is $x \in L$? (YES or NO?)

Some Simple Languages

$\Sigma = \{0, 1\}$ $\Sigma = \{a, b, c\}$

$\emptyset$ (Empty set)

Σ^* (All strings)

$\Sigma^n = \{x \in \Sigma^* \mid |x| = n\}$
(All strings of length n)

Some More Interesting Languages

- L_1 = The set of strings $x \in \{a, b\}^*$ that have an equal number of a's and b's

- L_2 = The set of { } t start with (0 or more) a's and ar l number of b's

- L_3 = The set of strings $x \in \{0, 1\}^*$ that contain the substring '0100'

Some More Interesting Languages

- L_4 = The set of strings $x \in \{a, b\}^*$ of length at most 4

- L_5 = The set of { } t contain at least two a's

New Languages from Old

$L_6 =$ The set of strings $x \in \{a, b\}^*$ that have an equal number of a's and b's and length greater than 4

Since languages are just sets of strings, can build them using set operati

$A \cup B$ "union"

$A \cap B$ "intersection"

$\bar{A}$ "complement"

New Languages from Old

$L_6 =$ The set of strings $x \in \{a, b\}^*$ that have an equal number of a's and b's and have length greater than 4

- $L_1 =$ The set of strings $x \in \{a, b\}^*$ that have an equal number of a's a

- $L_4 =$ The set of strings $x \in \{a \quad\}$ gth at most 4

$\Rightarrow L_6 =$

Operations Specific to Languages

- **Reverse**: $L^R = \{x^R \mid x \in L\}$

  Ex. $L = \{\varepsilon, \text{a}, \text{ab}, \text{aab}\}$ $\Rightarrow L^R =$

- **Concatenation:** $\{\quad \mid \quad, y \in L_2\}$

  Ex. $L_1 = \{\text{ab}, \text{aab}\}$ $L_2 =$

  $\Rightarrow L_1 \circ L_2 =$

A Few "Traps"

String, language, or something else?

ε

$\emptyset$

$\{\varepsilon\}$

$\{\emptyset\}$

Languages

Languages = computational (decision) problems

Input: String $x \in \Sigma^*$

Output: Is $x \in L$? (YES or NO?)

The language **rec** is the set of strings $x \in \Sigma^*$ that it *acc*

What Language Does This Program Recognize?

Alphabet $\Sigma = \{a, b\}$

On input $x = x_1 x_2 \ldots x_n$:

count = 0

For $i = 1, \ldots, n$:

If $x_i = a$:

count = count + 1

If count ≤ 4: accept

Else: reject

1. $\{x \in \Sigma^* \mid |x| > 4\}$
2. $\{x \in \Sigma^* \mid |x| \leq 4\}$
3. $\{x \in \Sigma^* \mid |x| = 4\}$
4. $\{x \mid x$ has more than 4 a's$\}$
5. $\{x \mid$ has at most 4 a's$\}$
6. $\{x \mid x$ has exactly 4 a's$\}$