

BU CS 332 – Theory of Computation

Lecture 9: Assignment Project Exam Help

Reading:

ser Ch 3.1, 3.3

- Turing Mac

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Mark Bun

February 22, 2021

Turing Machines – Motivation

We've seen finite automata as a restricted model of computation

Finite Automata / Regular Expressions

- Can do simple pattern matching (e.g., substrings), check parity, addition
- Can't perform u <https://eduassistpro.github.io/>
- Can't recognize palindromes

Add WeChat edu_assist_pro

Somewhat more powerful (not in this course):

Pushdown Automata / Context-Free Grammars

- Can count and compare, parse math expressions
- Can't recognize $\{a^n b^n c^n \mid n \geq 0\}$

Turing Machines – Motivation

Goal:

Define a model of computation that is

- Assignment Project Exam Help
- 1) General purpose — things that can be implemented <https://eduassistpro.github.io/>
- Add WeChat edu_assist_pro
- 2) Mathematically simple. We can hope to prove that things are not computable in this model.

A Brief Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

1900 – Hilbert's Tenth Problem

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Given a Diophantine equation with a number of unknown quantities and with rational integral numerical coefficients: To devise a process according to which it can be determined in a finite number of operations whether the equation is solvable in rational integers.

Add WeChat [edu_assist_pro](#)

David Hilbert 1862-1943

1928 – The *Entscheidungsproblem*

The “Decision Problem”

Assignment Project Exam Help

<https://eduassistpro.github.io/>


*decides whether
logically valid?*
Add WeChat edu_assist_pro



Wilhelm Ackermann 1896-1962

David Hilbert 1862-1943

1936 – Solution to the *Entscheidungsproblem*



"An unsolvable problem of elementary number theory"

Assignment Project Exam Help Calculus (CS 320)

Alonzo Church 1903-199

<https://eduassistpro.github.io/>



Add WeChat edu_assist_pro


"On computable numbers, with an application to the *Entscheidungsproblem*"

Model of computation: Turing Machine

Alan Turing 1912-1954

Turing Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

The Basic Turing Machine (TM)




Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

- Input is written on an infinite tape
- Head can both read and write, and move in both directions
- Computation halts as soon as control reaches “accept” or “reject” state


Example



Example



Example



What does this TM do on input 000?

- a) Halt and accept
- b) Halt and reject
- c) Halt in state q_3
- d) Loop forever without halting

Three Levels of Abstraction

High-Level Description

An algorithm (like CS 330)

Implementation-Level Description

Describe (in English) a TM
<https://eduassistpro.github.io/>

- How to move the head
 - What to write on the tape
- Add WeChat edu_assist_pro

Low-Level Description

State diagram or formal specification

Example

Determine if a string $w \in A = \{0^{2^n} \mid n \geq 0\}$

High-Level Description
Assignment Project Exam Help

Repeat the follow <https://eduassistpro.github.io/>

- If there is exactly one 0 in w , accept [Add WeChat edu_assist_pro](https://eduassistpro.github.io/)
- If there is an odd number of 0s in w (> 1), reject
- Delete half of the 0s in w

Example

Determine if a string $w \in A = \{0^{2^n} \mid n \geq 0\}$

Implementation-Level Description

Assignment Project Exam Help

1. While moving <https://eduassistpro.github.io/> right:
 - a) Cross off every other 0
 - b) If there is exactly one 0 when we reach the right end of the tape, accept
 - c) If there is an odd number of 0s when we reach the right end of the tape, reject
2. Return the head to the left end of the tape
3. Go back to step 1

Example

Determine if a string $w \in A = \{0^{2^n} \mid n \geq 0\}$

Low-Level Description

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

TMs vs. Finite Automata

Teacher: “zoom breakout rooms are critically important for online learning”

Zoom breakout rooms:



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Formal Definition of a TM

A TM is a 7-tuple $M = (Q, \Sigma, \Gamma, \delta, q_0, q_{\text{accept}}, q_{\text{reject}})$

- Q is a finite set of states
- Σ is the input alphabet (does **not** include \sqcup)
- Γ is the tape alphabet ($\Sigma \subset \Gamma$)
- δ is the transition function
- $q_0 \in Q$ is the start state
- $q_{\text{accept}} \in Q$ is the accept state
- $q_{\text{reject}} \in Q$ is the reject state ($q_{\text{reject}} \neq q_{\text{accept}}$)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

TM Transition Function

$$\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$$

L means “move left” and R means “move right”

$\delta(p, a) = (q, b, R)$ means:

- Replace a with b
- Transition from state p to state q
- Move tape head right

Add WeChat edu_assist_pro

$\delta(p, a) = (q, b, L)$ means:

- Replace a with b in current cell
- Transition from state p to state q
- Move tape head left UNLESS we are at left end of tape, in which case don't move


Configuration of a TM

A string with captures the state of a TM together with the contents of the tape

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Configuration of a TM: Formally

A **configuration** is a string uqv where $q \in Q$ and $u, v \in \Gamma^*$

- Tape contents = uv (followed by blanks \sqcup)


- Current state = q

- Tape head on fi


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Example: ~~1010111~~ ~~q₅~~ ~~0111~~ Add WeChat edu_assist_pro



...



How a TM Computes

Start configuration: $q_0 w$



One step of computation:

- $u a q b v$ yields $u a c q' v$ if $\delta(q, b) = (q', c, R)$
- $u a q b v$ yields $u a c q' b v$ if $\delta(q, b) = (q', c, L)$
- If we are at the left end of the configuration $q b v$, what configuration do we reach if $\delta(q, b) = (q', c, L)$?

How a TM Computes

Start configuration: $q_0 w$

One step of computation:

- $u a q b v$ yields $u a c q' v$ if $\delta(q, b) = (q', c, R)$
- $u a q b v$ yields $u a c q' b v$ if $\delta(q, b) = (q', c, L)$
- $q b v$ yields $q' c v$ if $\delta(q, b) = (q', c, \epsilon)$

Accepting configuration: $q = q_{\text{accept}}$

Rejecting configuration: $q = q_{\text{reject}}$

How a TM Computes

M **accepts** input w if there is a sequence of configurations C_1, \dots, C_k such that:

- $C_1 = q_0 w$
- C_i yields C_{i+1} **for every i**
- C_k is an accepti

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

$L(M)$ = the set of all strings w **accepts**

A is **Turing-recognizable** if $A = L(M)$ for some TM M :

- $w \in A \Rightarrow M$ halts on w in state q_{accept}
- $w \notin A \Rightarrow M$ halts on w in state q_{reject} **OR**
 M runs forever

Recognizers vs. Deciders

$L(M)$ = the set of all strings w which M accepts

A is Turing-recognizable if $A = L(M)$ for some TM M :

- $w \in A \Rightarrow M$ halts on w in state q_{accept}

- $w \notin A \Rightarrow M$ halts on w in state q_{reject}

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

A is (Turing-)decidable if $A = L(M)$ for some TM M

which halts on every input

- $w \in A \Rightarrow M$ halts on w in state q_{accept}

- $w \notin A \Rightarrow M$ halts on w in state q_{reject}

Back to Hilbert's Tenth Problem

Computational Problem: Given a Diophantine equation, does it have a solution over the integers?

$L =$

- L is Turing-recognizable

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- L is **not** decidable (1949-70)

