
CIS 471/571 (Fall 2020): Introduction to Artificial Intelligence

Assignment Project Exam Help

Lecture 16 – Sampling

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Thanh H. Nguyen

Source: <http://ai.berkeley.edu/home.html>



Bayes' Nets

✓ Representation

✓ Conditional Independences

Assignment Project Exam Help

▪ Proba

✓ Enu
com

<https://eduassistpro.github.io/>

✓

Variable elimination (base
exponential complexity)

Add WeChat edu_assist_pro

✓

Inference is NP-complete

▪ Sampling (approximate)

▪ Learning Bayes' Nets from Data



Approximate Inference: Sampling

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Sampling

- Sampling is a lot like repeated simulation

- Predicting the weather, basketball games, ...

- Why sample?

- Learning: get samples from a distribution you don't know
 - Inference: getting a sample is faster than computing the right answer (e.g. with variable elimination)


- Basic idea

- Draw N samples from a sample
 - Compute an approximate posterior probability
 - Show this converges to the true probability P

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Sampling

■ Sampling from given distribution ■ Example

- Step 1: Get sample u from uniform distribution over $[0, 1)$

- E.g. `random()` in python

- Step 2: Convert this sample u into outcome for the given distribution

- Each target outcome is associated with a sub-interval of $[0, 1)$
 - Sub-interval size is equal to probability of the outcome.


C	P(C)
red	.6
green	.1
blue	

$0 \leq u < 0.6, \rightarrow C = \text{red}$

$0.6 \leq u < 0.7, \rightarrow C = \text{green}$

$0.7 \leq u < 1, \rightarrow C = \text{blue}$

- If `random()` returns $u = 0.83$, then our sample is $C = \text{blue}$
- E.g, after sampling 8 times:



Sampling in Bayes' Nets

- Prior Sampling

Assignment Project Exam Help

- Rejection Sampling

<https://eduassistpro.github.io/>

- Likelihood Weighted Sampling

Add WeChat: edu_assist_pro

- Gibbs Sampling



Prior Sampling


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Prior Sampling



Prior Sampling

- For $i = 1, 2, \dots, n$
 - Sample x_i from $P(X_i \mid \text{Parents}(X_i))$
- Return

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro



Prior Sampling

- This process generates samples with probability:

$$S_{PS}(x_1 \dots x_n) = \prod_{i=1}^n P(x_i | \text{Parents}(X_i)) = P(x_1 \dots x_n)$$

...i.e. the BN's

<https://eduassistpro.github.io/>

- Let the number of samples $N_{PS}(x_1 \dots x_n)$

- Then
$$\begin{aligned} \lim_{N \rightarrow \infty} \hat{P}(x_1, \dots, x_n) &= \lim_{N \rightarrow \infty} N_{PS}(x_1, \dots, x_n) / N \\ &= S_{PS}(x_1, \dots, x_n) \\ &= P(x_1 \dots x_n) \end{aligned}$$

- I.e., the sampling procedure is **consistent**



Example

- We'll get a bunch of samples from the BN:

+c, -s, +r, +w

+c, +s, +r, +w


-c, +s, +r, -w

+c, -s, +r, +w

-c, -s, -r, +w

Assignment Project Exam Help

<https://eduassistpro.github.io/>



- If we want to know $P(W)$

Add WeChat edu_assist_pro

- We have counts $\langle +w:4, -w:1 \rangle$
- Normalize to get $P(W) = \langle +w:0.8, -w:0.2 \rangle$
- This will get closer to the true distribution with more samples
- Can estimate anything else, too
- What about $P(C \mid +w)$? $P(C \mid +r, +w)$? $P(C \mid -r, -w)$?
- Fast: can use fewer samples if less time (what's the drawback?)



Rejection Sampling

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Rejection Sampling

- Let's say we want $P(C)$
 - No point keeping all samples around
 - Just tally counts of C as we go



- Let's say we want $P(S)$
 - Same thing: tally S outcomes, but (reject) samples which don't have
 - This is called rejection sampling
 - It is also consistent for conditional probabilities (i.e., correct in the limit)

<https://eduassistpro.github.io/>


Add WeChat: [edu_assist_pro](#)

+c, -s, +r, +w
+c, +s, +r, +w
-c, +s, +r, -w
+c, -s, +r, +w
-c, -s, -r, +w



Rejection Sampling

- Input: evidence instantiation
- For $i = 1, 2, \dots, n$
 - Sample x_i from $P(X_i \mid \text{Parents}(X_i))$
 - If x_i
 - R generated in this cycle
- Return (x_1, x_2, \dots, x_n)



Likelihood Weighting

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Likelihood Weighting

- Problem with rejection sampling:
 - If evidence is unlikely, rejects lots of samples
 - Evidence not exploited as ~~your sample~~
 - Consider $P(\text{Shape} \mid \text{blue})$


- Idea: fix evidence variables and sample the rest

- Problem: sample distribution not consistent!
- Solution: weight by probability of evidence

Assignment Project Exam Help

<https://eduassistpro.github.io/>



Add WeChat edu_assist_pro



pyram
pyram
sphere, blue
cube, red
-sphere, green



pyramid, blue
pyramid, blue
sphere, blue
cube, blue
sphere, blue



Likelihood Weighting

$$P(C)$$

+c	0.5
-c	0.5

$$P(S|C)$$

+c	+s	0.1
	-s	0.9
-c	+s	0.5
	-s	0.5

$$P(R|C)$$

+c	+r	0.8
	-r	0.2
-c	+r	0.2
	-r	0.8


$$P(W|S, R)$$

+s	+r	+w	0.99
		-w	0.01
	-r	+w	0.90
		-w	0.10
-s	+r	+w	0.90
		-w	0.10
	-r	+w	0.01
		-w	0.99

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Samples:

+c, +s, +r, +w

...

$$w = 1.0 \times 0.1 \times 0.99$$




Likelihood Weighting

- Input: evidence instantiation
- $w = 1.0$
- for $i = 1, 2, \dots, n$
 - if X_i is an evidence variable

<https://eduassistpro.github.io/>

- Sample x_i from $P(\cdot)$
- return (x_1, x_2, \dots, x_n)




Likelihood Weighting

- Sampling distribution if z sampled and e fixed evidence

$$S_{WS}(z, e) = \prod_{i=1}^l P(z_i | \text{Parents}(Z_i))$$

- Now, samples have <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



- Together, weighted sampling distribution is consistent

$$\begin{aligned} S_{WS}(z, e) \cdot w(z, e) &= \prod_{i=1}^l P(z_i | \text{Parents}(z_i)) \prod_{i=1}^m P(e_i | \text{Parents}(e_i)) \\ &= P(z, e) \end{aligned}$$





Likelihood Weighting

- Likelihood weighting is good
 - We have taken evidence into account as we generate the sample
 - E.g. here, W 's value will get adjusted based on the evidence values of S , R
 - More of our samples will reflect the world suggested by the evidence
- Likelihood weighting doesn't solve all our problems
 - Evidence influences the choice of downstream variables, but not upstream ones (C isn't more likely to get a value changing the evidence)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Gibbs Sampling

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Gibbs Sampling

- *Procedure*: keep track of a full instantiation x_1, x_2, \dots, x_n . Start with an arbitrary instantiation consistent with the evidence. Sample one variable at a time, conditioned on all the rest, but keep evidence fixed. Keep repeating this for a long time.
- *Property*: in the limit many times the resulting samples converge to the joint distribution (i.e. conditioned on evidence).
- *Rationale*: both upstream and downstream variables condition on evidence.
- In contrast: likelihood weighting only conditions on upstream evidence, and hence weights obtained in likelihood weighting can sometimes be very small. Sum of weights over all samples is indicative of how many “effective” samples were obtained, so we want high weight.

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro



Gibbs Sampling Example: $P(S \mid +r)$


- Step 1: Fix evidence

- $R = +r$



- Step 2: Initialize other variables

- Randomly




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Steps 3: Repeat

- Choose a non-evidence variable X
 - Resample X from $P(X \mid \text{all other variables})$



Sample from $P(S \mid +c, -w, +r)$


Sample from $P(C \mid +s, -w, +r)$

Sample from $P(W \mid +s, +c, +r)$



Efficient Resampling of One Variable

- Sample from $P(S \mid +c, +r, -w)$



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Many things cancel out – only CPTs with S remain!
- More generally: only CPTs that have resampled variable need to be considered, and joined together




Bayes' Net Sampling Summary

- Prior Sampling $P(Q)$
- Rejection Sampling $P(Q | e)$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Likelihood Weighting $P(Q | e)$
- Add WeChat [edu_assist_pro](#)



Further Reading on Gibbs Sampling*

- Gibbs sampling produces sample from the query distribution $P(Q | e)$ in limit of re-sampling infinitely often
- Gibbs sampling is a **Assignment Project Exam Help** general methods called Markov chain **https://eduassistpro.github.io/** methods
- Metropolis-Hastings is one of the **Add WeChat edu_assist_pro** MCMC methods (in fact, Gibbs sampling is a special case of Metropolis-Hastings)
- You may read about Monte Carlo methods – they're just sampling

