
CIS 471/571 (Fall 2020): Introduction to Artificial Intelligence

Assignment Project Exam Help

<https://eduassistpro.github.io/>
Lecture Search
Add WeChat edu_assist_pro

Thanh H. Nguyen

Most slides are by Pieter Abbeel, Dan Klein, Luke Zettlemoyer, John DeNero,
Stuart Russell, Andrew Moore, or Daniel Lowd
Source: <http://ai.berkeley.edu/home.html>

Reminder

- Homework 1: Search
 - Deadline: Oct 10, 2020
[Assignment](#) [Project](#) [Exam](#) [Help](#)
- Project 1: Search <https://eduassistpro.github.io/>
 - Deadline: Oct 13, 2020
[Add WeChat edu_assist_pro](#)

Today

- Uninformed Search
 - Uniform Cost Search
 - Informed Search
 - Heuristics
 - Greedy Search
 - A* Search
 - Graph Search
- Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro



Recap: Search

- Search problem:
 - States (configurations of the world)
 - Actions and costs
 - Successor function (world dynamics) **Assignment Project Exam Help**
 - Start state and goal test
- Search tree:
 - Nodes: represent plans for reaching states
 - Plans have costs (sum of action costs)
- Search algorithm:
 - Systematically builds a search tree
 - Chooses an ordering of the fringe (unexplored nodes)
 - Optimal: finds least-cost plans

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Uninformed Search

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Uniform-Cost Search(UCS)


Strategy: expand a cheapest node first:

Fringe is a priority queue
(priority: cumulative cost)



Assignment Project Exam Help

<https://eduassistpro.github.io/>



UCS Properties

- What nodes does UCS expand?

- Processes all nodes with cost less than cheapest solution!
 - If that solution costs C^* and arcs cost at least ε , then the “effective depth” is roughly C^*/ε “tiers”
 - Takes time $O(b^{C^*/\varepsilon})$ (exponentia

<https://eduassistpro.github.io/>

- How much space does the fri

- Has roughly the last tier, so $O(b^{C^*/\varepsilon})$

- Is it complete?

- Assuming best solution has a finite cost and minimum arc cost is positive, yes!

- Is it optimal?


- Yes!

Assignment Project Exam Help

$c \leq \varepsilon$

$c \leq 2\varepsilon$

$c \leq 3\varepsilon$




Uniform Cost Search

- Strategy: expand lowest path cost


Assignment Project Exam Help

- The good: UCS is com <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



- The bad:
 - Explores options in every “direction”
 - No information about goal location



Informed Search

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro






Search Heuristics

- A heuristic is:
 - A function that *estimates* how close a state is to a goal
 - Designed for a particular search problem
 - Examples: Manhattan distance, Euclidean distance for pathing

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Example: Heuristic Function

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

$h(x)$



Example: Pancake Problem




Cost: Number of pancakes flipped




Example: Pancake Problem

State space graph with costs as weights



Example: Heuristic Function

Heuristic: the number of the largest pancake that is still out of place



Greedy Search

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro




Greedy Search

- Expand the node that seems closest...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



$h(x)$




Greedy Search

- Expand the node that seems closest...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



- What can go wrong?





Greedy Search

- A common case:
 Assignment Project Exam Help
 Best-first takes you straight down

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Worst-case: like a badly-guided DFS



A* Search

Assignment Project Exam Help



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Combining UCS and Greedy


- Uniform-cost orders by path cost, or *backward cost* $g(n)$
- Greedy orders by goal proximity, or *forward cost* $h(n)$



- A* Search orders by the sum: $f(n) = g(n) + h(n)$

When should A* terminate?


- Should we stop when we enqueue a goal?



- No: only stop when we dequeue a goal



Is A* Optimal?



- What went wrong?
- Actual bad goal cost < estimated good goal cost
- We need estimates to be less than actual costs!



Admissible Heuristics

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Idea: Admissibility

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Inadmissible (pessimistic) heuristics
break optimality by trapping good plans
on the fringe

Admissible (optimistic) heuristics never
outweigh true costs




Admissible Heuristics

- A heuristic h is *admissible* (optimistic) if:

$$0 \leq h(n) \leq h^*(n)$$

where $h^*(n)$ is the shortest distance to the goal

- Examples:



- Coming up with admissible heuristics is most of what's involved in using A* in practice.



Optimality of A* Tree Search

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Optimality of A* Tree Search

- Heuristic function h is admissible
- Claim: A* tree search is optimal

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Optimality of A* Tree Search

Assume:

- A is an optimal goal node
- B is a suboptimal goal node
- h is admissible


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Claim:

- A will exit the fringe before B




Optimality of A* Tree Search: Blocking

Proof:

- Imagine B is on the fringe
- Some ancestor n of A is on the fringe, too (maybe A!)
- Claim: n will be expanded
 - 1. $f(n)$ is less or equal to $f(A)$

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro



$$f(n) = g(n) + h(n)$$

$$f(n) \leq g(A)$$

$$g(A) = f(A)$$

Definition of f-cost


Admissibility of h

$h = 0$ at a goal

Optimality of A* Tree Search: Blocking

Proof:

- Imagine B is on the fringe
- Some ancestor n of A is on the fringe, too (maybe A!)
- Claim: n will be expanded
 - 1. $f(n)$ is less or equal to $f(A)$
 - 2. $f(A) < f(B)$



$$g(A) < g(B)$$

$$f(A) < f(B)$$

B is suboptimal

$h = 0$ at a goal



Optimality of A* Tree Search: Blocking


Proof:

- Imagine B is on the fringe
- Some ancestor n of A is on the fringe, too (maybe A!)
- Claim: n will be expanded
 - 1. $f(n)$ is less or equal to $f(A)$
 - 2. $f(A)$ is less than $f(B)$
 - 3. n expands before B
- All ancestors of A expand before B
- A expands before B
- A* search is optimal

Assignment Project Exam Help


<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

$$f(n) \leq f(A) < f(B)$$



Properties of A*

Uniform-Cost



A*



UCS vs A* Contours



- Uniform-cost expands equally in all “directions”

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- A* expands mainly toward the goal, but does hedge its bets to ensure optimality




A* Applications


- Video games
- Pathing / routing problems
[Assignment](#) [Project](#) [Exam](#) [Help](#)
- Resource planning
- Robot motion plann <https://eduassistpro.github.io/>
- Language analysis [Add WeChat edu_assist_pro](#)
- Machine translation
- Speech recognition
- ...



Example: 8 Puzzle



Start State



Goal State

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A

- What are the states?
- How many states?
- What are the actions?
- How many successors from the start state?
- What should the costs be?



8 Puzzle I


- Heuristic: Number of tiles misplaced

- Why is it admissible?

- $h(\text{start}) = 8$

Assignment Project Exam Help

- This is a *relaxed-problem* <https://eduassistpro.github.io/>



Add WeChat `edu_assist_pro`

t State

Goal State

Average nodes expanded when the optimal path has...			
	...4 steps	...8 steps	...12 steps
UCS	112	6,300	3.6×10^6
TILES	13	39	227

Statistics from Andrew Moore

8 Puzzle II

- What if we had an easier 8-puzzle where any tile could slide any direction at any time, ignoring other tiles?

Assignment Project Exam Help

- Total *Manhattan* distance <https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro` state

Goal State

	Average nodes expanded when the optimal path has...	
TILES	...4 steps	...8 steps
MANHATTAN	12	25

Average nodes expanded when the optimal path has...

...4 steps ...8 steps ...12 steps

13 39 227

12 25 73

- Why is it admissible?

- $h(\text{start}) =$

$$3 + 1 + 2 + \dots = 18$$

8 Puzzle III

- How about using the *actual cost* as a heuristic?
 - Would it be admissible?
 - Would we save on nodes expanded?
 - What's wrong with it?

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

- With A*: a trade-off between quality of estimate and work per node
 - As heuristics get closer to the true cost, you will expand fewer nodes but usually do more work per node to compute the heuristic itself



Creating Admissible Heuristics

- Most of the work in solving hard search problems optimally is in coming up with admissible heuristics
- Often, admissible heuristics are solutions to *relaxed problems*, where <https://eduassistpro.github.io/>



15

- Inadmissible heuristics are often useful too (why?)



Trivial Heuristics, Dominance

- Dominance: $h_a \geq h_c$ if


$$\forall n : h_a(n) \geq h_c(n)$$

Assignment Project Exam Help $\max(h_a, h_b)$

- Heuristics form a <https://eduassistpro.github.io/>

- Max of admissibl

Add WeChat edu_assist_pro



- Trivial heuristics

- Bottom of lattice is the zero heuristic (what does this give us?)
- Top of lattice is the exact heuristic



Tree Search: Extra Work!

- Failure to detect repeated states can cause exponentially more work. Why?

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro



Graph Search

- In BFS, for example, we shouldn't bother expanding some nodes (which, and why?)

Assignment Project Exam Help



Graph Search

- Very simple fix: never expand a state type twice

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro




- Can this wreck completeness? Why or why not?
- How about optimality? Why or why not?



A* Graph Search Gone Wrong



Consistency of Heuristics



- Main idea: estimated heuristic costs \leq actual costs

- Admissibility: heuristic cost \leq actual cost to goal

Assignment Project Exam Help
 $h(A) \leq$ actual cost from A to G

<https://eduassistpro.github.io/> and cost \leq actual cost for each arc

Add WeChat $h(A)$ to G [edu_assist_pro](#)

- Consequences of consistency:

- The f value along a path never decreases

$$h(A) \leq \text{cost}(A \text{ to } C) + h(C)$$

$$f(A) = g(A) + h(A) \leq g(A) + \text{cost}(A \text{ to } C) + h(C) \leq f(C)$$

- A* graph search is optimal



Optimality of A* Graph Search

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Optimality of A* Graph Search

- Sketch: consider what A* does with a consistent heuristic:


Assignment Project Exam Help

- Fact 1: In tree search, A* expands nodes in increasing f contours
 $\text{https://eduassistpro.github.io/}$

Add WeChat edu_assist_pro

- Fact 2: For every state s , nodes that reach s optimally are expanded before nodes that reach s suboptimally

- Result: A* graph search is optimal



Optimality

- Tree search:
 - A* is optimal if heuristic is admissible
 - UCS is a special case ($h = 0$)

Assignment Project Exam Help

- Graph search:
 - A* optimal if heuristic is consistent
 - UCS optimal ($h = 0$ is consistent)
- Consistency implies admissibility
- In general, most natural admissible heuristics tend to be consistent, especially if from relaxed problems

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



A*: Summary

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



A*: Summary

- A* uses both backward costs and (estimates of) forward costs

Assignment Project Exam Help

- A* is optimal with consistent heuristics
<https://eduassistpro.github.io/>
- Heuristic design is key: often ~~Add WeChat edu_assist_pro~~ solved problems



Tree Search Pseudo-Code

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Graph Search Pseudo-Code

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro




Optimality of A* Graph Search

- Consider what A* does:
 - Expands nodes in increasing total f value (f-contours)
Reminder: $f(n) = g(n) + h(n)$ = cost to n + heuristic
 - Proof idea: the optimal f value, so it must get exp

Add WeChat edu_assist_pro

There's a problem with this argument.
What are we assuming is true?



Optimality of A* Graph Search

Proof:

- New possible problem: some n on path to G^* isn't in queue when we need it, because some worse n' for the same state dequeued and expanded
- Take the highest such <https://eduassistpro.github.io/>
- Let p be the ancestor of n that was on the queue when n' was popped
- $f(p) < f(n)$ because of consistency
- $f(n) < f(n')$ because n' is suboptimal
- p would have been expanded before n'
- Contradiction!

