

## CO526 Databases: Exercises

2018

In **family\_history** database, there is a **person** table, where people are identified by their name, and always have their gender, date of birth (**dob**) and place of birth (**born\_in**) recorded. In addition, each person may optionally have recorded the name of their father, and the name of their mother. If the person has died, then the date of death **dod** must be present. Note that only a fragment of the data held in the database is listed below.

person						
<u>name</u>	gender	dob	dod?	father?	mother?	born_in
Alice	F	1885-02-25	1969-12-05	null	null	Windsor
Andrew	M	1960-02-19	null	Philip	Elizabeth II	London
Andrew of Greece	M	1882-02-02	1944-12-03	George I of Greece	null	Athens
Anne (Princess)	F	1950-08-15	null	Philip	Elizabeth II	London
Charles	M	1948-11-14	null	Philip	Elizabeth II	London
Elizabeth II	F	1926-04-21	null	George VI	Elizabeth	London

⋮

$$\text{person}(\text{father}) \xrightarrow{fk} \text{person}(\text{name})$$

$$\text{person}(\text{mother}) \xrightarrow{fk} \text{person}(\text{name})$$

### Questions

In the following questions you can test for a value  $v$  being null using the predicate  $\text{isNull}(v)$ , and  $v$  being not null using  $\text{isNotNull}(v)$ . You may use subscripts on relation names to create aliases of relations, such that  $\text{person}_1$ ,  $\text{person}_2$ , etc. are aliases for **person**.

- Describe how you would enhance the database schema (with additional tables, columns, primary keys or foreign keys) to record the succession of a monarch, and ensure that we record the name of the monarch as **succ\_year**, and (ii) the name of the monarch.
- Write a query in each of the following languages that returns the scheme (**name**,**born\_in**) containing the name and place of birth of all people known to have been born in the same place as their mother.
  - RA
  - Datalog
- Write a query in each of the following languages that returns the scheme (**name**) containing names of all people known to be parents.
  - RA
  - Datalog
- Write a query in each of the following languages that returns the scheme (**name**) containing the names of all men not known to be fathers.
  - RA
  - Datalog
- Write a query in each of the following languages returning the scheme (**name**) listing those people that have had at least one child of each gender that appears in the database.

(a) RA

Note that the above answer does make the assumption that each person can be just a father, or just a mother. If you want to capture the concept of a person sometimes being a mother, and sometimes being a father, you would need a union on the LHS of each division.

(b) Datalog

6. Suppose the following RA query  $q$  has been executed:

$\pi_{\text{person}_b.\text{name}, \text{person}_a.\text{father}} \sigma_{\text{person}_a.\text{name}=\text{person}_b.\text{mother} \wedge \text{isNotNull}(\text{person}_a.\text{father})}(\text{person}_a \times \text{person}_b)$

(a) If the query has been executed at one point in time, since which  $\Delta$  row have been inserted into **person** to give  $\text{person}' = \text{person} \cup \Delta_p$ , give an RA query that returns any additional answers to the original query.

(b) If the enhancements requested in Question 1(a) have been added, how could your answer be improved?

7. Write an SQL query that returns the scheme (**name, born\_in**) ordered by **name** containing the name and place of birth of all people known to have been born in the same place as their mother.

8. Write an SQL query that returns the scheme (**name**) ordered by **name** containing the name of all people known to be parents.

9. Write an SQL query that returns the scheme (**name**) ordered by name that lists parents for whom all known children are of the same sex.

10. Suppose you have to design a new database to hold the following information about the companies that do business with ACME Computing Ltd. These companies may be customers, suppliers, or both. For all companies we record their name and contact email address, and for companies that are suppliers we also record their telephone number.

For suppliers, we record the sales manager that deals with the customer, and a credit limit. We also record all orders made by the customer. Each order is on a particular date, is given an order number, and has a reference number given by the customer. An order may have any number of stock items, with the quantity and price for each stock item recorded. When orders are sent, we record the tracking number of each parcel the order was sent in, and the date on which the parcel was sent. We also wish to record how much of each stock item was put in each parcel, in case the parcel gets lost and an insurance claim must be made. We record the delivery address for each order, from a record of delivery addresses, for which we record the customer name, postcode and address. We identify an address record by the combination of the customer name and postcode.

For customers, we record the sales manager that deals with the customer, and a credit limit. We also record all orders made by the customer. Each order is on a particular date, is given an order number, and has a reference number given by the customer. An order may have any number of stock items, with the quantity and price for each stock item recorded.

When orders are sent, we record the tracking number of each parcel the order was sent in, and the date on which the parcel was sent. We also wish to record how much of each stock item was put in each parcel, in case the parcel gets lost and an insurance claim must be made. We record the delivery address for each order, from a record of delivery addresses, for which we record the customer name, postcode and address. We identify an address record by the combination of the customer name and postcode.

(a) Design an ER<sup>ADHKLMNOSVW</sup> schema to represent this new database.

(b) Map the ER schema you designed in (i) into a relational schema.

11. Suppose that a relation  $R(A, B, C, D, E, F, G, H)$  has the functional dependency set  $S = \{A \rightarrow BE, AC \rightarrow G, AFG \rightarrow E, B \rightarrow ACG, CF \rightarrow D, D \rightarrow G, DEG \rightarrow FCD, G \rightarrow H\}$

(a) Compute a minimum cover  $S_c$  of  $S$ .

- (b) Identify and justify all the candidate keys of  $R$ .
- (c) Decompose the relation  $R$  into 3NF.
- (d) Decompose the relation  $R$  into BCNF.

12. The following histories describe the sequence of operations performed respectively by four transactions  $T_1$ – $T_4$ .

$H_1 = r_1[c_{CZ}], r_1[c_R], r_1[c_B], r_1[c_{GB}], c_1$   
 $H_2 = r_2[c_B], r_2[c_R], r_2[c_{CZ}], w_2[c_{CZ}], c_2$   
 $H_3 = r_3[c_B], w_3[c_B], r_3[c_{CZ}], w_3[c_{CZ}], c_3$   
 $H_4 = w_4[c_R], w_4[c_B], w_4[c_{GB}], c_4$

- (a) Briefly explain if the following concurrent execution is serialisable and recoverable. If non-serialisable, explain what anomaly occurs.

$H_a = r_1[c_{CZ}], r_1[c_R], r_3[c_B], w_3[c_B], r_3[c_{CZ}], w_3[c_{CZ}],$   
 $r_1[c_B], r_1[c_{GB}], c_1, c_3,$

- (b) Briefly explain if the following concurrent execution is serialisable and recoverable. If non-serialisable, explain what anomaly occurs.

$H_b = r_3[c_B], w_4[c_R], w_4[c_B], w_4[c_{GB}], w_3[c_B],$   
 $r_3[c_{CZ}], w_3[c_{CZ}], c_4, c_3$

- (c) Briefly explain if the following concurrent execution is serialisable and recoverable. If non-serialisable, explain what anomaly occurs.

$H_c = r_1[c_{CZ}], w_4[c_R], r_1[c_R], w_4[c_B], r_1[c_B], w_4[c_{GB}], c_4, r_1[c_{GB}], c_1$

- (d) Briefly explain which (if any) pair of the transactions taken from  $T_1$ – $T_4$  will be serialisable for all concurrent executions of the pair, and also briefly explain which (if any) pair of the transactions taken from  $T_1$ – $T_4$  will be recoverable for all concurrent executions of the pair.

- (e) Give a concurrent execution of all four transactions that uses a deadlock involving all four transactions.

13. The table below lists the contents of a database log, which keeps DO records on a table country.

UNDO	$w_1[c_R, \text{population} = 148,579,000]$	na	area	population
UNDO	$w_4[c_{TR}, \text{population} = 62,481,123]$	Czech Republic	CZ	Prague 78,703 10,321,120
UNDO	$w_2[c_{CH}, \text{population} = 7,392,444]$	Switzerland	CH	Bern 41,290 7,207,060
UNDO	$w_2[c_{GB}, \text{population} = 58,543,111]$	Russia	R	Moscow 17,075,200 148,178,487
UNDO	$w_3[c_{CH}, \text{population} = 7,312,222]$	Belgium	B	Brussels 30,510 10,170,241
UNDO	$w_5[c_{CH}, \text{population} = 7,210,000]$	Turkey	TR	Ankara 780,580 62,484,478
LOG	$c_4$	United Kingdom	GB	London 244,820 58,489,975
UNDO	$w_3[c_B, \text{population} = 11,020,000]$	Egypt	ET	Cairo 1,001,450 63,575,107
LOG	$c_3$			:

- (a) If the country table has the contents illustrated above, describe the actions performed by the recovery procedure using the above log, and what population figures will be left after recovery.
- (b) If an additional LOG record were added for  $a_5$  to record the completion of aborting  $T_5$ , would your answer to (a) change, and if so, how does it change?
- (c) Considering the time just after when  $c_4$  occurs, describe and justify which updates from the above log must have been written to disc, which might have been written to disc, and which must not have been written to disc.