

Parallel Computing with GPUs:

Assignment Project Exam Help

Op on
<https://eduassistpro.github.io/>

Dr Paul Ric

<http://paulrichmond.shef.ac.uk> Add WeChat [edu_assist_pro](https://eduassistpro.github.io/) COM4521/



The
University
Of
Sheffield.

 NVIDIA

GPU
RESEARCH
CENTER

Last Lecture

- ❑ All about memory, pointers and storage
- ❑ We have seen that C is a low level language
- ❑ Now we would like to consider what makes a program fast.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

This Lecture

- ❑ Optimisation Overview
- ❑ Compute Bound
- ❑ Memory Bound

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

When to Optimise

☐ Is your program complete?

☐ If not then don't start optimising

☐ If you haven't started coding then don't try to perform advanced optimisations until its complete

☐ This might be counter intuitive

☐ Is it worth it?

☐ Is your code already f

☐ Are you going to optimise the right bi

☐ What are the likely benefits? Is it cost

☐ $(\text{number of runs} \times \text{number of users} \times \text{time savings} \times \text{user's salary})$
- $(\text{time spent optimizing} \times \text{programmer's salary})$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

*“Programmers waste enormous amounts of time thinking about, or worrying about, the speed of noncritical parts of their programs, and these attempts at efficiency actually have a strong negative impact when debugging and maintenance are considered. We should forget about small efficiencies, say about 97% of the time: **premature optimization** is the root of all evil. Yet we should not pass up our opportunities in that critical 3%.”* Donald Knuth, Computer Programming as an Art (1974)

First step: Profiling

- ❑ Which part of the program is the bottleneck
 - ❑ This may be obvious if you have a large loop
 - ❑ May be less obvious in a complicated program or procedure
- ❑ Manually profiling using `time()` function
 - ❑ We can time critical a g the time command
 - ❑ This gives us insight in <https://eduassistpro.github.io/>ecute.
- ❑ Profiling using a profiler
 - ❑ Unix: gprof
 - ❑ VS2017: Built in profiler

Profiling with clock() – Windows only

- ❑ `#include time.h`
- ❑ The `clock()` function returns a `clock_t` value the number of clock ticks elapsed since the program was launched
- ❑ To calculate the time in seconds divide by `CLOCKS_PER_SEC`

```
clock_t begin, end;  
float seconds;  
  
begin = clock();  
func();  
end = clock();  
  
seconds = (end - begin) / (float)CLOCKS_PER_SEC;
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

VS2017 Profiling Example

❑ Debug->Performance and Diagnostics

❑ Start

❑ Select CPU Sampling, Finish (or next and select project)

❑ No Data? Your program might not run for long enough to sample

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

VS2017 Profiling Example

☐ Samples

- ☐ The profiler interrupts at given time intervals to collect information on the stack

- ☐ Default sampling is 10,000,000 clock cycles

☐ Inclusive Samples

- ☐ Time samples including

☐ Exclusive Samples

- ☐ Time samples excluding any sub calls

☐ Hot Path

- ☐ Slowest path of execution through the program

- ☐ **Best candidate for optimisation**

- ☐ Select the function for a line-by-line breakdown of sampling percentage

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Compute vs Memory Bound

☐ Compute bound

- ☐ Performance is limited by the speed of the CPU
- ☐ CPU usage is high: typically 100% for extended periods of time

☐ Memory Bound **Assignment Project Exam Help**

- ☐ Performance is limited
- ☐ CPU usage might be low
- ☐ Typically the cache usage will be poor
 - ☐ poor hit rate if fragmented or random accesses

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

❑ Optimisation Overview

❑ Compute Bound

❑ Memory Bound

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Compute Bound: Optimisation

❑ Approach 1: Compile with full optimisation

- ❑ msvc compiler is very good at optimising code for efficiency
- ❑ Many of the techniques we will examine can be applied automatically by a compiler.

❑ Optimisation: Compile

❑ Help the compiler

- ❑ Refactor code to make it clear (clear to u a compiler)

- ❑ Avoid complicated control flow

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Optimisation Level	Description
/O1	Optimises code for minimum size
/O2	Optimises code for maximum speed
/Od	Disables optimisation for debugging
/Oi	Generates intrinsic functions for appropriate calls
/Og	Enables global optimisations

Compute Bound: Optimisation

- ❑ Approach 2: Redesign the program
 - ❑ Compilers cant do this and it is most likely to have the biggest impact
 - ❑ If you have a loop that is executed 1000's of times then find a way to do it without the loop.
 - ❑ Be familiar with algorithms
 - ❑ Understand big $O(n)$ n
 - ❑ E.g. Sequential search

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro [://bigocheatsheet.com/](https://bigocheatsheet.com/)

Compute Bound: Optimisations

❑ Approach 3: Understand operation performance

❑ Cost of going to disk is massive

❑ Loop Invariant Computations: move operations out of loops where possible

❑ Strength reduction: replace expression with cheaper ones

Assignment Project Exam Help

Core i7 Instruction	https://eduassistpro.github.io/
Integer ADD SUB (x32 and x64)	1
Integer MUL (x32 and x64)	3
Integer DIV (x32)	17-28
Integer DIV (x64)	28-90
Floating Point ADD SUB (x32)	3
Floating Point MUL (x32)	5
Floating Point DIV (x32)	7-27

Add WeChat edu_assist_pro

http://www.agner.org/optimize/instruction_tables.pdf

Compute Bound: Optimisations

❑ Approach 4: function in-lining

❑ In-lining increases code size but reduces function calls.

❑ Make your simple function a macro

❑ Use the `_inline` operator

❑ Be sensible: Not everything should be in-lined

Assignment Project Exam Help

```
float vec2f_len(vec2f a, vec2f b)
{
    vec2f r;
    r.x = a.x - b.x;
    r.y = a.y - b.y;
    return (float)sqrt(r.x*r.x + r.y*r.y); //requires #include <math.h>
}
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
#define vec2f_len(a, b) ((float)sqrt((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y)))
```

```
_inline float vec2f_len(vec2f a, vec2f b)
{
    return (float)sqrt((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y));
}
```

Compute Bound: Optimisations

❑ Approach 5: Loop unrolling

❑ msvc can do this automatically

❑ Reduces the number of branch executions

```
for (int i=0; i<100; i++) {  
    some_function(i);  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

```
for (int i=0; i<100;) {  
    some_function(i); i++;  
    some_function(i); i++;  
    some_function(i); i++;  
    some_function(i); i++;  
    some_function(i); i++;  
    some_function(i); i++;  
    some_function(i); i++;  
    some_function(i); i++;  
    some_function(i); i++;  
    some_function(i); i++;  
}
```

Add WeChat edu_assist_pro

Compute Bound: Optimisations

❑ Approach 6: Loop jamming

❑ Combine adjacent loops to minimise branching (for ranges over the same variable)

❑ E.g. Reduction of iterating and testing value i

```
for (i=0; i<dim, i++){  
    for (j=0; j<dim; j++){  
        matrix[i][j] = rand()  
    }  
}  
for (i=0; i<dim, i++){  
    matrix[i][i] = 0;  
}
```

```
for (i=0; i<dim, i++){  
    for (j=0; j<dim; j++){  
        matrix[i][j] = rand();  
    }  
    matrix[i][i] = 0;  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Compute Bound: Optimisations

❑ Approach 6: Global or heap variables

❑ Avoid referencing global or heap variables from within loops

- ❑ Global variables can not be cached in registers
- ❑ Better to write to a local variable

❑ Make a local copy of t be cached

- ❑ Be careful that nothing else requires the variable before you modify it

```
int count;

void test1(void)
{
    int i;
    for(i=0;i<N;i++){
        count += f();
    }
}

void test2(void)
{
    int i, local_count;
    local_count = count;
    for(i=0;i<N;i++){
        local_count += f();
    }
    count = local_count;
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Compute Bound: Optimisations

❑ Approach 7: Function calls

❑ Functions are a good way of modularising code

❑ Function calls do however have an overhead

❑ Stack and program counter must be manipulated

❑ It can be beneficial to

Assignment Project Exam Help
loops

```
void f()  
{  
    //lots of work  
}  
  
void test_f()  
{  
    int i;  
    for(i=0;i<N;i++){  
        f();  
    }  
}
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
{  
    int i;  
    for(i=0;i<N;i++){  
        //lots of work  
    }  
}  
  
void test_g()  
{  
    g();  
}
```

Compute Bound: Optimisations

❑ Approach 8: Don't over use the stack

❑ Loops rather than recursion

- ❑ C compilers are very good at optimising loops

- ❑ Only certain recursive functions can be optimised

- ❑ Function calls increase stack usage

❑ Avoid compile time all

- ❑ E.g. `int x[100000]`

- ❑ Use the **heap** or global arrays

❑ Avoid passing large structures as argument

- ❑ They are copied by value

- ❑ Pass a pointer instead

r arrays on the stack

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

❑ Optimisation Overview

❑ Compute Bound

❑ Memory Bound

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Memory Bound: Optimisation


❑ Approach 1: Locality of data access

- ❑ This is by far the most important consideration
- ❑ CPU cache is small amount of very fast hierarchical memory
 - ❑ Holds contents of recently accessed memory locations
 - ❑ MUCH faster than main memory (orders of magnitude)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Memory Bound: Optimisation (Locality)

- ❑ Memory is read in cache lines of 64 bytes
 - ❑ Accessing a single bytes requires movement of the entire cache line
 - ❑ Reading patterns with common locality within cache lines reduced memory movement
 - ❑ Fewer wait (or idle) cycles
- ❑ Memory lines are pre-fetched
 - ❑ Predictable access patten
 - ❑ Linear access patterns are predictable and good locality)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Memory Bound: Optimisation

❑ Approach 2: Column major access

❑ A special case of approach 1

❑ Important for FORTRAN users.

❑ Column major access has poor utilisation of cache lines

❑ Despite predictability only a single value from each cache line is accessed

❑ The alternative: row

❑ Iterate the righter most index first

❑ Good utilisation of the cache line

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
float array[N][M];
int i, j;

for (j = 0; j < M; j++){
    for (i = 0; i < N; i++){
        array[i][j] = 0.0f;
    }
}
```

No!





Memory Bound: Optimisation

❑ Approach 3: Nice structures

❑ Make your structures cache friendly

- ❑ Multiples of cache size

- ❑ Structures are padded: $\text{Zp (Struct Member Alignment)}$: default

- ❑ Any member whose size is less than 8 bytes will be at an offset that is a multiple of its own size based on the la

- ❑ any member whose size is less than 8 bytes will be at an offset that is a multiple of 8 bytes

❑ Reduce struct size as a result of padding

- ❑ Arrange similar sized structure elements

❑ Increase struct size to help padding

- ❑ Add chars at the end of your structure to help it align with cache line size

```
struct sa{  
    int a;  
    char b;  
    int c;  
    char d;  
};
```

```
struct sb{  
    int a;  
    int c;  
    char b;  
    char d;  
};
```

What is the size of each struct?

Memory Bound: Optimisation

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
struct sa{          /* 16 bytes
total */
int a;             /* 4 bytes */
char b;            /* 1 byte */
char pad[3];       /* 3 bytes */
int c;             /* 4 bytes */
char d;            /* 1 byte */
char pad[3];       /* 3 bytes */
};
```

```
struct sa{
    int a;
    char b;
    int c;
    char d;
};
```

sizeof(): 16

```
struct sb{          /* 12 bytes
total */
int c;             /* 4 bytes */
char b;            /* 1 byte */
char d;            /* 1 byte */
char pad[2];       /* 2 bytes */
};
```

```
struct sb{
    int a;
    int c;
    char b;
    char d;
};
```

sizeof(): 12

Further Reading:

<http://www.catb.org/esr/structure-packing/>

Summary

- ❑ Profiling can be used to tell us where programs spend time
- ❑ Time critical sections are candidates for optimisation
- ❑ Optimisations can be used to improve both compute and memory bound applications
- ❑ Most obvious optimisations are to replace one algorithm with another
- ❑ The msvc compiler performs many optimisations but careful coding can help it
- ❑ Always try and have good locality of memory accesses to improve cache usage
- ❑ Optimisation requires lots of trial and error!