

# SQL Basics Cheat Sheet

## SQL

**SQL**, or *Structured Query Language*, is a language to talk to databases. It allows you to select specific data and to build complex reports. Today, SQL is a universal language of data. It is used in practically all technologies that process data.

## SAMPLE DATA

COUNTRY				
id	name	population	area	
1	France	66600000	640680	
2	Germany	80700000	357000	
...	...	...	...	

CITY				
id	name	country_id	population	rating
1	Paris	1	2243000	5
2	Berlin	2	3460000	3
...	...	...	...	...

## QUERYING SINGLE TABLE

Fetch all columns from the country table:

```
SELECT *
FROM country;
```

Fetch id and name columns from the city table:

```
SELECT id, name
FROM city;
```

Fetch city names sorted by the rating column in the default ASCending order:

```
SELECT name
FROM city
ORDER BY rating [ASC];
```

Fetch city names sorted by the rating column in the DESCending order:

```
SELECT name
FROM city
ORDER BY rating DESC;
```

## ALIASES

### COLUMNS

```
SELECT name AS city_name
FROM city;
```

### TABLES

```
SELECT co.name, ci.name
FROM city AS ci
JOIN country AS co
ON ci.country_id = co.id;
```

## FILTERING THE OUTPUT

### COMPARISON OPERATORS

Fetch names of cities that have a rating above 3:

```
SELECT name
FROM city
WHERE rating > 3;
```

Fetch names of cities that are neither Berlin nor Madrid:

```
SELECT name
FROM city
WHERE name != 'Berlin'
AND name != 'Madrid';
```

### TEXT OPERATORS

Fetch names of cities that start with a 'P' or end with an 's':

```
SELECT name
FROM city
WHERE name LIKE 'P%'
OR name LIKE
```

Fetch names of cities that contain 'ublin' (like Dublin in Ireland):

```
SELECT name
FROM city
WHERE name LIKE '%ublin%';
```

### OTHER OPERATORS

Fetch names of cities that have a population between 500K and 5M:

```
SELECT name
FROM city
WHERE population BETWEEN 500000 AND 5000000;
```

Fetch names of cities that don't miss a rating value:

```
SELECT name
FROM city
WHERE rating IS NOT NULL;
```

Fetch names of cities that are in countries with IDs 1, 4, 7, or 8:

```
SELECT name
FROM city
WHERE country_id IN (1, 4, 7, 8);
```

## QUERYING MULTIPLE TABLES

### INNER JOIN

**JOIN** (or explicitly **INNER JOIN**) returns rows that have matching values in both tables.

```
SELECT city.name, country.name
FROM city
[INNER] JOIN country
ON city.country_id = country.id;
```

CITY			COUNTRY	
id	name	country_id	id	name
1	Paris	1	1	France
2	Berlin	2	2	Germany
3	Warsaw	4	3	Iceland

### LEFT JOIN

**LEFT JOIN** returns all rows from the left table with corresponding rows from the right table. If there's no as values from the second

CITY			COUNTRY	
id	name	country_id	id	name
1	Paris	1	1	France
2	Berlin	2	2	Germany
3	Warsaw	4	NULL	NULL

### RIGHT JOIN

**RIGHT JOIN** returns all rows from the right table with corresponding rows from the left table. If there's no matching row, **NULLS** are returned as values from the left table.

```
SELECT city.name, country.name
FROM city
RIGHT JOIN country
ON city.country_id = country.id;
```

CITY			COUNTRY	
id	name	country_id	id	name
1	Paris	1	1	France
2	Berlin	2	2	Germany
NULL	NULL	NULL	3	Iceland

### FULL JOIN

**FULL JOIN** (or explicitly **FULL OUTER JOIN**) returns all rows from both tables – if there's no matching row in the second table, **NULLS** are returned.

```
SELECT city.name, country.name
FROM city
FULL [OUTER] JOIN country
ON city.country_id = country.id;
```

CITY			COUNTRY	
id	name	country_id	id	name
1	Paris	1	1	France
2	Berlin	2	2	Germany
3	Warsaw	4	NULL	NULL
NULL	NULL	NULL	3	Iceland

### CROSS JOIN

**CROSS JOIN** returns all possible combinations of rows from both tables. There are two syntaxes available.

```
SELECT city.name, country.name
FROM city
CROSS JOIN country;
```

```
SELECT city.name, country.name
FROM city, country;
```

CITY			COUNTRY	
id	name	country_id	id	name
1	Paris	1	1	France
1	Paris	1	2	Germany
2	Berlin	2	1	France
2	Berlin	2	2	Germany

### NATURAL JOIN

**NATURAL JOIN** will join tables by all columns with the same name.

```
SELECT city.name, country.name
FROM city
NATURAL JOIN country;
```

CITY			COUNTRY	
country_id	id	name	name	id
6	6	San Marino	San Marino	6
7	7	Vatican City	Vatican City	7
5	9	Greece	Greece	9
10	11	Monaco	Monaco	10

**NATURAL JOIN** used these columns to match rows: **city.id, city.name, country.id, country.name**  
**NATURAL JOIN** is very rarely used in practice.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# SQL Basics Cheat Sheet

## AGGREGATION AND GROUPING

GROUP BY **groups** together rows that have the same values in specified columns. It computes summaries (aggregates) for each unique combination of values.

CITY		
id	name	country_id
1	Paris	1
101	Marseille	1
102	Lyon	1
2	Berlin	2
103	Hamburg	2
104	Munich	2
3	Warsaw	4
105	Cracow	4



CITY	
country_id	count
1	3
2	3
4	2

## AGGREGATE FUNCTIONS

- **avg**(expr) – average value for rows within the group
- **count**(expr) – count of values for rows within the group
- **max**(expr) – maximum value within the group
- **min**(expr) – minimum value within the group
- **sum**(expr) – sum of values within the group

## EXAMPLE QUERIES

Find out the number of cities:

```
SELECT COUNT(*)  
FROM city;
```

Find out the number of cities with non-null ratings:

```
SELECT COUNT(rating)  
FROM city;
```

Find out the number of distinctive country values:

```
SELECT COUNT(DISTINCT country_id)  
FROM city;
```

Find out the smallest and the greatest country populations:

```
SELECT MIN(population), MAX(population)  
FROM country;
```

Find out the total population of cities in respective countries:

```
SELECT country_id, SUM(population)  
FROM city  
GROUP BY country_id;
```

Find out the average rating for cities in respective countries if the average is above 3.0:

```
SELECT country_id, AVG(rating)  
FROM city  
GROUP BY country_id  
HAVING AVG(rating) > 3.0;
```

## SUBQUERIES

A subquery is a query that is nested inside another query, or inside another subquery. There are different types of subqueries.

### SINGLE VALUE

The simplest subquery returns exactly one column and exactly one row. It can be used with comparison operators =, <, <=, >, or >=.

This query finds cities with the same rating as Paris:

```
SELECT name FROM city  
WHERE rating = (  
    SELECT rating  
    FROM city  
    WHERE name = 'Paris'  
);
```

### MULTIPLE VALUES

A subquery can also return multiple columns or multiple rows. Such subqueries can be used with operators IN, EXISTS, SOME, or ANY.

This query finds cities in countries that have a population above 20M:

```
SELECT name
```

```
);
```

### CORRELATED

A correlated subquery refers to the table(s) introduced. A subquery depends on the outer query. It cannot be a query.

This query finds cities with a population greater than the average population in the country:

```
SELECT *  
FROM city main_city  
WHERE population > (  
    SELECT AVG(population)  
    FROM city average_city  
    WHERE average_city.country_id = main_city.country_id  
);
```

This query finds countries that have at least one city:

```
SELECT name  
FROM country  
WHERE EXISTS (  
    SELECT *  
    FROM city  
    WHERE country_id = country.id  
);
```

## SET OPERATIONS

Set operations are used to combine the results of two or more queries into a single result. The combined queries must return the same number of columns and compatible data types. The names of the corresponding columns can be different.

CYCLING		
id	name	country
1	YK	DE
2	ZG	DE
3	WT	PL
...	...	...

SKATING		
id	name	country
1	YK	DE
2	DF	DE
3	AK	PL
...	...	...

### UNION

UNION combines the results of two result sets and removes duplicates. UNION ALL doesn't remove duplicate rows.

This query displays German cyclists together with German skaters:

```
SELECT name  
FROM cycling  
WHERE country = 'DE'  
UNION / UNION ALL  
SELECT name  
FROM skating  
WHERE country = 'DE';
```

### INTERSECT

INTERSECT returns only rows that appear in both result sets.

This query displays German cyclists who are also German skaters at the same time:

```
SELECT name  
FROM cycling  
WHERE country = 'DE'  
INTERSECT  
SELECT name  
FROM skating  
WHERE country = 'DE';
```

### EXCEPT

EXCEPT returns only the rows that appear in the first result set but do not appear in the second result set.

This query displays German cyclists unless they are also German skaters at the same time:

```
SELECT name  
FROM cycling  
WHERE country = 'DE'  
EXCEPT / MINUS  
SELECT name  
FROM skating  
WHERE country = 'DE';
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro