

COMP 250

Assignment Project Exam Help

INTRODUC TER SCIENCE

<https://eduassistpro.github.io/>

Week 4-4: QOD7

Add WeChat edu_assist_pro

Giulia Alberini, Fall 2020

WHAT ARE WE GOING TO DO IN THIS VIDEO?



OOD7

Assignment Project Exam Help

- instanceof

<https://eduassistpro.github.io/>

- Intro to Polymorphism

Add WeChat edu_assist_pro

- Abstract Classes and Methods

A LITTLE ABOUT instanceof

- The instanceof operator is used to test whether an object is an instance of the specified type.

Assignment Project Exam Help

- It returns either true or false when used with any variable that has a null value.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
Dog myDog = new Dog();  
Beagle snoopy = new Beagle();  
Dog aDog = null;  
System.out.println(myDog instanceof Dog); // true  
System.out.println(snoopy instanceof Dog); // true  
System.out.println(aDog instanceof Dog); // false
```

instanceof AND DOWNCASTING

- When can use instanceof to make sure that downcasting to a subclass will not cause a run time error.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
public static void myMethod(Dog myDog) {  
    if(myDog instanceof Beagle) {  
        Beagle b = (Beagle) myDog; // downcasting  
        b.hunt();  
    }  
}
```

instanceof AND equals ()

- Note that in general we want to use `instanceof` as a last resort. We'll see why shortly.
- That said, we have to use `instanceof` when overriding `equals ()`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
public class
    Person owner;
    :
    public boolean equals(Object obj) {
        if(obj instanceof Dog) {
            ...
        }
    }
}
```



WHERE WE LEFT OFF

class Dog

Person owner

```
public void bark() {  
    print("woof!");  
}
```

:

↑ extends

class Beagle

void hunt ()

```
public void bark() {  
    print("aowwwuuu");  
}
```

:

```
public class Test {  
    public static void main(String[] args) {  
        log.silly(new Beagle());  
    }  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Is this
allowed??

If so, which
bark() will
execute???

Yes, it's an
example of
upcasting!

Assignment Project Exam Help

P

M

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

POLYMORPHISM

- Each object can have different “forms”.


Assignment Project Exam Help

- One important aspect of <https://eduassistpro.github.io/> “the Java virtual machine (JVM) calls the appropriate method for that is referred to in each variable. It does not call the method th d by the variable's type”.

Add WeChat edu_assist_pro

- More general discussion about polymorphism in higher level courses.
(e.g. COMP 302)

RECALL HIERARCHY FROM OUR EXAMPLES



EXAMPLE

```
Dog myDog = new Dog();
```

```
myDog.bark();
```

```
Dog snoopy = new Beagle();
```

```
snoopy.bark();
```

OUTPUT

```
woof!
```

```
aowwwuuu
```

The compiler sees `bark()` in the `Dog` class (myDog is of type `Dog`) at compile time, the JVM invokes `bark()` from the `Dog` class at runtime (snoopy points to an object of type `Dog`).

At compile time, the compiler uses `bark()` in the `Dog` class to validate the statement. At runtime, however, the JVM invokes `bark()` from the `Beagle` class. (snoopy is actually referring to a `Beagle` object)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

THE "OO WAY"

- Favor polymorphism and dynamic binding to downcasting and `instanceOf`. **Assignment Project Exam Help**

<https://eduassistpro.github.io/>

- From *Effective C++*, by Scott Meyers
Add WeChat edu_assist_pro

"Anytime you find yourself writing code of the form 'if the object is of type T1, then do something, but if it's of type T2, then do something else', slap yourself".

TRY IT!

- Let's go back to our Shape classes. On the first video I suggested you to `Info()` in the Shape class and override `gle`. Let's then create an array of Shapes and see how polymorphism works when displaying the info of the elements in the array.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

LET'S LOOK AT AN EXAMPLE

- Suppose we created the following two classes to work with Circles and Triangles.

Assignment Project Exam Help

Circle

```
- color: String
- radius: double
+ getColor(): String
+ setColor(c:String)
+ getRadius():double
+ getArea(): double
```

<https://eduassistpro.github.io/>

~~- color: String~~
Add WeChat edu_assist_pro

```
- base: double
- height: double
+ getColor(): String
+ setColor(c:String)
+getArea(): double
```

LET'S LOOK AT AN EXAMPLE

- Suppose we created the following two classes to work with Circles and Triangles.

Assignment Project Exam Help

Circle

```
- color: String
- radius: double
+ getColor(): String
+ setColor(c:String)
+ getRadius():double
+ getArea(): double
```

<https://eduassistpro.github.io/>

```
- color: String
- base: double
- height: double
+ getColor(): String
+ setColor(c:String)
+getArea(): double
```

Observations:

- The two classes are closely related. They are both used to represent geometrical shapes.

LET'S LOOK AT AN EXAMPLE

- Suppose we created the following two classes to work with Circles and Triangles.

Assignment Project Exam Help

Circle

```
- color: String
- radius: double
+ getColor(): String
+ setColor(c:String)
+ getRadius():double
+ getArea(): double
```

<https://eduassistpro.github.io/>

```
- color: String
- base: double
- height: double
+ getColor(): String
+ setColor(c:String)
+ getArea(): double
```

Observations:

- There's code that is repeated: the two classes share fields and methods that are implemented in the same way.

LET'S LOOK AT AN EXAMPLE

- Suppose we created the following two classes to work with Circles and Triangles.

Assignment Project Exam Help

Circle

```
- color: String
- radius: double
+ getColor(): String
+ setColor(c:String)
+ getRadius():double
+ getArea(): double
```

<https://eduassistpro.github.io/>

```
- color: String
- base: double
- height: double
+ getColor(): String
+ setColor(c:String)
+ getArea(): double
```

Observations:

- There's a method that serves the same purpose in both classes, but it's implemented differently depending on the class.

LET'S LOOK AT AN EXAMPLE

- Suppose we created the following two classes to work with Circles and Triangles.

Assignment Project Exam Help

Circle

```
- color: String
- radius: double
+ getColor(): String
+ setColor(c:String)
+ getRadius():double
+ getArea(): double
```

<https://eduassistpro.github.io/>

```
- color: String
- base: double
- height: double
+ getColor(): String
+ setColor(c:String)
+ getArea(): double
```

Observations:

- There are fields and methods that are specific to each class.

LET'S LOOK AT AN EXAMPLE

- Suppose we created the following two classes to work with Circles and Triangles.

Assignment Project Exam Help

Circle

```
- color: String
- radius: double
+ getColor(): String
+ setColor(c:String)
+ getRadius():double
+ getArea(): double
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
- color: String
- base: double
- height: double
+ getColor(): String
+ setColor(c:String)
+getArea(): double
```

Observations:

- It is the perfect situation to create an abstract superclass!

abstract METHODS

- If you want a class to contain a particular method, but you would like the implementation of this method to be specified by the subclasses, then you can declare the method to be **abstract**.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- An abstract method is a method that is without implementation:

Add WeChat edu_assist_pro

```
public abstract double getArea ();
```

The method has no body! Instead of the curly braces, we use the semicolon at the end of the header.

abstract METHODS

Declaring a method as abstract has 2 consequences:

Assignment Project Exam Help

- The class containing <https://eduassistpro.github.io/> abstract.

Add WeChat edu_assist_pro

- Every subclass of the current class **MUST** either override the abstract method or declare it itself as abstract.

abstract CLASSES

- An abstract class must be declared using the `abstract` keyword.

- It can have `abstract` and `non-abstract` methods.

<https://eduassistpro.github.io/>

- It cannot be instant


Add WeChat `edu_assist_pro`

- It can have constructors and static methods.
- It can have `final` methods which will force the subclass not to change the body of the method

abstract CLASSES – OBSERVATIONS

- We can have abstract classes with no abstract methods. This allow us to create instantiated, but can only be inherited <https://eduassistpro.github.io/>
Add WeChat edu_assist_pro
- We cannot instantiate an abstract class, but we can define constructors. These constructors are called when an instance of a subclass is created.

BACK TO OUR EXAMPLE



TRY IT!

- Go back to the Shape class and modified it by adding an abstract `getArea()` method

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Add constructors to t

Add WeChat edu_assist_pro

- Play around with the classes!

An orange paint roller with a red handle, positioned horizontally. The roller is partially filled with orange paint, and there are orange paint splatters and drips around it. The background features faint, concentric circles and a horizontal line.

Coming Soon

Assignment Project Exam Help

In the next

- Linear d <https://eduassistpro.github.io/> s and linked lists!

Add WeChat edu_assist_pro