

# COMP 250

## INTRODUCTORY SCIENCE

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Week 13-1 Add WeChat edu\_assist\_pro

Giulia Alberini, Fall 2020

Slides adapted from Michael Langer's

# WHAT ARE WE GOING TO DO IN THIS VIDEO?




- **Maps**

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## MAP (MATHEMATICS)



A map is a set of pairs  $\{ (x, f(x)) \}$ .

Each  $x$  in domain maps to exactly one  $f(x)$  in codomain, but it can happen that  $f(x_1) = f(x_2)$  for different  $x_1, x_2$ , i.e. many-to-one.

## FAMILIAR EXAMPLES

Calculus 1 and 2 ("functions"):  
Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro  
Asymptotic complexity in CS:

$t$  : input size  $\rightarrow$  number of steps in a algorithm.

# MAPS IN EVERYDAY LIFE

The term "map" commonly refers to a 2D spatial representation of a region of the earth's surface.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

map(x, y) : position in image → position in 2D Montreal

Add WeChat edu\_assist\_pro

## COLOR MAP

The color map representing the USA election results in 2020.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

$\text{vote\_result} : \text{US\_state} \rightarrow \{\text{D}, \text{R}\}$

# RESTAURANT MENU

menu : dish\_name → price

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## INDEX IN A BOOK

index : term → list of pages


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro




## MAP (ADT)




A map is a set of (key, value) pairs.  
For each key, there is at most one value.

## MAP (ADT)




Note that it is possible for two keys to map to the same value.

## MAP (ADT)



It is NOT allowed for one key to map to two different values! The example above is NOT a map.


## MAP ENTRIES



The black dots here indicate objects (or potential objects) of type K or V that are *not* in the map.

Each (key, value) pair is called an *entry*. In this example, there are four entries.

## EXAMPLE



In COMP 250 this semester, the above mapping has ~650 entries.  
Most McGill students are not taking COMP 250 this semester.

Student ID also happens to be part of the student record.

## MAP ADT

`put( key, value )`

// Add the entry (key, value) to the map. If the map previously contained an entry with key, the old value is replaced by the specified value.

Assignment Project Exam Help

<https://eduassistpro.github.io/>


`get(key)`

// Returns the value mapped to the specified key if the key is mapped. Why not `get(key, value)` ?

`remove(key)`


// Removes the entry with the specified key.  
Returns true if the entry was removed, false otherwise.

## DATA STRUCTURES FOR MAPS



How to organize a set of (**key**, **value**) pairs, i.e. entries ?

# ARRAY LIST



How can we implement the following methods?

`put( key, value )`

`get( key )`  
`remove( key )`

`put()` would be  $O(1)$ , while `get()` and `remove()` would be  $O(n)$


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# SINGLY (OR DOUBLY) LINKED LIST



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

How can we implement the following methods?

put( key, value )

get( key )  
(key)

put() would be  $O(1)$ , while get() and remove() would be  $O(n)$

## LET'S ADD ASSUMPTIONS


- Special case #1: what if keys are *comparable* ?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## ARRAY LIST (SORTED BY KEY)



How can we implement the following methods?

Assignment Project Exam Help

( key, value )

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro


put() and remove() would be  $O(n)$ ,  
while get() could be performs in time  
 $O(\log n)$  using binary search

# BINARY SEARCH TREE (SORTED BY KEY)

## How can we implement the following methods?

```
put( key, value )
get(key)
remove(key)
```

The performance of `put()`, `get()` and `remove()` depends on the tree. If we have a balanced tree, then these operations would all take time  $O(\log n)$  in worst case. You will learn more about balanced tree in COMP 251.



# Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# MINHEAP (PRIORITY DEFINED BY KEY)

How can we implement the following methods?


```
put( key, value )  
get(key)  
remove(key)
```

The performance of `put()` would be  $O(\log n)$ . Implementing `get()` would require traversing the tree, so it would be  $O(n)$ . Implementing `remove()` would be a little weird for heaps...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



## LET'S ADD ASSUMPTIONS

- ~~Special case #1: what if keys are comparable?~~
- Special case #2: what if keys are unique positive integers in small range?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# ARRAYS OF VALUES

Assignment Project Exam Help

4


Then, we could use  
type **V** (value) as  
access.

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

This would not work well if keys  
are 9 digit student IDs.

22



## IN GENERAL

- Keys might not be comparable

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Keys might be not

e.g. Keys might be strings or so

Add WeChat edu\_assist\_pro




## STRATEGY IN THE GENERAL CASE

Try to define a map from keys to *small* range of positive integers (array index), and then store the corresponding values in the array.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



Recall notation: black dots  
are not part of the map.

## IN THIS VIDEO


Define a map from keys to *large* range of positive integers  
Such map is called *h*

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# JAVA'S Object.hashCode ()



1-to-1

Assignment Project Exam Help  
(not many-to-1) {0, 1, 2, ...,  $2^{24} - 1$ }

<https://eduassistpro.github.io/>

objects in a Java  
program (runtime)

Add WeChat: edu\_assist\_pro  
address in JVM memory  
(

*By default, "obj1 == obj2" means "obj1.hashCode() == obj2.hashCode()"*

# JAVA'S String.hashCode ()

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

<https://docs.oracle.com/javase/7/docs/api/java/lang/String.html>

## EXAMPLE HASH CODE FOR STRINGS

(not used in Java)

Assignment Project Exam Help  
 $s.length-1$

$(\quad)$   $[t]$   
<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

e.g.

$$h("eat") = h("ate") = h("tea")$$

ASCII values of 'a', 'e', 't' are 97, 101, 116.

## JAVA'S String.hashCode ()

$$s.hashCode () \equiv \sum_{i=0}^{s.length-1} s[i] * x^{s.length-1-i}$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>  
here  $x = 31$ .

Add WeChat edu\_assist\_pro

## JAVA'S String.hashCode ()

$$s.hashCode() \equiv \sum_{i=0}^{s.length-1} s[i] x^{s.length-1-i}$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>  
here  $x = 31$ .

Add WeChat edu\_assist\_pro

e.g.  $s = \text{"eat"}$  then  $s.hashCode() = 101 * 31^2 + 97 * 31 + 116$

'e'

'a'

't'

s[0]

s[1]

s[2]

## JAVA'S String.hashCode()

$$s.hashCode() \equiv \sum_{i=0}^{s.length-1} s[i] x^{s.length-1-i}$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>  
here  $x = 31$ .

Add WeChat edu\_assist\_pro

e.g.  $s = \text{"ate"}$  then  $s.hashCode() = 97 * 31^2 + 116 * 31 + 101$

'a'

't'

'e'

s[0]

s[1]

s[2]



## JAVA'S `String.hashCode()`

$$s.hashCode() \equiv \sum_{i=0}^{s.length-1} s[i] * (31)^{s.length-1-i}$$


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro`

If `s1.hashCode() == s2.hashCode()` then what can we conclude about `s1.equals(s2)` ?

*s1 may or may not be the same string as s2.*



## JAVA'S String.hashCode ()

$$s.hashCode () \equiv \sum_{i=0}^{s.length-1} s[i] * (31)^{s.length-1-i}$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

If `s1.hashCode () != s2.hashCode ()` then what can we conclude about `s1.equals (s2)` ?

`s1` is a different string than `s2`.

An orange paint roller with a red handle, positioned horizontally. The roller is partially filled with orange paint, and there are orange paint splatters and drips around it. The text "Coming Soon" is written in white on the orange surface of the roller.

# Coming Soon

## Assignment Project Exam Help

In the next

■ Hash Ma <https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro