

# COMP 250

Assignment Project Exam Help

## INTRODUC TER SCIENCE

<https://eduassistpro.github.io/>

Week 5-1: A  
Add WeChat edu\_assist\_pro

Giulia Alberini, Fall 2020

# WHAT ARE WE GOING TO DO IN THIS VIDEO?



- **Arraylist**

**Assignment Project Exam Help**

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# ARRAYS IN JAVA

- Arrays whose elements have a primitive type

```
int[] myInts = new int[15];  
myInts[3] = -732;
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Arrays whose elements have a reference

```
Shape[] myShapes = new Shape[428];  
shapes[293] = new Shape(▲);
```



```
int[] myInts = new int[15];  
myInts[3] = -732;
```

```
Shape[] myShapes = new Shape[428];  
shapes[293] = new Shape(▲);
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu\_assist\_pro



You can think of an array as a block of consecutive slots in memory

## ARRAYS HAVE CONSTANT TIME ACCESS

A computer accesses an element in an array in constant time

**Assignment Project Exam Help**

i.e. constant, independent of the index of the array.

<https://eduassistpro.github.io/>

```
.... = a[k] ; // read
a[k] = .... ; // write
```

**Add WeChat edu\_assist\_pro**

You will learn more about how this works in COMP 206 and 273.

# LIST

---

An ordered set of elements

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

$N$  is the number of elements in the list, often called the “size” of the list.

# WHAT WOULD WE LIKE TO DO WITH A LIST?

<code>get(i)</code>	<code>// Returns the i-th element (but doesn't remove it)</code>
<code>set(i,e)</code>	<code>// Replaces the i-th element with e</code>
<code>add(e)</code>	<code>// Adds element e to the end of the list</code>
<code>add(i,e)</code>	<code>// Inserts element e at the i-th position</code>
<code>remove(i)</code>	<code>// Removes the element at the i-th position</code>
<code>remove(e)</code>	<code>// Removes first occurrence of element e from the list (if it is there)</code>
<code>clear()</code>	<code>// Empties the list.</code>
<code>isEmpty()</code>	<code>// Returns true if empty, false if not empty.</code>
<code>size()</code>	<code>// Returns number of elements in the list</code>

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# IMPLEMENTATIONS

There are different implementations of a list:

- Array list **Assignment Project Exam Help**
- Singly linked list **<https://eduassistpro.github.io/>**
- Doubly linked list **Add WeChat edu\_assist\_pro**

# IMPLEMENTATIONS

There are different implementations of a list:

- Array list → [Assignment Project Exam Help](#)
- Singly linked list <https://eduassistpro.github.io/>
- Doubly linked list [Add WeChat edu\\_assist\\_pro](#)

# ARRAYLIST

## Idea:

- Use an array to store the elements of the list
- Keep track of how many elements inserted in the list

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## To decide:

- How big should the underlying array be when we first create an object of type ArrayList?  
(this is referred to as the *initial capacity* of the list)

*ArrayList.java*

```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
}
```

# ARRAYLIST

## Idea:

- Use an array to store the elements of the list
- Keep track of how many elements inserted in the list

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## To decide:

- How big should the underlying array be when we first create an object of type ArrayList?  
→ Java's ArrayList creates an array of length 10.

*ArrayList.java*

```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
    public ArrayList() {  
        arr = new Shape[10];  
        size = 0;  
    }  
}
```

## EXAMPLE

*ArrayList.java*


```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
    public ArrayList() {  
        arr = new Shape[10];  
        size = 0;  
    }  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
ArrayList list = new ArrayList();
```



0	null
1	null
2	null
3	null
4	null
5	null
6	null
7	null
8	null
9	null

## EXAMPLE – WHAT WE WANT WHEN ADDING ELEMENTS

*ArrayList.java*

```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
    public ArrayList() {  
        arr = new Shape[10];  
        size = 0;  
    }  
}
```



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
ArrayList list = new ArrayList();  
// add 7 elements...
```

list



# HOW TO IMPLEMENT VARIOUS OPERATIONS? – get ()

*Returns the element at the specified position in this list.*


```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
    :  
  
    public Shape get(int i) {  
        if(  
            )  
            return arr[i];  
        // otherwise?  
    }  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

list



# HOW TO IMPLEMENT VARIOUS OPERATIONS? – get ()

*Returns the element at the specified position in this list.*


```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
    :  
  
    public Shape get(int i) {  
        if( i >= 0 && i < size )  
            return arr[i];  
        // otherwise?  
    }  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

throw new IndexOutOfBoundsException();  
I will not mention this for all the other methods today, but it should be added for proper implementations.





# HOW TO IMPLEMENT VARIOUS OPERATIONS? – set ()

*Replaces the element at the specified position in this list with the specified element.*

```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
    :  
  
    public Shape set(int i, Shape e)  
    {  
        if(i >= 0 && i < size) {  
            Shape tmp = arr[i];  
            arr[i] = e;  
            return tmp;  
        }  
    }  
}
```


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

For example:

`list.set(5, e);`



# HOW TO IMPLEMENT VARIOUS OPERATIONS? – add ()

*Appends the specified element to the end of this list.*

```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
    :  
  
    public void add(Shape e)  
    {  
        arr[    ] = e;  
        size = size + 1;  
    }  
}
```

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

list

For example:  
`list.add(e);`

What if the array `arr` is full?



# HOW TO IMPLEMENT VARIOUS OPERATIONS? – add ()

*Appends the specified element to the end of this list.*

```
public class ArrayList {  
    private Shape[] arr;  
    private int size;  
  
    :  
  
    public void add(Shape e)  
    {  
        arr[size] = e;  
        size = size + 1;  
    }  
}
```

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

list

For example:  
`list.add(e);`

What if the array `arr` is full?



## HOW TO IMPLEMENT VARIOUS OPERATIONS? – add ()

*Appends the specified element to the end of this list.*

What if the array arr is already full?

```
public void add(Shape e) {  
    if ( Assignment Project Exam Help  
        resize();  
    arr[size] = https://eduassistpro.github.io/  
    size = size  
}  
  
Add WeChat edu_assist_pro  
  
private void resize() {  
    Shape[] bigger = new Shape[arr.length*2]; // example  
    for(int i=0; i < size; i++) {  
        bigger[i] = arr[i];  
    }  
    arr = bigger;  
}
```

## HOW TO IMPLEMENT VARIOUS OPERATIONS? – add ()

*Appends the specified element to the end of this list.*

What if the array arr is already full?

```
public void add(Shape e) {  
    if (arr.length == size)  
        resize();  
    arr[size] = e;  
    size = size + 1;  
}  
  
private void resize() {  
    Shape[] bigger = new Shape[arr.length*2]; // example  
    for(int i=0; i < size; i++) {  
        bigger[i] = arr[i];  
    }  
    arr = bigger;  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## OVERLOADING

`add( e )`      `// inserts element e at end of list`

`add( i ,e)`      `// Inserts element e into the i-th position`

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

`remove(i)`      `// Removes the i-th element from list`


`remove(e)`      `// Removes first occurrence of element e`  
`// from the list (if it is there)`

# HOW TO IMPLEMENT `add(i, e)`

*Inserts the specified element at the specified position in the list.*

For example:

```
list.add(3, e);
```




# HOW TO IMPLEMENT `add(i, e)`

*Inserts the specified element at the specified position in the list.*

IDEA: make room by shifting the elements, then add `e`

For example:

```
list.add(3, e);
```





## HOW TO IMPLEMENT `add(i,e)`

*Inserts the specified element at the specified position in the list.*

```
public void add(int i, Shape e) {  
    // Throw of bounds  
    // Resize if not enough  
    // Shift elements down  
    // Add the new element  
}
```


**Assignment Project Exam Help**

<https://eduassistpro.github.io/>

**Add WeChat edu\_assist\_pro**

# ADDING N ELEMENTS TO AN ARRAY LIST

Suppose we initialize an array list with an empty array of length 1.  
We then add an element.



# ADDING N ELEMENTS TO AN ARRAY LIST

Suppose each time we add to a full array list, we double the length of the array.



Assignment Project Exam Help

arraylist of  
size 1  
(length 1)



of  
<https://eduassistpro.github.io/>  
(length 2)

Add WeChat edu\_assist\_pro



add **second**  
**element**

# ADDING N ELEMENTS TO AN ARRAY LIST

Assignment Project Exam Help

arraylist of  
size 2  
(length 2)



<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

(length



aylist of  
size 4  
th 4)



add third element

# ADDING N ELEMENTS TO AN ARRAY LIST

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



add fourth  
element

## ADDING N ELEMENTS TO AN ARRAY LIST

arraylist of  
size 4  
(length 4)



arraylist of  
size 4  
(length 8)



arraylist of  
size 5  
(length 8)



Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

add fifth element

# ADDING N ELEMENTS TO AN ARRAY LIST

Double length and  
copy one element




add two elements

Double length and  
copy two elements

Assignment Project Exam Help

Double length and  
copy four elements



<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

add 3-4 elements

add 5-8 elements

Q: How many times  $k$  do we need to double the length of the array so that it is of length  $N$  ?

A:

Assignment Project Exam Help

Q: How many **cop** **ui**red to add  $N$  elements to an empty array

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

A:



Q: How many times  $k$  do we need to double the length of the array so that it is of length  $N$  ?

A:  $2 \cdot 2 \cdots 2 = 2^k = N \rightarrow k = \log_2 N$   
Assignment Project Exam Help

Q: How many **cop** <https://eduassistpro.github.io/> uired to add  $N$  elements to an empty array  
Add WeChat edu\_assist\_pro

A:

Q: How many times  $k$  do we need to double the length of the array so that it is of length  $N$  ?

A:  $2 \cdot 2 \cdots 2 = 2^k = N \rightarrow k = \log_2 N$   
Assignment Project Exam Help

Q: How many **copies** required to add  $N$  elements to an empty array  
<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

A:  $1 + 2 + 4 + \dots + 2^{k-1}$

## SERIES

- *Geometric series*

$$\sum_{i=0}^n x^i = 1 + x + x^2 + \cdots + x^n = \frac{1 - x^{n+1}}{1 - x}$$

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- *Arithmetic series*

$$\sum_{i=1}^n i = 1 + 2 + \cdots + n = \frac{1}{2}n(n + 1)$$

Q: How many times  $k$  do we need to double the length of the array so that it is of length  $N$  ?

A:  $2 \cdot 2 \cdots 2 = 2^k = N \rightarrow k = \log_2 N$   
Assignment Project Exam Help

Q: How many **copies** required to add  $N$  elements to an empty array  
<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

A:  $1 + 2 + 4 + \dots + 2^{k-1} = \sum_{i=0}^{k-1} 2^i = \frac{1-2^k}{1-2} = 2^k - 1 = N - 1$

# JAVA ARRAYLIST CLASS

<https://docs.oracle.com/javase/8/docs/api/java/util/ArrayList.html>

## Assignment Project Exam Help

- It uses an array as the underlying data structure.

<https://eduassistpro.github.io/>

- It grows the array (by 50%, not 100%) when it is full and a new element is added.
- As a client, we don't have access to the fields directly. We need to use the methods provided (get(), set(), ...) to manipulate the list.

## JAVA ARRAYLIST – GENERIC CLASS

- ArrayList is a generic class with a type parameter.
- When you create an object of type ArrayList you specify the type of the element ArrayList a class name enclosed

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Example:

```
// creates an arraylist of integers with initial capacity 10
ArrayList<Integer> words = new ArrayList<Integer>();

// creates an arraylist of shapes with initial capacity 23
ArrayList<Shape> myShapes = new ArrayList<Shape>(23);
```

If we write `int` instead we get a compile-time error!

## WRAPPER CLASSES

- Integer, Double, and Character wrap a value of the primitive type `int`, `double`, and `char` (respectively) in an object. Thus, they turn primitive types into reference types.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- The conversion between their wrappers is done automatically. For example, the following code will cause a compile-time error:

Add WeChat edu\_assist\_pro

```
Integer x = 5;
```

- Note that these classes have static methods/attributes that you might have already used. For example: `Integer.MAX_VALUE`, `Double.parseDouble()`

# AUTOBOXING AND UNBOXING

- *Autoboxing* is the automatic conversion that the Java compiler makes between the primitive types and their corresponding object wrapper classes. For example converting an `int` to an `Integer`.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- If the conversion goes the other way, this is called *unboxing*.

```
Integer x = new Integer(5);  
int y = x;
```

- <https://docs.oracle.com/javase/tutorial/java/data/autoboxing.html>



## IMMUTABLE TYPES

- Note that `Integer`, `Double`, and `Character` are **immutable** (`String`).  
<https://eduassistpro.github.io/>
- As with `String`, you can append values, but you are never changing the actual Object. A new Object gets created each time we “change” a value.

## WHY WRAPPER CLASSES?

Assignment Project Exam Help

It is much simpler (in terms of code re-use) to have  
ArrayList req <https://eduassistpro.github.io/> hject (a reference  
type), instead of using primitiv

Add WeChat edu\_assist\_pro

For example, all reference types can be compared using  
.equals(), while we have to use == for primitive types.

# THE FOREACH LOOP

```
int[] numbers = {1, 2, 3, 4, 5};  
for (int i : numbers) {  
    System.out.println(i);  
}
```

Assignment Project Exam Help  
<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

The foreach loop (also called enhanced for loop) can make your code more readable and can be convenient to use. It is not helpful when you need to refer to the index of an element.

An orange paint roller with a red handle, positioned horizontally. The roller is partially filled with orange paint, and there are orange paint splatters and drips around it. The text "Coming Soon" is written in white on the orange surface of the roller.

# Coming Soon

## Assignment Project Exam Help

In the next

- Linked li <https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro