

<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Broadc Add WeChat edu_assist_pro g

<https://eduassistpro.github.io/>

Outline

Assignment Project Exam Help

- Broadcasting
- Fault-free Broadcasting
- Fault-Tolerant Broadcasting
- Multiple Integers

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Broadcasting (1/2)

Assignment Project Exam Help

- Broadcasting refers to sending a message simultaneously to many users.
- It is usually initiated by a user in a network.
- We are interested in efficient broadcasting, as measured by
 - number of messages
 - time required
 to complete successfully the broadcast
- Broadcasting uses available communication channels.
 - We must specify the communication channels to be used and in what order.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Broadcasting (2/2)

Assignment Project Exam Help

- Broadcasting is a preferred route because it is flat.

Add WeChat edu_assist_pro

- Broadcasting is used in

- Ethernet,

- Wireless.

Assignment Project Exam Help

and other network

<https://eduassistpro.github.io/>

- Efficiency of broadcasting is trained

by) underlying graph $G = (V, E)$

Add WeChat edu_assist_pro

- Broadcasting in general graphs is multihop.
 - Typically, message transmission for broadcasting is based on building a BFS tree from the “broadcast initiating” node.

<https://eduassistpro.github.io/>

General Setting

Assignment Project Exam Help

- Consider a (strongly) connected graph with N processes $0 \dots N - 1$.
 - This may be a multi-hop graph.
- Each process i has a “stable (unchanging) value” $s(i)$ associated with it.
- The goal is to devise a distributed algorithm such that each process i can broadcast its value $s(i)$ to every other process in the system.
 - This may require multiple hops.
- At the end, each process i will have the set of all possible values $V_i = \{s(k) : 0 \leq k \leq N - 1\}$.
- Generally, the problem is solved with a so-called “heart beat” algorithm.

<https://eduassistpro.github.io/>

Heartbeat Algorithms

Assignment Project Exam Help

- Initially $V_i = \{s(i)\}$.
- To complete the broadcast:^a in every process i will periodically
 1. send its current V_i along each of its outgoing channels,
 2. receive whatever values have been received by it along the incoming channels
 3. update V_i .
- The operation resembles the pumping of water, so these types of algorithms are called heartbeat algorithms.
- Two important issues need attention:
 - The termination of the algorithm
 - The message complexity

^aEach round involves **Send; Receive; Process;**

<https://eduassistpro.github.io/>

Heartbeat Algorithm (1/2)

Assignment Project Exam Help

- No need to send V_i , if it has n he last send operation. suffices to send the in ge only
- Each process i is associated with two sets of values:
 - V_i denotes the current set of values collected so far,
 - W_i will repre nt along the outgoing cha
- Let (i, j) represent the channel to j .
- The algorithm terminates when no process receives any new value, and every channel is empty.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Heartbeat Algorithm (2/2)

Assignment Project Exam Help

- The program for process .

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Correctness is proved in two steps.
 - 1st step: show that when **empty**(i, k) holds, $W_i \subseteq V_k$.
 - 2nd step: show that at the end every process must have received the value $s(i)$ from every other process i .

<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu_assist_pro

Assignment Project Exam Help

F <https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Main Question

Assignment Project Exam Help

- Is broadcasting possible in a network where some nodes (may) fail to transmit messages?
- Two main issues:
 - In which networks?
 - What does it mean?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Broadcasting

Assignment Project Exam Help

- In the sequel we look at broadcast ncy when the underlying network is a complete graph on n nodes).
 - In this setting, broadcasting is an instance of flat routing.
- Further, the communication model does not allow for “multicasting”, whereby a given node can communicate with specific nodes at a ti

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Calling

Assignment Project Exam Help

- Alice wants to organize a party for herself). including

[Add WeChat edu_assist_pro](#)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

[Add WeChat edu_assist_pro](#)

- She does not know their email addresses, but
 - she has a list of all 120 students with their phone numbers which was recently given to by every student.

<https://eduassistpro.github.io/>

Calling and Broadcasting

Assignment Project Exam Help

- Broadcasting depends on the (channels) used.
 - If Alice can shout simultaneously then it takes only one step (Ethernet uses this idea!).
- However this may cause collisions and in any case it is not an option in our current study.
- Here the communication calls.
 - This is the so-called point-to-point processor can talk to another process
 - We will approach the problem imposing “message scheduling and processor coordination”.
 - We also call this the *phone call* model.

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Broadcasting

Assignment Project Exam Help

- In the *phone call* model, broadcast would require the availability of 120 separate channels for the phone calls:
 - which may not be available.
- Alice could try to do 120 phone calls herself,
 - which would cost

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

New Idea: Assisted Broadcasting

Assignment Project Exam Help

- Any other nodes can assist in the b
- Not only Alice can call but certain er users.
 - Therefore the design would require some form of coordination of who can send to whom and by when.

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Alternative Approach (1/2)

Assignment Project Exam Help

- The first strategy that comes to mind is resembling whispering.



- Alice just calls the first person on the list and asks him/her to call the next one.
- who will then call the next one on the list.
- and so on,
- until everybody on the list has been reached.
- The advantage of this strategy is that every student only has to make one call.
- To make this work, an order of users must have been agreed on.

<https://eduassistpro.github.io/>

Alternative Approach (2/2)

Assignment Project Exam Help

- Since the calls have to be performed sequentially, a very long time can go by until all students are reached.
 - Algorithm imposes an underlying “Line Graph” topology’.
 - For n students this takes time $n - 1$
- Some issues:
 - If just 10% of the students are reached, the next one on the list within the same day is not called, it takes at least 12 days until everyone is informed.
 - Even worse: if someone does not bother to call the next one on the list, the whole system will break down!

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Partitioning Strategy

Assignment Project Exam Help

- Alice could divide the phone list into two halves and call the first person on each of the two halves.

[Add WeChat edu_assist_pro](#)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

[Add WeChat edu_assist_pro](#)

- Each of them will then be asked to cut their list into two further halves and call the first person on these halves.
- This is continued until everybody has been called, i.e., we reach a level in which people are called who just have to take care of an empty list.

<https://eduassistpro.github.io/>

Partitioning

Assignment Project Exam Help

- In this way, the students can be re-arranged by checker.
 - For n students this takes $O(n^2)$
- Alice determines that just seven rounds of calls are sufficient to reach all 120 fellow students.
- This is much better than the previous strategy.
- However, the strategy is not optimal,
 - it's questionable whether the other students are able to adhere to the rules without errors.
- Thus, Alice thinks about an alternative strategy.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Natural Calling Rounds

Assignment Project Exam Help

- Alice calls the first two people on the list, and so on. sks 1
 to call the students at positions 3 and 4, and so on. to call
 the students at positions 5 and 6, and so on.

– User i calls users $2i + 1$ and $2i + 2$.

- **General rule:** everybody at position i in the list will call the students at positions $2i + 1$ and $2i + 2$.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Example

Assignment Project Exam Help

- Assume $n = 31$ (Alice included)
- **Rule:** $i \rightarrow 2i + 1, 2i + 2$
- **Start:** Alice $\rightarrow 1, 2$
 - $1 \rightarrow 3, 4$ and $2 \rightarrow 5, 6$
 - $3 \rightarrow 7, 8$ and $4 \rightarrow 9, 10$ and $6 \rightarrow 13, 14$
 - $7 \rightarrow 15, 16$ and $8 \rightarrow 17, 18$ and $10 \rightarrow 21, 22$
and $11 \rightarrow 23, 24$ and $12 \rightarrow 25, 26$ and $14 \rightarrow 29, 30$
- Information spreads as fast as the previous strategy,
 - calling rule seems much more natural and
 - easier to understand.

<https://eduassistpro.github.io/>

Not Robust Enough

Assignment Project Exam Help

- Alice is not quite happy with this c .
- What if one of her fellow student ht and calls a wrong pair of students on the list?
- Moreover, there can still be a couple of students who just forget or do not both
- In this case, some st
- Therefore, Alice thinks about a more robust

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

New Idea: Allow Overlap

Assignment Project Exam Help

- allow overlappnig calls
 - to ensure fault tolerance
- allow calls from multiple initiators!
 - to ensure fault tolerance

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

More Robust (1/2)

Assignment Project Exam Help

- One possibility would be that for i , the person in “list” position i would call the four positions

$$2i + 1, 2i + 2, 2i + 3, 2i + 4.$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Thus, for each i ,

$$i \rightarrow 2i + 1, 2i + 2, 2i + 3, 2i + 4.$$

<https://eduassistpro.github.io/>

More Robust (2/2)

Assignment Project Exam Help

- In Summary

Add WeChat edu_assist_pro

$$i \rightarrow 2i \qquad i + 3, 2i + 4$$

$$i + 1 \rightarrow 2i + 3, 2i + 4, 2i + 5, 2i + 6$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Notice the overlap between consecutive s!

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Calling Patterns

Assignment Project Exam Help

- Who is going to call user
- Assume $k = 2l$ is even.
 - k is called by users $l - 1$ and $l - 2$.

$$l - 2 \rightarrow 2(l - 2) + 1, 2(l - 2) + 2, 2(l - 2) + 3, 2(l - 2) + 4$$

$$l - 1 \rightarrow 2(l - 1) + 1, 2(l - 1) + 2, 2(l - 1) + 3, 2(l - 1) + 4$$

- Assume $k = 2l$
 - k is called by users $l - 1$ and l .

$$l - 1 \rightarrow 2(l - 1) + 1, 2(l - 1) + 2, 2(l - 1) + 3, 2(l - 1) + 4$$

$$l \rightarrow 2l + 1, 2l + 2, 2l + 3, 2l + 4$$

- All students (except for the first four on the list who will directly be called by Alice) will be called by exactly two students in the ideal case.

<https://eduassistpro.github.io/>

Example (1/2)

Assignment Project Exam Help

- Assume $n = 17$ (Including Al^a)

Add WeChat edu_assist_pro

- **Start:** Alice $\rightarrow 1, 2, 3, 4$

- **Rule:** $i \rightarrow 2i + 1, 2i + 2, 2i + 3, 2i + 4$

– $1 \rightarrow 3, 4, 5, 6, 2 \rightarrow 5, 6, 7, 8$

– $3 \rightarrow 7, 8, 9,$

– $4 \rightarrow 9, 10, 1$

– $5 \rightarrow 11, 12, 13, 14,$

– $6 \rightarrow 13, 14, 15, 16,$

– $7 \rightarrow 15, 16$

^a**NB:** user 7 sends only to two users instead of four. To overcome this problem the algorithm can wrap-around to the beginning nodes 1, 2, We will not discuss this issue in detail.

<https://eduassistpro.github.io/>

Example (2/2)

Assignment Project Exam Help

- Information spreads as fast as t
 - calling rule sounds now mu
 - the system is now fault tolerant.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

More Robust

Assignment Project Exam Help

- Thus, as long as for each such pair a dents
is unreliable (by not being reach g to make the
call), all of the reliable students will still be informed.
- Intuitively, this can be argued as follows:
 - If one can select a caller for each student who works
reliably, then le call
chain from hi
- This strategy can be made even more robu
be really sure to reach everybody who is reachable:

<https://eduassistpro.github.io/>

Even More Robust (1/2)

Assignment Project Exam Help

- For some fixed r :^a

If every student at position $2i + 1, 2i + 2, \dots, 2i + 2r$ calls students at positions

$$2i + 1, 2i + 2, \dots, 2i + 2r$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

then every student (except for the first $2r$ ones who are directly called by Alice) will be called by exactly r many students in the ideal case.

^aThe parameter r is related to the desired fault tolerance.

<https://eduassistpro.github.io/>

Even More Robust (2/2)

Assignment Project Exam Help

- In Summary

Add WeChat edu_assist_pro

$$i \rightarrow 2i + 1, 2 \quad + 2r$$

$$i + 1 \rightarrow 2i + 3, 2i + 4, \dots, 2i + 2r + 2$$

$$i + 2 \rightarrow 2i + 5, 2i + 6, \dots, 2i + 2r + 4$$

\vdots

<https://eduassistpro.github.io/>

$$i + r - 1 \rightarrow 2(i + r) - 1, 2(i + r) + 2r - 2$$

Add WeChat edu_assist_pro

$\vdots \rightarrow \vdots$

- Notice the overlap of consecutive transmissions!

<https://eduassistpro.github.io/>

Calling Patterns (1/2)

Assignment Project Exam Help

- How many users will call user
- Use the Euclidean algorithm to divide k by $2r$ and let $j < 2r$ be the remainder and $q \geq 1$ the quotient so that

$$k = 2qr + j$$

Assignment Project Exam Help

- Observe that

<https://eduassistpro.github.io/>

$$k = 2qr + j = 2(\quad 2s,$$

Add WeChat edu_assist_pro

for all s (positive or negative).

- Recall the calling rule for $i = qr + s$:

$$i \rightarrow 2i + 1, 2i + 2, \dots, 2i + 2r$$

- Hence user k will be called by users i such that $i = qr + s$, provided that $0 \leq j - 2s \leq 2r$.

<https://eduassistpro.github.io/>

Calling Patterns (2/2)

Assignment Project Exam Help

- Therefore, if r was used in the r -cast each user is called by r alternate users

Add WeChat edu_assist_pro

- Hence, as long as **at most** $r - 1$ of these are faulty (e.g., they are not calling) all reliable students will still be reached.

Assignment Project Exam Help

- Thus, the algorithm $r - 1$ faults!

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Initia
Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Question: If Alice Fails?

Assignment Project Exam Help

- A weakness of the algorithm is that the initiator, namely Alice, is not a single node.
- Consider the following scenario:
 - k initiator nodes wake-up at the same time.
 - A given number of nodes, may fail.
- Can we design a fault-tolerant algorithm?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Exercises^a

Assignment Project Exam Help

1. Prove the correctness of the Heart by proving.

(a) show that when $\text{cmp } V_i \sqsubseteq V_k$.

(b) show that at the end every process must have received the value $s(i)$ from every other process i .

2. List some of the issues that may arise in the complete network K_n by the simultaneous calls by many nodes.

3. Verify the calling patterns discussed in the lecture. Every student at position i calls the students at positions

$$2i + 1, 2i + 2, \dots, 2i + 2r$$

4. Show that for n students the partitioning algorithm takes time $O(\log n)$.

^aNot to submit

<https://eduassistpro.github.io/>

5. (★) Design a broadcast algorithm which is fault tolerant under k initiators.

6. (★) Extend the previous broadcast to be fault tolerant under $< r$ participants.

7. (★★) An interesting analysis for broadcasting is the average case. For a given number x (e.g., 10) of unreliable students, who are assumed to be x out of n students, we want to determine for which the probability that all reliable students are reached is at least, say, 90%. In other words,

Given n participants and a parameter $0 < p < 1$, what is the minimum value of r such that

$$\Pr[\text{all reliable students are reached}] \geq p$$

Give a broadcasting algorithm and analyze its complexity. As a

<https://eduassistpro.github.io/>

Assignment Project Exam Help

hint this can be based on an array that is defined as follows:

- (a) N is the total number of students.
- (b) A : array $[1 \dots N]$ of integers; $A[i]$ counts, for a reliable student at position i , the number of calls that student would get from
- (c) For every reliable student i , $A[i] \geq 0$.
- (d) For all unreliable students at position i , $A[i]$ will initially be set to $-r$ (so that even after r calls there will not be a positive value in $A[i]$).

In order to determine this r , one can use the algorithm presented below (Below Steffi = Alice).

<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Simulate this algorithm and test its performance.

8. Design fault tolerant broadcasting algorithms assuming multiple initiators.

<https://eduassistpro.github.io/>

- Assignment Project Exam Help
Add WeChat edu_assist_pro
9. Design a probe-echo algorithm to compute the topology of a network whose topology is a strongly connected graph. When the algorithm terminates, the algorithm should have knowledge about all the nodes in the network.
10. Design an algorithm to count the total number of processes in a unidirectional ring. The algorithm should be able to use the ring can initialize the algorithm. The algorithm should be able to use process ids.
- <https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

References

Assignment Project Exam Help

- Christian Scheideler. Broad Disseminate Information: I plugged. Berthold Vöcking H, Alt, M. Dietzfelbinger, R. Reischuk, C. Scheideler, H. Vollmer, D. Wagner (Editors), 2011.
- R. Karp, S. Shenker, C. Schindelhauer, and B. Vöcking: Randomized Routing on Foundations of C-574, 2000.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro