

<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu_assist_pro

Assignment Project Exam Help

Univ <https://eduassistpro.github.io/> rsals

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Labeling Schemes

Assignment Project Exam Help

- How can we use port labeling schemes for communication?
- What role do port labeling schemes play in distributed computing?
- The execution of a distributed algorithm depends on the sequence of ports used by the algorithm at that node.
- Can we solve a problem in a way that all nodes have the same sequence at each node?

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

1

<https://eduassistpro.github.io/>

Outline

Assignment Project Exam Help

- Probabilistic Method

[Add WeChat edu_assist_pro](#)

- Universal traversals

Assignment Project Exam Help

<https://eduassistpro.github.io/>

[Add WeChat edu_assist_pro](#)

<https://eduassistpro.github.io/>

Probabilistic Method

Assignment Project Exam Help

- Using probability to prove the existence of a combinatorial object is called the Probabilistic Method.

Add WeChat edu_assist_pro

- It has many applications, especially in graph theory.
- It uses the following principle:

Assignment Project Exam Help

If, in a given set of objects,

the probability of a randomly chosen object having a certain property is

less than 1 then there must exist a

subset of objects with

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Union Form of the Probabilistic Method

Assignment Project Exam Help

- Consider n events A_1, A_2, \dots, A_n (not necessarily independent).
- The union (or Boole) Inequality

Add WeChat edu_assist_pro

$$\Pr \left[\bigcup_{i=1}^n A_i \right] \leq \sum_{i=1}^n \Pr[A_i]$$

Assignment Project Exam Help

- Therefore if we want

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

it is enough to show that

$$\sum_{i=1}^n \Pr[A_i] < 1.$$

<https://eduassistpro.github.io/>

Expectation Form of the Probabilistic Method

Assignment Project Exam Help

- Consider an integer valued random variable X which takes only non-negative integer values
- Observe that

$$\Pr[X > 0] = \sum_{k=1}^{\infty} \Pr[X = k]$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

Therefore

$$\Pr[X > 0] \leq E[X] \quad (1)$$

<https://eduassistpro.github.io/>

Expectation Form of the Probabilistic Method

Assignment Project Exam Help

- Equation (1) is a special case of Markov's inequality which states that

Add WeChat edu_assist_pro

$$\Pr[X > kE[X]] \leq \frac{1}{k}$$

- Therefore using Equation (1) if we want to prove that

Assignment Project Exam Help

<https://eduassistpro.github.io/>

it is enough to prove that

Add WeChat edu_assist_pro

$$E[X]$$

<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Explorations

Assignment Project Exam Help

- Graph traversal (also known as <https://eduassistpro.github.io/>) refers to the process of visiting (checking and/or updating) each vertex in a graph. E.g.,
 - BFS
 - DFS
- Used in Search and <https://eduassistpro.github.io/>
- Each starting node is equipped with a <https://eduassistpro.github.io/>
 - typically a sequence of port labels that it must follow from node to node) which is used to traverse the graph.
- However, the program used may depend on the starting node.

<https://eduassistpro.github.io/>

Universal Traversals

Assignment Project Exam Help

- A sequence is universal for graph G with n vertices if for every graph G and every start vertex s , the sequence will visit every vertex in the graph.
- Can you produce a universal traversal program that will work for every graph and every starting node of the graph?
- To produce a walk of graph labeling.
 - For each vertex u , label the edges e_u (ports) from 1 to $\deg(u)$ (in fact any numbering will do).
 - This is what we defined as port labelings!
- Then a sequence is a string of edge labels which determines some walk through the graph.

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Universal Traversals on Labyrinths

Assignment Project Exam Help

- A robot is placed in a labyrinth in a $m \times n$ square grid.
- It runs a program: a sequence of commands $N(orth), S(outh), E(ast), W(est),$

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- As an example consider the program $NESWEW$ which is given to every node.
- A robot has the sequence “ $NESWEW$ ” and starting at a node makes movements following the sequence of labels.

<https://eduassistpro.github.io/>

Universal Traversals

Assignment Project Exam Help

- In addition to external walls on the outer boundary, walls are also placed between cells.
- Executing each command, the robot moves in the prescribed direction if possible (and does nothing when there is a wall in this direction).

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

E.g., *NESWEEW*

<https://eduassistpro.github.io/>

Universal Traversals

Assignment Project Exam Help

- We can show that

Theorem 1 (Universal Traversal) *For any n , there exists a program that works correctly for all labyrinths of size at most $n \times n$ (independently of the positions of walls inside the square and the robot's initial position).*

Assignment Project Exam Help

- “Works correctly” means that the robot visits all reachable cells.

<https://eduassistpro.github.io/>

- To solve the traversal problem, we prove that a sufficiently long random program will work with positive probability.
- We will do this using the union bound.

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>


Preorder Traversals (1/2)

Assignment Project Exam Help

- For each $n \times n$ labyrinth of size $4n^4$ that works for it, as each cell is reachable in n^2 steps (round-trip) and there are at most n^2 admissible cells.
- To prove this note that for each starting cell there is a spanning tree reaching all the n^2 cells of a given labyrinth, think of it as a distrib

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



- Assign ports to each vertex (edge labels associated to the edges connected)

<https://eduassistpro.github.io/>

Preorder Traversals (2/2)

Assignment Project Exam Help

- Using a pre-order traversal of the tree which has length at most $4n^2$ every c at most $4n^2$ steps (round trip).

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Therefore, a random program of size $N = 4n^4$ will work with probability at least $\epsilon = (1/4)^{4n^4}$ and fail with probability at most $1 - \epsilon$.

<https://eduassistpro.github.io/>

Universal Traversals

Assignment Project Exam Help

- Select among such programs of $= 4n^2$ independently and uniformly at random

[Add WeChat edu_assist_pro](#)

- Now for each k concatenate k such programs:

Assignment Project Exam Help

- By independence N will fail with probability

<https://eduassistpro.github.io/>

- More generally, a random program kN will fail with probability at most $(1 - \epsilon)^k$.

[Add WeChat edu_assist_pro](#)

- This probability is computed for a fixed labyrinth L .
- Let F_L be the event that a program of size kN fails for the labyrinth L .
- It follows from the above that $\Pr[F_L] \leq (1 - \epsilon)^k$.

<https://eduassistpro.github.io/>

Universal Traversals

Assignment Project Exam Help

- Now take the union \bigcup_L runs over all labyrinths.
As a consequence,

Add WeChat edu_assist_pro

$$\Pr \left[\bigcup_L F_L \right] \leq \sum_L \Pr[F_L]$$

Assignment Project Exam Help

where ℓ_n is the number of $n \times n$ grids.

<https://eduassistpro.github.io/>

- However, we can choose k such that

Add WeChat edu_assist_pro

$$\ell_n < \frac{1}{(1 - \epsilon)^k} \quad (2)$$

- So,

$$\Pr \left[\bigcup_L F_L \right] < 1$$

<https://eduassistpro.github.io/>

Universal Traversals

Assignment Project Exam Help

- In particular, for a k satisfying (2), we have that

Add WeChat edu_assist_pro

$$\Pr \left[\bigcap_L \neg F_L \right] = 1 - \Pr \left[\bigcup_L F_L \right]$$

Assignment Project Exam Help

- Therefore for k <https://eduassistpro.github.io/> am of size kN works for all labyrinths

Add WeChat edu_assist_pro

- Therefore such a program must exist!

<https://eduassistpro.github.io/>

Efficiency of Universal Traversals

Assignment Project Exam Help

- How about the length of the sequence?
 - Can we construct a universal traversal sequence of polynomial length in polynomial time (in the size n of the graph)?
- How about efficiency?
 - Can we give an algorithm for universal traversal sequence?
- Can we make the construction distributed?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Universal Traversals on Graphs

Assignment Project Exam Help

- The Universal Traversal the n vertices of a given size n . Add WeChat edu_assist_pro
- Instead of N, S, E, W used in $n \times n$ grids one now uses ports and port-labelings.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

Exercises^a

Assignment Project Exam Help

1. The traversal of the labyrinth was ce that
 was provided to the robot and will st follow.
 Consider the situation where the robot constructs the sequence
 “on the fly”: looks at the surrounding environment and based
 on what it sees makes its next move according to some rule.
 This will be a local alg
 depend on the env rform a
 successful traversal?
2. (★) Use the probabilistic method to prov versal
 theorem on graphs of a given size n . **Hint:** Instead of
 N, S, E, W used in $n \times n$ grids one now uses ports.
 Consider a set of points in the plane. Form n sets
 A_1, A_2, \dots, A_n on the plane each of which has k points.

^aNot to submit.

<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu_assist_pro

Assignment Project Exam Help

The sets are arbitrary and may share points. Assume that $n < 2^k$. Show that I can color each point red or blue in such a way that every set A_i has both colors. **Hint:** Color each of the 2^k points independently choosing red or blue with equal probability and use the probabilistic method.

3. A certain commodity is sold with two lottery tickets, a and b , for Prize A and Prize B , respectively. Suppose the winning probability for A and that for B are both $2/3$. Show that there

<https://eduassistpro.github.io/>

must exist a commodity with two winning tickets.^b

Assignment Project Exam Help

4. (★) The sets S_1, S_2, \dots, S_k are subsets of a set S that has $2n$ elements. $\{S_1, S_2, \dots, S_k\}$ is a Sperner family^c if $S_i \not\subseteq S_j$, for all $i \neq j$. Use the probabilistic method to prove Spener's theorem, namely "If $\{S_1, S_2, \dots, S_k\}$ is a Sperner family then $k \leq \binom{2n}{n}$." For the proof, follow the steps below.

Assignment Project Exam Help

- (a) Consider the following process: randomly select a subset $A \subseteq S$ of size a (after $2n$ steps) we get the whole set S . Let X_i be the indicator variable for the event that $S_i \subseteq A$. Show that $\Pr[X_i = 1] = \frac{1}{\binom{2n}{a}}$.
- (b) Consider k random variables X_1, X_2, \dots, X_k so that the value of X_i is equal to 1 if the given set S_i appears during the process, otherwise, it is equal to 0. Show that the

^bNote that the conclusion is derived without using event dependence.

^cSperner families have applications in Cryptography and elsewhere.

<https://eduassistpro.github.io/>

expected value of X_i is $1 / \binom{2n}{s_i}$, where s_i is the number of elements in S_i ,

- (c) Now, consider the random variable $X = X_1 + X_2 + \cdots + X_k$. Show that this sum is less than 1 in expectation.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://eduassistpro.github.io/>

References

Assignment Project Exam Help

- Alon, N., Spencer, J. H. (2004). *The Probabilistic Method*. John Wiley & Sons.
- Hirokasu Iwasawa, Using Probability to Prove Existence, *Mathematical Intelligencer*, Volume 34, Number 3, 2012.
- Mathematical Induction, 1998
- Aleliunas, R. Karlin, Random walks, universal traversal sequences, and complexity of maze problems. 20th Annals of Foundations of Computer Science (FOCS 1979): 218-223

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro