Advanced Network Technologies

Multimedia 2/2

Dr. Wei Bao | Lecturer
School of Computer Science

THE UNIVERSITY OF SYDNEY

Network support for Multimedia

Network support for multimedia

Three broad approaches towards providing network-level support for multimedia apps

Approach	Granularity	Guarantee	Mechanisms	Complex	Deployed?
1. Making best of best effort service	All traffic treated equal	None	No network support(all at	low	everywhere
2. Differentiated service	Traffi			medium	some
3. Per-connection QoS	Per-connection flow	Soft or hard after flow admitted	Packet mark, scheduling policing	high	Little to none

Providing multiple classes of services

- thus far: making the best of best effort service
  - one-size fits all service model
- alternative: multiple classes of service
  - partition traffic into classes
  - network treats differ versus regular servi

analogy: VIP service

- granularity: differential service among multiple classes, not among individual connections
- How: ToS bits



Multiple classes of services: scenarios



Scenario 1: mixed HTTP and VoIP

› example: 1Mbps VoIP (Video and Voice), HTTP share 1.5 Mbps link.

- HTTP bursts can congest router, cause video/audio loss
- want to give priority to audio over HTTP



Principle 1

packet marking needed for router to distinguish between different classes; and new router policy to treat packets accordingly

Principles for QOS guarantees

- what if applications misbehave (VoIP sends higher than declared rate)
  - policing: force source adherence to bandwidth allocations
- *marking*, *policing*



Principle 2

provide protection for one class from others

Principles for QOS guarantees (con't)

› allocating *fixed* (non-sharable) bandwidth to flow: *inefficient* use of bandwidth if flows doesn't use its allocation



Principle 3

while providing protection, it is desirable to use resources as efficiently as possible

Scheduling and policing mechanisms

- *scheduling:* choose next packet to send on link
- *FIFO (first in first out) scheduling:* send in order of arrival to queue
  - real-world example?
  - *discard policy:* if packet arrives to full queue: who to discard?
    - *tail drop:* drop
    - *priority:* drop/
    - *random:* drop/remove rando



Scheduling policies: priority

priority scheduling: send highest priority queued packet

non-preemptive



- multiple *classes*, w priorities
  - class may depend on marking or other header info, e.g. IP source/dest, port numbers, etc.
  - real world example?



Scheduling policies: priority



Scheduling policies: priority



Scheduling policies: priority



Scheduling policies (con't)

Round Robin (RR) scheduling:

- multiple classes, with equal priority
- cyclically scan class queues, sending one complete packet from each class (if available)



Scheduling policies: RR



Scheduling policies: RR



Scheduling policies: RR



Scheduling policies: RR



THE UNIVERSITY OF SYDNEY

Scheduling policies (con't)

Weighted Fair Queuing (WFQ):

- generalized Round Robin
- each class gets weighted amount of service in each cycle

Scheduling policies (con't)

Weighted Fair Queuing (WFQ):

- Each class *i* is assigned a weight w_i
- *Guarantee*: if there are class *i* packets to send (during some interval) then class *i* receives a fraction of service which is $w_i / (\sum w_j)$
- On a link with transmis ghput $Rw_i / (\sum w_j)$
- WFQ is part of route

Scheduling policies (con't)

Example:

One link has capacity 1 Mbps. Three flows: Flow 1 is ensured with 0.5 Mbps data rate; Flow 2 is ensured with 0.25 Mbps; Flow 3 is ensured with 0.25 Mbps.

Weighted queu

Efficiency:

When flow 3 has nothing to transmit, but flow 1 and flow 2 have many packets to send

Flow 1: 2/3 Mbps

Flow 2: 1/3 Mbps

Marking and Policing

Policing mechanisms

goal: to limit traffic to not exceed declared parameters (the rate at which a class or flow is allowed to inject packets into the network)

› *Three important policing criteria (differing on the time scale):*

› *1. (long term) average rate:* how many pkts can be sent per unit of time (in the long run)

- e.g., 6000 packe

- 2.*peak rate:* limit the number of pa sent over a relatively shorter period of time, e. per minute (ppm) in average but 3000 packets per 5 second peak rate max.

- *3. (max.) burst size:* max number of pkts sent “instantaneously” into the networks, e.g., 1500 packets.

Policing mechanisms: implementation

token bucket: limit input to specified *burst size* and *average rate* (useful to police the flow)

- bucket can hold b tokens
- a packet must remove a token from bucket to be transmitted into the network
- tokens generated at rate *r token/sec* unless bucket full (token ignored)
- *over interval of length t: number of packets admitted less than or equal to (rt + b)*
- *Token-generation rate r limits the rate at which packets enter the network*

t->0, b packets *t->∞, (rt+b)/t = r packets/second*

Policing and QoS guarantees

- Combining token bucket and WFQ to provide guaranteed upper bound on delay, i.e., *QoS guarantee!*



- Packets arrive while the bucket is full (b_1). The last packet has a maximum delay of D_{max}. L packet size.

Differentiated services in reality

- want “qualitative” service classes
  - relative service distinction: Platinum (VIP), Gold, Silver

- *scalability:* simple functions in network core, relatively complex functions at edge ro

THE UNIVERSITY OF SYDNEY

chitecture

edge router:

- per-flow traffic management
- marks packets as differently
  - E.g. Alice' traffic: hi
  - Bob's traffic: high
  - Chris's traffic: low

core router:

- per class traffic management
- buffering and scheduling based on marking at edge
- Red packets vs green packets



Edge-router packet marking

- profile: pre-negotiated rate r, burst (bucket) size b
- packet marking at edge based on per-flow profile



Example:

- class-based marking: packets of different classes marked differently
- intra-class marking: conforming portion of flow marked differently compared with non-conforming one
  - Bob agrees to transmit at 1Mbps, but he is transmitting at 2Mbps
  - Half of them (conforming) are marked green.
  - Others (non-conforming) are marked red (lower priority) or dropped.

- Example

- green > yellow >red .
  - 2Mbps link, Bob, telephone traffic, declare 1Mbps
    - Green if c ing
  - Chris, web br
    - Yellow
  - Priority queue in the core network
- Bob can guarantee 1Mbps data rate
- If Bob transmits >1Mbps
  - If Chris transmits at 1Mbps, all red will be dropped. Bob gets 1Mbps
  - If Chris transmits at <1Mbps, some red will still get through.

Classification, conditioning

- user declares traffic profile (e.g., rate, burst size)
- traffic metered, shaped if non-conforming

- the meter compares the incoming flow to the negociated traffic profile. Network administrator can decide whether to remark, forward, delay, or drop a non- conforming packet

Per-connection QoS guarantees

› *basic fact of life:* cannot support traffic demands beyond link capacity



Principle 4

call admission: flow declares its needs, network may block call (e.g., busy signal) if it cannot meet needs

Wireless and mobile networks

Elements of a wireless network



Elements of a wireless network



Elements of a wireless network



Elements of a wireless network



wireless link

- typically used to connect mobile(s) to base station, also used as backbone link
- multiple access protocol coordinates link access

smission rates and distances,
anps

Characteristics of selected wireless links



IEEE 802.11 WiFi

IEEE 802.11 standard	Year	Max data rate	Range	Frequency
802.11b	1999	11 Mbps	30m	2.4 Ghz
802.11a	1999	54 Mbps	30m	5 Ghz
802.11g	2003	54 Mbps	30m	2.4 Ghz
802.11n (WiFi 4)				2.4, 5 Ghz
802.11ac (WiFi 5)				5 Ghz
802.11ax (WiFi 6)	2020 (exp.)	14 Gbps		2.4, 5 Ghz
802.11af	2014	35 – 560 Mbps	1 Km	unused TV bands (54-790 MHz)
802.11ah	2017	347Mbps	1 Km	900 Mhz

- all use CSMA/CA for multiple access, and have base-station and ad-hoc network versions

Elements of a wireless network



infrastructure mode

- base station connects mobiles into wired network
- handoff: mobile changes base roviding connection into twork

Elements of a wireless network



ad hoc mode

- no base stations
- nodes can only transmit to ithin link
- no
  nte
  rou
  a network:
  mselves

Wireless network taxonomy

	single hop	multiple hops
infrastructure (e.g., APs)	host connects to base station (WiFi, cellular) w la	hos may have to relay through several wireless to connect to larger t *mesh net*
no infrastructure	no base station, no connection to larger Internet (Bluetooth, ad hoc nets)	tation, no connection nternet. May have to relay to reach other a given wireless node MANET, VANET

Wireless link characteristics

Wireless Link Characteristics (1)

important differences from wired link ….

- *decreased signal strength:* radio signal attenuates as it propagates through matter (path loss)
- *interference fro* ized wireless network frequ ared by other devices (e.g., p
- *multipath propagation:* radio si off objects ground, arriving at destination at slightly different times

…. make communication across (even a point to point) wireless link much more "difficult"

dB decibel

- logarithmic unit used to express the ratio of two (power) values
- $10*\log_{10}\ (P_S/P_N)$
- $P_S/P_N=10$ 10 dB
- $P_S/P_N=100$ 20 dB
- $P_S/P_N=1000$ 30 d
- $P_S/P_N=10000$ 40 dB
- …

Wireless Link Characteristics (2)

- SNR: signal-to-noise ratio
  - larger SNR – easier to extract signal from noise (a "good thing")
  - BER: bit error rate
- *SNR versus BER tr*
  - *given physical layer modulation:* increase power -> increase SNR -> decrease BER
  - *Different physical layer modulation:*



Quadrature amplitude modulation

Binary Phase-shift keying

Higher data rate -> Higher BER

Wireless Link Characteristics (2)

- SNR: signal-to-noise ratio
  - larger SNR – easier to extract signal from noise (a "good thing")
  - BER: bit error rate
- *SNR versus BER tr*
  - *given SNR, BER requirement:* choose modulation to achieve highest throughput
    - 15 dB, require 10^{-3} BER
    - Which modulation?
    - QAM16



Wireless network characteristics (3)

Multiple wireless senders and receivers create additional problems (beyond multiple access):





Hidden terminal problem

- B, A hear each other
- B, C hear each other
- A, C can not hear each other means A, C unaware of their interference at B

Signal attenuation:

- B, A hear each other
- B, C hear each other
- A, C can not hear each other interfering at B

CDMA

Code Division Multiple Access (CDMA)

- unique "code" (chipping sequence) assigned to each user;
- all users share same frequency, but each user has own "chipping" sequence (i.e., code) to encode data
  - length of sequence: M
  - allows multiple users to "coexist" and transmit simultaneously with minimal interference (if codes are "orthogonal")
  - orthogonal:
    - inner product of $c_{i,1}\ c_{i,2}\ \ldots\ c_{i,M}$ and $c_{j,1}\ c_{j,2}\ \ldots\ c_{j,m}$
    - inner product(user i's chipping sequence, sequence) =0
    - inner product(user i's chipping sequence, user i's chipping sequence) =M
- *encoded signal* = (original data) X (chipping sequence)
- *decoding:* inner-product of encoded signal and chipping sequence

CDMA encode/decode



User i receives user i's signals

sender d_i 1 -1

c_m -1 -1 -1 1 -1 1 1 1 -1 -1 -1 1 -1 1 1 1

$Z_{i,m}$ 1 1 1 -1 1 -1 -1 -1

receiver 1 1 1 -1 1 -1 -1 -1

Inner product $D_i = \frac{\sum_{m=1}^{M} Z_{i,m} c_m}{M}$ -1 -1 -1 1 -1 1 1 1

1+1+1+1+1

D_i 8/8=1 -8/8=-1

uses its chipping sequence to send and to receive: receive the correct bits

User 2 receives user 1's signals

sender 1's bits

d_i 1 -1

c_m -1 -1 -1 1 -1 1 1 1 -1 -1 -1 1 -1 1 1 1

$Z_{i,m}$ 1 1 1 -1 1 -1 -1 -1

receiver 2

$$D_i = \frac{\sum_{m=1}^{M} Z_{i,m} c'_m}{M}$$

Inner product

1 1 1 -1 1 -1 -1 -1

1 -1 -1 1 -1 1 1 -1

-1-1+1+1-

D_i 0/8=0 0/8=0

Use 1's chipping sequence to send and use 2's chipping sequence to receive: receive nothing!

Reason: 1's chipping sequence is orthogonal to 2's chipping sequence.







CDMA: two-sender interference

channel sums together transmissions by sender 1 and 2

Sender 1

Sender 2

using same code as sender 1, receiver recovers sender 1's original data from summed channel data!