

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Contents

Assignment Project Exam Help

- Motivation : why do
- Type domains rev
- Define your own typ
- Constructors
- Usage
- Different from type synonyms!

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Motivation

Assignment Project Exam Help

- Types seen so far : `char`
- Type constructor
- Why do we need more?
 - ▶ Readability
 - ▶ Built-in validation
- Example : if a type called `"dice"` has only six legal values (One
 - ▶ `f : : dice -> bool` is more informative
 - ▶ A value that is **not** one of the legal values (One ...

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

Type Domains Revisited

Assignment Project Exam Help

- We can **define**
- The type `bool` has just two legal values : `[]`, `['A']`, `['B']`, `['h']`,
- The type `[char]` has potentially infinite legal values : `[]`, `['A']`, `['B']`, `['h']`,
- Pattern-matching allows equality checks against these legal values

<https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro`

Define your own Types

mybool ::= *Mytrue* | *Myfalse*

MUST use capitals!!!!

f :: *c type*)
<https://eduassistpro.github.io/>

f True = 34

f any = 13

Add WeChat edu_assist_pro

g :: *mybool* → *num*

g Mytrue = 34

g any = 13

Constructors

Assignment Project Exam Help

- The wrong way :

- ▶ `wrong_dice` ::
- ▶ `also_wrong`

- The correct way :

- ▶ `dice` :: *One* | *Two* | *Three* | *Four* | *Five* | *Six*

- Constructors start with a capital letter

- ▶ Built-in type `bool` adheres to this rule
- ▶ Built-in types `num` and `char` break the rule (for convenience)

<https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro`

Constructors (2)

- Each legal value must have a constructor
- Each legal value may also have some extra data (if so, we specify its type following the constructor) :

<https://eduassistpro.github.io/>

Add WeChat *edu_assist_pro*

x : tankLevel

x = Parttank (Gallons 3)

Usage

Assignment Project Exam Help

```
coord3D :: Coord (num, num, num)
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
midpoint :: Coord3D -> coord3
```

```
midpoint (Coord (x1, y1, z1)) (Coord (x2, y2, z2))
= Coord ( (x1 + x2)/2, (y1 + y2)/2, (z1 + z2)/2 )
```


Usage (2)

Assignment Project Exam Help

```
studentdata ::= StudentByname [char] num
              | StudentByregid num    num
```

```
topmarks
```

```
topmarks
```

```
topmarks ((StudentByname any x) : rest)
```

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](https://eduassistpro.github.io/)

```
topmarks ((StudentByregid id x) : rest)
```

```
= (x : (topmarks rest)), if x >= 70
```

```
= topmarks rest, otherwise
```

Different from type synonyms

Assignment Project Exam Help

```
syncoord == (num, num, num)
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
coord3D ::= Coord (nu
```

```
y :: coord3D
```

```
y = Coord (3, 4, 16)
```

Summary

Assignment Project Exam Help

- Motivation : why do
- Type domains revi
- Define your own types !
- Constructors
- Usage
- Different from type synonyms

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro