

# Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Contents

# Assignment Project Exam Help

- Introduction
- Recursive function
- Recursive function
  - ▶ Binding for function name
  - ▶ Fixed point
  - ▶ Fixed point operator
  - ▶ self-application

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Introduction

# Assignment Project Exam Help

Recursive function  $f$



Intermediate function



<https://eduassistpro.github.io/>

Definition of  $f$  in terms of  $Y$



Add WeChat edu\_assist\_pro

How to define  $Y$  in the lambda calculus

Final Lambda-calculus definition of  $f$

## Recursion and the lambda calculus

# Assignment Project Exam Help

- Consider :

$f\ x = 3, \text{ if } (x = 0)$   
 $= 11, \text{ other}$

<https://eduassistpro.github.io/>

- In the lambda calculus this is :

Add WeChat edu\_assist\_pro

$\lambda x. (\text{if } (x = 0) 3 11)$

## Recursion and the lambda calculus

# Assignment Project Exam Help

- However, now consider :

$$f\ x = \begin{cases} 3, & \text{if } (x = 0) \\ 1 + f(x - 1), & \text{otherwise} \end{cases}$$

<https://eduassistpro.github.io/>

- What's wrong with this? :

Add WeChat edu\_assist\_pro

$$\lambda x. (\text{if } (x = 0) \ 3 \ (1 + (f(x - 1))))$$

## Recursion and the lambda calculus

- Consider it again in the context of the whole program :

```
f x    = 3, if (x = 0)
      = 1 + f(x - 1)
main  = f 7
```

- This would translate to the following, which still has a problem :

$$\lambda f.(f \ 7) (\lambda x.(\text{if } (x = 0) \ 3 \ (1 + (f(x - 1)))))$$

$$\rightarrow^{\beta} \lambda x.(\text{if } (x = 0) \ 3 \ (1 + (f(x - 1))))) \ 7$$

## Recursion and the lambda calculus

# Assignment Project Exam Help

- SO how can we represent a recursive function in the lambda calculus?

- 1 First define a new NO  
"f" but which takes "f"

<https://eduassistpro.github.io/>

$$\begin{aligned} h \ f \ x &= 3, \text{ if } (x = 0) \\ &= 1 + f(x-1), \text{ otherwise} \end{aligned}$$

Add WeChat edu\_assist\_pro

---

1. NB here we are using a *curried* style of function definition.

## Recursion and the lambda calculus

# Assignment Project Exam Help

- ① Now the following lambda expression for “h” is fine, because “f” is bound :

$\lambda f.(\lambda x.(\text{if } (x = \text{https://eduassistpro.github.io/}$

BUT “h” is not “f”, so we haven’t solved the problem yet !

- ② However, notice that the partial application  $(h\ f)$  gives the same result  $\equiv f$  (this is an identity, not a definition)



## Recursion and the lambda calculus

- A “fixed point” (or “fixpoint”) of any function  $g$  is a value  $x$  from the input domain of  $g$  such that  $(g\ x) \equiv x$

- Example 1 :

- ▶  $id$  is called the identity function
- ▶ Every value in  $t$  is a fixed point of  $id$

- Example 2 :

$three\ x \equiv 3, if\ (x + 1)$

- ▶ The input value 3 is the only fixed point of the function  $three$

- Note that (from the previous slide) the function  $f$  is a fixpoint of the function  $h$  because  $(h\ f) \equiv f$

## Recursion and the lambda calculus

- There is a special operator (called the "fixpoint operator") that we can incorporate into the  $\lambda$ -calculus, which will return the fixed-point of any function.

- The fixpoint opera

- It takes a function as it

▶ Thus, by defin

▶ If the identifie

the least amount of arbitrary additional information) version of th

- So now  $(Y\ h)$  gives the least fixpoint of  $h$ , which we know is  $f$  (because  $(Y\ h)\equiv f$ )

$f = Y\ h$

<https://eduassistpro.github.io/>

i.e. the definition with

Add WeChat edu\_assist\_pro

2. We already know that in the  $\lambda$  calculus we can easily pass functions as arguments, and return them as results.
3. We skate over some interesting problems : what if  $g$  doesn't have a fixpoint? can  $g$  have more than one "least" fixpoint? This is outside the scope of this module, but further explanations are found in Stoy's excellent book *Denotational Semantics : The Scott-Strachey Approach to Programming Language Theory* by J.E.Stoy, 1979.

# Assignment Project Exam Help

- f 1 = (Y h) 1  
 = (h (Y h)) 1  
 = ((λ f.  
 = (λ x.(  
 = (if (1 = 0) 3 (1  
 = (if *false* 3 (1 + ((Y h)(1 - 1))))  
 = 1 + ((Y h) (1 - 1))  
 = 1 + ((h (Y h)) (1 - 1))  
 = 1 + (((λ f.(λ x.(if (x=0) 3 (1 + (f  
 = 1 + ((λ x.(if (x = 0) 3 (1 + ((Y h  
 = 1 + ((if ((1 - 1) = 0) 3 (1 + ((Y h  
 = 1 + ((if (0 = 0) 3 (1 + ((Y h  
 = 1 + 3

<https://eduassistpro.github.io/>

after another  $\beta$  reduction  
after  $\delta$  reduction of =  
after reduction of *if* loop!  
because  $\lambda g \rightarrow \lambda (\lambda x. g(x))$   
after one  $\beta$  reduction  
after another  $\beta$  reduction  
after  $\delta$  reduction of =  
after  $\delta$  reduction of *if*

Add WeChat edu\_assist\_pro

4. Other reduction orders may not terminate.

## Recursion and the lambda calculus

# Assignment Project Exam Help

- Now we have a lambda

<https://eduassistpro.github.io/>

$Y (\lambda f. (\lambda x. (\text{if } (x = 0) \ 3 \ (1 + (f \ (x - 1))))))$

Add WeChat edu\_assist\_pro

- But haven't we really just shifted the problem? — how do we define lambda calculus?

## Recursion and the lambda calculus

# Assignment Project Exam Help

The real magic : self-appli

<https://eduassistpro.github.io/>

$Y \equiv \lambda q. ( (\lambda x. (q (x x))) (\lambda x. (q (x x))) )$

Add WeChat edu\_assist\_pro

## Recursion and the lambda calculus

# Assignment Project Exam Help

Example :

$$\begin{aligned} Y\ h &= \lambda q. ( (\lambda x. ( \\ &= (\lambda x. (h\ (x\ x)) \\ &= h\ ((\lambda x. (h\ (x\ x)))\ (\lambda x. (h\ (x\ x)))) \\ &= h\ (Y\ h) \end{aligned}$$

<https://eduassistpro.github.io/>

2

line<sub>3</sub>

because

$\equiv Y\ h$

Add WeChat edu\_assist\_pro

## Recursion and the lambda calculus

# Assignment Project Exam Help

Deriving a  $\lambda$ -calculus

$$\begin{aligned} f &= (Y \ h) \\ &= (Y \ (\lambda \ f. (\lambda \ x. (\text{if } (x=0) \ 3 \ (1+(f(x-1))))))) \\ &= ((\lambda q. ((\lambda x. (q \ (x \ x))) (\lambda y. (q \ (y \ y)))) (\lambda z. (\lambda x. (\text{if } (x \end{aligned}$$

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Summary

# Assignment Project Exam Help

- Recursive function
- Recursive function

- ▶ Binding for function name
- ▶ Fixed point
- ▶ Fixed point operator
- ▶ Self-application

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro