

Assignment Project Exam Help

COMP0020 Functional Programming

<https://eduassistpro.github.io/>

(2)

Add WeChat edu_assist_pro

Contents

Assignment Project Exam Help

- Structural induction
- Passing data between functions
- Modes of recursion : tail recursion
- Removing mutual recursion
- Lazy evaluation : infinite lists

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Induction on Lists : “append”

- The “append” function takes two lists of anything and returns a single list consisting of all the elements of the first list, followed by all the elements of the second list.
- Type :
 $\text{append} : ([*], [*]) \rightarrow [*]$
- Possible Induction

<https://eduassistpro.github.io/>

$\text{append } (xs$

OR : $\text{append } ((x$

OR : $\text{append } (xs$

to help define the general case :

$\text{append } ((x : xs), (y : ys)) = \text{????}$

Add WeChat [edu_assist_pro](#)

Induction on Lists : “append”

Assignment Project Exam Help

- Think about what each possible induction hypothesis would give you
- For example, if we w

<https://eduassistpro.github.io/>

ap (, (:)) [, , , ,] *hat help?*

append((x : xs), ys) *gives* *lp?*

append(xs, ys) *gives* ?

Add WeChat edu_assist_pro

Induction on Lists : “append”

Assignment Project Exam Help

- Answer : use append recursion. The gen

<https://eduassistpro.github.io/>

- Or, simply :

Add WeChat `edu_assist_pro`

`append((x:ls), any) = x ++ (append(x`

Induction on Lists : “append”

Assignment Project Exam Help

- Base case (for para

- We choose the answ

- Or, simply :

<https://eduassistpro.github.io/>

$\text{append}([], (y : ys)) = (y : y$

Add WeChat edu_assist_pro

$\text{append}([], \text{any}) = a$

Induction on Lists : “append”

Assignment Project Exam Help

- Final solution :

<https://eduassistpro.github.io/>

$([], \quad) =$

$\text{append}((x : xs), \text{any}) = x$

Add WeChat edu_assist_pro

Passing data between functions

Assignment Project Exam Help

- A functional programming
- Focus on how data passes
- Example : insertion sort “isort”

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Insertion Sort (specification)

Assignment Project Exam Help

- Define “sorted list”

- ▶ An empty list is sorted
- ▶ A singleton list is sorted
- ▶ The list $(x : xs)$ is sorted

- ★ x is less than all items in xs , AND
- ★ xs is sorted

- NB only lists of numbers

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Insertion Sort (strategy)

Assignment Project Exam Help

- Start with two lists A and B
- A is the input list
- B is initially empty
- One at a time, move an element from A to B
- Ensure that at all times B is sorted

- ▶ We will need a function that can insert a number into a sorted list and return

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Insertion Sort (design)

Assignment Project Exam Help

- The list B is an accumu
 - ▶ So use accumu

- Top-down appro
(leap of faith !)

- Then design “insert”

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Insertion sort

Assignment Project Exam Help

`||comments...`

<https://eduassistpro.github.io/>

`||comments...`

Add WeChat `edu_assist_pro`

```
xsort :: [num] -> [num]
xsort [] = sorted
xsort (x : xs) sorted = sorted
```

```
xsort (x : xs) sorted = xsort xs (sorted < x)
```

Insertion sort

Assignment Project Exam Help

- Code for “insert

<https://eduassistpro.github.io/>

`[] = []`

`insert x (y : ys) = (x : (y`

Add WeChat `edu_assist_pro`

Insertion sort (code 3)

Assignment Project Exam Help

- Use induction hypothesis : assume that “insert x ys” correctly inserts x into the list ys and produces the correct sorted lis

<https://eduassistpro.github.io/>

$[] = []$

$\text{insert } x (y : ys) = (x : (y :$

Add WeChat $= y) : (\text{ins}$ edu_assist_pro

Insertion sort — full code

Assignment Project Exam Help

```
isort :: [num] -> [num]
isort any = xsort any []
```

<https://eduassistpro.github.io/>

```
xsort (x : xs) sorted = xsort xs
```

Add WeChat edu_assist_pro

```
insert :: num -> [num] -> [num]
insert x [] = [x]
insert x (y : ys) = (x : (y : ys)), if (x < y)
                  = (y : (insert x ys)), otherwise
```

More modes of recursion

1 : tail recursion

Assignment Project Exam Help

<https://eduassistpro.github.io/>

mylast ($x : []$) = x

mylast ($x : xs$) = *mylast* xs

Add WeChat edu_assist_pro

More modes of recursion

2 : mutual recursion

Assignment Project Exam Help

<https://eduassistpro.github.io/>
 (:) = (: ())

Add WeChat edu_assist_pro

```

xnasty : [char] -> [char]
xnasty [] = error "mi
xnasty (')' : rest) = nasty rest
xnasty (x : xs) = xnasty xs
  
```

Removing mutual recursion

Assignment Project Exam Help

skip :: [char] -> [char]

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

doskip :: [char] -> [char]

doskip [] = error "m"

doskip (':') : rest) = rest

doskip (x : xs) = doskip xs

Lazy evaluation : infinite lists

- Lazy evaluation of function arguments

- ▶ Evaluate `fst (24, (37 / 0))`

- ▶ Remember `de`

```
fst :: (*,**) -> *
```

```
fst (x,y) = x
```

- Lazy evaluation of `data`

- ▶ Some forms of “bad” recursion may NOT result in infinite execution because lazy evaluation of data constructors means that they are evaluated ONLY AS FAR AS NE

```
f :: num -> [num]
```

```
f x = (x : (f (x + 1)))
```

```
main = hd (tl (f 34))
```

- ▶ Another example :

```
ones = (1 : ones)
```

```
main = hd (tl (tl ones))
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Summary

Assignment Project Exam Help

- Structural induction
- Passing data betw
- Modes of recursion : tail recursion and mutual recursion
- Removing mutual recursion
- Lazy evaluation : infinite lists

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro