

Assignment Project Exam Help

<https://eduassistpro.github.io/>

2 : reversed lists

Add WeChat edu_assist_pro

Motivation

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Primarily to give a be

Add WeChat edu_assist_pro

Contents

Assignment Project Exam Help

- Preamble (repeat

- ▶ Curried functions
- ▶ Higher order functions
- ▶ Higher order functions

- Example :

- ▶ reminder : normal lists and functions
- ▶ new : adding elements to a list in reverse order

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Preamble (1)

- Recall CURRIED functions :

- ▶ $f \circ b \circ a \in (a \rightarrow b)$

- ▶ Can help to think of binary tree giving syntax of the function applied to its arguments :

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Preamble (2)

- Recall HIGHER ORDER functions :

- ▶ $f \circ b \circ c = c(a \circ b)$
- ▶ c must be a function (of at least one argument)
- ▶ a must be a function (of at least one argument)
- ▶ e.g. $f (*2) 4 (+1)$
 $= (+1) ((*2) 4)$
 $= 1 + (2 * 4)$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Preamble (3)

- Recall HIGHER ORDER functions can return functions

- ▶ `g a b = (+ a)`
`main = g 3 4 5`
- ▶ Too many arg
- ▶ No!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

$\text{cons } a \ b \ f = f$
 $\text{nil} \quad f = f$

head tail isnil
 \downarrow \downarrow \downarrow
 a b False
 $(\text{error "head of nil"})$ $(\text{error "tail of nil"})$ True

Assignment Project Exam Help

$\text{head } x$
 $=$
 $\text{tail } x = x \ t$
 $\text{isnil } x = x \ g$

where
 $t \ a \ b \ c = b$
 $g \ a \ b \ c = c$

$\text{https://eduassistpro.github.io/}$
 $=$
 $'B' \ z$

Add WeChat edu_assist_pro

where
 $g \ a \ b \ c = c$

$\parallel \rightarrow \text{cons } 'B' \ z \ h$
 $\parallel \rightarrow h \ 'B' \ z \ \text{False}$
 $\parallel \rightarrow 'B'$

- Consider :

```

head (tail (tail (cons a (cons b nil))))
→ (tail (tail (cons a (cons b nil)))) h
→ ( (tail (cons a (cons b nil))) t) h
→ ( ( (cons a (cons b nil)
→ ( ( cons a (cons b nil) t
→ ( ( t a (cons b nil) ) f a
→ ( (cons b nil) t) h
→ ( cons b nil t) h
→ (t b nil False) h
→ nil h
→ h (error "head of nil") (error "tail of nil") True
→ error "head of nil"

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Consider :

`isnil nil`

→ nil g

→ g (error "head of n

→ True

`isnil (cons a nil)`

→ (cons a nil) g

→ g a nil False

→ False

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Reversed lists as functions !

Assignment Project Exam Help

- Sometimes you may want to reverse the order of a list
 - ▶ Either save in a list
 - ▶ Or use a special data type that allows you to add in reverse order but create around !

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Reversed lists as functions !

Assignment Project Exam Help

Type definition of a reversed list (called an "rlist") — it's a function
 $rlist * == [*] \rightarrow [*]$

Definition $rcons :: _ \rightarrow [*] \rightarrow [*]$
 $rcons v g =$

f

where

$f\ x = g(v : x)$

Definition of rnil which is the empty rlist

$rnil :: rlist *$

$rnil\ x = x$

<https://eduassistpro.github.io/>
 Add WeChat edu_assist_pro

rlist (alternative definition for rcons)

Assignment Project Exam Help

$$rcons :: * \rightarrow * \rightarrow rlist \quad || \quad * \rightarrow ([*] \rightarrow [*]) \rightarrow ([*] \rightarrow [*])$$

$$> [*] \rightarrow [*]$$

$rcons \ v \ g \ x$

<https://eduassistpro.github.io/>

NB : for function types, type expressions bracket from the right. Thus :

Add WeChat edu_assist_pro

$$num \rightarrow num \rightarrow nu$$

$$\equiv num \rightarrow (num \rightarrow (num \rightarrow num))$$

rlist

Assignment Project Exam Help

*|| Defined previously :**rlist ***rcons r g x**rnil x**|| Definition of rhd which gives the head of the list**rhd :: rlist a -> a**rhd g = hd (g [])*<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

rlist

|| Defined previously :

```

rlist * == [*] -> [*]
rcons v g x = g (v : x)
rnil x = x

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

```

x = (rcons 2 (rcons

```

Add WeChat edu_assist_pro

```

main = rhd x
→ hd ((rcons 2 (rcons
→ hd ((rcons 3 rn timer) (2 : []))
→ hd (rn timer (3 : (2 : [])))
→ hd (3 : (2 : []))
→ 3

```

rlist

Assignment Project Exam Help

Defined previously :

<https://eduassistpro.github.io/>
= ([])

Add WeChat [edu_assist_pro](#)

Turning an rlist into a list

rlist2list :: rlist → [a]

rlist2list r = r []

rlist

|| Defined previously :

```

rlist * ==> [*]
rcons v g x = g (v : x)
rnil x = x

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

|| Example :

Add WeChat [edu_assist_pro](https://eduassistpro.github.io/)

```

main = rlist (rcons 'A
→ rcons 'A' (rcons 'B' rn timer) [
→ (rcons 'B' rn timer) ('A' : [])
→ rn timer ('B' : ('A' : []))
→ ('B' : ('A' : [])) ≡ ['B', 'A']

```


Summary

Assignment Project Exam Help

- Two Examples : <https://eduassistpro.github.io/>
 - ▶ reminder : normal lists represented by functions
 - ▶ new : adding elements to a list in reverse order
- Motivation : [Add WeChat edu_assist_pro](#)
 - ▶ Primarily, to give a better understanding of, and facility with, high

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro