

# Assignment 2: blobby, Blobby

version: 1.4 last updated: 2020-11-10 15:30:00

## Aims

- building a concrete understanding of file system objects
- practising C including byte-level operations
- understanding file operations, including I/O of binary data and robust error-handling

## Background

A [file archive](#) is a single file which can contain the contents, names and other metadata of multiple files. File archives make backups and transport of files more convenient, and make compression more efficient.

The some common archive formats are:

- [tar](#) for linux. (uses external compression tools)
- [zip](#) for windows. (with inbuilt compression)

Wikipedia's [list](#) of common file archive formats.

## Your Task

Assignment Project Exam Help

Your task in this assignment is to write

<https://eduassistpro.github.io/>

The file archiv

Each **blob** con [edu\\_assist\\_pro](https://eduassistpro.github.io/)

Each **blobette** system object.

Their format is described below

Assignment Project Exam Help

**blobby.c** should be able to:

Add WeChat edu\_assist\_pro

- list the contents of a *blob* ([subset 0](#)),
- list the permissions of files in a *blob* ([subset 0](#)),
- list the size (number of bytes) of files in a *blob* ([subset 0](#)),
- check the *blobette* magic number ([subset 0](#)),
- extract files from a *blob* ([subset 1](#)),
- check *blobette* integrity (hashes) ([subset 1](#)),
- set the file permissions of files extracted from a *blob* ([subset 1](#)),
- create a *blob* from a list of files ([subset 2](#)),
- list, extract, and create *blobs* that include directories ([subset 3](#)),
- list, extract, and create *blobs* that are compressed ([subset 4](#)).

## Subset 0

Given the `-l` command line argument `blobby.c` should for each file in the specified *blob* print:

1. The file/directory permissions in octal
2. The file/directory size in bytes
3. The file/directory pathname

It should check *blob* magic number on each *blobette*, and emit an error if it is incorrect.

```
# List the details of each item in the blob called text_file.blob, which is in the examples
directory
$ ./blobby -l examples/text_file.blob
100644    56 hello.txt
# List the details of each item in the blob called 4_files.blob, which is in the examples
directory
$ ./blobby -l examples/4_files.blob
100644    256 256.bin
100644     56 hello.txt
100404    166 last_goodbye.txt
100464    148 these_days.txt
# List the details of each item in the blob called hello_world.blob, which is in the examples
directory
$ ./blobby -l examples/hello_world.blob
100644     87 hello.c
100644     82 hello.cpp
100644     65 hello.d
100644     77 hello.go
100644     32 hello.hs
100644    117 hello.java
100644     30 hello.js
100755     47 hello.pl
100755     97 hello.py
100644     45 hello.rs
100644    107 hello.s
100755     41 hello.sh
100644     24 hello.sql
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

#### HINT:

Use [fopen](#)

Use [fgetc](#) to read bytes

Use C bitwise operations such as `<<` & and `>>` to convert bytes into integers.

Think carefully about the functions you can use to avoid repeated code.

For example, for every byte you read with `fgetc` you need to call `blobby_hash` to calculate a new hash value, so write a function that does both. Hint: have the function take a pointer to a hash value which it can update.

Review `print_borts_file.c`, from our [week 8 tutorial](#) and `print_bytes.c` from our [week 8 lab](#).

[fseek](#) can be used to skip over parts of the *blob* file, but you can also use a loop and [fgetc](#)

#### NOTE:

The order you list files is the order they appear in the *blob*.

*blob* files do not necessarily end with *.blob*.

This has been done with the provided example files purely as a convenience.

The starting code contains a suitable `printf` to match the required format.

The correct format string for this output `"%06lo %5lu %s\n"` is provided in the given `blobby.c` file.

# Subset 1

Given the `-x` command line argument `blobby.c` should:

Extract the files in the specified *blob*.

It should set file permissions for extracted files to the permissions specified in the *blob*.

It should check *blob* integrity by checking each *blobette* hash, and emit an error if any are incorrect.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

[edu\\_assist\\_pro](https://eduassistpro.github.io/)[eduassistpro.github.io/](https://eduassistpro.github.io/)

Assignment Project Exam Help

Add WeChat edu\_assist\_pro

```

# Your program extracts the files into the current working directory.
# So we will run your program from a temporary directory (tmp) as to not clutter the base
directory.
# Once in the tmp directory your program and examples/ will be in the parent directory.
# Hence the use of .. in pathnames.

# Make a directory called tmp.
$ mkdir -p tmp/
# Change into the tmp directory.
$ cd tmp/
# Forcibly remove all files inside the tmp directory.
$ rm -f * .*
# Use your program to extract the contents of text_file.blob.
$ ../blobby -x ../examples/text_file.blob
Extracting: hello.txt
# Show the contents of hello.txt in the terminal.
# You can manually open it in your text editor too, if you like.
$ cat hello.txt
Hello COMP1521
I hope you are enjoying this assignment.
# Forcibly remove all files inside the tmp directory.
$ rm -f * .*
# Use your program to extract the contents of hello_world.blob.
$ ../blobby -x ../examples/hello_world.blob
Extracting: hello.c
Extracting: hello.cpp
Extracting: hello.d
Extracting: hello.go
Extracting: hello.hs
Extracting:
Extracting:
Extracting: hello.pl
Extracting: hello.py
Extracting: hello.rs
Extracting: hello.s
Extracting: hello.sh
Extracting: hello.sql
# Show the first 25 lines from the extracted files to confirm the extraction was successful.
$ cat $(echo * | sort) | head -n 25
extern int puts(const char *s);

int main(void)
{
    puts("Hello, World!");
    return 0;
}
#include <iostream>

int main () {
    std::cout << "Hello, world!" << std::endl;
}
import std.stdio;

void main() {
    writeln("Hello, world!");
}
package main

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

[edu\\_assist\\_pro](https://eduassistpro.github.io/)

Assignment Project Exam Help

Add WeChat edu\_assist\_pro

```
import "fmt"

func main() {
    fmt.Println("Hello, World!")
}

main = putStrLn "Hello, World!"
# Forcibly remove all files inside the tmp directory
$ rm -f * .*
# Use your program to extract the contents of meta.blob.
$ ../blobby -x ../examples/meta.blob
Extracting: 1_file.subdirectory.blob
Extracting: 1_file.subdirectory.compressed.blob
Extracting: 2_files.blob
Extracting: 2_files.compressed.blob
Extracting: 3_files.bad_hash.blob
Extracting: 3_files.bad_magic.blob
Extracting: 3_files.blob
Extracting: 3_files.compressed.blob
Extracting: 3_files.subdirectory.bad_hash.blob
Extracting: 3_files.subdirectory.bad_magic.blob
Extracting: 3_files.subdirectory.blob
Extracting: 3_files.subdirectory.compressed.blob
Extracting: 4_files.blob
Extracting: 4_files.compressed.blob
Extracting: all_the_modes.subdirectory.blob
Extracting: all_the_modes.subdirectory.compressed.blob
Extracting: binary_file.blob
Extracting: binary_file.compressed.blob
Extracting:
Extracting:
Extracting:
Extracting: hello_world.compressed.blob
Extracting: lecture_code.subdirectory.blob
Extracting: lecture_code.subdirectory.
Extracting: text_file.bad_hash.blob
Extracting: text_file.bad_magic.blob
Extracting: text_file.blob
Extracting: text_file.compressed.blob
# Show the first 10 items in this directory alphabetically to check extraction was successful.
$ ls -1 $(echo * | sort) | head
1_file.subdirectory.blob
1_file.subdirectory.compressed.blob
2_files.blob
2_files.compressed.blob
3_files.bad_hash.blob
3_files.bad_magic.blob
3_files.blob
3_files.compressed.blob
3_files.subdirectory.bad_hash.blob
3_files.subdirectory.bad_magic.blob
# Go back into the directory with your code.
$ cd ../
# Remove the tmp directory and everything inside it.
$ rm -rf tmp/
```

#### HINT:

Use [`fopen`](#) to open each file you are extracting.

Use [`fputc`](#) to write bytes to each file..

In our [lectures on files](#) we covered copying bytes to a file in the [`cp\_fgetc.c`](#) example and setting the permissions of a file in the [`chmod.c`](#) example.

#### NOTE:

blobby should overwrite an files that already exist.

blobby can leave already extracted/partially extracted files in the event of an error.

## Subset 2

Given the `-c` command line argument `blobby.c` should:

Create a *blob* containing the specified files.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

[edu\\_assist\\_pro](https://eduassistpro.github.io/)

Assignment Project Exam Help

Add WeChat edu\_assist\_pro

```
# These "echo" lines show you how to create these test files and what their contents are.

# Create a file called hello.txt with the contents "hello".
$ echo hello > hello.txt
# Create a file called hola.txt with the contents "hola".
$ echo hola > hola.txt
# Create a file called hi.txt with the contents "hi".
$ echo hi > hi.txt
# Set the permissions of these files to 644 (octal permission string (equivalent to rw-r--r--)).
# When you list the contents of the blob, the permissions should match this.
$ chmod 644 hello.txt hola.txt hi.txt
# Create a blob called selamat.blob with the files hello.txt, hola.txt, and hi.txt.
$ ./blobby -c selamat.blob hello.txt hola.txt hi.txt
Adding: hello.txt
Adding: hola.txt
Adding: hi.txt
# List the contents of selamat.blob.
$ ./blobby -l selamat.blob
100644      6 hello.txt
100644      5 hola.txt
100644      3 hi.txt
# Make a directory called tmp.
$ mkdir -p tmp/
# Change into the tmp directory.
$ cd tmp/
# Forcibly remove all files in
$ rm -f * .*
# Use your program to extract
$ ../blobby
Extracting:
Extracting: hola.txt
Extracting: hi.txt
# Check that the extracted file hello.txt is the same as the source file ../hello.txt.
$ diff -s ../hello.txt hello.txt
Files ../hello.txt and hello.txt are identical
# Check that the extracted file hola.txt is the same as the source file ../hola.txt.
$ diff -s ../hola.txt hola.txt
Files ../hola.txt and hola.txt are identical
# Check that the extracted file hi.txt is the same as the source file ../hi.txt.
$ diff -s ../hi.txt hi.txt
Files ../hi.txt and hi.txt are identical
# Go back into the directory with your code.
$ cd ../
# Remove the tmp directory and everything inside it.
$ rm -rf tmp/
```

#### HINT:

Use [fopen](#) and [fputc](#) to create the new blob.

In our [lectures on files](#) we covered obtaining file metadata including its size and mode (permissions) in the [stat.c](#) example.

#### NOTE:



You must add/store files in the order they are given.

## Subset 3

Given the **-c** command line argument `blobby.c` should:

Be able to add files in sub-directories, for examples:

```
# Create a blob called a.blob with the file "hello.txt" that is contained within 2 levels of
directories.
$ ./blobby -c a.blob examples/2_files.d/hello.txt
Adding: examples
Adding: examples/2_files.d
Adding: examples/2_files.d/hello.txt
```

If a directory is specified when creating a *blob* `blobby.c` should add the entire directory tree to the *blob*.

```
# Create a blob called a.blob with *all* the contents within the directory
"3_files.subdirectory.d"
# which is in the "examples" directory.
$ ./blobby -c a.blob examples/3_files.subdirectory.d
Adding: examples
Adding: examples/3_files.subdirectory.d
Adding: examples/3_files.subdirectory.d/goodbye
Adding: examples/3_files.subdirectory.d/goodbye/last_goodbye.txt
Adding: examples/3_files.subdirectory.d/hello
Adding: examples/3_files.subdirectory.d/hello/hello.txt
Adding: examples/3_files.subdi
```

Given the **-l** command line argument a `blobby.c` should:

Be able to list f

```
$ ./blobby -l examples/1_file.subdirectory.blob
040755    0 hello
100644   56 hello/hello.txt
```

Given the **-x** command line argument and a *blob* `blobby.c` should:

Be able to extract files and directories, for example:

```
$ ./blobby -x examples/3_files.subdirectory.blob
Creating directory: goodbye
Extracting: goodbye/last_goodbye.txt
Creating directory: hello
Extracting: hello/hello.txt
Extracting: these_days.txt
```

### HINT:

In our [lectures on files](#) we covered creating a directory in the [mkdir.c](#) example and listing a directories contents in the [list\\_directory.c](#) example.

Traversing a directory tree is challenging and can be done in several ways.

### NOTE:



The *blobby* reference implementation will add subdirectories in alphabetical order

This behaviour doesn't need to be matched.

Your implementation can add subdirectories in any order.

If a file in a different directory is added to a *blob*, then the directories in the path need to be added to the *blob*.

When extracting a *blob* with directories, the directory needs to be created if it does not already exist and the directories permissions need to be set to those specified in *blob*

## Subset 4

Given the `-c` and the `-z` command line argument `blobby.c` should:

Compress all bytes of the *blob* using the external program [xz](#).

The function [posix\\_spawn](#) or [posix\\_spawnnp](#) must be used to run [xz](#).

```
# Create a blob called h.blob with the file selamat.txt.
# Using the "xz" program for compression.
$ ./blobby -z -c h.blob selamat.txt
Adding: selamat.txt
# Show the file type of h.blob to confirm it was compressed using "xz".
$ file h.blob
h.blob: XZ compressed data
```

The `-z` option does not need to be specified when extracting (`-x`) or listing (`-l`) compressed *blobs* and is ignored if it is specified.

`blobby.c` should automatically recognize compressed *blobs* when extracting (`-x`) or listing (`-l`)

```
$ ./blobby -x examples/4_files.compressed.blob
100644 56
$ ./blobby -l examples/4_files.compressed.blob
100644 256 256.bin
100644 56 hello.txt
100404 166 last_goodbye.txt
100464 148 these_days.txt
$ ./blobby -l examples/hello_world.compressed.blob
100644 87 hello.c
100644 82 hello.cpp
100644 65 hello.d
100644 77 hello.go
100644 32 hello.hs
100644 117 hello.java
100644 30 hello.js
100754 47 hello.pl
100754 97 hello.py
100644 45 hello.rs
100644 107 hello.s
100754 41 hello.sh
100644 24 hello.sql
```

### HINT:

Subset 4 is highly challenging. The [spawn\\_read\\_pipe](#) example and the [spawn\\_write\\_pipe.c](#) example from our [lectures on processes](#) show most of the necessary operations but implementing this subset will require research and careful experimentation.

NOTE:

You are not permitted to use: [system](#), [popen](#), [fork/execve](#) or any other C functions to run [xz](#).

You must run [xz](#) as an external program via `posix_spawn(3)` or `posix_spawnnp(3)` .

Temporary files are not permitted.

Compressed *blob* files do not necessarily end with `.compressed.blob`.

This has been done with the provided example files purely as a convenience.

## Reference implementation

A reference implementation is available as `1521_blobby` which can use to find the correct output for any input, like this:

```
$ 1521_blobby -l <blob file to list>
# [] means "optionally", ... means "repeated"
$ 1521_blobby [-z] -c <blob file to create> <file to add to the blob> [...]
$ 1521_blobby -x <blob file to extract>
```

HINT:

All the examples in the in the subsets above are runnable using the reference implementation.

Simply replace `./blobby` with `15`

Provision of a [reference implementation](#) and an effective method to provide or define an operational space for something you will likely need to work with after you leave UNSW.

Where any aspect of this assignment is undefined in this specification you should match the reference implementation's behaviour.

Discovering and matching the reference implementation or is deliberately part of the assignment.

If you discover what you believe to be a bug in the reference implementation, report it in the class forum. If it is a bug, we may fix the bug, or indicate that you do not need to match the reference implementation's behaviour in this case.

## Blob Format

*blobs* must follow exactly the format produced by the reference implementation.

A *blob* consists of 1 or more *blobettes*. Each *blobette* contains the information about one file or directory.

Field Length (bytes)	Field Name	Possible Values	Description
1	magic_number	0x42	byte 0 in every blobette must be 0x42 (ASCII 'B')
3	mode		file type and permissions as returned in <code>st_mode</code> field from <code>lstat(2)</code>
2	pathname_length	1..65535	number of bytes in file/directory pathname
6	content_length	0..281474976710655	number of bytes in file 0 for directories
pathname_length	pathname		file/directory pathname

content_length	contents	bytes (contents) of file empty for directories
1	hash	0..255
		blobby_hash( ) of all bytes of this blobette except this byte

blobette format

*mode*, *pathname\_length* and *content\_length* are always stored in [big-endian format](#). It is recommended you construct their values from their individual bytes using bit-operations.

Side-note: an interesting property of the *blob* format is the concatenation of 2 or more *blobs* is a valid *blob*.

We can use the reference implementation to create simple *blobs* and inspect their contents.

For example, using the `print_bytes.c` program written as a lab exercise:

```
$ echo hola > hi.txt
$ chmod 640 hi.txt
$ 1521 blobby -c h.blob hi.txt
Adding: hi.txt
$ ./print_bytes h.blob
byte 0: 66 0x42 'B'
byte 1: 0 0x00
byte 2: 129 0x81
byte 3: 160 0xa0
byte 4: 0 0x00
byte 5: 6 0x06
byte 6: 0 0x00
byte 7: 0 0x00
byte 8: 0 0x00
byte 9:
byte 10:
byte 11:
byte 12: 104 0x68 'h'
byte 13: 105 0x69 'i'
byte 14: 46 0x2e '.'
byte 15: 116 0x74 't'
byte 16: 120 0x78 'x'
byte 17: 116 0x74 't'
byte 18: 104 0x68 'h'
byte 19: 111 0x6f 'o'
byte 20: 108 0x6c 'l'
byte 21: 97 0x61 'a'
byte 22: 10 0x0a
byte 23: 95 0x5f '_'
```

Note in the above example *pathname\_length* is **6** *content\_length* is **5** and the blobby hash is **0x5f**.  
The Linux utility `xxd(1)` is a good way to inspect *blobs*, for example, here is a *blob* containing 2 files (2 *blobettes*).

```
$ xxd examples/2_files.blob
00000000: 4200 81a4 0009 0000 0000 0038 6865 6c6c  B.....8hell
00000010: 6f2e 7478 7448 656c 6c6f 2043 4f4d 5031  o.txtHello COMP1
00000020: 3532 310a 4920 686f 7065 2079 6f75 2061  521.I hope you a
00000030: 7265 2065 6e6a 6f79 696e 6720 7468 6973  re enjoying this
00000040: 2061 7373 6967 6e6d 656e 742e 0a66 4200  assignment..fB.
00000050: 81a4 0010 0000 0000 00a6 6c61 7374 5f67  .....last_g
00000060: 6f6f 6462 7965 2e74 7874 5468 6973 2069  oodbye.txtThis i
00000070: 7320 6f75 7220 6c61 7374 2067 6f6f 6462  s our last goodb
00000080: 7965 0a49 2068 6174 6520 746f 2066 6565  ye.I hate to fee
00000090: 6c20 7468 6520 6c6f 7665 2062 6574 7765  l the love betwe
000000a0: 656e 2075 7320 6469 650a 4275 7420 6974  en us die.But it
000000b0: 2773 206f 7665 720a 4a75 7374 2068 6561  's over.Just hea
000000c0: 7220 7468 6973 2061 6e64 2074 6865 6e20  r this and then
000000d0: 4927 6c6c 2067 6f0a 596f 7520 6761 7665  I'll go.You gave
000000e0: 206d 6520 6d6f 7265 2074 6f20 6c69 7665  me more to live
000000f0: 2066 6f72 0a4d 6f72 6520 7468 616e 2079  for.More than y
00000100: 6f75 276c 6c20 6576 6572 206b 6e6f 770a  ou'll ever know.
00000110: 64                                     d
```

In this example the first *blobette* starts at byte `0x00000000` and has the hash value `0x66` (ASCII `'f'`). While the second *blobette* starts at byte `0x0000004E` and has the hash value `0x64` (ASCII `'d'`).

Also usable are the `od(1)`

and `hexdump(1)` utilities.

## Blobby Hash

Each *blobette* contains a hash value called *blobette*.

This allows us to detect corruption, for example by disk or network errors.

The hash value is calculated by the `blobby_hash()` function.

You are given code which already implements `blobby_hash()`.

If we create a tiny *blob* containing a single 1 byte file like this:

```
# write a single new file (ASCII 'm')
$ echo > a
$ 1521 blobby -c a.blob a
```

We can inspect the *blob* with `xxd(1)` and see its hash is `0x6d` (ASCII `'m'`).

```
$ xxd a.blob
00000000: 4200 81a4 0001 0000 0000 0001 610a 6d      B.....a.m
```

These are the calls to `blobby_hash()` which calculate this value:

```

blobby_hash(00, 42) = de
blobby_hash(de, 00) = 3f
blobby_hash(3f, 81) = 81
blobby_hash(81, a4) = fc
blobby_hash(fc, 00) = c8
blobby_hash(c8, 01) = 57
blobby_hash(57, 00) = a3
blobby_hash(a3, 00) = ab
blobby_hash(ab, 00) = 69
blobby_hash(69, 00) = 7f
blobby_hash(7f, 00) = 11
blobby_hash(11, 01) = fb
blobby_hash(fb, 61) = 3b
blobby_hash(3b, 0a) = 6d

```

The initial hash value starts as 0,

But then becomes the resulting hash value of the previous call to `blobby_hash()`

```
blobby_hash(<initial hash value>, <byte value>) = <resulting hash value>
```

## Getting Started

Create a new directory for this assignment called `blobby`,  
change to this directory, and fetch the provided examples:  
by running these commands:

```

$ mkdir -m 700 blobby
$ cd blobby
$ 1521 fetch blobby
$ unzip examples.zi

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Or, if you're not comfortable with the command line, you can find the `examples.zip` and [starting code](#) at [edu\\_assist\\_pro](https://eduassistpro.github.io/)

You have been given starting code for this assignment in `blobby.c` which already implements handling command line arguments.

Assignment Project Exam Help

```

$ gcc blobby.c -o blobby
$ ./blobby
Usage:
  ./blobby -l <blob-file>
  ./blobby -x <blob-file>
  ./blobby [-z] -c <blob-file> pathnames [...]

```

Add WeChat edu\_assist\_pro

The supplied code calls:

- the function `list_blob()` to list the contents of a *blob* ([subset 0](#))
- the function `extract_blob()` to extract files from a *blob* ([subset 1](#))
- the function `create_blob()` to create a *blob* ([subset 2](#))

You need to add code to these functions.

You will need to add extra functions and `#defines`.

You may optionally create extra `.c` or `.h` files if you choose.

## Error Handling

Error checking is an important part of this assignment and automarking will test error handling.

Error messages should be one line (only) and be written to `stderr` (not `stdout`).

`blobby.c` should exit with status 1 after an error.



If you need clarification on what you can and cannot use or do for this assignment:  
ask in the class forum.

You are not permitted to create or use temporary files.

You are required to submit intermediate versions of your assignment:  
See below for details.

Your program must not require extra compile options.

It must compile with:

```
$ dcc *.c -o blobby
```

It will be run with dcc when marking.

Run-time errors from illegal C will cause your code to fail automarking.

If your program writes out debugging output, it will fail automarking tests:  
make sure you disable debugging output before submission.

## Assessment

## Testing

Assignment Project Exam Help

When you think your program is working, you can run simple automated tests:

```
$ 1521 auto
```

If you only want to test a subset of the tests.

You can specify a filter:

```
$ 1521 autotest blobby subset? blobby.c [any other .c or .h files]
```

1521 autotest will not test everything.

Always do your own testing.

Automarking will be run by the lecturer after the submission deadline, using a superset of tests to those autotest runs for you.

### WARNING:

The errors from 1521 autotest will become less and less useful as you continue into later subsets.

Our ability to show what error has occurred becomes substantially harder than our ability to detect errors in subsets 3 and 4.

Thus, 1521 autotest may show a failed test and not give the best explanation as to why the test has failed in later subsets.

## Submission

When you are finished working on the assignment, you must submit your work by running give:

```
$ give cs1521 ass2_blobby blobby.c [other .c or .h files]
```



You must run give before **Sunday November 22 21:00 2020** to obtain the marks for this assignment. Note that this is an individual exercise, the work you submit with give must be entirely your own.

You can run give multiple times.  
Only your last submission will be marked.

If you are working at home, you may find it more convenient to upload your work via [give's web interface](#).

You *cannot* obtain marks by e-mailing your code to tutors or lecturers.

You can check your latest submission on CSE servers with:

```
$ COMP1521 classrun -check ass2_blobby
```

You can check the files you have submitted [here](#).

Manual marking will be done by your tutor, who will mark for style and readability, as described in the **Assessment** section below. After your tutor has assessed your work, you can [view your results here](#); The resulting mark will also be available [via give's web interface](#).

## Due Date

This assignment is tentatively due **Sunday November 22 21:00 2020**.  
If your assignment is submitted after this date, each hour it is late reduces the maximum mark it can achieve by 2%. For example, if an assignment worth 74% was submitted 10 hours late, the late submission would have no effect. If the same assignment was submitted 15 hours late, it would be awarded 70%, the maximum mark it can achieve at that time.

## Assessment Scheme

This assignment will contribute **15 marks** to your final mark. **80%** of the mark will be awarded on the basis of the percentage of your code on a large series of tests. **20%** of the mark will come from hand marking.

These marks will be awarded on the basis of clarity, commenting, elegance and style. In other words, you will be assessed on how easy it is to read and understand your program.

An indicative assessment scheme follows. The lecturer may vary the assessment scheme after inspecting the assignment submissions, but it is likely to be broadly similar to the following:

<b>HD (95+%)</b>	beautiful documented code, perfectly readable code, all subsets (0-4) working for all blobs.
<b>HD (85+%)</b>	well documented code, very readable code, subsets 0-3 working for all blobs.
<b>DN (75+%)</b>	some documentation in code, readable code, subsets 0-2 working for all blobs.
<b>CR (65%)</b>	some documentation in code, readable code, subset 0-1 working for all blobs.
<b>PS (60%)</b>	subset 0 working for all blobs.

<b>0%</b>	knowingly providing your work to anyone; and it is subsequently submitted (by anyone).
<b>0 FL for COMP1521</b>	submitting any other person's work; this includes joint work.
<b>academic misconduct</b>	submitting another person's work without their consent; paying another person to do work for you.

## Intermediate Versions of Work

You are required to submit intermediate versions of your assignment.

Every time you work on the assignment and make some progress you should copy your work to your CSE account and submit it using the `give` command below. It is fine if intermediate versions do not compile or otherwise fail submission tests. Only the final submitted version of your assignment will be marked.

All these intermediate versions of your work will be placed in a Git repository and made available to you via a web interface at `https://gitlab.cse.unsw.edu.au/z5555555/20T3-comp1521-ass2_blobby` (replacing `z5555555` with your own zID). This will allow you to retrieve earlier versions of your code if needed.

## Attribution of Work

This is an individual assignment.

The work you submit must be entirely your own work, apart from any exceptions explicitly included in the assignment specification above. Submission of work partially or completely derived from any other person or jointly written with any other person is not permitted.

You are only permitted to request help from, help sessions, or from the teaching staff (the lectu

Do not provide on (including by posting it on the forum), apart from the teaching staff of COMP1521. If you knowingly provide or show your assignment work to another person for any reason, and work derived from it is submitted, you may be penalized, even if that work was submitted without your knowledge or consent; this may apply even if yo ed by a third party unknown to you. You will not be penalized if your work is taken without your cons.

Do not place your assignment work in online repositories such as github or any where else that is publically accessible. You may use a private repository.

Submissions that violate these conditions will be penalised. Penalties may include negative marks, automatic failure of the course, and possibly other academic discipline. We are also required to report acts of plagiarism or other student misconduct: if students involved hold scholarships, this may result in a loss of the scholarship. This may also result in the loss of a student visa.

Assignment submissions will be examined, both automatically and manually, for such submissions.

## Change Log

### Version 1.0

(2020-11-03 13:00:00)

- Initial release.

### Version 1.1

(2020-11-06 11:00:00)

- Update subset 3 autotests to ignore order of files in the blob

### Version 1.2

(2020-11-07 07:00:00)

- Clean-up the spec html, no changes to the assignment

### Version 1.3

(2020-11-09 13:10:00)

- Hints improved - mainly links to relevant lecture examples

### Version 1.4

(2020-11-10 15:30:00)

- Bug in reference implementation handling of blobs with invalid content length fixed

COMP1521 20T3: Computer Systems Fundamentals is brought to you by  
the [School of Computer Science and Engineering](#)  
at the [University of New South Wales](#), Sydney.  
For all enquiries, please email the class account at [cs1521@cse.unsw.edu.au](mailto:cs1521@cse.unsw.edu.au)  
CRICOS Provider 00098G

Assignment Project Exam Help

<https://eduassistpro.github.io/>

[edu\\_assist\\_pro](https://eduassistpro.github.io/)<https://eduassistpro.github.io/>

Assignment Project Exam Help

Add WeChat edu\_assist\_pro