

Assignment Project Exam Help

Turing Machines: Limits of Decidability
COMP1600 / COMP6260

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

Semester 2, 202

Interlude: What can Haskell programs do?

Observation. Turing machines 'recognise' strings. Haskell functions of type `String -> Bool` also recognise strings. For a Haskell program

Assignment Project Exam Help

we can define $L(p) = \{ w \mid w :: \text{String} \text{ and } pw = \text{True} \}$.

Question

```
> p :: String -> Bool
> p s = even (length s)
>
> q :: String -> Bool
> q s | even (length s) = True
>     | otherwise = q(s)
```

which of the following are true?

- $L(p)$ and $L(q)$ are the same, as non termination is non acceptance.
- $L(p)$ and $L(q)$ are not the same, as q does not always terminate.

Language of Haskell Programs

```
> p :: String -> Bool
> p s = even (length s)
> q :: String -> Bool
> q s | even (len
>      | otherwise = q(s
```

Recall.

Q. If $p\ w$ doesn't terminate, does it make sense to say $w \notin L(p)$?

Put differently.

- if $p\ w$ does not terminate, then w is not in $L(p)$.
- if $p\ w$ does terminate, and evaluates to `False`, then w is not in $L(p)$.
- The only way in which w can be in $L(p)$ is if $p\ w$ terminates *and* evaluates to `True`.

Language of Haskell Programs

```
> p :: String -> Bool
```

```
> p s = even (length s)
```

```
>
```

```
> q :: String -
```

```
> q s | even (len
```

```
>      | otherwise = q(s
```

Slogan.

Non-Termination or Termination with value Pa

For the programs above, that means $L(p) = L(q)$.

TM flashback. A machine M accepts w , if running M on w *terminates* and leaves M in an accepting state.

Assignment Project Exam Help

Q. Can TMs do more or less than Haskell acceptors?

- for e
 Bool
- for e $f :: \text{String} \rightarrow \text{Bool}$ TM M
 such so that $L(M) = L(f)$

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

From TMs to Haskell Programs.

Q. For every TM M , can we write a Haskell function $f :: \text{String} \rightarrow \text{Bool}$ so that $L(M) = L(f)$?

A. Easy. Implement / install / download a TM simulator, e.g.

https://github.com/eduardoassistenteproject/edu_assist_pro
s-0.1.0.
1/src/s

From Has

Q. For every Haskell function $f :: \text{String} \rightarrow \text{Bool}$
 M such so that $L(M) = L(f)$?

A. We would need to simulate the evaluation of Haskell p
Turing machine. This is hairy. But if we believe the Church-Turing thesis
(which we do), it's possible in principle.

Language Recogniser Hello World

Let's implement our first string recogniser in Haskell:

```
> simple :: String -> Bool
```

```
> simple s = (s == "hello world")
```

Hello Wor

ec, if:

- p ("h
- p(s

Q. Can we (in principle) write a Haskell program

```
hello-world-check :: String -> Bool
```

such that:

- hello-world-check(s) = True if s is a syntactically correct Haskell program that satisfies the hello world spec
- hello-world-check(s) = False if s is either not syntactically correct, or does not satisfy the hello world spec.

Interlude: Weird Integer Sequences

This unrelated function just computes an infinite sequence of Integers

```
> collatz :: Int -> [Int]
> collatz n | even n = n:(collatz (n `div` 2))
>             | otherwise = n:(collatz (3 * n + 1))
```

Observe

(try it!).

Contrived Hello World Recogniser.

```
> contrived :: String -> Bool
> contrived s = 1 `elem` (collatz (1 + length s)) &&
    (s == "hello world")
```

Q. Does contrived satisfy the hello world spec?

Assignment Project Exam Help

```
> contrived :: String -> Bool
> contrived s = 1 `elem` (collatz (1 + length s)) &&
```

Hello World

- return True if the argument is equal to "hello world"
- return False otherwise.

In particular, it should always return something!

Hence contrived is correct iff there's a 1 in collatz n for all $n \geq 1$.

Sneaky

```
> contrived :: String -> Bool
> contrived s = 1 `elem` (collatz (1 + length s)) &&
  (s == "hello world")
```

```
> collatz :
> collatz n | e
> otherwise = n / collatz
```

Apparently Simple.

- does a program satisfy the hello world spec?

Seemingly complicated.

- does `collatz n` contain a 1 for all $n \geq 1$?

Connection (by sneakily inserting `collatz`)

- *if* we can check whether a program satisfies hello word spec, *then* we can check whether `collatz n` contains a 1.

Bombshell Revelation

Collatz conjecture.

Assignment Project Exam Help

Does collatz n contain a 1 for every $n \geq 1$?

This is an un

<https://eduassistpro.github.io/>

Interpretation.

- this doesn't make it *impossible* that we
- but we would have to be more clever than generations of mathematicians.

What problems can we solve in principle?

Assignment Project Exam Help

Definition. A *problem* over an alphabet Σ is a set strings over Sigma. For Haskell, we consider $\Sigma = \text{Char}$.

A problem

$\text{String} \rightarrow \text{Bool}$

<https://eduassistpro.github.io>

$$P = L(f) = \{w :: \text{String} \mid f(w) = \text{True}\}$$

(repeating our earlier definition.)

Add WeChat edu_assist_pro

Example

$L = \{ w :: \text{String} \mid w \text{ is syntactically correct Haskell and defines a function } \text{String} \rightarrow \text{Bool} \text{ that accepts at least one string} \}$

To see that L is recursively enumerable: given $w :: \text{String}$

- che

Has

- now

```
(                                -- all pairs that add to 0
(0, 1), (1, 0)                  -- all pairs that add to 1
(0, 2), (1, 1), (2, 0)          -- all pairs that add to 2
.....
```

and walk through the list of all pairs. Whenever we see (i, j) , run w for i computation steps on all strings s of length j . If this gives 'True', terminate and return True, otherwise go to the next pair.

(We could implement this by inserting a evaluation step counter into a Haskell interpreter)

Discussion

Algorithm (short form) given $w :: \text{String}$:

- check that p defines a program p of type $\text{String} \rightarrow \text{Bool}$
- simulate execution of p for increasingly more steps on increasingly longer strings
- return

Observation

- we need to know n
- at runtime, we can't distinguish between not yet

Discussion

- Recursive enumerability is *weak*, and co-recursive enumerability terminates on positive instances, can ignore negative instances
- Stronger, and more difficult (and later): require that acceptor $\text{String} \rightarrow \text{Bool}$ always terminates.

Assignment Project Exam Help

$W = \{ w :: \text{Stri}$

<https://eduassistpro.github.io>

Q. Is W recursively enumerable, i.e. can we write a H $f ::$
String \rightarrow Bool such that $W = L(f)$?

Add WeChat edu_assist_pr

W is not Recursively Enumerable

$W = \{ w :: \text{String} \mid w \text{ is syntactically correct haskell and defines } f :: \text{String} \rightarrow \text{Bool} \text{ and } f \text{ w doesn't evaluate to True} \}$

Let's assume that there is $f :: \text{String} \rightarrow \text{Bool}$ with $W = L(f)$. Let

$sc :: \text{String}$

Case 1:

- Because $f \text{ } sc = \text{True}$, $sc \notin W$ (contradiction)
- Because $f \text{ } sc = \text{True}$, $sc \notin W$ (contradiction)

So case 1 cannot apply.

Case 2: $sc \notin W$.

- Then either sc is not syntactically correct or $f \text{ } sc$ does not eval to True.
- as sc is syntactically correct, it must be that $f \text{ } sc = \text{True}$.
- By definition of W , this means that $sc \in W$ (contrary to our assumption).

So case 2 can't apply, either, and therefore f cannot exist.

Back to Turing Machines

Preview. We will now do the same with Turing machines instead of Haskell programs. But why?

Mathematical Precision.

- wha


Simplicity

- to make the above precise, we have to dive deep into
- many features of Haskell are not used

Applicability to Other Models

- Using the TM model, we drill down to the very basics
- Can apply similar reasoning to any language that is Turing complete.

Coding a TM onto tape – example



The transition table is:

0	1	00	1	0	1	00	1	00
0	1	000	1	000	1	00	1	00
000	1	000	1	00	1	00	1	000

Recall: States, Symbols, Directions.

So the TM as a whole is encoded by the binary string

010010100100 11 010001000100100 11 00010001001001000

The coding plays the role of 'source code' in the Haskell examples.

Strings and Machines

TM Encoding

- a TM may have several encodings (i.e. order states or symbols)
- some strings may not be encodings at all, e.g. 110.

Question

- Is w
- If w is an encoding of a TM M , does M accept the string w , or reject it?

Q. Why does this make sense?

- it amounts to asking whether a TM accepts itself
- key step to exhibit non-recursively enumerable languages

A language that is not recursively enumerable

Definition. L_d is the set of binary strings w such that

w is a code of a Turing Machine M that rejects w

Assignment Project Exam Help

- d f
- 'rej

<https://eduassistpro.github.io>

Theorem. L_d is not recursively enumerable, i.e the accepts *precisely* L_d .

Proof (Sketch)

- Suppose for contradiction that TM M exists with $L(M) = L_d$.
- M has a binary encoding C (pick one of them)
- Question: is $C \in L_d$?

A language that is not recursively enumerable ctd.

Two Possibilities.

Option 1. $C \in L_d$

- then M accepts C because M accepts all strings in L_d
- but L_d contains only those TM (codes) w that *reject* w
- hen

Option 2.

- then M rejects C because M rejects all s
- but L_d contains all the encodings w of f
- so $C \in L_d$ – contradiction!

As we get a contradiction either way, our assumption that L_d can be recognised by a TM must be false.

In Short. There cannot exist a TM whose language is L_d .

Reflecting on this example

Assignment Project Exam Help

Reflections on the proof.

- the language L_d is artificial, designed for easy contradiction proof
- but it is
- if we had a machine that would be able to

<https://eduassistpro.github.io>

Questions.

- are all non-recursively enumerable languages
- are the problems that are not computable but of in

Add WeChat edu_assist_pro

The Halting Problem

Halting Problem.

Assignment Project Exam Help

Given a Turing machine M and input w , does M halt (either accepting or rejecting) on w ?

Blue Scre

- ans <https://eduassistpro.github.io>
- programs that don't get stuck in infinite loops ...

Partial Answers

- Add WeChat edu_assist_pro
- can give an answer for *some* pairs M ,
 - e.g. if M accepts straight away, or has no loops
 - difficulty: answer for *all* M , w .

The Halting Problem – a First Stab

First Attempt at solving the halting problem

- Feed M the input w , sit back, and see if it halts!

Critique.

- this is *not* a solution
- if M halts, we know it halts
- will get *no* answer if M doesn't halt!

Comparison with L_d

- this is *better* than L_d
- for L_d , we cannot guarantee *any* answer at all!

Recursively Enumerable vs. Recursive Languages

Recursively Enumerable Languages.

A language L is *recursively enumerable* if there is a Turing machine M so that M accepts precisely all strings in L ($L = L(M)$)

- if $w \notin L$, the T.M. may never terminate and give an answer.
- also called *semidecidable*
- can e
- whe

Recursive

A language L is *recursive* if there is a Turing machine M that accepts precisely the strings in L and rejects all strings not in L .

- *always* gives a yes/no answer
- also called *decidable*

Example.

- the language L_d is not recursively enumerable
- the halting problem is recursively enumerable
- ... but not recursive (as we will see next)

Recursive Problems in Haskell

Recall. A problem $P \subseteq \Sigma^*$ is recursively enumerable if

Assignment Project Exam Help

for some function $f :: \text{String} \rightarrow \text{Bool}$.

(The form

Criticism

Definition. A problem $P \subseteq \Sigma^*$ is recursive if

Add WeChat edu_assist_pr

$P = \{w :: \text{String} \mid f w = \text{True}\}$

for some function $f :: \text{String} \rightarrow \text{Bool}$ *that always terminates*.

(We will define this more formally with TMs later.)

Examples

Encoding.

- We have seen how Turing machines can be encoded as strings.
- Similarly, DFAs can be encoded as strings (we don't make this explicit).
- This

Question

enumerable?

1. $\{s \mid s \text{ is a code of a DFA that accepts } \epsilon\}$
2. $\{s \mid s \text{ is a code of a DFA that accepts at least one string}\}$
3. $\{s \mid s \text{ is a code of a TM that accepts } \epsilon\}$
4. $\{s \mid s \text{ is a code of a TM that accepts at least one string}\}$

Some Answers

DFA's accepting the empty string.

- decidable: just check whether the initial state is accepting.

Assignment Project Exam Help

DFA's accepting at least one string

- decidable: compute the set of reachable states

```
n = 0;
```

```
reach n = { q
```

```
repea
```

```
  n := n + 1
```

```
  reach (n) = { s | can reach s in one step from
```

```
    reach (n-1) } -- rea
```

```
until reach (n) = reach (n-1)      -- no new states found
```

```
reach := reach n
```

- check whether reach n contains a final state.

Other Problems. see Tutorial.

Assignment Project Exam Help

Halting Pr

$H = \{ \langle w, i \rangle \mid \text{St}$

so that f terminates $\}$

Add WeChat edu_assist_pr

H is recursively enumerable

$H = \{(w :: \text{String}, i :: \text{String}) \mid w \text{ is syntactically correct and defines } f: \text{String} \rightarrow \text{Bool} \text{ so that } f \text{ terminates}\}$

Algorithm to check whether (w, i) is in H:

- che
- che
- run

<https://eduassistpro.github.io>

Meta Programming.

- need to write a Haskell interpreter in Haskell
- this can be done (gcc is written in gcc)
- later: universal Turing machines

Add WeChat edu_assist_pro

Via Church Turing Thesis.

- we can write a Haskell interpreter
- by Church-Turing, this can be done in a TM
- as Haskell is Turing complete, this can be done in Haskell.

H is not recursive

$H = \{(w :: \text{String}, i :: \text{String}) \mid w \text{ valid Haskell}$
and defines $f :: \text{String} \rightarrow \text{Bool}$
and i terminates

Impossibility Argument assume total d exists with $L(d) = H \dots$

Detour. If w

$P :: \text{String} \rightarrow \text{Bool}$
 $P\ w = \text{if } d\ (w, w) \text{ then } P\ w \text{ else True}$

(infinite recursion whenever $d\ (w, w) = \text{True}$)

Let sc be the source code of P .

Case 1. $P\ sc$ terminates.

- then (sc, sc) is in H .
- then $d\ (sc, sc)$ evaluates to True
- then $P\ sc$ doesn't terminate. But this can't be!

H is not recursive

$H = \{(w :: \text{String}, i :: \text{String}) \mid w \text{ valid Haskell}$
and defines $f :: \text{String} \rightarrow \text{Bool}$
and i terminates

Impossibility Argument assume total d exists with $L(d) = H \dots$

Detour. If w

$P :: \text{String} \rightarrow \text{Bool}$

$P\ w = \text{if } d\ (w, w)\ \text{t}$

(infinite recursion whenever $d\ (w, w) = \text{True}$

Let sc be the source code of P .

Case 2. $P\ sc$ does not terminate.

- then (sc, sc) is not in H .
- then $d(sc, sc)$ returns `False`
- then $P\ sc$ does terminate. This can't be either!

As a conclusion, the function f (that decides H) cannot exist.

The Halting Problem

General Formulation (via Church Turing Thesis)

Assignment Project Exam Help

There is no program that always terminates, and determines whether (another) program terminates on a given input.'

Interpret

<https://eduassistpro.github.io>

There are problems that cannot be solved at all

- 'solve' means by a program that doesn't get stuck
- Halting problem is one example.

Add WeChat edu_assist_pro

(We have argued in terms of Haskell programs. Will do this via TMs next)

Assignment Project Exam Help

Flashback: `p :: String -> Bool` satisfies hello world spec, i.e.

- `p ("hello world") = True`
- `p(s`

Earlier.

<https://eduassistpro.github.io>

- checking whether `p` satisfies hello world sp

Now.

Add WeChat `edu_assist_pr`

- checking whether `p` satisfies hello world sp

Hello World Spec

Recall. $p :: \text{String} \rightarrow \text{Bool}$ satisfies hello world spec, if:

- $p(\text{"hello world"}) = \text{True}$
- $p(s) = \text{False}$, if $s \neq \text{"hello world"}$.

Impossibility argument. If there was

Define

```
halt :: S
halt w i = hello-world-check aux
where aux s = (s == "hello world") &&
              (w i = True || w i = False)
```

Observation

- if hello-world-check were to exist, we could solve the Halting problem
- general technique: *reduction*, i.e. use a hypothetical solution to a problem to solve one that is unsolvable.

Assignment Project Exam Help

Question. Consider the set

$$T = \{ w :: \text{Stri} \}$$

<https://eduassistpro.github.io>

Is T recursively enumerable? Even recursive?

Add WeChat edu_assist_pr

Back to TMs: The Universal TM

TMs that simulate other TMs

- given a TM M , it's easy to work out what M does, given some input
- it is an *algorithm*. If we believe the Church-Turing thesis, this can be accomplished by (another) TM.

Universal TM

- is a TM that takes a TM M_s and a string w as input
- it *simulates* the execution of M_s on w
- and accepts if and only if M_s accepts

Construction of a universal TM

- keep track of current state and head position of M_s
- scan the TM instructions of M_s and follow them
- (this requires lots of coding but is possible)

The Halting Problem as a Language Problem

Slight Modification of universal TM:

- U_1 is a universal TM with all states accepting
- hence if U_1 halts, then U_1 accepts.

Halting Problem

- Is L

Observation.

- all problems can be expressed as language problem
- we know that $L(U_1)$ is recursively enumerable

Q. Is $L(U_1)$ even recursive?

- can we design a “better” TM for $L(U_1)$ that *always* halts?

The Halting Problem is Undecidable

Theorem. The halting problem is undecidable.

Proof (Sketch).

- Suppose we had a TM H that always terminates so that $L(H) = L(U_1)$ (H for halt)

- con

Construct

- If H halts on P , then P does not halt forever.
- If H rejects (M, M) , halt

Q. does P halt on input (an encoding of)

- **No** – then H accepted (P, P) , so P should have halted on input P .
- **Yes** – then H rejected (P, P) , so P should *not* have halted on input P .

Contradiction in both cases, so H cannot exist.

Reflections on the proof

Positive Information.

- to show that a language is (semi-) decidable, one usually needs to exhibit an algorithm. This generates information (the algorithm)

Negative Information.

- to show that a language is not decidable, one usually needs to show that no algorithm exists for it

Reduction

- standard proof technique
- assume that a TM exists for a language
- *reduce* L to a known undecidable language
- so that a solution for L would give a solution to the known problem

Example.

- if a TM for language L existed, we could solve the halting problem!
- many other undecidable problems ...

Total Turing Machines

Question. Is there a TM T (for total) that

- always terminates
- takes an encoding of a TM M as input
- acc

Reduction

- Sup
- for a TM M and string w define a new TM M_w that runs like M would on w but
- running T on M_w tells us whether M
- so we would have solved the halting problem
- since the halting problem cannot be solved, T cannot exist.

The Chomsky Hierarchy

Recall. Classification of language according to complexity of grammars

- regular languages – FSA's
- context-free languages – PDA's
- context-sensitive languages
- recursively enumerable languages – TM's

Q. Where d
for them?

- the
- and are recognised by *total* TMs that ha

Structure vs Property

- all other automata had a clear cut definition
- total TMs have a *condition* attached

Problem.

- cannot *test* whether this condition is fulfilled
- so the definition is mathematical, not computational

Back to the Entscheidungsproblem

Q. Can we design an algorithm that *always terminates* and checks whether a mathematical formula is a theorem?

- this is the *Entscheidungsproblem* posed by Hilbert
- and what Alan Turing's original paper was about

More detail.

- mat
- pro

Ramifica

- all mathematicians could be replaced by machi

Turing's Result

- the set of first-order formulae that are provable is not recursive.
- the existence of a TM that computes the Entscheidungsproblem leads to a contradiction

Other Approaches.

- Church showed the same (using the λ -calculus) in 1932
- was not widely accepted as λ -calculus is less intuitive