Entity-Relationship Model – Part 4

Recap - Data Modeling



- ER design is **subjective**:
  - There are many ways to model a given scena
  - Analyzing alternative schemas is import

- Constraints play an important role in designing a good database. But,
  - Not all constraints can be expressed in the ER model;
  - Not all constraints in the ER model can be translated.
- A good database design requires to further refining a relational database schema obtained through translating an ER diagram.

An ER Diagram - The Company Database



ER-to-Relations Algorithm

- 7-step algorithm to convert the basic ER model into relations and more steps for the EER model.

- Foreign key approach
- Merged relation appro
- Cross-reference app

Step 4: Mapping of Binary 1:N Relationshi
Step 5: Mapping of Binary M:N Relationship Types
Step 6: Mapping of Multi-valued Attributes
Step 7: Mapping of N-ary Relationship Types
Step 8: Mapping of Superclass/Subclass

Step 1: Regular Entity types

- For each regular entity type E, create a relation schema with the attributes of E (ignore multi-valued attributes until Step 6), where
  - **PK:** the key attributes of E

- DEPARTMENT(Name, Address) with PK: {Name}
  PROJECT(Pnumber, Pname, Location) with PK: {Pnumber}
- **Note:** These are not necessarily the final relation schemas of DEPARTMENT and PROJECT.

Step 1: Regular Entity types

- How can we translate the regular entity type EMPLOYEE?



- EMPLOYEE(SSN, Name, Salary) with PK:
- **Note:**
  - This is not the final relation schema of EMPLOYEE (will be further extended later on).
  - Multi-valued attributes are ignored until Step 6.

Step 2: Weak Entity Types

- For each weak entity type E_w, **create a relation schema** with the attributes of E_w plus the PK of its identifying entity type, where
  - **PK:** the partial key attributes of E_w plus the PK of its identifying entity



- CHILD(SSN, Cname, Age) with
  PK: {SSN, Cname}
  FK: [SSN]⊆EMPLOYEE[SSN]

Step 3: Binary 1:1 Relationship Types - (Foreign key approach)

- For a 1:1 relationship type R with one total participation, extend the relation schema of the total-side entity type by the attributes of R and the PK of the partial-side entity type, where



- DEPARTMENT(Name, Address, Mgr_SSN, Start_date) with
  PK: {Name}
  FK: [Mgr_SSN]⊆EMPLOYEE[SSN].

Step 3: Binary 1:1 Relationship Types - (Merged relation approach)

- How can we translate the following kind of 1:1 relationship type?



- If participation on both sides is total, we may **of both entity types and the attributes of the rela single relation**.

- EMPLOYEE-DEP(SSN, Name, Salary, Start_date, Dname, Address) with PK: {SSN} or {Dname}

Step 3: Binary 1:1 Relationship Types - (Cross-reference approach)

- How can we translate the following kind of 1:1 relationship type?



- If both sides are partial, we may create a F cross-references the PKs of the relation schema

- MANAGES(SSN, Dname, Start_date) with
  PK: {SSN} or {Dname}
  FKs: [SSN]⊆EMPLOYEE[SSN] and [Dname]⊆DEPARTMENT[Name]

Step 4: Binary 1:N Relationship Types

- For each 1:N relationship type R, extend the relation schema of the N-side entity type by the attributes of R and the PK of the 1-side entity type, where



- EMPLOYEE(SSN, Name, Salary, Dname) with

  PK: {SSN}

  FK: [Dname]$\subseteq$DEPARTMENT[Name]

Step 4: Binary 1:N Relationship Types

- How can we translate the 1:N relationship type SUPERVISE?



- EMPLOYEE(SSN, Name, Salary, Dname, Super_SSN) with
  PK: {SSN}
  FK: [Dname]⊆DEPARTMENT[Name] and [Super_SSN]⊆EMPLOYEE[SSN]

Step 5: Binary M:N Relationship Types

- For each M:N relationship type R, create a relation schema with the attributes of R plus the PKs of the participating entity types, where
  - **PK:** the combination of the PKs of the participating entity types
  -



- WORKS_ON(SSN, Pnumber, Hours) with

  PK: {SSN, Pnumber}

  FKs: [SSN]⊆EMPLOYEE[SSN] and [Pnumber]⊆PROJECT[Pnumber]

Step 6: Multi-valued Attributes

- For each multi-valued attribute A, create a relation schema with an attribute corresponding to A plus the PK of the entity/relationship type that has A as an attribute, where
  -
  -



- EMPLOYEE_ADDRESS(SSN, Address) with
  PK: {SSN, Address}
  FK: [SSN]⊆EMPLOYEE[SSN]

Step 7: N-ary Relationship Types

- For each N-ary relationship type R, **create a relation schema** with the attributes of R plus the PKs of the participating entity types where
  - **PK:** the combination of the PKs of the participating entity types
  -



- MENTORS(SSN, Sname, Pnumber, From, To) with
  PK: {SSN, Sname, Pnumber}
  FK: [SSN]⊆EMPLOYEE[SSN], [Sname]⊆INTERN_STUDENT[Sname], and
  [Pnumber]⊆PROJECT[Pnumber]

Step 8: Superclass and Subclass

- For each superclass, **create a relation schema** with its attributes.
- For each subclass, **create a relation schema** with its attributes plus the key at



- EMPLOYEE(...) (as done
-),

ENGINEER(SSN, Type),
which all have

PK: {SSN}

FK: [SSN]⊆EMPLOYEE[SSN]

ER-to-Relations Algorithm (Recall)

- The algorithm to first convert the basic ER model into relations and then convert superclass/subclass from the EER model into relations.

- Foreign key approach
- Merged relation appro
- Cross-reference app

Step 4: Mapping of Binary 1:N Relationshi
Step 5: Mapping of Binary M:N Relationship Types
Step 6: Mapping of Multi-valued Attributes
Step 7: Mapping of N-ary Relationship Types
Step 8: Mapping of Superclass/Subclass

A Relational Database Schema - The Company Database

- EMPLOYEE(SSN , Name, Salary, Dname, Super_SSN)
- WORKS_ON(SSN , Pnumber , Hours)
- D
- P
- EMPLOYEE_ADDRESS(SSN , Address)
- CHILD(SSN , Cname, Age)