

COMP2610/6261 - Information Theory

Lecture 16: Arithmetic Coding

Assignment Project Exam Help

<https://eduassistpro.github.io>



Australian
National
University

Add WeChat edu_assist_pro

25 September, 2018

1 From SFE to Arithmetic Coding

2 Arithmetic Coding: Encoder

- Intervals for Sequences
- Co
- Pu

<https://eduassistpro.github.io>

3 Arithmetic Coding: Decoder

Add WeChat edu_assist_pr


4 Adapting Distributions On-The-Fly

Interval Codes (Recap)

Shannon-Fano-Elias Coding method:

- Order the alphabet \mathcal{A} .
- Represent distribution \mathbf{p} by cumulative distribution F .
- Construct code by finding intervals of width $\frac{p_i}{2}$ that lie in each symbol interval $[F(a_{i-1}), F(a_i))$

<https://eduassistpro.github.io>



Intervals and Prefix Codes (Recap)

The set of numbers in $[0, 1)$ that start with a given sequence of bits

$\mathbf{b} = b_1 \dots b_n$ form the interval

$$\left[0.\mathbf{b} \quad \frac{1}{2^n} \quad 0.0 \dots 1) \right]$$

This interval

$\begin{matrix} 1 & 2 & & n & & \text{refix} \end{matrix}$

Prefix property (interval form): Once you pick b_n , you cannot pick any codeword in the codeword interval

$$\left[0.b_1 b_2 \dots b_n, 0.b_1 b_2 \dots b_n + \frac{1}{2^n} \right)$$

1 From SFE to Arithmetic Coding

2 Arithmetic Coding: Encoder

- Intervals for Sequences
- Co
- Pu

<https://eduassistpro.github.io>

3 Arithmetic Coding: Decoder

Add WeChat edu_assist_pr

4 Adapting Distributions On-The-Fly

Interval Coding Blocks

What if we apply SFE coding to blocks of an ensemble X ?

Example: Let $\mathcal{A} = \{aa, ab, ba, bb\}$ with $\mathbf{p} = (0.2, 0.6, 0.1, 0.1)$.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Interval Coding Blocks

What if we apply SFE coding to blocks of an ensemble X ?

Example: Let $\mathcal{A} = \{aa, ab, ba, bb\}$ with $\mathbf{p} = (0.2, 0.6, 0.1, 0.1)$.

Assignment Project Exam Help

\mathbf{x}	p	\bar{F}	\bar{F}_2	ℓ	Code
aa	0.2	0.1	0.00011	4	0001
ab					
ba					
bb					

<https://eduassistpro.github.io>

Extend to longer sequences


Add WeChat edu_assist_pr

Interval Coding Blocks

What if we apply SFE coding to blocks of an ensemble X ?

Example: Let $\mathcal{A} = \{aa, ab, ba, bb\}$ with $\mathbf{p} = (0.2, 0.6, 0.1, 0.1)$.

\mathbf{x}	p	\bar{F}	\bar{F}_2	ℓ	Code
aa	0.2	0.1	0.00011	4	0001
ab					
ba					
bb					



<https://eduassistpro.github.io>

Extend to longer sequences

This works too:

- Need $P(\mathbf{x})$ for all \mathbf{x}
- Total $|\mathcal{A}|^N$ values for length N
- Huffman has similar complexity but shorter codes.

Arithmetic Coding: A Bird's Eye View

Basic idea of arithmetic coding follows SFE coding

	SFE Coding	Arithmetic coding
Input	Single outcome x_i	Sequence of outcomes $x_1 x_2 \dots x_N$

Key st

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

Output

Binary string corresponding
to chosen interval

to chosen interval

Arithmetic Coding: A Bird's Eye View

Basic idea of arithmetic coding follows SFE coding

	SFE Coding	Arithmetic coding
Input	Single outcome x_i	Sequence of outcomes $x_1 x_2 \dots x_N$

Key step

<https://eduassistpro.github.io>

Use $[F(x_{i-1}), F(x_i))$

Output

Binary string corresponding
to chosen interval

to chosen interval

Output first $\ell(x_i)$ bits of mid-
point of interval

Output first $\ell(x_1 x_2 \dots x_N)$
bits of midpoint of interval

Assignment Project Exam Help

Arithmetic coding has some important properties:

- We do **not** compute a symbol coding for X and then concatenate

- We do

- We do not assume that each of the x_i

- ▶ Not restricted to extended ensembles
- ▶ Adapts to data distribution

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

1 From SFE to Arithmetic Coding

2 Arithmetic Coding: Encoder

- Intervals for Sequences
- Co
- Pu

<https://eduassistpro.github.io>

3 Arithmetic Coding: Decoder

Add WeChat edu_assist_pr

4 Adapting Distributions On-The-Fly

Computing an Interval for Sequences

Say $N = 2$ and we want to code $x_1 x_2$

Assignment Project Exam Help

Ideally, we'd like to compute $p(\mathbf{x})$ for all possible \mathbf{x} of length 2, and then find the interval for $p(x_1 x_2)$

Key ideas

- we can
▶ decompose joint into conditional probabilities

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Computing an Interval for Sequences

Say $N = 2$ and we want to code $x_1 x_2$

Ideally, we'd like to compute $p(\mathbf{x})$ for all possible \mathbf{x} of length 2, and then find the interval for $p(x_1 x_2)$

Key ideas

- we can
▶ decompose joint into conditional probabilities
- $p(\cdot | x_1)$ is just another probability distribution
▶ so we can compute intervals as per SFE

Computing an Interval for Sequences

Say $N = 2$ and we want to code $x_1 x_2$

Ideally, we'd like to compute $p(\mathbf{x})$ for all possible \mathbf{x} of length 2, and then find the interval for $p(x_1 x_2)$

Key ideas

- we can
▶ decompose joint into conditional probabilities
- $p(\cdot | x_1)$ is just another probability distribution
▶ so we can compute intervals as per SFE
- we can find an interval for $p(x_2 | x_1)$ **within** the interval for x_1
▶ normal SFE computes the interval within $[0, 1)$ by default

Computing an Interval for Sequences

Example: Suppose $\mathcal{A} = \{a, b, c\}$ and $p(a) = 0.25, p(b) = 0.5, p(c) = 0.25$

Like with SFE coding, we'd begin by slicing up $[0, 1)$ into three subintervals:

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Computing an Interval for Sequences


Example: Suppose $\mathcal{A} = \{a, b, c\}$ and $p(a) = 0.25, p(b) = 0.5, p(c) = 0.25$

Like with SFE coding, we'd begin by slicing up $[0, 1)$ into three subintervals:

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr



So e.g. we treat $[0.25, 0.75)$ as the interval for b

Computing an Interval for Sequences

Suppose the first symbol is b, and $p(a|b) = 0.25$, $p(b|b) = 0.5$, $p(c|b) = 0.25$

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Computing an Interval for Sequences

Suppose the first symbol is b, and $p(a|b) = 0.25$, $p(b|b) = 0.5$, $p(c|b) = 0.25$

To code ba, bb, bc, now slice up $[0.25, 0.75)$, the interval for b itself:

Assignment Project Exam Help


<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Computing an Interval for Sequences

Suppose the first symbol is b, and $p(a|b) = 0.25$, $p(b|b) = 0.5$, $p(c|b) = 0.25$

To code ba, bb, bc, now slice up $[0.25, 0.75]$, the interval for b itself:



For ba we choose the interval of length $p(a|b) = 0.25$ times the length of the enclosing interval ($0.75 - 0.25 = 0.5$), i.e. $(0.25)(0.5) = 0.125$

Arithmetic Coding: End of Stream Symbol

Assignment Project Exam Help

It is convenient to explicitly have a special “end of stream” symbol, \square

We add this

- e.g. see <https://eduassistpro.github.io> availability of
- Implicitly we think of ab as actually being $ab\square$

End of stream is by definition reached when we choose this special symbol

Add WeChat edu_assist_pro

Arithmetic Coding: End of Stream Example

Example: Suppose $\mathcal{A} = \{a, b, c, \square\}$ and
 $p(a) = 0.25, p(b) = 0.5, p(c) = 0.15, p(\square) = 0.1$

Like with SFE coding, we'd begin by slicing up $[0, 1)$ into three subintervals:

Assignment Project Exam Help


<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

Arithmetic Coding: End of Stream Example

Example: Suppose $\mathcal{A} = \{a, b, c, \square\}$ and
 $p(a) = 0.25, p(b) = 0.5, p(c) = 0.15, p(\square) = 0.1$

Like with SFE coding, we'd begin by slicing up $[0, 1)$ into three subintervals:



Arithmetic Coding: End of Stream Example

Now suppose that $p(\cdot|b)$ stays the same as $p(\cdot)$

If the first symbol is b , we carve the interval for b into four pieces:

Assignment Project Exam Help


<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Arithmetic Coding: End of Stream Example

Now suppose that $p(\cdot|b)$ stays the same as $p(\cdot)$

If the first symbol is b , we carve the interval for b into four pieces:



Exact same idea as before, just with special symbol \square

Arithmetic Coding for Arbitrary Sequences

These ideas generalise to arbitrary length sequences

- We don't even need to know the sequence length beforehand!

Assignment Project Exam Help

As we see more symbols, we slice the appropriate sub-interval of $[0, 1)$ based on t

- Ter

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

1 From SFE to Arithmetic Coding

2 Arithmetic Coding: Encoder

- Intervals for Sequences
- Co
- Pu

<https://eduassistpro.github.io>

3 Arithmetic Coding: Decoder

Add WeChat edu_assist_pr

4 Adapting Distributions On-The-Fly

Arithmetic Coding: Codeword Generation

Once we've seen the entire sequence, we end up with interval $[l, u)$

- How to output a codeword?

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Arithmetic Coding: Codeword Generation

Once we've seen the entire sequence, we end up with interval $[l, u)$

- How to output a codeword?

As per SF


- Her
- As b

contained in the codeword interval

Generally, we can output some bits on the fly, rather than process the entire sequence


Arithmetic Coding: Codeword Generation Example

In previous example with input b, we'd stop in the interval for b□, i.e. $[0.7, 0.75)$



Arithmetic Coding: Codeword Generation Example

In previous example with input b, we'd stop in the interval for $b\Box$, i.e. $[0.7, 0.75)$



Midpoint is $0.725 = 10111\overline{0011}$, and $p(b\Box) = (1/2) \cdot (0.1) = 0.05$

Output the first $\lceil \log_2 1/0.05 \rceil + 1 = 6$ bits, i.e. 101110

1 From SFE to Arithmetic Coding

2 Arithmetic Coding: Encoder

- Intervals for Sequences
- Co
- Pu

<https://eduassistpro.github.io>

3 Arithmetic Coding: Decoder

Add WeChat edu_assist_pr

4 Adapting Distributions On-The-Fly

Arithmetic Coding: Formal Encoder

Formally, we compute the interval $[u, v)$ for a generic sequence as follows:

Arithmetic Coding of stream $x_1 x_2 \dots$

$u \leftarrow 0.0$
 $v \leftarrow 1.0$
 $p \leftarrow v - u$

for $n = 1,$

- Compute $L_n(a_i | x_1, \dots, x_{n-1}) = \prod_{i'=1}^n p(x_n = a_{i'} | x_1, \dots, x_{n-1})$
- $v \leftarrow u + p \cdot U_n(x_n | x_1, \dots, x_{n-1})$
- $u \leftarrow u + p \cdot L_n(x_n | x_1, \dots, x_{n-1})$
- $p \leftarrow v - u$
- if $x_n = \square$, terminate

Output first $\ell(x_1 x_2 \dots x_N) = \lceil \log 1/p \rceil + 1$ bits of $(u + v)/2$

Here, L_n, U_n just compute the appropriate lower and upper bounds, as per SFE coding

- We rescale these based on the current interval length

1 From SFE to Arithmetic Coding

2 Arithmetic Coding: Encoder

- Intervals for Sequences
- Co
- Pu

<https://eduassistpro.github.io>

3 Arithmetic Coding: Decoder

Add WeChat edu_assist_pr

4 Adapting Distributions On-The-Fly

Decoding

How do we **decode** a sequence of bits?

Rough Sketch

- Carve out $[0, 1)$ based on initial distribution

- Ke

- Out

- Carve out appropriate interval based on prob

- \vdots

We can stop once we have containment in interval for \square

Decoding: Example

Suppose $p(a) = 0.5, p(b) = 0.125, p(c) = 0.25, p(\square) = 0.125$ for every outcome in sequence

Assignment Project Exam Help

Decode 0110111:

Seque	Symbol a
0	

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Decoding: Example

Suppose $p(a) = 0.5, p(b) = 0.125, p(c) = 0.25, p(\square) = 0.125$ for every outcome in sequence

Assignment Project Exam Help

Decode 0110111:

Seque	Symbol
0	a
01	b
	2
	10

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Decoding: Example

Suppose $p(a) = 0.5, p(b) = 0.125, p(c) = 0.25, p(\square) = 0.125$ for every outcome in sequence

Assignment Project Exam Help

Decode 0110111:

Seque			
0			symbol a
01	2	10	
011	$[0.011, 0.100)_2$	$[0.37$	bol c

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Decoding: Example

Suppose $p(a) = 0.5, p(b) = 0.125, p(c) = 0.25, p(\square) = 0.125$ for every outcome in sequence

Assignment Project Exam Help

Decode 0110111:

Seque

0

symbol a

01

2

10

011

$[0.011, 0.100)_2$

$[0.37$

bol c

0110

$[0.0110, 0.0111)_2$

$[0.37$

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Decoding: Example

Suppose $p(a) = 0.5, p(b) = 0.125, p(c) = 0.25, p(\square) = 0.125$ for every outcome in sequence

Assignment Project Exam Help

Decode 0110111:

Seque

0			symbol a
01	2	10	
011	$[0.011, 0.100)_2$	$[0.37$	bol c
0110	$[0.0110, 0.0111)_2$	$[0.37$	
01101	$[0.01101, 0.0111)_2$	$[0.40$	

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Decoding: Example

Suppose $p(a) = 0.5, p(b) = 0.125, p(c) = 0.25, p(\square) = 0.125$ for every outcome in sequence

Assignment Project Exam Help

Decode 0110111:

Seque			
0			symbol a
01	²	¹⁰	
011	$[0.011, 0.100)_2$	$[0.37$	bol c
0110	$[0.0110, 0.0111)_2$	$[0.37$	
01101	$[0.01101, 0.01110)_2$	$[0.40$	
011011	$[0.011011, 0.011100)_2$	$[0.42$	bol \square

The last bit here is actually redundant (inherited from +1 bit in midpoint representation)

1 From SFE to Arithmetic Coding

Assignment Project Exam Help

2 Arithmetic Coding: Encoder

- Intervals for Sequences
- Co
- Pu

<https://eduassistpro.github.io>

3 Arithmetic Coding: Decoder

Add WeChat edu_assist_pr

4 Adapting Distributions On-The-Fly

Adaptive Probabilities

So far we assume the sequence of probabilities are given in advance

Assignment Project Exam Help
In Lecture 5, you saw Bernoulli distribution for two outcomes

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Adaptive Probabilities

So far we assume the sequence of probabilities are given in advance

Assignment Project Exam Help

In Lecture 5, you saw Bernoulli distribution for two outcomes

- Bet

- The

Bet $(\theta | h + n_h, t + n_t)$

- The expected value of θ under the posterior

$$p(x = h | n_h, n_t, m_h, m_t) = \frac{m_h + n_h}{m_h + n_h + m_t + n_t}$$

Dirichlet Model

A **Dirichlet distribution** is a generalisation of the Beta distribution to more than two outcomes. Its parameter is a vector $\mathbf{m} \equiv (m_1, \dots, m_K)$ can be viewed as “virtual counts” for each symbol a_1, \dots, a_K .

<https://eduassistpro.github.io>

Can impl

Add WeChat edu_assist_pr

Dirichlet Model

A **Dirichlet distribution** is a generalisation of the Beta distribution to more than two outcomes. Its parameter is a vector $\mathbf{m} \equiv (m_1, \dots, m_K)$ can be viewed as “virtual counts” for each symbol a_1, \dots, a_K .

<https://eduassistpro.github.io>

Can impl

Flexible

- e.g., Choose \mathbf{m} to be frequency of English l
- $\sum_k m_k$ Large = Stable; Small = Responsive

Example: Start with $m_h = m_t = 1$ and observe sequence hht.

$$p(\cdot|\epsilon) = (\frac{1}{2}, \frac{1}{2}), p(\cdot|h) = (\frac{2}{3}, \frac{1}{3}), p(\cdot|h h) = (\frac{3}{4}, \frac{1}{4}), p(\cdot|h h t) = (\frac{3}{5}, \frac{2}{5})$$

viz. Laplace's Rule, where ϵ means empty string

Why? Be

<https://eduassistpro.github.io>

Add WeChat edu_assist_pro

$$p(h|h) = \frac{1+1}{1+0+1}$$

$$p(t|h) = \frac{0+1}{1+0+1+1} = 1/3$$

We'll assume this learning is only for non \square symbols

- assume \square occurs with fixed probability each time

Adaptive Probabilities: Example

Possible outcomes a, b, \square

Assignment Project Exam Help

Sequenc

Probabil

Encoder: ϵ

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

We start off with virtual counts $m_a = m_b = 1$

Adaptive Probabilities: Example

Possible outcomes a, b, \square

Assignment Project Exam Help

Observa

Probabil

Encoder Output: ϵ

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Seeing b makes us update $p(a|b) = (0.85) \cdot (1/3) \approx 0.28$, and $p(b|b) = (0.85) \cdot (2/3) \approx 0.57$. We keep $p(\square|b) = p(\square)$.

Adaptive Probabilities: Example

Possible outcomes a, b, □

Assignment Project Exam Help

Observa

Probabil

Encoder Output: 1

a

b

bb

bbb

0 011011...
0 10 0 0...
0 100110...

01111...
10010...
10 110...

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Seeing bb makes us update $p(a|bb) = (0.85) \cdot (1/4) \approx 0.21$, and

$p(b|bb) = (0.85) \cdot (3/4) \approx 0.64$

Now the first bit is unambiguously 1

Adaptive Probabilities: Example

Possible outcomes a, b, □

Assignment Project Exam Help

Observa

Probabil

Encoder Output: 1

$|bbb \approx (\cdot , \cdot , \cdot)$

bba



<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

Adaptive Probabilities: Example

Possible outcomes a, b, \square

Observa

Probabil

Encoder Output: 1001

bbba

bbbaa

bbba

bbbab

0.100110000...

0.100110100...

0.10011100...

0.10011110...

On seeing a, we can fill in three further bits unambiguously

Adaptive Probabilities: Example

Possible outcomes a, b, \square

Assignment Project Exam Help

Observa

Probabil

Encoder Output: 100111101

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr



To terminate, we find midpoint of 0.100111100... and 0.100111110...

Assignment Project Exam Help

ba 01111
10000
10001 1000
bba 10010 100
bbb 10011 100
bb 10100 10
bbb 10101 1010

ba 01111
10000
10001 1000
bba 10010 100
bbb 10011 1001
bb 10100 10
bbb bbbb 10101 1010

Summary and Reading

Main Points

- Arithmetic Coding:

- ▶ Uses interval coding and conditional probability



▶ <https://eduassistpro.github.io>

- Predictive distributions:

- ▶ Update distribution after each symbol

- ▶ Beta and Dirichlet priors = virtual counts

Reading

- Section 6.2 of MacKay