



# Assignment Project Exam Help

## Algorithms

<https://eduassistpro.github.io>

Aleks Ignjatović, ignjat@cse

office: 504 (CSE building)

Course Admin: Anahita Namvar, CS312

Add WeChat **edu\_assist\_pro**

School of Computer Science and Engineering  
University of New South Wales Sydney

### 1. INTRODUCTION

What is this course about?

It is about **designing algorithms** for solving practical problems.

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

What is this course about?

It is about **designing algorithms** for solving practical problems.

## Assignment Project Exam Help

What is an algorithm?

An algorithm is a set of steps that can be followed to solve a problem or perform a task. It consists of a series of instructions that are executed in a specific order to produce a desired outcome.

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## What is this course about?

It is about **designing algorithms** for solving practical problems.

# Assignment Project Exam Help

## What is an algorithm?

An algorithm is a set of steps that can be executed by a computer to solve a problem.

<https://eduassistpro.github.io>

By “mechanical” we mean the methods that do not involve any creativity, intuition or even intelligence. Thus, algorithms are usually detailed, easily repeatable “recipes”.

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro)

# Introduction

What is this course about?

It is about **designing algorithms** for solving practical problems.

## Assignment Project Exam Help

What is an algorithm?

An algorithm is a set of steps that can be executed by a computer to solve a problem.

<https://eduassistpro.github.io/>

By “mechanical” we mean the methods that do not involve any creativity, intuition or even intelligence. Thus, algorithms are usually detailed, easily repeatable “recipes”.

Add WeChat `edu_assist_pro`

The word “algorithm” comes by corruption of the name of *Muhammad ibn Musa al-Khwarizmi*, a Persian scientist 780-850, who wrote an important book on algebra, “*Al-kitab al-mukhtasar fi hisab al-gabr wal-muqabala*”. You are encouraged to read about him in Wikipedia.

# Assignment Project Exam Help

In this course we will deal only with sequential deterministic algorithm

- the state
- the action of each step gives the same result when executed for the same input

Add WeChat edu\_assist\_pro

Why should you study algorithms design?

Can you find every algorithm you might need using Google?

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

Why should you study algorithms design?

Can you find every algorithm you might need using Google?

# Assignment Project Exam Help

Our goal

To learn  
problem

iliar

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pr

Why should you study algorithms design?

Can you find every algorithm you might need using Google?

# Assignment Project Exam Help

Our goal

To learn  
problem

iliar

<https://eduassistpro.github.io>

Course co

- a survey of algorithm **design** techni

Add WeChat edu\_assist\_pro

Why should you study algorithms design?

Can you find every algorithm you might need using Google?

# Assignment Project Exam Help

Our goal

To learn  
problem

iliar

<https://eduassistpro.github.io>

Course co

- a survey of algorithm **design** techniques
- particular algorithms will be mostly used to illustrate techniques

Add WeChat **edu\_assist\_pro**

Why should you study algorithms design?

Can you find every algorithm you might need using Google?

# Assignment Project Exam Help

Our goal

To learn  
problem

iliar

<https://eduassistpro.github.io>

Course co

- a survey of algorithm **design** techniques
- particular algorithms will be mostly used to illustrate techniques
- emphasis on development of your algorithm design **skills**

Add WeChat **edu\_assist\_pro**

Textbook:

Kleinberg and Tardos' *Algorithm Design*  
paperback edition available at the UNSW book store

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

Textbook:

# Assignment Project Exam Help

Kleinberg and Tardos' *Algorithm Design*  
paperback edition available at the UNSW book store

- exc

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

Textbook:

# Assignment Project Exam Help

Kleinberg and Tardos' *Algorithm Design*  
paperback edition available at the UNSW book store

- exc
- not s

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

Textbook:

Kleinberg and Tardos: *Algorithm Design*  
paperback edition available at the UNSW book store

- exc
- not s

<https://eduassistpro.github.io>

An alternative textbook:

Cormen, Leiserson, Rivest and Stein: *In  
preferably the third edition, should also be availab*

[Add WeChat edu\\_assist\\_pro](#)

## Textbook:

Kleinberg and Tardos: *Algorithm Design*  
paperback edition available at the UNSW book store

- exc
- not s

<https://eduassistpro.github.io>

## An alternative textbook:

Cormen, Leiserson, Rivest and Stein: *In  
preferably the third edition, should also be availab*

[Add WeChat edu\\_assist\\_pro](#)

- excellent: to be used later as a reference manual

Textbook:

# Assignment Project Exam Help

Kleinberg and Tardos: *Algorithm Design*  
paperback edition available at the UNSW book store

- exc
- not s

<https://eduassistpro.github.io>

An alternative textbook:

Cormen, Leiserson, Rivest and Stein: *In  
preferably the third edition, should also be availab*

**Add WeChat edu\_assist\_pro**

- excellent: to be used later as a reference manual
- not so good: somewhat formalistic and written in a rather dry style.

## Problem:

Two thieves have robbed a warehouse and have to split a pile of items without price tags on them. Design an algorithm for doing this in a way that ensures that each thief believes that he has got at least one half of the lo

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

# Examples of Algorithms

## Problem:

Two thieves have robbed a warehouse and have to split a pile of items without price tags on them. Design an algorithm for doing this in a way that ensures that each thief believes that he has got at least one half of the lo

The solu

One of the t

that both parts are of equal value. The other thief then c  
part that he believes is no worse than the other.

Add WeChat edu\_assist\_pr

## Examples of Algorithms

### Problem:

Two thieves have robbed a warehouse and have to split a pile of items without price tags on them. Design an algorithm for doing this in a way that ensures that each thief believes that he has got at least one half of the lo

The solu

<https://eduassistpro.github.io>

One of the t

that both parts are of equal value. The other thief then c  
part that he believes is no worse than the other.

Add WeChat edu\_assist\_pr

The hard part: how can a thief split the pile into two equal parts? Remarkably, this turns out that, most likely, there is no more efficient algorithm than the brute force: we consider all partitions of the pile and see if there is one which results in two equal parts.

# Examples of Algorithms

## Problem:

Three thieves have robbed a warehouse and have to split a pile of items without price tags on them. How do they do this in a way that ensures that each thief believes that he has got at least one third of the loot?

- Re

pro

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

# Examples of Algorithms

## Problem:

Three thieves have robbed a warehouse and have to split a pile of items without price tags on them. How do they do this in a way that ensures that each thief believes that he has got at least one third of the loot?

- Re  
pro
- Let u

first thief splits the loot into three piles which he thinks have equal value; then the remaining two thieves can decide which pile they want to take.

Add WeChat edu\_assist\_pro

# Examples of Algorithms

## Problem:

Three thieves have robbed a warehouse and have to split a pile of items without price tags on them. How do they do this in a way that ensures that each thief believes that he has got at least one third of the loot?

- Re  
pro <https://eduassistpro.github.io>
- Let us assume that there are three thieves. The first thief splits the loot into three piles which he thinks have equal value; then the remaining two thieves can choose which pile they want to take.
- If they choose different piles, they can each take the piles they have chosen and the first thief gets the remaining pile; in this case clearly each thief thinks that he got at least one third of the loot.

# Examples of Algorithms

## Problem:

Three thieves have robbed a warehouse and have to split a pile of items without price tags on them. How do they do this in a way that ensures that each thief believes that he has got at least one third of the loot?

- Re  
pro <https://eduassistpro.github.io>
- Let us assume that the first thief splits the loot into three piles which he thinks have equal value; then the remaining two thieves can choose which pile they want to take.
- If they choose different piles, they can each take the piles they have chosen and the first thief gets the remaining pile; in this case clearly each thief thinks that he got at least one third of the loot.
- But what if the remaining two thieves choose the same pile?

- One might think that in this case the first thief can pick any of the two piles that the second and the third thief did not choose; the remaining two piles are put together and the two remaining thieves split them as in Problem 1 with only two thieves.

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

- One might think that in this case the first thief can pick any of the two piles that the second and the third thief did not choose; the remaining two piles are put together and the two remaining thieves split them as in Problem 1 with only two thieves.

- Unfortunately this does not work:

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

- One might think that in this case the first thief can pick any of the two piles that the second and the third thief did not choose; the remaining two piles are put together and the two remaining thieves split them as in Problem 1 with only two thieves.

- Unfortunately this does not work:

after the first thief splits the loot into three piles A, B, C, it might happen, for example, that the second thief thinks that

of the <https://eduassistpro.github.io>

$$A = 50\%, B = 10\%, C = 40\%.$$

Add WeChat edu\_assist\_pro

- One might think that in this case the first thief can pick any of the two piles that the second and the third thief did not choose; the remaining two piles are put together and the two remaining thieves split them as in Problem 1 with only two thieves.

- Unfortunately this does not work:

after the first thief splits the loaf into three piles A, B, C, it might happen, for example, that the second thief thinks that

of the <https://eduassistpro.github.io>

$$A = 50\%, B = 10\%, C = 40\%.$$

- Thus, if the first thief picks pile B, the second thief objects that the first thief is getting 40% while he was promised only  $60\%/2 = 30\%$ .

- One might think that in this case the first thief can pick any of the two piles that the second and the third thief did not choose; the remaining two piles are put together and the two remaining thieves split them as in Problem 1 with only two thieves.

- Unfortunately this does not work:

after the first thief splits the loot into three piles A, B, C, it might happen, for example, that the second thief thinks that

of the <https://eduassistpro.github.io>

$$A = 50\%, B = 10\%, C = 40\%.$$

- Thus, if the first thief picks pile B, the second thief will object that the first thief is getting 40% while he is getting only  $60\%/2 = 30\%$ .
- If the first thief picks pile C then the third thief will object for the same reason.

- One might think that in this case the first thief can pick any of the two piles that the second and the third thief did not choose; the remaining two piles are put together and the two remaining thieves split them as in Problem 1 with only two thieves.

- Unfortunately this does not work:

after the first thief splits the loot into three piles A, B, C, it might happen, for example, that the second thief thinks that

of the <https://eduassistpro.github.io>

$$A = 50\%, B = 10\%, C = 40\%.$$

- Thus, if the first thief picks pile B, the third thief will object that the first thief is getting 40% while he is getting only  $60\%/2 = 30\%$ .
- If the first thief picks pile C then the third thief will object for the same reason.
- What would be a correct algorithm?

- One might think that in this case the first thief can pick any of the two piles that the second and the third thief did not choose; the remaining two piles are put together and the two remaining thieves split them as in Problem 1 with only two thieves.

- Unfortunately this does not work:

after the first thief splits the loaf into three piles A, B, C, it might happen, for example, that the second thief thinks that

of the <https://eduassistpro.github.io>

$$A = 50\%, B = 10\%, C = 40\%.$$

- Thus, if the first thief picks pile B, the third thief will object that the first thief is getting 40% while he is getting only  $60\%/2 = 30\%$ .
- If the first thief picks pile C then the third thief will object for the same reason.
- What would be a correct algorithm?
- Let the thieves be  $T_1, T_2, T_3$ ;

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Algorithm:

$T_1$  makes a pile  $P_1$  which he believes is  $1/3$  of the whole loot;

$T_1$  proceeds to ask  $T_2$  if  $T_2$  agrees that  $P_1 \leq 1/3$ ;

**If**  $T_2$  says YES, then  $T_1$  asks  $T_3$  if  $T_3$  agrees that  $P_1 \leq 1/3$ ;

**If**  $T_3$  says YES, then  $T_1$  takes  $P_1$ ;

$T_2$  and  $T_3$  split the rest as in Problem 1.

**Else if**  $T_3$  says NO, then  $T_3$  takes  $P_1$ ;

**Else if**

that  $T_2$

$T_2$

3

2

**If**  $T_3$  says YES then  $T_2$  takes  $P_2$ ;

$T_1$  and  $T_3$  split the rest as in Problem 1.

**Else if**  $T_3$  says NO then  $T_3$  takes

$T_1$  and  $T_2$  split the rest as in Problem 1.

### Algorithm:

$T_1$  makes a pile  $P_1$  which he believes is  $1/3$  of the whole loot;

$T_1$  proceeds to ask  $T_2$  if  $T_2$  agrees that  $P_1 \leq 1/3$ ;

**If**  $T_2$  says YES, **then**  $T_1$  asks  $T_3$  if  $T_3$  agrees that  $P_1 \leq 1/3$ ;

**If**  $T_3$  says YES, **then**  $T_1$  takes  $P_1$ ;

$T_2$  and  $T_3$  split the rest as in Problem 1.

**Else if**  $T_3$  says NO, **then**  $T_3$  takes  $P_1$ ;

**Else if**

that  $T_2$

$T_2$

3

2

**If**  $T_3$  says YES **then**  $T_2$  takes  $P_2$ ;

$T_1$  and  $T_3$  split the rest as in Problem 1.

**Else if**  $T_3$  says NO **then**  $T_3$  takes

$T_1$  and  $T_2$  split the rest as in Problem 1.

**Homework:** Try generalising this to  $n$  thieves! (a bit harder than with three thieves!)

### Algorithm:

$T_1$  makes a pile  $P_1$  which he believes is  $1/3$  of the whole loot;

$T_1$  proceeds to ask  $T_2$  if  $T_2$  agrees that  $P_1 \leq 1/3$ ;

If  $T_2$  says YES, then  $T_1$  asks  $T_3$  if  $T_3$  agrees that  $P_1 \leq 1/3$ ;

If  $T_3$  says YES, then  $T_1$  takes  $P_1$ ;

$T_2$  and  $T_3$  split the rest as in Problem 1.

Else if  $T_3$  says NO, then  $T_3$  takes  $P_1$ ;

Else if

that  $T_2$

$T_2$

3

2

If  $T_3$  says YES then  $T_2$  takes  $P_2$ ;

$T_1$  and  $T_3$  split the rest as in Problem 1.

Else if  $T_3$  says NO then  $T_3$  takes

$T_1$  and  $T_2$  split the rest as in Problem 1.

**Homework:** Try generalising this to  $n$  thieves! (a bit harder than with three thieves!)

Hint: there is a *nested recursion* happening even with 3 thieves!

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Assignment Project Exam Help

When do we need to give a mathematical proof that an algorithm we have just designed terminates and returns a solution to the problem at hand?

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Assignment Project Exam Help

When do we need to give a mathematical proof that an algorithm we have just designed terminates and returns a solution to the problem at hand?

<https://eduassistpro.github.io>

When this  
sense!

Add WeChat edu\_assist\_pro

## Assignment Project Exam Help

When do we need to give a mathematical proof that an algorithm we have just designed terminates and returns a solution to the problem at hand?

When this sense!

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

Mathematical proofs are NOT academic to justify things which are not obvious to common sense

## Example: MERGESORT

Merge-Sort( $A, p, r$ )

\*sorting  $A[p..r]$ \*

- ① if  $p < r$
- ② then  $q \leftarrow \lfloor \frac{p+r}{2} \rfloor$
- ③ MERGE-SORT( $A, p, q$ )
- ④ MERGE-SORT( $A, q + 1, r$ )
- ⑤

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Example: MERGESORT

Merge-Sort( $A, p, r$ )

\*sorting  $A[p..r]$ \*

- ① if  $p < r$
- ② then  $q \leftarrow \lfloor \frac{p+r}{2} \rfloor$
- ③ MERGE-SORT( $A, p, q$ )
- ④ MERGE-SORT( $A, q + 1, r$ )
- ⑤

① Th <https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Example: MERGESORT

Merge-Sort( $A, p, r$ ) \*sorting  $A[p..r]$ \*

- ① if  $p < r$
- ② then  $q \leftarrow \lfloor \frac{p+r}{2} \rfloor$
- ③ MERGE-SORT( $A, p, q$ )
- ④ MERGE-SORT( $A, q + 1, r$ )
- ⑤

- ① Th <https://eduassistpro.github.io>
- ② On each level of recursion merging intermediate steps.  $O(n)$

Add WeChat edu\_assist\_pro

## Example: MERGESORT

Merge-Sort( $A, p, r$ )

\*sorting  $A[p..r]$ \*

- ① if  $p < r$
- ② then  $q \leftarrow \lfloor \frac{p+r}{2} \rfloor$
- ③ MERGE-SORT( $A, p, q$ )
- ④ MERGE-SORT( $A, q + 1, r$ )
- ⑤

① Th <https://eduassistpro.github.io>

- ② On each level of recursion merging intermediate steps.  $O(n)$
- ③ Thus, MERGESORT always terminates in  $O(n \log_2 n)$  many steps.

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro)

## Example: MERGESORT

Merge-Sort( $A, p, r$ )

\*sorting  $A[p..r]$ \*

- ① if  $p < r$
- ② then  $q \leftarrow \lfloor \frac{p+r}{2} \rfloor$
- ③ MERGE-SORT( $A, p, q$ )
- ④ MERGE-SORT( $A, q + 1, r$ )
- ⑤

Assignment Project Exam Help

- ① The running time of MERGE-SORT is  $O(n \log_2 n)$ .
- ② On each level of recursion merging intermediate arrays takes  $O(n)$  steps.
- ③ Thus, MERGE-SORT always terminates in  $O(n \log_2 n)$  many steps.
- ④ Merging two sorted arrays always produces a sorted array, thus, the output of MERGE-SORT will be a sorted array.

Add WeChat edu\_assist\_pro

## Example: MERGESORT

Merge-Sort( $A, p, r$ )

\*sorting  $A[p..r]$ \*

- ① if  $p < r$
- ② then  $q \leftarrow \lfloor \frac{p+r}{2} \rfloor$
- ③ MERGE-SORT( $A, p, q$ )
- ④ MERGE-SORT( $A, q + 1, r$ )
- ⑤

① Th <https://eduassistpro.github.io>

- ② On each level of recursion merging intermediate steps.  $O(n)$
- ③ Thus, MERGESORT always terminates in  $O(n \log_2 n)$  many steps.
- ④ Merging two sorted arrays always produces a sorted array, thus, the output of MERGESORT will be a sorted array.
- ⑤ The above is essentially a proof by induction, but we will never bother formalising proofs of (essentially) obvious facts.

Add WeChat [edu\\_assist\\_pro](https://eduassistpro.github.io)

## The role of proofs in algorithm design

- However, sometimes it is **NOT** clear from a description of an algorithm that such an algorithm will not enter an infinite loop and fail to terminate.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## The role of proofs in algorithm design

- However, sometimes it is **NOT** clear from a description of an algorithm that such an algorithm will not enter an infinite loop and fail to terminate.
- Sometimes it is **NOT** clear that an algorithm will not run in exponentially many steps (in the size of the input), which is usu

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## The role of proofs in algorithm design

- However, sometimes it is **NOT** clear from a description of an algorithm that such an algorithm will not enter an infinite loop and fail to terminate.
- Sometimes it is **NOT** clear that an algorithm will not run in exponentially many steps (in the size of the input), which is usually the case for backtracking algorithms.
- So <https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## The role of proofs in algorithm design

- However, sometimes it is **NOT** clear from a description of an algorithm that such an algorithm will not enter an infinite loop and fail to terminate.

Assignment Project Exam Help

- Sometimes it is **NOT** clear that an algorithm will not run in exponentially many steps (in the size of the input), which is usually the case.
- So <https://eduassistpro.github.io/>
- Proofs are needed for such circumstances; in a logical way to know that the algorithm terminates.

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro)

## The role of proofs in algorithm design

- However, sometimes it is **NOT** clear from a description of an algorithm that such an algorithm will not enter an infinite loop and fail to terminate.
- Sometimes it is **NOT** clear that an algorithm will not run in exponentially many steps (in the size of the input), which is usu

- So <https://eduassistpro.github.io>
- Proofs are needed for such circumstances; in a l  
the only way to know that the algorithm
- For that reason we will **NEVER** p  
textbook sometimes does just that, by sometimes formulating and proving trivial little lemmas, being too pedantic!). We will prove only what is genuinely nontrivial.

## The role of proofs in algorithm design

- However, sometimes it is **NOT** clear from a description of an algorithm that such an algorithm will not enter an infinite loop and fail to terminate.

**Assignment Project Exam Help**

- Sometimes it is **NOT** clear that an algorithm will not run in exponentially many steps (in the size of the input), which is usually the only way to know that the algorithm terminates.
- So <https://eduassistpro.github.io>
- Proofs are needed for such circumstances; in a logical textbook sometimes does just that, by sometimes formulating and proving trivial little lemmas, being too pedantic!). We will prove only what is genuinely nontrivial.
- **However, BE VERY CAREFUL what you call trivial!!**

### The Stable Matching Problem

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Role of proofs - example

### The Stable Matching Problem

# Assignment Project Exam Help

- Assume that you are running a dating agency and have  $n$  men and  $n$  women as customers;

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Role of proofs - example

### The Stable Matching Problem

# Assignment Project Exam Help

- Assume that you are running a dating agency and have  $n$  men and  $n$  women as customers;

- Th

:<https://eduassistpro.github.io>

•

Add WeChat edu\_assist\_pro

## Role of proofs - example

### The Stable Matching Problem

# Assignment Project Exam Help

- Assume that you are running a dating agency and have  $m$  men and  $n$  women as customers;

- Th

:<https://eduassistpro.github.io>

- Design an algorithm which produces a stable matching between  $m$  men and  $n$  women.

Add WeChat edu\_assist\_pro is:

### The Stable Matching Problem

# Assignment Project Exam Help

- Assume that you are running a dating agency and have  $n$  men and  $n$  women as customers;

- Th

:<https://eduassistpro.github.io>

- Design an algorithm which produces a set of  $n$  pairs  $p = (m, w)$  of a man and a woman such that at the following situation never happens:

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro) is:

### The Stable Matching Problem

# Assignment Project Exam Help

- Assume that you are running a dating agency and have  $n$  men and  $n$  women as customers;

- Th

:<https://eduassistpro.github.io>

- Design an algorithm which produces a set of  $n$  pairs  $p = (m, w)$  of a man  $m$  and a woman  $w$  such that the following situation never happens:

for two pairs  $p = (m, w)$  and  $p' = (m', w')$ :

- man  $m$  prefers woman  $w'$  to woman  $w$ , **and**
- woman  $w'$  prefers man  $m$  to man  $m'$ .

# Assignment Project Exam Help

<https://eduassistpro.github.io>


Add WeChat edu\_assist\_pro

## Stable Matching Problem: examples

Preferences:

Case1:  
stable matching

not stable



Assignment Project Exam Help  
<https://eduassistpro.github.io>


Add WeChat edu\_assist\_pro

## Stable Matching Problem: examples


Preferences:

Case1:  
stable matching

not stable



-----  
Case2:  
stable matching



Is there always a stable matching for any preferences of two pairs?

Case1: two men like two different women (or vice versa)

Preferences:

stable matching

Assignment Project Exam Help



<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

Is there always a stable matching for any preferences of two pairs?

Case1: two men like two different women (or vice versa)

Preferences:

stable matching

# Assignment Project Exam Help




<https://eduassistpro.github.io>

Case2: men like the same woman and

Preferences:

stab

Add WeChat edu\_assist\_pro



## Stable Matching Problem: Gale - Shapley algorithm

**Question:** Is it true that for every possible collection of  $n$  lists of preferences provided by all men, and  $n$  lists of preferences provided by all women a stable matching always exists?

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Question:** Is it true that for every possible collection of  $n$  lists of preferences provided by all men, and  $n$  lists of preferences provided by all women a stable matching always exists?

Assignment Project Exam Help

*Answer:*

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Question:** Is it true that for every possible collection of  $n$  lists of preferences provided by all men, and  $n$  lists of preferences provided by all women a stable matching always exists?

Assignment Project Exam Help

*Answer:*

Given  $n$  i.e., just to <https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Question:** Is it true that for every possible collection of  $n$  lists of preferences provided by all men, and  $n$  lists of preferences provided by all women a stable matching always exists?

Assignment Project Exam Help

*Answer:*

Given  $n$

i.e., just to f

<https://eduassistpro.github.io>

*Answer:*  $n!$

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Question:** Is it true that for every possible collection of  $n$  lists of preferences provided by all men, and  $n$  lists of preferences provided by all women a stable matching always exists?

# Assignment Project Exam Help

*Answer:*

Given  $n$  i.e., just to find  
<https://eduassistpro.github.io/>

*Answer:*  $n! \approx (n/e)^n$  - more than exponential (2.71);

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Question:** Is it true that for every possible collection of  $n$  lists of preferences provided by all men, and  $n$  lists of preferences provided by all women a stable matching always exists?

Assignment Project Exam Help

*Answer:*

Given  $n$

i.e., just to f

<https://eduassistpro.github.io>

*Answer:*  $n! \approx (n/e)^n$  - more than exponential

2.71);

Can we find a stable matching in a reasonable amount

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro)

## Stable Matching Problem: Gale - Shapley algorithm

**Question:** Is it true that for every possible collection of  $n$  lists of preferences provided by all men, and  $n$  lists of preferences provided by all women a stable matching always exists?

Assignment Project Exam Help

*Answer:*

Given  $n$  i.e., just to find a stable matching.

*Answer:*  $n! \approx (n/e)^n$  - more than exponential time (see slide 2.71);

Can we find a stable matching in a reasonable amount of time?

*Answer:* YES, using the **Gale - Shapley algorithm**.

## Stable Matching Problem: Gale - Shapley algorithm

**Question:** Is it true that for every possible collection of  $n$  lists of preferences provided by all men, and  $n$  lists of preferences provided by all women a stable matching always exists?

Assignment Project Exam Help

*Answer:*

Given  $n$  i.e., just to find a stable matching.

*Answer:*  $n! \approx (n/e)^n$  - more than exponential time (2.71);

Can we find a stable matching in a reasonable amount of time?

*Answer:* YES, using the **Gale - Shapley algorithm**.

Originally invented to pair newly graduated physicians with US hospitals for residency training.

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r

<https://eduassistpro.github.io>

If      no one has proposed to  $w$  yet

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r

<https://eduassistpro.github.io>

If      no one has proposed to  $w$  yet  
          she always accepts and a pair

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r

<https://eduassistpro.github.io>

If      no one has proposed to  $w$  yet  
          she always accepts and a pair

Else     she is already in a pair  $P'$

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro)

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r

<https://eduassistpro.github.io>

If no one has proposed to  $w$  yet

she always accepts and a pair

Else she is already in a pair  $P'$

If  $m$  is higher on her preference

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro)

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r <https://eduassistpro.github.io>

If no one has proposed to  $w$  yet

she always accepts and a pair

Else she is already in a pair  $p'$

If  $m$  is higher on her preference

the pair  $p' = (m', w)$  is deleted;

Add WeChat `edu_assist_pro`

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r <https://eduassistpro.github.io>

If no one has proposed to  $w$  yet

she always accepts and a pair

Else she is already in a pair  $p'$

If  $m$  is higher on her preference

the pair  $p' = (m', w)$  is deleted;

$m'$  becomes a free man;

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro)

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r

<https://eduassistpro.github.io>

If no one has proposed to  $w$  yet

she always accepts and a pair

Else she is already in a pair  $p'$

If  $m$  is higher on her preference

the pair  $p' = (m', w)$  is deleted;

$m'$  becomes a free man;

a new pair  $p = (m, w)$  is formed;

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

- Produces pairs in stages, with possible revisions;
- A man who has not been paired with a woman will be called *free*.
- Men will be proposing to women. Women will decide if they accept a proposal or not.
- Start with all men free;

While

p  
r

<https://eduassistpro.github.io>

If no one has proposed to  $w$  yet  
she always accepts and a pair

Else she is already in a pair  $p'$

If  $m$  is higher on her preference list

the pair  $p' = (m', w)$  is deleted;

$m'$  becomes a free man;

a new pair  $p = (m, w)$  is formed;

Else  $m$  is lower on her preference list than  $m'$ ;

the proposal is rejected and  $m$  remains free.



## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- Every man can propose to a woman at most once;

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there a

ls.

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there are  $n$  men.

Thus the

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there are  $n$  men and  $n$  women.

Thus the

<https://eduassistpro.github.io>

**Claim 2:** Algorithm produces a matching, i.e., every man is eventually paired with a woman (and thus also every woman is paired with a man).

Add WeChat [edu\\_assist\\_pro](https://edu_assist_pro)

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there are  $n$  men and  $n$  women.

Thus the

number of proposals made by all men is  $n \cdot n = n^2$  times.

**Claim 2:** Algorithm produces a matching, i.e., every man is eventually paired with a woman (and thus also every woman is paired).

**Proof:** Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there are  $n$  men and  $n$  women.

Thus the

number of proposals made by all men is  $n \cdot n = n^2$  times.

**Claim 2:** Algorithm produces a matching, i.e., every man is eventually paired with a woman (and thus also every woman is paired).

**Proof:** Add WeChat edu\_assist\_pro

- Assume that the while *While* loop has terminated and there is still one free man.

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there are  $n$  men and  $n$  women.

Thus the

number of proposals is  $n \cdot n = n^2$  times.

**Claim 2:** Algorithm produces a matching, i.e., every man is eventually paired with a woman (and thus also every woman is paired).

**Proof:** Add WeChat edu\_assist\_pro

- Assume that the while *While* loop has terminated and there is still one man  $m$  left free.
- This means that  $m$  has already proposed to every woman.

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there are  $n$  men and  $n$  women.

Thus the

<https://eduassistpro.github.io>

**Claim 2:** Algorithm produces a matching, i.e., every man is eventually paired with a woman (and thus also every woman is paired).

**Proof:** Add WeChat edu\_assist\_pro

- Assume that the while *While* loop has terminated. Every woman is free.
- This means that  $m$  has already proposed to every woman.
- Thus, every woman is paired with a man, because a woman is not paired with anyone only if no one has made a proposal to her.

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there are  $n$  men and  $n$  women, so there are  $n^2$  proposals in total.

Thus the

<https://eduassistpro.github.io/stable-matching/>

**Claim 2:** Algorithm produces a matching, i.e., every man is eventually paired with a woman (and thus also every woman is paired with a man).

**Proof:** Add WeChat edu\_assist\_pro

- Assume that the while *While* loop has terminated and there is still one man  $m$  who is free.
- This means that  $m$  has already proposed to every woman.
- Thus, every woman is paired with a man, because a woman is not paired with anyone only if no one has made a proposal to her.
- But this would mean that  $n$  women are paired with all of  $n$  men so  $m$  cannot be free.

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 1:** Algorithm terminates after  $\leq n^2$  rounds of the *While* loop

**Proof:**

- In every round of the *While* loop one man proposes to one woman;
- every man can propose to a woman at most once;
- thus, every man can make at most  $n$  proposals;
- there are  $n$  men and  $n$  women, so there are  $n^2$  proposals in total.

Thus the

<https://eduassistpro.github.io/stable-matching/>

**Claim 2:** Algorithm produces a matching, i.e., every man is eventually paired with a woman (and thus also every woman is paired with a man).

**Proof:** Add WeChat edu\_assist\_pro

- Assume that the while *While* loop has terminated and there is still one man  $m$  who is free.
- This means that  $m$  has already proposed to every woman.
- Thus, every woman is paired with a man, because a woman is not paired with anyone only if no one has made a proposal to her.
- But this would mean that  $n$  women are paired with all of  $n$  men so  $m$  cannot be free. **Contradiction!**

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:**

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list

Assignment Project Exam Help

Assume n

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list

Assignment Project Exam Help

Assume n  
thus, ther

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list

Assignment Project Exam Help

Assume n  
thus, ther

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list.

Assignment Project Exam Help

Assume n  
thus, ther

<https://eduassistpro.github.io/>

- Since  $m$  prefers  $w'$  over  $w$ , he must have proposed to  $w$ ;

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list

Assume n  
thus, ther

<https://eduassistpro.github.io/>

- Since  $m$  prefers  $w'$  over  $w$ , he must have proposed to  $w$ ;
- Since he is paired with  $w$ , woman  $w$  ore

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list.

# Assignment Project Exam Help

Assume n  
thus, ther

<https://eduassistpro.github.io>

- Since  $m$  prefers  $w'$  over  $w$ , he must have proposed to  $w$ ;
  - rejected him because she was already with someone whom she prefers, or
- Since he is paired with  $w$ , woman  $w$

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list

# Assignment Project Exam Help

Assume n  
thus, ther

<https://eduassistpro.github.io/>

- Since  $m$  prefers  $w'$  over  $w$ , he must have proposed to  $w$ ;  
ore
- Since he is paired with  $w$ , woman  $w$ 
  - rejected him because she was already with someone whom she prefers, or
  - dropped him later after a proposal from someone whom she prefers;

Add WeChat edu\_assist\_pro

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list

# Assignment Project Exam Help

Assume n  
thus, ther

<https://eduassistpro.github.io>

- Since  $m$  prefers  $w'$  over  $w$ , he must have proposed to  $w$ ;  
ore
- Since he is paired with  $w$ , woman  $w$ 
  - rejected him because she was already with someone whom she prefers, or
  - dropped him later after a proposal from someone whom she prefers;
- In both cases she would now be with  $m'$  whom she prefers over  $m$ .

## Stable Matching Problem: Gale - Shapley algorithm

**Claim 3:** The matching produced by the algorithm is stable.

**Proof:** Note that during the *While* loop:

- a woman is paired with men of increasing ranks on her list;
- a man is paired with women of decreasing ranks on his list

# Assignment Project Exam Help

Assume n  
thus, ther

<https://eduassistpro.github.io>

- Since  $m$  prefers  $w'$  over  $w$ , he must have proposed to  $w$ ;  
ore
- Since he is paired with  $w$ , woman  $w$ 
  - rejected him because she was already with someone whom she prefers, or
  - dropped him later after a proposal from someone whom she prefers;
- In both cases she would now be with  $m'$  whom she prefers over  $m$ .
- **Contradiction!**

# A Puzzle!!!

Why puzzles? It is a fun way to practice problem solving!

## Assignment Project Exam Help

Problem: Tom and his wife Mary went to a party where nine more couples were present.

- Not each
- People who knew each other from before did no
- Later that evening Tom got bored, so he walked all other guests (including his wife) how many hands shaken that evening, and got 19 different answers.
- How many hands did Mary shake?
- How many hands did Tom shake?

Add WeChat [edu\\_assist\\_pro](https://eduassistpro.github.io)

# Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu\_assist\_pro

That's All, Folks!!