

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Liam O'Conn
University of Edinburgh, IFCS (an
Term 2 2020

Add WeChat [edu_assist_pro](#)

Methods of Assurance

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Methods of Assurance

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Methods of Assurance

Assignment Project Exam Help

Monitors, watchdogs

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Methods of Assurance

Assignment Project Exam Help

Monitors, watchdogs

<https://eduassistpro.github.io/>

Types

Add WeChat edu_assist_pro

Methods of Assurance

Assignment Project Exam Help

Monitors, watchdogs

<https://eduassistpro.github.io/>

Types

Add WeChat edu_assist_pro

Methods of Assurance

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Methods of Assurance

Assignment Project Exam Help

Static Analysers

Monitors, watchdogs

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Types


Model Checkers

Methods of Assurance

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro




Methods of Assurance

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Static means of assurance analyse a program **without running it**.

Static vs. Dynamic

Assignment Project Exam Help

- Static checks can be exhaustive.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Static vs. Dynamic

Assignment Project Exam Help

- Static checks can be exhaustive.

Exhaustivity

An exhaustive the
program.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Static vs. Dynamic

Assignment Project Exam Help

- Static checks can be **exhaustive**.

Exhaustivity

An exhaustive check covers all possible cases of the program.

<https://eduassistpro.github.io/>

- **However**, some properties cannot be checked statically (**problem**), or are intractable to easily check statically (Add WeChat **edu_assist_pro**)
- Dynamic checks cannot be exhaustive, but can be used to catch errors where static methods are unsuitable.

Compiler Integration

Most static and all dynamic methods of assurance are **not** integrated into the compilation process.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Compiler Integration

Most static and all dynamic methods of assurance are **not** integrated into the compilation process.

- You can co

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Compiler Integration

Most static and all dynamic methods of assurance are **not** integrated into the compilation process.

- You can co
- You can cla

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Compiler Integration

Most static and all dynamic methods of assurance are **not** integrated into the compilation process.

- You can co
- You can cla
- Your proof

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Compiler Integration

Most static and dynamic methods of assurance are **not** integrated into the compilation process.

- You can co
- You can cla
- Your proof

<https://eduassistpro.github.io/>

Types

Because types **are** integrated into the compiler, they cannot di
code. This means that type signatures are a kind of **machine-che**
for your code.

Add WeChat [edu_assist_pro](#)

Types

Assignment Project Exam Help

Types are the **most widely used** kind of formal verification in programming today.

- They are che
- They can be e
expressivi
- They are an **exhaustive** analysis.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Types

Assignment Project Exam Help

Types are the **most widely used** kind of formal verification in programming today.

- They are che
- They can be e
expressivi
- They are an **exhaustive** analysis.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

This week, we'll look at techniques to encode various correctness properties in
Haskell's type system.



Phantom Types

Definition

A type parameter is *phantom* if it does not appear in the right hand side of the type definition.

```
newtype Size s = S Int
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Phantom Types

Definition

A type parameter is *phantom* if it does not appear in the right hand side of the type definition.

```
newtype Size s = S Int
```

Lets examine each one of the following use cases:

- We can use this parameter to track what *data invariants* h
about a value.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Phantom Types

Definition

A type parameter is *phantom* if it does not appear in the right hand side of the type definition.

```
newtype Size a = S Int
```

<https://eduassistpro.github.io/>

Lets examine each one of the following use cases:

- We can use this parameter to track what *data invariants* h about a value.
- We can use this parameter to track information about the representation (e.g. units of measure).

Add WeChat edu_assist_pro



Phantom Types

Definition

A type parameter is *phantom* if it does not appear in the right hand side of the type definition.

```
newtype Size a = S Int
```

<https://eduassistpro.github.io/>

Lets examine each one of the following use cases:

- We can use this parameter to track what *data invariants* h about a value.
- We can use this parameter to track information about the representation (e.g. units of measure).
- We can use this parameter to enforce an *ordering* of operations performed on these values (*type state*).

Add WeChat edu_assist_pro

Validation

```
data UG -- empty type  
data PG  
data StudentID x = SID Int
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Validation

```
data UG -- empty type
data PG
data StudentID x = SID Int
```

We can define a `sma`

```
sid :: Int -> Either
```

(Recalling the following definition of `Either`)

```
data Either a b = Left a | Right b
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Validation

```
data UG -- empty type
data PG
data StudentID x = SID Int
```

We can define a `sma`

```
sid :: Int -> Either
```

(Recalling the following definition of `Either`)

```
data Either a b = Left a | Right b
```

And then define functions:

```
enrolInCOMP3141 :: StudentID UG -> IO ()
lookupTranscript :: StudentID x -> IO String
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Units of Measure

In 1999, software confusing units of measure (pounds and newtons) caused a mars orbiter to burn up on atmospheric entry.

```
data Kilometres
```

```
data Miles
```

```
data Value x = U Int
```

```
sydneyToMel
```

```
losAngelesToSanFran = (U 383 :: Value Miles)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Units of Measure

In 1999, software confusing units of measure (pounds and newtons) caused a mars orbiter to burn up on atmospheric entry.

```
data Kilometres
```

```
data Miles
```

```
data Value x = U Int  
sydneyToMel
```

```
losAngelesToSanFran = (U 383 :: Value Miles)
```

In addition to tagging values, we can also enforce constraints on

```
data Square a
```

```
area :: Value m -> Value m -> Value (Square m)
```

```
area (U x) (U y) = U (x * y)
```

Note the arguments to area must have the same units.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Type State

Example

A Socket can either be ready to receive data, or busy. If the socket is busy, the user must first use the wait operation, which blocks until the socket is ready. If the socket is ready, the user can make the socket busy again.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Type State

Example

A Socket can either be ready to receive data, or busy. If the socket is busy, the user must first use the wait operation, which blocks until the socket is ready. If the socket is ready, the user can make the socket busy again.

```
data Busy
```

```
data Ready
```

```
newtype Socket s = Socket
```

```
wait :: Socket Busy -> IO (Socket Ready)
```

```
send :: Socket Ready -> String -> IO (Socket Busy)
```

What assumptions are we making here?

Linearity and Type State

The previous code assumed that we didn't re-use old Sockets:

```
send2 :: Socket Ready -> String -> String  
      -> IO (Socket Busy)  
send2 s x y = do s' <- send s x
```

<https://eduassistpro.github.io/>
pure s'''

Add WeChat edu_assist_pro

Linearity and Type State

The previous code assumed that we didn't re-use old Sockets:

```
send2 :: Socket Ready -> String -> String  
      -> IO (Socket Busy)  
send2 s x y = do s' <- send s x
```

<https://eduassistpro.github.io/>
pure s''

But we can just re-use old values to send without waiting:

```
send2' s x y = do _ <- send s x  
                  s' <- send s y  
                  pure s'
```

Linearity and Type State

The previous code assumed that we didn't re-use old Sockets:

```
send2 :: Socket Ready -> String -> String  
      -> IO (Socket Busy)  
send2 s x y = do s' <- send s x
```

<https://eduassistpro.github.io/>
pure s''

But we can just re-use old values to send without waiting:

```
send2' s x y = do _ <- send s x  
                 s' <- send s y  
                 pure s'
```

Linear type systems
can solve this, but
not in Haskell (yet).

Datatype Promotion

data UG

data PG

data StudentID x = SID Int

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Datatype Promotion

`data UG`

`data PG`

`data StudentID x = SID Int`

Defining empty d

also StudentI

dentID UG, but

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Datatype Promotion

```
data UG
```

```
data PG
```

```
data StudentID x = SID Int
```

Defining empty d
also StudentI

dentID UG, but

Recall

Haskell types themselves have types, called **kinds**. Can we make types more precise than *****?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Datatype Promotion

```
data UG
data PG
data StudentID x = SID Int
```

Defining empty d
also StudentID

StudentID UG, but

Recall

Haskell types themselves have types, called **kinds**. Can we make types more precise than `*`?

The `DataKinds` language extension lets us use data types

```
{-# LANGUAGE DataKinds, KindSignatures #-}
data Stream = UG | PG
data StudentID (x :: Stream) = SID Int
-- rest as before
```

Motivation: Evaluation

Assignment Project Exam Help

<https://eduassistpro.github.io/>

```
data Expr = BConst Bool  
          | IConst Int  
          | T  
          | L  
          | A  
          | I
```

```
data Value = BVal Bool | IVal Int
```

Example

Define an expression evaluator:

```
eval :: Expr -> Value
```

Add WeChat edu_assist_pro

Motivation: Partiality

Unfortunately the `eval` function is *partial*, undefined for input expressions that are not well-typed, like:

And (ICons 3) (BC

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Motivation: Partiality

Unfortunately the `eval` function is *partial*, undefined for input expressions that are not well-typed, like:

`And (ICons 3) (BC`

Recall

With any partial function, we can make it total by either *expanding* the co-domain (e.g. with a `Maybe` type), or *constraining* the domain.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Motivation: Partiality

Unfortunately the `eval` function is *partial*, undefined for input expressions that are not well-typed, like:

And `(ICons 3) (BC`

Recall

With any partial function, we can make it total by either *expanding* the co-domain (e.g. with a `Maybe` type), or *constraining* the domain.

Can we use phantom types to constrain the domain of `eval` to only accept well-typed expressions?

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Attempt: Phantom Types

Let's try adding a phantom parameter to `Expr`, and defining typed constructors with precise types:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Attempt: Phantom Types

Let's try adding a phantom parameter to Expr, and defining typed constructors with precise types:

```
data Expr t = ...  
bConst :: Bool -> Expr Bool  
bConst = BConst  
iConst :: Int -> Expr Int  
iConst = IConst  
times :: Expr Int -> Expr Int -> Expr Int  
times = Times  
less :: Expr Int -> Expr Int -> Expr Bool  
less = Less  
and :: Expr Bool -> Expr Bool -> Expr Bool  
and = And  
if' :: Expr Bool -> Expr a -> Expr a -> Expr a  
if' = If
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Attempt: Phantom Types

This makes invalid expressions into type errors (yay!):

```
-- Couldn't match Int and Bool  
and (iCons 3) (bConst True)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Attempt: Phantom Types

This makes invalid expressions into type errors (yay!):

```
-- Couldn't match Int and Bool  
and (iCons 3) (bConst True)
```

How about our

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Attempt: Phantom Types

This makes invalid expressions into type errors (yay!):

```
-- Couldn't match Int and Bool  
and (iCons 3) (bConst True)
```

How about our

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Attempt: Phantom Types

This makes invalid expressions into type errors (yay!):

```
-- Couldn't match Int and Bool  
and (iCons 3) (bConst True)
```

How about our

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Attempt: Phantom Types

This makes invalid expressions into type errors (yay!):

```
-- Couldn't match Int and Bool  
and (iCons 3) (bConst True)
```

How about our

<https://eduassistpro.github.io/>

Bad News

Inside eval, the Haskell type checker cannot be sure that we use constructors, so in e.g. the IConst case

```
eval :: Expr t -> t  
eval (IConst i) = i -- type error
```

We are unable to tell that the type `t` is definitely `Int`.

Add WeChat edu_assist_pro

Attempt: Phantom Types

This makes invalid expressions into type errors (yay!):

```
-- Couldn't match Int and Bool  
and (iCons 3) (bConst True)
```

How about our

<https://eduassistpro.github.io/>

Bad News

Inside eval, the Haskell type checker cannot be sure that we use constructors, so in e.g. the IConst case

```
eval :: Expr t -> t  
eval (IConst i) = i -- type error
```

We are unable to tell that the type `t` is definitely `Int`.

Phantom types aren't strong enough!

GADTs

Generalised Algebraic Datatypes (GADTs) is an extension to Haskell that, among other things, allows data types to be specified by writing the types of their constructors:

```
{-# LANGUAGE GADTs -#}  
-- Unary natural numbers  
data Nat = Z | S Nat  
-- is the same as  
data Nat :: * where  
  Z :: Nat  
  S :: Nat -> Nat
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

GADTs

Generalised Algebraic Datatypes (GADTs) is an extension to Haskell that, among other things, allows data types to be specified by writing the types of their constructors:

```
{-# LANGUAGE GADTs #-}
-- Unary natural numbers
data Nat = Z | S Nat
-- is the same as
data Nat :: * where
  Z :: Nat
  S :: Nat -> Nat
```

When combined with the *type indexing* trick of phantom types, this becomes very powerful!

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Expressions as a GADT

```
data Expr :: * -> * where
```

```
BConst :: Bool -> Expr Bool
```

```
IConst :: Int -> Expr Int
```

```
Times :: Expr Int -> Expr Int -> Expr Int
```

```
Less :: Expr Int
```

```
And :: Expr Bool
```

```
If :: Expr Bool -> Expr
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Expressions as a GADT

```
data Expr :: * -> * where
```

```
BConst :: Bool -> Expr Bool
```

```
IConst :: Int -> Expr Int
```

```
Times :: Expr Int -> Expr Int -> Expr Int
```

```
Less :: Expr Int
```

```
And :: Expr Bool
```

```
If :: Expr Bool -> Expr
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Observation

There is now only *one* set of precise v-typed construc

Add WeChat edu_assist_pro

Expressions as a GADT

```
data Expr :: * -> * where
```

```
BConst :: Bool -> Expr Bool
```

```
IConst :: Int -> Expr Int
```

```
Times :: Expr Int -> Expr Int -> Expr Int
```

```
Less :: Expr Int
```

```
And :: Expr Bool
```

```
If :: Expr Bool -> Expr
```

Observation

There is now only *one* set of *precisely* v-typed constructs

Inside `eval` now, the Haskell type checker accepts our previously problematic case:

```
eval :: Expr t -> t
```

```
eval (IConst i) = i -- OK now
```

Expressions as a GADT

```
data Expr :: * -> * where
```

```
BConst :: Bool -> Expr Bool
```

```
IConst :: Int -> Expr Int
```

```
Times :: Expr Int -> Expr Int -> Expr Int
```

```
Less :: Expr Int
```

```
And :: Expr Bool
```

```
If :: Expr Bool -> Expr
```

Observation

There is now only *one* set of *precisely* v-typed constructs

Inside `eval` now, the Haskell type checker accepts our previously problematic case:

```
eval :: Expr t -> t
```

```
eval (IConst i) = i -- OK now
```

GHC now knows that if we have `IConst`, the type `t` must be `Int`.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Lists

Assignment Project Exam Help

We could define our own list type using GADT syntax as follows:

```
data List (a :: *) :: * →
```

```
Nil :: List a
```

```
Cons :: a → List a →
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Lists

Assignment Project Exam Help

We could define our own list type using GADT syntax as follows:

```
data List (a :: *) :: * where
  Nil  :: List a
  Cons :: a -> List a ->
```

But, if we define head

```
hd (Cons x xs) = x
tl (Cons x xs) = xs
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Lists

Assignment Project Exam Help

We could define our own list type using GADT syntax as follows:

```
data List (a :: *) :: * →
```

```
  Nil :: List a
```

```
  Cons :: a → List a →
```

But, if we define head

```
hd (Cons x xs) = x
```

```
tl (Cons x xs) = xs
```

We will constrain the domain of these functions by tracking the level.
the type level.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Vectors

As before, define a natural number kind to use on the type level:

```
data Nat = Z | S Nat
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Vectors

As before, define a natural number kind to use on the type level:

```
data Nat = Z | S Nat
```

Now our length-*i*

```
data Vec (a :: *) :: Nat  
  Nil    :: Vec a Z  
  Cons   :: a -> Vec a n -> Vec a (S n)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Vectors

As before, define a natural number kind to use on the type level:

```
data Nat = Z | S Nat
```

Now our length-*i*

```
data Vec (a :: *) :: Nat  
  Nil    :: Vec a Z  
  Cons   :: a -> Vec a n -> Vec a (S n)
```

Now `hd` and `tl` can be total:

```
hd :: Vec a (S n) -> a  
hd (Cons x xs) = x  
tl :: Vec a (S n) -> Vec a n  
tl (Cons x xs) = xs
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Vectors, continued

Our map for vectors is as follows:

```
mapVec :: (a -> b) -> Vec a n -> Vec b n
mapVec f Nil = Nil
mapVec f (Cons x xs)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Vectors, continued

Our map for vectors is as follows:

```
mapVec :: (a -> b) -> Vec a n -> Vec b n
mapVec f Nil = Nil
mapVec f (Cons x xs)
```

<https://eduassistpro.github.io/>

Properties

Using this type, it's impossible to write a map of length of the vector.

Properties are verified by the compiler!

Add WeChat [edu_assist_pro](#)

Tradeoffs

The benefits of this extra static checking are obvious, however:

- It can be difficult to convince the Haskell type checker that your code is correct, even when it is.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Tradeoffs

The benefits of this extra static checking are obvious, however:

- It can be difficult to convince the Haskell type checker that your code is correct, even when it is.
- Type-level understanding

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Tradeoffs

The benefits of this extra static checking are obvious, however:

- It can be difficult to convince the Haskell type checker that your code is correct, even when it is.
- Type-level understanding
- Sometime productivity

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Tradeoffs

The benefits of this extra static checking are obvious, however:

- It can be difficult to convince the Haskell type checker that your code is correct, even when it is.
- Type-level understanding
- Sometime productivity

<https://eduassistpro.github.io/>

Pragmatism

We should use type-based encodings only when the assurance clarity disadvantages.

Add WeChat edu_assist_pro

Tradeoffs

The benefits of this extra static checking are obvious, however:

- It can be difficult to convince the Haskell type checker that your code is correct, even when it is.
- Type-level understanding
- Sometime productivity

<https://eduassistpro.github.io/>

Pragmatism

We should use type-based encodings only when the assurance clarity disadvantages.

The typical use case for these richly-typed structures is to eliminate **partial functions** from our code base.

Add WeChat edu_assist_pro

Tradeoffs

The benefits of this extra static checking are obvious, however:

- It can be difficult to convince the Haskell type checker that your code is correct, even when it is.
- Type-level understanding
- Sometime productivity

<https://eduassistpro.github.io/>

Pragmatism

We should use type-based encodings only when the assurance clarity disadvantages.

The typical use case for these richly-typed structures is to eliminate **partial functions** from our code base.

If we never use partial list functions, length-indexed vectors are not particularly useful.

Add WeChat edu_assist_pro

Appending Vectors

Example (Problem) Assignment Project Exam Help

```
appendV :: Vec a m -> Vec a n -> Vec a ???
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Appending Vectors

Example (Problem)

Assignment Project Exam Help

```
appendV :: Vec a m -> Vec a n -> Vec a ???
```

We want to write
kind Nat.

for

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Appending Vectors

Example (Problem)

```
appendV :: Vec a m -> Vec a n -> Vec a ???
```

We want to write

for

kind Nat.

We can define a nor

```
plus :: Nat -> Nat -> Nat
```

```
plus Z y = y
```

```
plus (S x) y = S (plus x y)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Appending Vectors

Example (Problem)

```
appendV :: Vec a m -> Vec a n -> Vec a ???
```

We want to write

for

kind Nat.

We can define a nor

```
plus :: Nat -> Nat -> Nat
```

```
plus Z y = y
```

```
plus (S x) y = S (plus x y)
```

This function is not applicable to **type-level** Nats, though.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Appending Vectors

Example (Problem)

```
appendV :: Vec a m -> Vec a n -> Vec a ???
```

We want to write

for

kind Nat.

We can define a nor

```
plus :: Nat -> Nat -> Nat
```

```
plus Z y = y
```

```
plus (S x) y = S (plus x y)
```

This function is not applicable to **type-level** Nats, though.

⇒ we need a **type level function**.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Type Families

Assignment Project Exam Help

Type level functions, also called *type families*, are defined in Haskell like so:

```
{-# LANGUAGE Ty  
type family Plu  
  Plus Z      y = y  
  Plus (S x) y = S (Plu
```

We can use our type family to define appendV:

```
appendV :: Vec a n -> Vec a n -> Vec a (Plus n n)  
appendV Nil      ys = ys  
appendV (Cons x xs) ys = Cons x (appendV xs ys)
```

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Recursion

If we had implemented Plus by recursing on the second argument instead of the first:

```
{-# LANGUAGE TypeFamilies #-}  
type family Plus' (x :: Nat) (y :: Nat) :: Nat where  
  Plus' x Z      = x  
  Plus' x (S y)  = S (Pl
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Recursion

If we had implemented Plus by recursing on the second argument instead of the first:

```
{-# LANGUAGE TypeFamilies #-}  
type family Plus' (x :: Nat) (y :: Nat) :: Nat where  
  Plus' x Z      = x  
  Plus' x (S y)  = S (Pl
```

Then our app

```
appendV :: Vec a n -> V  
appendV Nil ys = ys  
appendV (Cons x xs) ys = Cons x (appendV xs ys)
```

Why?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Recursion

If we had implemented Plus by recursing on the second argument instead of the first:

```

{-# LANGUAGE TypeFamilies #-}
type family Plus' (x :: Nat) (y :: Nat) :: Nat where
  Plus' x Z      = x
  Plus' x (S y)  = S (Pl

```

Then our app

```

appendV :: Vec a m -> V
appendV Nil ys = ys
appendV (Cons x xs) ys = Cons x (appendV xs ys)

```

Why?

Answer

Consider the Nil case. We know $m = Z$, and must show that our desired return type $\text{Plus}' Z n$ equals our given return type n , but that fact is not immediately apparent from the equations.

Type-driven development

Assignment Project Exam Help

- This lecture is only a taste of the full power of type-based specifications.

- Language and value level

- Haskell is all

<https://eduassistpro.github.io/>

Next week: Fancy theory about types!

- Deep connections between types, logic and proof
- Algebraic type structure for generic algorithms and ref
- Using polymorphic types to infer properties for free.

Add WeChat [edu_assist_pro](#)

Homework

Assignment Project Exam Help

- ① Assignme
- ② The last pro
- ③ This week's quiz is also up, due in Friday of Week 9.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro