

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Liam O'Conn
CSE, UNSW (and Data6
Term 2 2019)
Add WeChat edu_assist_pro

Effects

Effects

Effects are observable phenomena from the execution of a program

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Effects

Effects

Effects are observable phenomena from the execution of a program

Exa

```
in  
... // read and write  
*p = *p + 1;
```

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Effects

Effects

Effects are observable phenomena from the execution of a program

Exa

```
in  
... // read and write  
*p = *p + 1;
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Effects

Effects

Effects are observable phenomena from the execution of a program

Exa

```
in  
... // read and write  
*p = *p + 1;
```

E

```
// exception effect  
throw new Exception();
```

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Effects

Effects

Effects are observable phenomena from the execution of a program

Example

```
in
... // read and write
*p = *p + 1;
```

Example (Non-termination)

```
// infinite loop
while (1) {};
```

Example

```
// exception effect
throw new Exception();
```

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Internal vs. External Effects

Assignment Project Exam Help

External Observability

An *external* effect is an effect that is *observable* outside the function.

Internal effects

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Internal vs. External Effects

External Observability

An *external* effect is an effect that is *observable* outside the function.

Internal effects

Example (External)

Console, file and network I/O; termination and non-termination etc.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Internal vs. External Effects

External Observability

An *external* effect is an effect that is *observable* outside the function.

Internal effects

Example (External)

Console, file and network I/O; termination and non-termination etc.

Are memory effects *external* or *internal*?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Internal vs. External Effects

Assignment Project Exam Help

External Observability

An *external* effect is an effect that is *observable* outside the function.

Internal effects

Example (External)

Console, file and network I/O; termination and non-termination etc.

Are memory effects *external* or *internal*?

Answer: Depends on the scope of the memory being accessed. Global variable accesses are *external*.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Purity

A function with no external effects is called a *pure* function.

Pure functions

A *pure function*

$a \rightarrow b$ is *fully*
codomain type

into the

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Purity

A function with no external effects is called a *pure* function.

Pure functions

A *pure function*

$a \rightarrow b$ is *fully*
codomain type

at to the

Consequences:

- Two invocations with the same arguments result in the same

Purity

A function with no external effects is called a *pure function*.

Pure functions

A *pure function*

$a \rightarrow b$ is *fully*
codomain type

into the

Consequences:

- Two invocations with the same arguments result in the same value
- No observable trace is left beyond the result of the function

Purity

A function with no external effects is called a *pure* function.

Pure functions

A *pure function*

$a \rightarrow b$ is *fully*
codomain type

into the

Consequences:

- Two invocations with the same arguments result in the same value
- No observable trace is left beyond the result of the function
- No implicit notion of time or order of execution.

Purity

A function with no external effects is called a *pure* function.

Pure functions

A *pure function*

$a \rightarrow b$ is *fully*
codomain type

at to the

Consequences:

- Two invocations with the same arguments result in the same value
- No observable trace is left beyond the result of the function
- No implicit notion of time or order of execution.

Question: Are Haskell functions *pure*?

Haskell Functions

Haskell functions are technically **not** pure.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Haskell Functions

Assignment Project Exam Help

Haskell functions are technically **not** pure.

- They can loop infinitely.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Haskell Functions

Haskell functions are technically **not** pure.

- They can loop infinitely.
- They can thr

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Haskell Functions

Haskell functions are technically **not** pure.

- They can loop infinitely.
- They can throw exceptions.
- They can fail.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Haskell Functions

Haskell functions are technically **not** pure.

- They can loop infinitely.
- They can throw exceptions.
- They can fail.

<https://eduassistpro.github.io/>

Caveat

Purity only applies to a particular level of abstraction. Even ignoring side effects, assembly instructions produced by GHC aren't really pure.

Add WeChat [edu_assist_pro](#)

Haskell Functions

Haskell functions are technically **not** pure.

- They can loop infinitely.
- They can throw exceptions.
- They can fail.

<https://eduassistpro.github.io/>

Caveat

Purity only applies to a particular level of abstraction. Even ignoring side effects, assembly instructions produced by GHC aren't really pure.

Despite the impurity of Haskell functions, we can often reason as though they are pure. Hence we call Haskell a **purely functional** language.

The Danger of Implicit Side Effects

Assignment Project Exam Help

- They introduce (often subtle) requirements on the evaluation order.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

The Danger of Implicit Side Effects

Assignment Project Exam Help

- They introduce (often subtle) requirements on the evaluation order.
- They are not v

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

The Danger of Implicit Side Effects

Assignment Project Exam Help

- They introduce (often subtle) requirements on the evaluation order.
- They are not v
- They introduce increasing

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

The Danger of Implicit Side Effects

Assignment Project Exam Help

- They introduce (often subtle) requirements on the evaluation order.
- They are not v
- They introduce increasing
- They interfere badly with strong typing, for example mu reference types in ML.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

The Danger of Implicit Side Effects

Assignment Project Exam Help

- They introduce (often subtle) requirements on the evaluation order.
- They are not v
- They introduce increasing
- They interfere badly with strong typing, for example mu reference types in ML.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

We can't, in general, reason equationally about effectful prog

Can we program with pure functions?

Yes! We've been doing it for the past 6 weeks.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Can we program with pure functions?

Yes! We've been doing it for the past 6 weeks.

Assignment Project Exam Help

Typically, a computation involving some state of type s and returning a result of type a can be expressed

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Can we program with pure functions?

Yes! We've been doing it for the past 6 weeks.

Assignment Project Exam Help

Typically, a computation involving some state of type s and returning a result of type a can be expressed

<https://eduassistpro.github.io/>

Rather than **change** the state, we return a **new copy** of the state

Add WeChat edu_assist_pro

Can we program with pure functions?

Yes! We've been doing it for the past 6 weeks.

Assignment Project Exam Help

Typically, a computation involving some state of type s and returning a result of type a can be expressed

<https://eduassistpro.github.io/>

Rather than **change** the state, we return a **new copy** of the state.

Add WeChat edu_assist_pro

Efficiency?

All that copying might seem expensive, but by using tree data structures, we can usually reduce the cost to an $\mathcal{O}(\log n)$ overhead.

State Passing

Example (Labelling Nodes)

```
data Tree a = Branch a (Tree a) (Tree a) | Leaf
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

State Passing

Example (Labelling Nodes)


```
data Tree a = Branch a (Tree a) (Tree a) | Leaf
```

Given a tree, label ea

```
label :: Tree () -> T
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro




State Passing

Example (Labelling Nodes)

```
data Tree a = Branch a (Tree a) (Tree a) | Leaf
```

Given a tree, label ea

```
label :: Tree () -> T
```



State Passing

Example (Labelling Nodes)


```
data Tree a = Branch a (Tree a) (Tree a) | Leaf
```

Given a tree, label ea

```
label :: Tree () -> T
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Let's use a **data type** to simplify this!

State

`newtype State s a = A` `procedure` that, manipulating some state of type `s`, returns a

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

State

`newtype State s a = A` procedure that, manipulating some state of type `s`, returns a

State Operations

```
get :: State s s  
put :: s -> State s ()  
pure :: a -> State s a  
evalState :: State s a -> s -> a
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Effects
○○○○○○

State
○●○

IO
○○○○○○○

QuickChecking Effects
○

State

`newtype State s a = A` procedure that, manipulating some state of type `s`, returns a

State Operations

```
get :: State s s
put :: s -> State s ()
pure :: a -> State s a
evalState :: State s a -> s -> a
```

Sequential Composition

do blocks:

```
(>>) :: St
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

State

`newtype State s a = A` procedure that, manipulating some state of type `s`, returns a

State Operations

```
get :: State s s
put :: s -> State s ()
pure :: a -> State s a
evalState :: State s a -> s -> a
```

Sequential Composition

do blocks:

```
(>>) :: St
```

Add WeChat [edu_assist_pro](https://eduassistpro.github.io/)

Bind

The 2nd step can depen

```
do x <- get
  pure (x+1)
   $\xRightarrow{\text{desugars}}$ 
  get >>= \x -> pure (x + 1)
```

```
(>>=) :: State s a -> (a -> State s b) -> State s b
```

State

`newtype State s a = A` `procedure` that, manipulating some state of type `s`, returns a

State Operations

```
get :: State s s
put :: s -> State s ()
pure :: a -> State s a
evalState :: State s a -> s -> a
```

Sequential Composition

do blocks:

```
(>>) :: St
```

Example

Implement modify:

```
(s -> s) -> State s ()
```

And re-do the tree labelling.

Bind

The 2nd step can depen

```
do x <- get    desugars  get >>= \x -> pure (x + 1)
  pure (x+1)    =>
```

```
(>>=) :: State s a -> (a -> State s b) -> State s b
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

State Implementation

Assignment Project Exam Help

The State type is essentially implemented as the same state passing we did before!

```
newtype State s a = State (s -> (s,a))
```

Example

Let's implement e

<https://eduassistpro.github.io/>

Caution

In the Haskell standard library `mtl`, the `State` type is implemented differently, but the implementation essentially works the same way.

Add WeChat edu_assist_pro

Effects

Assignment Project Exam Help

Sometimes we need side effects.

- We need to pe
- We might ne
(but usually i

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Effects

Assignment Project Exam Help

Sometimes we need side effects.

- We need to pe
- We might ne
(but usually i

<https://eduassistpro.github.io/>

Haskell's approach

Pure by default. Effectful when necessary.

Add WeChat edu_assist_pro

The IO Type

A **procedure** that performs some side effects, returning a result of type `a` is written as

`IO a` **Assignment Project Exam Help**

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

The IO Type

A **procedure** that performs some side effects, returning a result of type `a` is written as `IO a`

World interpretation

`IO a` is an abstra

<https://eduassistpro.github.io/>

(that's how it's implemented in GHC)

Add WeChat `edu_assist_pro`

The IO Type

A **procedure** that performs some side effects, returning a result of type `a` is written as `IO a`

World interpretation

`IO a` is an abstra

<https://eduassistpro.github.io/>

(that's how it's implemented in GHC)

```
(>>=) :: IO a -> (a -> IO b) -> IO b
pure  :: a -> IO a
```

```
getChar :: IO Char
readLine :: IO String
putStrLn :: String -> IO ()
```

Infectious IO

We can convert pure values to impure procedures with `pure`:

```
pure :: a -> IO a
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Infectious IO

We can convert pure values to impure procedures with `pure`:

```
pure :: a -> IO a
```

But we can't convert impure procedures to pure values:

```
???? :: IO a -> a
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Infectious IO

We can convert pure values to impure procedures with `pure`:

```
pure :: a -> IO a
```

But we can't convert impure procedures to pure values:

```
???? :: IO a -> a
```

The only function that

```
(>=>) :: IO a -> (a -> IO b) -> IO b
```

But it returns an IO procedure as well.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Infectious IO

We can convert pure values to impure procedures with `pure`:

```
pure :: a -> IO a
```

But we can't convert impure procedures to pure values:

```
???? :: IO a -> a
```

The only function that

```
(>=>) :: IO a -> (a -> IO b) -> IO b
```

But it returns an IO procedure as well.

Conclusion

The moment you use an IO procedure in a function, IO shows up in the types, and you can't get rid of it!

If a function makes use of IO effects directly or indirectly, it will have IO in its type!

Haskell Design Strategy

We ultimately “run” IO procedures by calling them from `main`:

```
main :: IO ()
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Haskell Design Strategy

We ultimately “run” IO procedures by calling them from `main`:

```
main :: IO ()
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Pure Logic

Add WeChat edu_assist_pro

IO Shell

Examples

Assignment Project Exam Help

Example (Triangles)

Given an input nu

n .

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Examples

Assignment Project Exam Help

Example (Triangles)

Given an input number n .

Example (Maze)

Design a game that reads in a $n \times n$ maze from a file and must reach position $(n-1, n-1)$ to win. It can move the player around the maze.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Benefits of an IO Type

Assignment Project Exam Help

- Absence of effects makes type system more informative:

- A type si
- All dep
- All dep

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Benefits of an IO Type

Assignment Project Exam Help

- Absence of effects makes type system more informative:

- A type si
- All dep
- All dep

<https://eduassistpro.github.io/>

- It is easier to reason about pure code and it is easier to test:

- Testing is local, doesn't require complex set-up and tea
- Reasoning is local, doesn't require state invariants
- Type checking leads to strong guarantees.

Add WeChat [edu_assist_pro](#)

Mutable Variables

Assignment Project Exam Help

We can have honest-to-goodness mutability in Haskell, if we really need it, using `IORef`.

```
data IORef a
newIORef  :: a -> IO ()
readIORef :: IORef a -> IO a
writeIORef :: IORef a -> a -> IO ()
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Mutable Variables

Assignment Project Exam Help

We can have honest-to-goodness mutability in Haskell, if we really need it, using `IORef`.

```
data IORef a
newIORef  :: a -> IO ()
readIORef :: IORef a -> IO a
writeIORef :: IORef a -> a -> IO ()
```

Example (Effectful Average)

Average a list of numbers using `IORefs`.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Mutable Variables, Locally

Something like averaging a list of numbers doesn't require external effects, even if we use mutation internally.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Mutable Variables, Locally

Something like averaging a list of numbers doesn't require external effects, even if we use mutation internally.

```
data STRef s a
newSTRef :: a -> ST (
readSTRef :: ST
writeSTRef :: s
runST :: (forall s. ST s a) -> a
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Mutable Variables, Locally

Something like averaging a list of numbers doesn't require external effects, even if we use mutation internally.

```
data STRef s a
newSTRef :: a -> ST (
readSTRef :: ST
writeSTRef :: s
runST :: (forall s. ST s a) -> a
```

The extra `s` parameter is called a `state thread`, that ensures don't leak outside of the ST computation.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Mutable Variables, Locally

Something like averaging a list of numbers doesn't require external effects, even if we use mutation internally.

```
data STRef s a
newSTRef :: a -> ST (
readSTRef :: ST
writeSTRef :: s
runST :: (forall s. ST s a) -> a
```

The extra `s` parameter is called a `state thread`, that ensures don't leak outside of the ST computation.

Note

The ST type is not assessable in this course, but it is useful sometimes in Haskell programming.

QuickChecking Effects

QuickCheck lets us test IO (and ST) using this special **property monad** interface:

```
monad.cIO :: PropertyM IO () -> Property
pre       :: Bool -> PropertyM IO ()
assert    :: Bool -> Prop
run       :: IO a -> PropertyM IO a
```

Do notation and `doIO` work the same as with `State` and `IO` procedures.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

QuickChecking Effects

QuickCheck lets us test IO (and ST) using this special **property monad** interface:

```
monadicIO :: PropertyM IO () -> Property
pre       :: Bool -> PropertyM IO ()
assert    :: Bool -> Prop
run       :: IO a -> PropertyM IO a
```

Do notation and `do` notation are used to write tests as with `State` and IO procedures.

Example (Testing average)

Let's test that our IO average function works like the n

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

QuickChecking Effects

QuickCheck lets us test IO (and ST) using this special **property monad** interface:

```
monadicIO :: PropertyM IO () -> Property
pre       :: Bool -> PropertyM IO ()
assert    :: Bool -> Prop
run       :: IO a -> PropertyM IO a
```

Do notation and `doIO` work just as with `State` `s` and IO procedures.

Example (Testing average)

Let's test that our IO average function works like the n

Example (Testing gfactor)

Let's test that the GNU factor program works correctly!

Homework

Assignment Project Exam Help

- ① New exercise
- ② Last week's
- ③ This week's quiz is due the **Friday after** the following Friday

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro