

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat University of Leeds edu_assist_pro

Lecture 15: GPU threads and k

Previous lecture

Assignment Project Exam Help

In the last lecture we started looking at General Purpose GPU
prog

- <https://eduassistpro.github.io>
- Thread scheduling is performed **in hardware**.
- Programmable using **OpenCL** (th others.
- Device discovery performed at run time (*cf.* the `displayDevices.c` example).

Today's lecture

Assignment Project Exam Help

Today we will see how to perform vector addition on a GPU:

- <https://eduassistpro.github.io>
-
- **Work items** are the basic unit of concurr
- Arranged into **work groups** for s
- How to set the work group size.

Add WeChat edu_assist_pr

Vector addition

Code on Minerva: `vectorAddition.c`, `vectorAddition.cl` and `helper.h`

Assignment Project Exam Help

Once again use **vector addition** as our first worked example:

In serial


```
1 for( i=0; i<N; i++ )  
2   c[i] = a[i] + b[i];
```

where vectors **a**, **b** and **c** all have N elements.
mathematical and computer indexing differ by 0

This is a **map/data parallel** problem with no **data dependencies**.

Host and device

The CPU is the **host**, and the GPU is the **device**:



Assu

If the initial data is only accessible to the CPU, must to the GPU to perform the calculations, then to the CPU.

- This requires **explicit communication**, somewhat similar to the distributed memory model.

¹Some modern GPUs support **unified memory** — see next lecture.

Typical program structure

Assignment Project Exam Help

① **Send** problem

② <https://eduassistpro.github.io>

calculations on
the device.

③ **Return** results
from device to
the host.



Contexts and command queues

Recall from last lecture that to use OpenCL we first need to

- 1 Identify the **platform** and a suitable **device**.

- 2 Create a **context** and a **command queue**.

The first two steps are done in the following code snippet:

```
1 cl_device_id device;  
2 cl_context context = simpleOpenContext_GPU(&device);  
3  
4 cl_int status;  
5 cl_command_queue queue = clCreateCommandQueue(context,  
        device, 0, &status);  
6 ... // Use the GPU.  
7 clReleaseCommandQueue(queue);  
8 clReleaseContext(context);
```

Device memory allocation

Suppose arrays `a`, `b` and `c` initialised on the host:

```
1 float* host_a = (float*) malloc(N*sizeof(float));
```

Similar

Can allocate on host a

```
1 cl_mem device_a = clCreateBuffer(  
2     context,  
3     CL_MEM_READ_ONLY|CL_MEM_COPY_HOST_PTR, // flags  
4     N*sizeof(float), // Size in bytes.  
5     host_a, // Copy from this host array.  
6     &status // Error status.  
7 );
```

Similar for `device_b`, `device_c`.

clCreateBuffer() usage

Assignment Project Exam Help

- The context has been initialised for the GPU.
- The flag CL_MEM_READ_ONLY refers to how the **device** accesses

<https://eduassistpro.github.io>

- The flag CL_MEM_COPY_HOST_PTR existing **host** array (the 4th argument)
- For device_c, where no host data (yet) exists, CL_MEM_WRITE_ONLY and the 4th argument is NULL.
- status is set to CL_SUCCESS if the operation was successful, otherwise some other error code.

GPU kernel

Assignment Project Exam Help

Definition

Kernels are functions that execute on the device.

<https://eduassistpro.github.io>

Use st

```
1 __kernel
2 void vectorAdd(__global float *a, __global float *b,
3               __global float *c)
4 {
5     int gid = get_global_id(0);
6     c[gid] = a[gid] + b[gid];
7 }
```

OpenCL kernels

Assignment Project Exam Help

- All kernels¹ preceded with `__kernel`.

-

- <https://eduassistpro.github.io>

- `get_global_id()` returns the (global

- For this problem it is the index of the vector.

- See later.

Add WeChat [edu_assist_pro](#)

¹CUDA kernels are preceded `__global__` (if they are callable by the host).

Building a kernel

Assignment Project Exam Help

OpenCL kernels are compiled at run time (of the C code).

- Allows optimisation for the device that executes it.

Require

- 1 Start with the program as a `char* string` (typically read from file ending in `.cl`).

- 2 Create the **program** for the context with `clCreateProgramWithSource()`

- 3 **Build** (compile and link) using `clBuildProgram()`.

- 4 Create a **kernel** using `clCreateKernel()`.

Building a kernel with helper.h

To simplify this process, the file `helper.h` contains the routine `compileKernelFromFile()`.

For th

```
1 cl_kern
2 "v
3 "vectorAdd",          // Name of function.
4 context,              // Same as before.
5 device                // Same as before.
6 );
7
8 ... // Use kernel.
9
10 clReleaseKernel(kernel);
```

It also includes some basic error handling.

Setting kernel arguments

Assignment Project Exam Help

Each kernel argument must be set by using `clSetKernelArg()`.

```
1 statu = c
2 ke // The kernel object.
3 0, // The argument number.
4 sizeof(cl_mem), // The size of the argument.
5 &device_a // The value.
6 );
```

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

This is repeated for argument 1 (\rightarrow device_b) and argument 2 (\rightarrow device_c) for the vector addition example.

Starting a kernel in OpenCL¹

To start a kernel, you place it on the **command queue** using

`clEnqueueNDRangeKernel()`:

```
1 // Will cover this later.
2 size_t
3 index
4 workGroupSize[3] = {1, 1, 1};
5
6 // Place the kernel onto the command queue.
7 status = clEnqueueNDRangeKernel(queue, kernel, 1, NULL,
    indexSpaceSize, workGroupSize, 0, NULL, NULL);
```

There are many arguments; we will cover some later.

Note that `size_t` is an **unsigned integer**.

¹In CUDA: `kernel<<<workGroupSize,indexSpaceSize>>>(...)`.

Copying data between device and host¹

To get the result (device_c) back to the host (host_c), enqueue a read buffer command:

```
1 status = clEnqueueReadBuffer(  
2     qu                                // The command queue  
3     de                                // Device  
4     CL_QUEUE_READ_BUFFER              // Block ID  
5     0,                                // Offset; must be zero.  
6     N*sizeof(float),                 // Data size.  
7     host_c,                           // Host memory.  
8     0, NULL, NULL                     // Events; ignore for now  
9 );
```

Note this is a **blocking** communication call - **it will not return until the copy has finished** — like MPI_Send()/MPI_Recv().

¹In CUDA: cudaMemcpy(..., cudaMemcpyDeviceToHost).

Copying data from host to device¹

If we had not used `CL_MEM_COPY_HOST_PTR` earlier, we would need two calls to `clEnqueueWriteBuffer()`:

```
1 statu = c
2 statu = c
```

- Copies **from** host **to** device.
- `CL_FALSE` used for **non-blocking**
- The device memory **always** come argument list.

¹In CUDA: `cudaMemcpy(..., cudaMemcpyHostToDevice)`.

Work items

Assignment Project Exam Help

Definition

The **work item** is the unit of concurrent execution. It usually

<https://eduassistpro.github.io>

As thr

is (essentially) **no overhead** in launchin

- No problem oversubscribing, i.e. there are physical cores.

Normally issue as many threads as the problem requires.

Work item hierarchy

Assignment Project Exam Help

To remain scalable, the hardware does not allow communication (including synchronisation) between *all* threads at once.

Inste

- <https://eduassistpro.github.io>
- Communication (including synchronisation) only possible **within** a work group.


Add WeChat edu_assist_pr

The full range of all threads is called *n*-dimensional range².

¹ *Threads* and *thread blocks* in CUDA.

² *Grid* in CUDA.

Hierarchy of work items: 2D example



Specifying the n -dimensional range NDRange

The NDRange must be 1, 2 or 3 dimensions

A 2-dimensional example:

```
1 size_ g
2 size_ w
3
4 statu = c
    globalSize,workGroupSize,0,NULL,NULL);
```

- Launches $X*Y$ kernels in total (one per work item)
- In work groups of $8*16$.

OpenCL 2.0 allows X and Y to be arbitrary, but in earlier versions they must be multiples of the work group size (8 and 16 here).

Once in a kernel, can get the **global** indices using

`get_global_id()`. For this 2D example:

```
1 get_global_id(0); // Varies from 0 to X-1 inc.
2 get_global_id(1); // Varies from 0 to Y-1 inc.
```

Similar
`get_`

```
1 get_local_id(0); // Varies from 0 to 7 inc.
2 get_local_id(1); // Varies from 0 to 15 inc.
```

Can also get the number of work items in a group or in the
NDRange using `get_local_size()` and `get_global_size()`:

```
1 get_local_size (1); // Returns 16.
2 get_global_size(0); // Returns X.
```

What group size to use?

Devices have a **maximum work group size** they can support.
This can be determined at run time as follows:

```
1 size_t maxWorkItems;  
2 clGet
```

Note

Other factors may suggest using work group size 1
maximum

- We will look at one of these next time.

Passing NULL as the work group argument lets OpenCL try to
determine a suitable size **automatically**.

Summary and next lecture

Assignment Project Exam Help

Today we have looked at a complete GPGPU solution:



- Group into **work groups**, within which is possible.

Add WeChat edu_assist_pr

Next time we will look at the different memory types on a GPU.