

PROGRAMMING IN HASKELL

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Chapter 6 - Recursive Functions

Introduction

Many functions can naturally be defined in terms of other functions.

Assignment Project Exam Help

```
fac :: Int  
fac n = product [1..n]
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

fac maps any integer n to the product of the integers between 1 and n .

Expressions are evaluated by a stepwise process of applying functions to their arguments.

For example:

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

`fac 4`
=
`product [1..4]`
=
`product [1,2,3,4]`
=
`1*2*3*4`
=
`24`

Recursive Functions

In Haskell, functions can also be defined in terms of themselves. Such functions are called recursive.

Assignment Project Exam Help

```
fac 0 = 1
```

```
fac n = n * fac (n-1)
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

fac maps 0 to 1, and any other integer to the product of itself and the factorial of its predecessor.

Using the definition of fac, we can reason about the result:

$$\begin{aligned} & \text{fac } 3 \\ = & 3 * \text{fac } 2 \\ = & 3 * 2 * \text{fac } 1 \\ = & 3 * 2 * 1 \\ = & 3 * 2 * 1 * 1 \\ = & 6 \end{aligned}$$

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Note:

❓ $\text{fac } 0 = 1$ is appropriate because 1 is the identity for multiplication: $1 * x = x = x * 1$.

❓ The recursive definition diverges on integers < 0 because the base case is never reached:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
> fac (-1)
```

```
Exception: stack overflow
```

Why is Recursion Useful?

❓ Some functions, such as factorial, are simpler to define in terms of other functions.

Assignment Project Exam Help

❓ As we shall see, functions can naturally be defined in terms of themselves.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

❓ Properties of functions defined using recursion can be proved using the simple but powerful mathematical technique of induction.

Recursion on Lists

Recursion is not restricted to numbers, but can also be used to define functions on lists.

Assignment Project Exam Help

```
product      https://eduassistpro.github.io/  
product []   = 1  
product (n:ns) = n * produ
```

Add WeChat edu_assist_pro

product maps the empty list to 1, and any non-empty list to its head multiplied by the product of its tail.

For example:

$$\begin{aligned} & \text{product [2,3,4]} \\ = & 2 * \text{product [3,4]} \\ = & 2 * (3 * \text{product [4]}) \\ = & 2 * (3 * (4 * \text{product []})) \\ = & 2 * (3 * (4 * 1)) \\ = & 24 \end{aligned}$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Using the same pattern of recursion as in product we can define the length function on lists.

length $:: [a] \rightarrow \text{Int}$

length $:: [a] \rightarrow \text{Int}$

Add WeChat edu_assist_pro

length maps the empty list to 0, and any non-empty list to the successor of the length of its tail.

For example:

length [1,2,3]
=
1 + length [2,3]
=
1 + (1 + length [3])
=
1 + (1 + (1 + length []))
=
1 + (1 + (1 + 0))
=
3

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Using a similar pattern of recursion we can define the reverse function on lists.

Assignment Project Exam Help
reverse $:: [a] \rightarrow [a]$
reverse <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

reverse maps the empty list to the empty list, and any non-empty list to the reverse of its tail appended to its head.

For example:

reverse [1,2,3]
=
reverse [2,3] ++ [1]
=
(reverse [3] ++ [2]) ++ [1]
=
((reverse [] ++ [3]) ++ [2]) ++ [1]
=
[3,2,1]

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Multiple Arguments

Functions with more than one argument can also be defined using recursion.
For example:

Assignment Project Exam Help

 Zipping the elements <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
zip      :: [a] → [b] → [(a,b)]  
zip xs ys = ?
```

? Remove the first n elements from a list:

```
drop      :: Int → [a] → [a]
```

```
drop      = ?
```

<https://eduassistpro.github.io/>

? Appending two lists: Add WeChat edu_assist_pro

```
(++)      :: [a] → [a] → [a]
```

```
(++)      = ?
```

Quicksort

The quicksort algorithm for sorting a list of values can be specified by the following two rules:

Assignment Project Exam Help

- ❑ The empty list is all <https://eduassistpro.github.io/>
- ❑ Non-empty lists can be sorted by sorting the head, sorting the tail values $>$ the head, and then appending the resulting lists on either side of the head value.

Using recursion, this specification can be translated directly into an implementation:

```
qsort    :: Ord a => [a] -> [a]
```

```
qsort []  = []
```

```
qsort (x:xs) =
```

```
  qsort small
```

```
  where
```

```
    smaller = [a | a <- xs, a <=
```

```
    larger  = [b | b <- xs, b >
```

Note:

-  This is probably the simplest implementation of quicksort in any programming language!

For example (abbreviating qsort as q):

q [3,2,4,1,5]



Assignment Project Exam Help

q [2,

<https://eduassistpro.github.io/>



Add WeChat edu_assist_pro



q [1]

++ [2] ++

q []

q []

++ [4] ++

q [5]



[1]



[]



[]



[5]

Exercises

- (1) Without looking at the standard prelude, define the following library functions using recursion:

Assignment Project Exam Help

-  Decide if all lo

<https://eduassistpro.github.io/>

 Concatenate a list of lists:

`and :: [Bool] → Bool`

- `concat :: [[a]] → [a]`

? Produce a list with n identical elements:

`replicate :: Int → a → [a]`

Assignment Project Exam Help

? Select the nth element of a list:

<https://eduassistpro.github.io/>

`(!!) :: [a] → Int → a`
Add WeChat edu_assist_pro

? Decide if a value is an element of a list:

`elem :: Eq a ⇒ a → [a] → Bool`

(2) Define a recursive function

```
merge :: Ord a => [a] -> [a] -> [a]
```

Assignment Project Exam Help

that merges two
example:

single sorted list. For

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
> merge [2,5,6] [1,3,4]
```

```
[1,2,3,4,5,6]
```

(3) Define a recursive function

`msort :: Ord a => [a] -> [a]`

Assignment Project Exam Help

that implements _____ ied by the following two rules:

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- ❓ Lists of length ≤ 1 are already sorted;
- ❓ Other lists can be sorted by sorting the two halves and merging the resulting lists.

PROGRAMMING IN HASKELL

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Chapter 5 - List Comprehensions

Set Comprehensions

In mathematics, the comprehension notation can be used to construct new sets from old sets.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

$\{x^2 \mid x \in \{1 \dots 5\}\}$

Add WeChat edu_assist_pro

The set $\{1,4,9,16,25\}$ of all numbers x^2 such that x is an element of the set $\{1 \dots 5\}$.

Lists Comprehensions

In Haskell, a similar comprehension notation can be used to construct new lists from old lists.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

`[x^2 | x ← [1..5]]`

Add WeChat edu_assist_pro

The list [1,4,9,16,25] of all numbers x^2 such that x is an element of the list [1..5].

Note:

- ❓ The expression $x \leftarrow [1..5]$ is called a generator, as it states how to generate values for x .
- ❓ Comprehensions can have multiple generators, separated by commas. For example:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
> [(x,y) | x ← [1,2,3], y ← [4,5]]  
[(1,4),(1,5),(2,4),(2,5),(3,4),(3,5)]
```

- ? Changing the order of the generators changes the order of the elements in the final list:

```
> [(x,y) for y in [4,5], x in [1,2,3]]
```

[(1,4),(2,4),(3,4), (1,5),(2,5),(3,5)]

Add WeChat edu_assist_pro

- ? Multiple generators are like nested loops, with later generators as more deeply nested loops whose variables change value more frequently.

? For example:

```
> [(x,y) | y ← [4,5], x ← [1,2,3]]
```

```
[(1,4),(2,4),(3,4),(1,5),(2,5),(3,5)]
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

$x \leftarrow [1,2,3]$ is the last generator, so the value of the x component of each pair changes most frequently.

Dependant Generators

Later generators can depend on the variables that are introduced by earlier generators.

Assignment Project Exam Help

$[(x,y) \mid x$ <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

The list $[(1,1),(1,2),(1,3),(2,2),(2,3),(3,3)]$
of all pairs of numbers (x,y) such that x,y are elements of the list
 $[1..3]$ and $y \geq x$.

Using a dependant generator we can define the library function that concatenates a list of lists:

```
concat :: [[a]] → [a]  
concat xss = ?
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

For example:

```
> concat [[1,2,3],[4,5],[6]]  
[1,2,3,4,5,6]
```

Guards

List comprehensions can use guards to restrict the values produced by earlier generators.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

`[x | x ← [1`

Add WeChat edu_assist_pro

The list `[2,4,6,8,10]` of all numbers `x` such that `x` is an element of the list `[1..10]` and `x` is even.

Using a guard we can define a function that maps a positive integer to its list of factors:

```
factors :: Int → [Int]
factors n =
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

For example:

```
> factors 15
```

```
[1,3,5,15]
```

Hint: Using `n `mod` x == 0` checks whether the remainder of integer division is 0.

A positive integer is prime if its only factors are 1 and itself. Hence, using factors we can define a function that decides if a number is prime:

```
prime :: Int → Bool  
prime n = ?
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

For example:

Add WeChat edu_assist_pro

```
> prime 15  
False  
  
> prime 7  
True
```

Using a guard we can now define a function that returns the list of all primes up to a given limit:

```
primes :: Int → [Int]
primes n =
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

For example:

```
> primes 40
```

```
[2,3,5,7,11,13,17,19,23,29,31,37]
```

The Zip Function

A useful library function is `zip`, which maps two lists to a list of pairs of their corresponding elements.

Assignment Project Exam Help

`zip :: [a] →` <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

For example:

```
> zip ['a','b','c'] [1,2,3,4]  
[('a',1),('b',2),('c',3)]
```

Using zip we can define a function returns the list of all pairs of adjacent elements from a list:

```
pairs :: [a] → [(a,a)]  
pairs xs = zip xs (tail xs)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

For example:

```
> pairs [1,2,3,4]  
[(1,2),(2,3),(3,4)]
```

Using pairs we can define a function that decides if the elements in a list are sorted:

```
sorted  :: Ord a => [a] → Bool
sorted xs =
  and [x ≤ y
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

For example:

Add WeChat edu_assist_pro

```
> sorted [1,2,3,4]
True

> sorted [1,3,2,4]
False
```

Using zip we can define a function that returns the list of all positions of a value in a list:

```
positions :: Eq a => a -> [a] -> [Int]
positions x
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

For example:

```
> positions 0 [1,0,0,1,0,1,1,0]
[1,2,4,7]
```

String Comprehensions

A string is a sequence of characters enclosed in double quotes. Internally, however, strings are represented as lists of characters.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

"abc" :: String

Means ['a', 'b', 'c'] :: [Char].

Because strings are just special kinds of lists, any polymorphic function that operates on lists can also be applied to strings. For example:

```
> length "abcde"
```

```
5
```

```
> take 3 "abcde"
```

```
"abc"
```

```
> zip "abc" [1,2,3,4]
```

```
[('a',1),('b',2),('c',3)]
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Similarly, list comprehensions can also be used to define functions on strings, such counting how many times a character occurs in a string:

```
count :: Char -> String -> Int
count x xs
  length [x'
```

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

For example:

```
> count 's' "Mississippi"
4
```

Exercises

(1)

A triple (x,y,z) of positive integers is called pythagorean if $x^2 + y^2 = z^2$. Using a list comprehension, define a function

Assignment Project Exam Help

pyths :: <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

that maps an integer n to all such triples with components in $[1..n]$. For example:

```
> pyths 5  
[(3,4,5),(4,3,5)]
```

- (2) A positive integer is perfect if it equals the sum of all of its factors, excluding the number itself. Using a list comprehension, define a function

`perfects = [int for int in range(1, limit) if sum(factors(int)) == int]`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

that returns the list of all perfect numbers up to a given limit. For example:

Add WeChat edu_assist_pro

```
> perfects 500
```

```
[6, 28, 496]
```

- (3) The scalar product of two lists of integers xs and ys of length n is give by the sum of the products of the corresponding integers:

Assignment Project Exam Help

$$\sum_{i=0}^{n-1}$$

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Using a list comprehension, define a function that returns the scalar product of two lists.