

PROGRAMMING IN HASKELL

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Chapter 9 - Interactive Programs


Introduction

To date, we have seen how Haskell can be used to write batch programs that take all their inputs at the start and give all their outputs at the end.


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



However, we would also like to use Haskell to write interactive programs that read from the keyboard and write to the screen, as they are running.



The Problem

Haskell programs are pure mathematical functions:

 Haskell programs have no side effects.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

However, reading from the keyboard and writing to the screen are side effects:

 Interactive programs have side effects.

The Solution

Interactive programs can be written in Haskell by using types to distinguish pure expressions from impure actions that may involve side effects.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

IO a

The type of actions that return a value of type a.

For example:

IO Char

The type of actions that return a character.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

IO ()

Add WeChat Edu_assistpro by side effecting
ac return no result value.


Note:

 () is the type of tuples with no components.

Basic Actions

The standard library provides a number of actions, including the following three primitives:

Assignment Project Exam Help

-  The action `getChar` reads <https://eduassistpro.github.io/> keyboard, echoes it to the screen, and returns the character as its result.
Add WeChat edu_assist_pro

`getChar :: IO Char`

- ? The action `putChar c` writes the character `c` to the screen, and returns no result value:

```
putChar :: Char → IO ()
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- ? The action `return v` simply returns the value `v` without performing any interaction:

```
return :: a → IO a
```


Sequencing

A sequence of actions can be combined as a single composite action using the keyword do.

For example:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
act :: IO (Char,Char)
act = do x ← getChar
        getChar
        y ← getChar
        return (x,y)
```

do-notation again

IO also supports the do-notation and again, similarly to what happened with Parsers, we need to be careful understanding the typing of the \leftarrow

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
act :: IO (Char,Char)
act = do x ← getChar
        char
        getChar
        return (x,y)
```

x :: Char

getChar :: IO Char

Derived Primitives

 Reading a string from the keyboard:

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

```
getLine :: IO String
getLine = do
  x <- getChar
  if x == '\n' then
    return []
  else
    do xs <- getLine
       return (x:xs)
```

? Writing a string to the screen:

```
putStr    :: String → IO ()
```

```
putStr []  = ?
```

```
putStr (x:xs) = ?
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

? Writing a string and moving to a new line:

```
putStrLn  :: String → IO ()
```

```
putStrLn xs = do putStr xs
```

```
putChar '\n'
```

Example

We can now define an action that prompts for a string to be entered and displays its length:

Assignment Project Exam Help

```
strlen :: IO ()
strlen = do putStr "Enter a
            xs ← getLine
            putStr "The string has "
            putStr (show (length xs))
            putStrLn " characters"
```

For example:

```
> strlen
```

```
Enter a string: abcde
```

```
The string h
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Note:

-  Evaluating an action executes its side effects, with the final result value being discarded.

Hangman

Consider the following version of hangman:

- ❑ One player secretly types in a word.
- ❑ The other player tries to guess the word by a sequence of guesses.
- ❑ For each guess, the computer indicates how many letters in the secret word occur in the guess.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

 The game ends when the guess is correct.

We adopt a top down approach to implementing hangman in Haskell, starting as follows:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
hangman :: IO ()
hangman =
  do putStrLn "Think of a word: "
     word ← sgetLine
     putStrLn "Try to guess it:"
     play word
```


The action `getCh` reads a single character from the keyboard, without echoing it to the screen:

```
import System.IO
```

Assignment Project Exam Help

```
getCh :: IO C https://eduassistpro.github.io/
```

```
getCh = do hSetEcho s e Add WeChat edu_assist_pro
```

```
    x ← getChar
```

```
    hSetEcho stdin True
```

```
    return x
```

The action sgetline reads a line of text from the keyboard, echoing each character as a dash:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

```
sgetline :: IO String  
sgeline = ?
```

Add WeChat edu_assist_pro

The function `match` indicates which characters in one string occur in a second string:

```
match :: String → String → String
```

```
match xs ys = ?
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

For example:

```
> match "haskell" "pascal"
```

```
"-as--ll"
```

The function `play` is the main loop, which requests and processes guesses until the game ends.

Assignment Project Exam Help

```
play :: String → IO ()  
play word =  
  ?
```

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Exercise

Implement the game of nim in Haskell, where the rules of the game are as follows:

Assignment Project Exam Help

 The board comprises five <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
1: * * * * *
2: * * * *
3: * * *
4: * *
5: *
```

- ❓ Two players take it turn about to remove one or more stars from the end of a single row.
- ❓ The winner is the player who removes the last star or stars from the board.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Hint:

Represent the board as a list of five integers that give the number of stars remaining on each row. For example, the initial board is [5,4,3,2,1].