

PROGRAMMING IN HASKELL

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Chapter 3 - Types and Classes
(Original slides by Graham Hutton)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

What is a Type?

A type is a name for a collection of related values. For example, in Haskell the basic type

Assignment Project Exam Help

Bool

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

contains the two logical values:

False

True

Type Errors

Applying a function to one or more arguments of the wrong type is called a type error.

Assignment Project Exam Help

```
> 1 + Fals  
Error
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

1 is a number and False is a logical value, but + requires two numbers.

Types in Haskell

? If evaluating an expression e would produce a value of type t , then e has type t , written

Assignment Project Exam Help

$e :: t$

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

? Every well formed expression has a type, which can be automatically calculated at compile time using a process called type inference.

- ❓ All type errors are found at compile time, which makes programs safer and faster by removing the need for type checks at run time.
- ❓ In GHCi, the `:type` command calculates the type of an expression, without evaluating it:

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
> not False  
True
```

```
> :type not False  
not False :: Bool
```

Basic Types

Haskell has a number of basic types, including:

Bool

Assignment Project Exam Help
- logical values

Char

<https://eduassistpro.github.io/>

String

Add WeChat edu_assist_pro
- strings of chara

Int

- fixed-precision integers

Integer

- arbitrary-precision integers

Float

- floating-point numbers

List Types

A list is sequence of values of the same type:

```
[False, True, False] :: [Bool]
```

```
['a', 'b', 'c', 'd'] :: [Char]
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

In general:

[t] is the type of lists with elements of type t.

Note:

- ❓ The type of a list says nothing about its length:

```
[False, True] :: [Bool]
```

```
[False, True]
```

Add WeChat edu_assist_pro

- ❓ The type of the elements is unrestricted. For example, we can have lists of lists:

```
[['a'], ['b', 'c']] :: [[Char]]
```

Note:

 Strings in Haskell are just lists of characters!

Assignment Project Exam Help
`['a'],['b','c'] :: [[Char]]`

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

is equivalent to:

`["a","bc"] :: [String]`

Tuple Types

A tuple is a sequence of values of different types:

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

```
(False, True) :: (Bool, Bool)  
(False, 'a', True) :: (Bool, Char, Bool)
```

In general:

(t_1, t_2, \dots, t_n) is the type of n -tuples whose i th components have type t_i for any i in $1 \dots n$.

Note:

 The type of a tuple encodes its size:

```
(False, True) :: (Bool, Bool)
```

```
(False, True, https://eduassistpro.github.io/)
```

 The type of the component [Add WeChat edu_assist_pro](https://eduassistpro.github.io/) is restricted:

```
('a', (False, 'b')) :: (Char, (Bool, Char))
```

```
(True, ['a', 'b']) :: (Bool, [Char])
```

Function Types

A function is a mapping from values of one type to values of another type:

Assignment Project Exam Help

```
not :: Bool
```

<https://eduassistpro.github.io/>

```
isDigit :: Char → Bool
```

Add WeChat edu_assist_pro

In general:

$t1 \rightarrow t2$ is the type of functions that map values of type $t1$ to values to type $t2$.

Note:

- ❓ The arrow \rightarrow is typed at the keyboard as `->`.
- ❓ The argument and result types are unrestricted. For example, functions with multiple arguments or results are possible

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
add      :: (Int,Int) → Int
```

```
add (x,y) = x+y
```

```
zeroto   :: Int → [Int]
```

```
zeroto n = [0..n]
```

Curried Functions

Functions with multiple arguments are also possible by returning functions as results:

Assignment Project Exam Help

```
add' :: Int -> Int -> Int
add' x y = x+y
```

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

add' takes an integer x and returns a function add' x. In turn, this function takes an integer y and returns the result x+y.

Note:

- ❓ add and add' produce the same final result, but add takes its two arguments at the same time, whereas add' takes them one at a time:

Assignment Project Exam Help

```
add :: (Int -> Int -> Int)
add' :: Int -> (Int -> Int)
```

- ❓ Functions that take their arguments one at a time are called curried functions, celebrating the work of Haskell Curry on such functions.

- ❓ Functions with more than two arguments can be carried by returning nested functions:

```
mult    :: Int → (Int → (Int → Int))  
mult x y z = x*
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

mult takes an integer x and returns a function mult x , which in turn takes an integer y and returns a function mult x y , which finally takes an integer z and returns the result $x*y*z$.

Why is Currying Useful?

Curried functions are more flexible than functions on tuples, because useful functions can often be made by partially applying a curried function.

Assignment Project Exam Help

For example: <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
add' 1 :: Int → Int
```

```
take 5 :: [Int] → [Int]
```

```
drop 5 :: [Int] → [Int]
```

Currying Conventions

To avoid excess parentheses when using curried functions, two simple conventions are adopted:

Assignment Project Exam Help

 The arrow <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

$\text{Int} \rightarrow \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$

Means $\text{Int} \rightarrow (\text{Int} \rightarrow (\text{Int} \rightarrow \text{Int}))$.

❓ As a consequence, it is then natural for function application to associate to the left.

`mult x y z`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Means `((mult x) y) z`.

Unless tupling is explicitly required, all functions in Haskell are normally defined in curried form.

Polymorphic Functions

A function is called polymorphic (“of many forms”) if its type contains one or more type variables.

Assignment Project Exam Help

length :: [<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

for any type a , length takes a list of values of type a and returns an integer.

Note:

- ❓ Type variables can be instantiated to different types in different circumstances:

Assignment Project Exam Help

```
> length
2
```

<https://eduassistpro.github.io/> a = Bool

Add WeChat edu_assist_pro

```
> length [1,2,3,4]
4
```

a = Int

- ❓ Type variables must begin with a lower-case letter, and are usually named a, b, c, etc.

- ❓ Many of the functions defined in the standard prelude are polymorphic. For example:

```
fst :: (a,b) → a
```

Assignment Project Exam Help

```
head :: [
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
take :: Int → [a] → [a]
```

```
zip :: [a] → [b] → [(a,b)]
```

```
id :: a → a
```

What's the type of sum?

What should be the type of sum (the function that sums a list of numbers)?

Assignment Project Exam Help

sum :: [a] ->

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

We should be able to use sum s types of numbers:

```
sum [1,2,3]    -> 6
sum [1.5,2.3]  -> 3.8
```


Overloaded Functions

A polymorphic function is called overloaded if its type contains one or more class constraints.

Assignment Project Exam Help

sum :: Num => [a] -> a <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

for any numeric type a, sum takes a list of values of type a and returns a value of type a.

Note:

- ❓ Constrained type variables can be instantiated to any types that satisfy the constraints:

Assignment Project Exam Help

```
> sum [1, 6]
6
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
> sum [1.1, 2.2, 3.3]
6.6
```

```
> sum ['a', 'b', 'c']
ERROR
```

a = Int

a = Float

Char is not a numeric type

? Haskell has a number of type classes, including:

Num - Numeric types

Eq - Equality types

Ord - \leq <https://eduassistpro.github.io/>

? For example: [Add WeChat edu_assist_pro](#)

```
(+) :: Num a => a -> a -> a
```

```
(==) :: Eq a => a -> a -> Bool
```

```
(<) :: Ord a => a -> a -> Bool
```

Hints and Tips

- ❓ When defining a new function in Haskell, it is useful to begin by writing down its type;

Assignment Project Exam Help

- ❓ Within a script, you can use the `typeOf` function to state the type of an expression.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

- ❓ When stating the types of polymorphic functions that use numbers, equality or orderings, take care to include the necessary class constraints.

Exercises

(1) What are the types of the following values?

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

```
['a','b',  
( 'a','b','c')  
[(False,'0'),(True,'1')]  
[(False,True),['0','1']]  
[tail,init,reverse]
```

(2) What are the types of the following functions?

```
second xs    = head (tail xs)
```

```
swap (x,y)   = (y,x)
```

```
pair x y
```

```
double x     = x*2
```

```
palindrome xs = reverse xs == xs
```

```
twice f x    = f (f x)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

(3) Check your answers using GHCi.

PROGRAMMING IN HASKELL

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Chapter 4 - Defining Functions

Conditional Expressions

As in most programming languages, functions can be defined using conditional expressions.

Assignment Project Exam Help

```
abs :: Int  
abs n = if n >= 0 then n else -n
```

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

abs takes an integer n and returns n if it is non-negative and $-n$ otherwise.

Conditional expressions can be nested:

```
signum :: Int → Int  
signum n = if n < 0 then -1 else
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Note:

- ❓ In Haskell, conditional expressions must always have an else branch, which avoids any possible ambiguity problems with nested conditionals.

Guarded Equations

As an alternative to conditionals, functions can also be defined using guarded equations.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

```
abs n | n ≥
```

```
    | otherwise = -n
```

Add WeChat edu_assist_pro

As previously, but using guarded equations.


Guarded equations can be used to make definitions involving multiple conditions easier to read:

Assignment Project Exam Help
signum n

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Note:

 The catch all condition otherwise is defined in the prelude by `otherwise = True`.

Pattern Matching

Many functions have a particularly clear definition using pattern matching on their arguments.

Assignment Project Exam Help

```
not :: B  
not False = True  
not True  = False
```

not maps False to True, and True to False.

Functions can often be defined in many different ways using pattern matching. For example

($\&\&$) [Assignment Project Exam Help](https://eduassistpro.github.io/)

($\&\&$) = ?

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

can be defined more compactly by


?

However, the following definition is more efficient, because it avoids evaluating the second argument if the first argument is False:

Assignment Project Exam Help
True && b
False && <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Note:

 The underscore symbol `_` is a wildcard pattern that matches any argument value.

 Patterns are matched in order. For example, the following definition always returns False:

```
_ && _ = False  
True && True = True
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

 Patterns may not repeat variables. For example, the following definition gives an error:

```
b && b = b  
_ && _ = False
```

List Patterns

Internally, every non-empty list is constructed by repeated use of an operator (:) called “cons” that adds an element to the start of a list.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

[1,2,3,4] Add WeChat edu_assist_pro

Means 1:(2:(3:(4:[]))).

Functions on lists can be defined using x:xs patterns.

```
head    :: [a] → a
```

```
head (x_)
```

```
tail    ::
```

```
tail = ?
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

head and tail map any non-empty list to its first and remaining elements.

Note:

 `x:xs` patterns only match non-empty lists:

```
> head []  
Error
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

 `x:xs` patterns must be pare because
application has priority over `(:)`. For example, the
following definition gives an error:

```
head x:_ = x
```

Lambda Expressions

Functions can be constructed without naming the functions by using lambda expressions.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

$\lambda x \rightarrow x+x$

Add WeChat edu_assist_pro

the nameless function that takes a number x and returns the result $x+x$.

Note:

❓ The symbol λ is the Greek letter lambda, and is typed at the keyboard as a backslash \.

Assignment Project Exam Help

❓ In mathematics, λ are usually denoted using <https://eduassistpro.github.io/> ❓ $x + x$.

Add WeChat edu_assist_pro

❓ In Haskell, the use of the λ nameless functions comes from the lambda calculus, the theory of functions on which Haskell is based.

Why Are Lambda's Useful?

Lambda expressions can be used to give a formal meaning to functions defined using currying.

Assignment Project Exam Help

For example:

<https://eduassistpro.github.io/>

add x y = x+y

Add WeChat edu_assist_pro

means

$\text{add} = \lambda x \rightarrow (\lambda y \rightarrow x+y)$

Lambda expressions are also useful when defining functions that return functions as results.

For example:

Assignment Project Exam Help

```
const ::  
const x _
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

is more naturally defined by

```
const :: a → (b → a)  
const x = λ_ → x
```

Lambda expressions can be used to avoid naming functions that are only referenced once.

For example:

Assignment Project Exam Help

```
odds n =
```

```
  where
```

```
    f x = x*2 + 1
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

can be simplified to

```
odds n = map ( $\lambda x \rightarrow x*2 + 1$ ) [0..n-1]
```

Sections

An operator written between its two arguments can be converted into a curried function written before its two arguments by [Assigning Project Exam Help](https://eduassistpro.github.io/)

For example: <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
> 1+2
```

```
3
```

```
> (+) 1 2
```

```
3
```


This convention also allows one of the arguments of the operator to be included in the parentheses.

For example:

Assignment Project Exam Help

```
> (1+) 2
3
> (+2) 1
3
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

In general, if \oplus is an operator then functions of the form (\oplus) , $(x\oplus)$ and $(\oplus y)$ are called sections.

Why Are Sections Useful?

Useful functions can sometimes be constructed in a simple way using sections. For example:

Assignment Project Exam Help

(1+) <https://eduassistpro.github.io/>

(1/) **Add WeChat edu_assist_pro**
- reciprocation fun

(*2) - doubling function

(/2) - halving function

Exercises

- (1) Consider a function safetail that behaves in the same way as tail, except that safetail maps the empty list to the empty list, whereas tail gives an error in this case. Define safetail using:

- (a) a conditional expression;
- (b) guarded equ
- (c) pattern match

Hint: the library function `null :: [a] -> Bool` is used to test if a list is empty.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- (2) Give three possible definitions for the logical or operator (||) using pattern matching.
- (3) Redefine the following version of (&&) using conditionals rather than patterns:

Assignment Project Exam Help

```
True && https://eduassistpro.github.io/  
_ && _ = False
```

Add WeChat edu_assist_pro

- (4) Do the same for the following version:

```
True && b = b  
False && _ = False
```