

gridworld.py ([original](#))

```
# gridworld.py
# -----
# Licensing Information: Please do not distribute or publish solutions to this
# project. You are free to use and extend these projects for educational
# purposes. The Pacman AI projects were developed at UC Berkeley, primarily by
# John DeNero (denero@cs.berkeley.edu) and Dan Klein (klein@cs.berkeley.edu).
# For more info, see http://inst.eecs.berkeley.edu/~cs188/sp09/pacman.html

import random
import sys
import mdp
import environment
import util
import optparse

class Gridworld(mdp.MarkovDecisionProcess):
    """
    Gridworld
    """
    def __init__(self, grid):
        # layout
        if type(grid) == type([]): grid = makeGrid(grid)
        self.grid = grid

        # parameters
        self.livingReward = 1.0
        self.noise = 0.2

    def setLivingReward(self, reward):
        """
        The (negative)

        Note that in the R+N text, this reward is
        a state and therefore is not clearly par
        future rewards.
        """
        self.livingReward = reward

    def setNoise(self, noise):
        """
        The probability of moving in an unintended direction.
        """
        self.noise = noise

    def getPossibleActions(self, state):
        """
        Returns list of valid actions for 'state'.

        Note that you can request moves into walls and
        that "exit" states transition to the terminal
        state under the special action "done".
        """
        if state == self.grid.terminalState:
            return ()
        x,y = state
        if type(self.grid[x][y]) == int:
            return ('exit',)
        return ('north', 'west', 'south', 'east')

    def getStates(self):
        """
        Return list of all states.
        """
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

```

# The true terminal state.
states = [self.grid.terminalState]
for x in range(self.grid.width):
    for y in range(self.grid.height):
        if self.grid[x][y] != '#':
            state = (x,y)
            states.append(state)
return states

def getReward(self, state, action, nextState):
    """
    Get reward for state, action, nextState transition.

    Note that the reward depends only on the state being
    departed (as in the R+N book examples, which more or
    less use this convention).
    """
    if state == self.grid.terminalState:
        return 0.0
    x, y = state
    cell = self.grid[x][y]
    if type(cell) == int or type(cell) == float:
        return cell
    return self.livingReward

def getStartState(self):
    for x in range(self.grid.width):
        for y in range(self.grid.height):
            if self.grid[x][y] == 'S':
                return (x,y)
    raise "Grid has no start state"

def isTerminal(s):
    """
    Only the TERMINAL state is terminal.
    The other "exit" state is not terminal.
    a single action "exit" which leads to the terminal state.
    This convention is to make the grids linear in the R+N textbook.
    """
    return state == self.grid.terminalState

def getTransitionStatesAndProbs(self, state, action):
    """
    Returns list of (nextState, prob) pairs
    representing the states reachable
    from 'state' by taking 'action' along
    with their transition probabilities.
    """

    if action not in self.getPossibleActions(state):
        raise "Illegal action!"

    if self.isTerminal(state):
        return []

    x, y = state

    if type(self.grid[x][y]) == int or type(self.grid[x][y]) == float:
        termState = self.grid.terminalState
        return [(termState, 1.0)]

    successors = []

    northState = (self.__isAllowed(y+1,x) and (x,y+1)) or state
    westState = (self.__isAllowed(y,x-1) and (x-1,y)) or state
    southState = (self.__isAllowed(y-1,x) and (x,y-1)) or state
    eastState = (self.__isAllowed(y,x+1) and (x+1,y)) or state

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```

if action == 'north' or action == 'south':
    if action == 'north':
        successors.append((northState, 1-self.noise))
    else:
        successors.append((southState, 1-self.noise))

    massLeft = self.noise
    successors.append((westState, massLeft/2.0))
    successors.append((eastState, massLeft/2.0))

if action == 'west' or action == 'east':
    if action == 'west':
        successors.append((westState, 1-self.noise))
    else:
        successors.append((eastState, 1-self.noise))

    massLeft = self.noise
    successors.append((northState, massLeft/2.0))
    successors.append((southState, massLeft/2.0))

successors = self.__aggregate(successors)

return successors

def __aggregate(self, statesAndProbs):
    counter = util.Counter()
    for state, prob in statesAndProbs:
        counter[state] += prob
    newStatesAndProbs = []
    for state, prob in counter.items():
        newStatesAndProbs.append((state, prob))
    return newStatesAndProbs

def __isAllowed(self, x, y):
    if y < 0 or y >= self.gridWorld.height: return False
    if x < 0 or x >= self.gridWorld.width: return False
    return self.gridWorld.grid[x][y] != '#'

class GridworldEnvironment(environment.Environment):

    def __init__(self, gridWorld):
        self.gridWorld = gridWorld
        self.reset()

    def getCurrentState(self):
        return self.state

    def getPossibleActions(self, state):
        return self.gridWorld.getPossibleActions(state)

    def doAction(self, action):
        successors = self.gridWorld.getTransitionStatesAndProbs(self.state, action)
        sum = 0.0
        rand = random.random()
        state = self.getCurrentState()
        for nextState, prob in successors:
            sum += prob
            if sum > 1.0:
                raise 'Total transition probability more than one; sample failure.'
            if rand < sum:
                reward = self.gridWorld.getReward(state, action, nextState)
                self.state = nextState
                return (nextState, reward)
        raise 'Total transition probability less than one; sample failure.'

    def reset(self):
        self.state = self.gridWorld.getStartState()

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```

class Grid:
    """
    A 2-dimensional array of immutables backed by a list of lists. Data is accessed
    via grid[x][y] where (x,y) are cartesian coordinates with x horizontal,
    y vertical and the origin (0,0) in the bottom left corner.

    The __str__ method constructs an output that is oriented appropriately.
    """
    def __init__(self, width, height, initialValue=' '):
        self.width = width
        self.height = height
        self.data = [[initialValue for y in range(height)] for x in range(width)]
        self.terminalState = 'TERMINAL_STATE'

    def __getitem__(self, i):
        return self.data[i]

    def __setitem__(self, key, item):
        self.data[key] = item

    def __eq__(self, other):
        if other == None: return False
        return self.data == other.data

    def __hash__(self):
        return hash(self.data)

    def copy(self):
        g = Grid(self.width, self.height)
        g.data = [x[:] for x in self.data]
        return g

    def deepCopy(self):
        return self.co

    def shallowCopy(self):
        g = Grid(self.width, self.height)
        g.data = self.data
        return g

    def _getLegacyText(self):
        t = [[self.data[x][y] for x in range(self.width)] for y in range(self.height)]
        t.reverse()
        return t

    def __str__(self):
        return str(self._getLegacyText())

def makeGrid(gridString):
    width, height = len(gridString[0]), len(gridString)
    grid = Grid(width, height)
    for ybar, line in enumerate(gridString):
        y = height - ybar - 1
        for x, el in enumerate(line):
            grid[x][y] = el
    return grid

def getCliffGrid():
    grid = [[ ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' '],
             ['S', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', 10],
             [-100, -100, -100, -100, -100, -100, -100, -100, -100, -100]]
    return Gridworld(makeGrid(grid))

def getCliffGrid2():
    grid = [[ ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' '],
             [8, 'S', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', 10],
             [-100, -100, -100, -100, -100, -100, -100, -100, -100, -100]]
    return Gridworld(grid)

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```

def getDiscountGrid():
    grid = [[[' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' '],
              [' ', ' ', '#', ' ', ' ', ' ', ' ', ' ', ' ', ' '],
              [' ', ' ', '#', ' ', '1', '#', ' ', '10', ' ', ' '],
              ['S', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' '],
              [-10, -10, -10, -10, -10, -10, -10, -10, -10, -10]]
    return Gridworld(grid)

def getBridgeGrid():
    grid = [[['#', -100, -100, -100, -100, -100, -100, '#'],
              [1, 'S', ' ', ' ', ' ', ' ', ' ', '10'],
              ['#', -100, -100, -100, -100, -100, -100, '#']]
    return Gridworld(grid)

def getBookGrid():
    grid = [[[' ', ' ', ' ', ' ', ' ', '+1'],
              [' ', ' ', '#', ' ', ' ', -1],
              ['S', ' ', ' ', ' ', ' ', ' ']]
    return Gridworld(grid)

def getMazeGrid():
    grid = [[[' ', ' ', ' ', ' ', ' ', '+1'],
              ['#', '#', ' ', ' ', '#'],
              [' ', '#', ' ', ' ', ' '],
              [' ', ' ', '#', '#', ' '],
              ['S', ' ', ' ', ' ', ' ']]
    return Gridworld(grid)

```

Assignment Project Exam Help

```

def getUserAction(state, actionFunction):
    """
    Get an action fr
    Used for debuggi
    """

```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```

import graphicsUtils
action = None
while True:
    keys = graphicsUtils.wait_for_keys()
    if 'Up' in keys: action = 'north'
    if 'Down' in keys: action = 'south'
    if 'Left' in keys: action = 'west'
    if 'Right' in keys: action = 'east'
    if 'q' in keys: sys.exit(0)
    if action == None: continue
    break
actions = actionFunction(state)
if action not in actions:
    action = actions[0]
return action

def printString(x): print x

def runEpisode(agent, environment, discount, decision, display, message, pause,
episode):
    returns = 0
    totalDiscount = 1.0
    environment.reset()
    if 'startEpisode' in dir(agent): agent.startEpisode()
    message("BEGINNING EPISODE: "+str(episode)+"\n")
    while True:

        # DISPLAY CURRENT STATE
        state = environment.getCurrentState()
        display(state)
        pause()

        # END IF IN A TERMINAL STATE

```

```

actions = environment.getPossibleActions(state)
if len(actions) == 0:
    message("EPISODE "+str(episode)+" COMPLETE: RETURN WAS "+str(returns)+"\n")
    return returns

# GET ACTION (USUALLY FROM AGENT)
action = decision(state)
if action == None:
    raise 'Error: Agent returned None action'

# EXECUTE ACTION
nextState, reward = environment.doAction(action)
message("Started in state: "+str(state)+
        "\nTook action: "+str(action)+
        "\nEnded in state: "+str(nextState)+
        "\nGot reward: "+str(reward)+"\n")

# UPDATE LEARNER
if 'observeTransition' in dir(agent):
    agent.observeTransition(state, action, nextState, reward)

returns += reward * totalDiscount
totalDiscount *= discount

if 'stopEpisode' in dir(agent):
    agent.stopEpisode()

def parseOptions():
    optParser = optparse.OptionParser()
    optParser.add_option('-d', '--discount', action='store',
                        type='float', dest='discount', default=0.9,
                        help='Discount on future (default %default)')
    optParser.add_option('-r', '--livingReward', action='store',
                        type='float', dest='livingReward', default=0.0,
                        help='Reward for a time step (default %default)')
    optParser.add_option('-e', '--epsilon', action='store',
                        type='float', dest='epsilon', default=0.3,
                        metavar="E", help='Chance of taking a random action in q-
learning (default %default)')
    optParser.add_option('-l', '--learningRate', action='store',
                        type='float', dest='learningRate', default=0.5,
                        metavar="P", help='TD learning rate (default %default)')
    optParser.add_option('-i', '--iterations', action='store',
                        type='int', dest='iters', default=10,
                        metavar="K", help='Number of rounds of value iteration
(default %default)')
    optParser.add_option('-k', '--episodes', action='store',
                        type='int', dest='episodes', default=1,
                        metavar="K", help='Number of epsiodes of the MDP to run
(default %default)')
    optParser.add_option('-g', '--grid', action='store',
                        metavar="G", type='string', dest='grid', default="BookGrid",
                        help='Grid to use (case sensitive; options are BookGrid,
BridgeGrid, CliffGrid, MazeGrid, default %default)')
    optParser.add_option('-w', '--windowSize', metavar="X",
                        type='int', dest='gridSize', default=150,
                        help='Request a window width of X pixels *per grid cell*
(default %default)')
    optParser.add_option('-a', '--agent', action='store', metavar="A",
                        type='string', dest='agent', default="random",
                        help='Agent type (options are \'random\', \'value\'
and \'q\', default %default)')
    optParser.add_option('-t', '--text', action='store_true',
                        dest='textDisplay', default=False,
                        help='Use text-only ASCII display')

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](https://eduassistpro.github.io/)

```

optParser.add_option('-p', '--pause', action='store_true',
                    dest='pause', default=False,
                    help='Pause GUI after each time step when running the MDP')
optParser.add_option('-q', '--quiet', action='store_true',
                    dest='quiet', default=False,
                    help='Skip display of any learning episodes')
optParser.add_option('-s', '--speed', action='store', metavar="S", type=float,
                    dest='speed', default=1.0,
                    help='Speed of animation, S > 1.0 is faster, 0.0 < S < 1.0
is slower (default %default)')
optParser.add_option('-m', '--manual', action='store_true',
                    dest='manual', default=False,
                    help='Manually control agent')
optParser.add_option('-v', '--valueSteps', action='store_true', default=False,
                    help='Display each step of value iteration')

opts, args = optParser.parse_args()

if opts.manual and opts.agent != 'q':
    print '## Disabling Agents in Manual Mode (-m) ##'
    opts.agent = None

# MANAGE CONFLICTS
if opts.textDisplay or opts.quiet:
    # if opts.quiet:
    opts.pause = False
    # opts.manual = False

if opts.manual:
    opts.pause = True

return opts

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

```

if __name__ == '__main__':
    opts = parseOptions()

    #####
    # GET THE GRIDWORLD
    #####

    import gridworld
    mdpFunction = getattr(gridworld, "get"+opts.grid)
    mdp = mdpFunction()
    mdp.setLivingReward(opts.livingReward)
    mdp.setNoise(opts.noise)
    env = gridworld.GridworldEnvironment(mdp)

    #####
    # GET THE DISPLAY ADAPTER
    #####

    import textGridworldDisplay
    display = textGridworldDisplay.TextGridworldDisplay(mdp)
    if not opts.textDisplay:
        import graphicsGridworldDisplay
        display = graphicsGridworldDisplay.GraphicsGridworldDisplay(mdp, opts.gridSize,
opts.speed)
    display.start()

    #####
    # GET THE AGENT
    #####

    import valueIterationAgents, qlearningAgents
    a = None
    if opts.agent == 'value':

```

Add WeChat edu_assist_pro

```

a = valueIterationAgents.ValueIterationAgent(mdp, opts.discount, opts.itsers)
elif opts.agent == 'q':
    #env.getPossibleActions, opts.discount, opts.learningRate, opts.epsilon
    #simulationFn = lambda agent, state:
simulation.GridworldSimulation(agent, state, mdp)
gridWorldEnv = GridworldEnvironment(mdp)
actionFn = lambda state: mdp.getPossibleActions(state)
qLearnOpts = {'gamma': opts.discount,
               'alpha': opts.learningRate,
               'epsilon': opts.epsilon,
               'actionFn': actionFn}
a = qlearningAgents.QLearningAgent(**qLearnOpts)
elif opts.agent == 'random':
    # # No reason to use the random agent without episodes
    if opts.episodes == 0:
        opts.episodes = 10
    class RandomAgent:
        def getAction(self, state):
            return random.choice(mdp.getPossibleActions(state))
        def getValue(self, state):
            return 0.0
        def getQValue(self, state, action):
            return 0.0
        def getPolicy(self, state):
            "NOTE: 'random' is a special policy value; don't use it in your code."
            return 'random'
        def update(self, state, action, nextState, reward):
            pass
    a = RandomAgent()
else:
    if not opts.manual: raise "Unknown agent type: "+opts.agent

#####
# RUN EPISODES
#####
# DISPLAY Q/V VALUES BEFORE SIMULATION OF
if not opts.manual and opts.agent == 'valu
    if opts.valueSteps:
        for i in range(opts.itsers):
            tempAgent = valueIterationAgents.ValueIterationAgent(mdp, opts.discount, i)
            display.displayValues(tempAgent, message = "VALUES AFTER "+str(i)+"
ITERATIONS")
            display.pause()

            display.displayValues(a, message = "VALUES AFTER "+str(opts.itsers)+" ITERATIONS")
            display.pause()
            display.displayQValues(a, message = "Q-VALUES AFTER "+str(opts.itsers)+"
ITERATIONS")
            display.pause()

# FIGURE OUT WHAT TO DISPLAY EACH TIME STEP (IF ANYTHING)
displayCallback = lambda x: None
if not opts.quiet:
    if opts.manual and opts.agent == None:
        displayCallback = lambda state: display.displayNullValues(state)
    else:
        if opts.agent == 'random': displayCallback = lambda state:
display.displayValues(a, state, "CURRENT VALUES")
        if opts.agent == 'value': displayCallback = lambda state:
display.displayValues(a, state, "CURRENT VALUES")
        if opts.agent == 'q': displayCallback = lambda state: display.displayQValues(a,
state, "CURRENT Q-VALUES")

messageCallback = lambda x: printString(x)
if opts.quiet:
    messageCallback = lambda x: None

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


```

# FIGURE OUT WHETHER TO WAIT FOR A KEY PRESS AFTER EACH TIME STEP
pauseCallback = lambda : None
if opts.pause:
    pauseCallback = lambda : display.pause()

# FIGURE OUT WHETHER THE USER WANTS MANUAL CONTROL (FOR DEBUGGING AND DEMOS)
if opts.manual:
    decisionCallback = lambda state : getUserAction(state, mdp.getPossibleActions)
else:
    decisionCallback = a.getAction

# RUN EPISODES
if opts.episodes > 0:
    print
    print "RUNNING", opts.episodes, "EPISODES"
    print
    returns = 0
    for episode in range(1, opts.episodes+1):
        returns += runEpisode(a, env, opts.discount, decisionCallback, displayCallback,
messageCallback, pauseCallback, episode)
    if opts.episodes > 0:
        print
        print "AVERAGE RETURNS FROM START STATE: "+str((returns+0.0) / opts.episodes)
        print
        print

# DISPLAY POST-LEARNING VALUES / Q-VALUES
if opts.agent == 'q' and not opts.manual:
    display.displayQValues(a, message = "Q-VALUES AFTER "+str(opts.episodes)+"
EPISODES")
    display.pause()
    display.displayQValues(a, message = "Q-VALUES AFTER "+str(opts.episodes)+"
EPISODES")
    display.pause(

```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro