
COMP90007 Internet Technologies

Week 7 Workshop

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Semester 2, 2021

Suggested solutions

Question 1

What are the benefits and disadvantages of Transparent fragmentation in Network Layer?

Assignment Project Exam Help

Ans. Good design parameters for transparent fragmentation within each network. Transparent fragmentation does not have problems. For one thing, the exit router must fragment the pieces, so either a count field or an “end of packet” bit must be provided. Because all packets must exit via the same router so that they can be reassembled, routes are constrained. By not allowing some fragments to follow one route to the ultimate destination and other fragments a disjoint route, some performance may be lost. More significant is the amount of work that the router may have to do. It may need to buffer the fragments as they arrive, and decide when to throw them away if not all of the fragments arrive. Some of this work may be wasteful, too, as the packet may pass through a series of small packet networks and need to be repeatedly fragmented and reassembled.

Question 2

Convert the IP address 11000001, 01010010, 11010010, 00001111 to dotted decimal notation.

Assignment Project Exam Help

Ans. 193.82.210. <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Question 3

Convert the IP address 240.68.10.10 to binary format
Use the following key:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Ans. 1111 0000 . 0100 0100 . 0000 1010 . 0000 1010

Question 4

A network on the Internet has a subnet mask of 255.255.240.0. What is the maximum number of hosts that it can handle?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Answer:

255.255.240.0 in binary is 11111111 11111111 11111111 11110000 00000000

The mask is 20 bits long, so the network part is 20 bits. The remaining 12 bits are for the host, so 4096 host addresses exist.

Question 5

IPv6 uses 16 bytes addresses. If a block of 1 million addresses is allocated every picosecond, how long will the addresses last?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Answer:

With 16 bytes there are 2^{128} or addresses. If allocated at a rate of $10^6 / 10^{-12} = 10^{18}$ addresses per second. Then $2^{128} / 10^{18} \approx 3.4 \times 10^{20}$ seconds to run out of IP addresses, which is about 10^{13} years.

This number is 1000 times the age of the universe. Of course, the address space is not flat, so they are not allocated linearly, but this calculation shows that even with an allocation scheme that has an efficiency of 1/1000 (0.1 percent), one will never run out.

Question 6

A router has an entry in its table that can be represented with mask as 135.46.56.0/21. What is the maximum number of hosts that this network can represent?

Assignment Project Exam Help

Ans. 21 bits means 21 bits are reserved, and remaining 11 bits are for hosts.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Hence maximum number of hosts = $2^{11} = 2048$

Question 7

- A router has the following entries in its routing table:

<u>Prefix</u>	<u>Next hop</u>
151.46.184.0/22	Interface 0
151.46.188.0/22	Interface 1
151.53.40.0/23	Router 1
default	

For each of the following
with that address arrives?

(a) 151.46.191.10

⇒ Interface 1

(b) 151.46.187.2

⇒ Interface 0

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

the router do If a packet