



THE UNIVERSITY OF
MELBOURNE

COMP90038

Algorithms and Complexity

Assignment Project Exam Help

Lecture 3: Growth of Algorithm Efficiency
(with thanks to Hara Ergaard)

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Toby Murray



toby.murray@unimelb.edu.au



DMD 8.17 (Level 8, Doug McDonnell Bldg)



<http://people.eng.unimelb.edu.au/tobym>



@tobycmurray

Update

- Compulsory Quizzes (first one closes Tuesday Week 3)
- Tutorials start this week
- Background knowledge catch-up tutorials:
 - Weeks 2 and 3 <https://eduassistpro.github.io/>
 - Thursday 1-2pm and 2:15-
Alice Hoy, Room 101
- Consultation Hours
- Discussion Board

Algorithm Efficiency

Two **algorithms** for computing gcd:

```
def gcd(m,n):  
    while n != 0:  
        r = m % n;  
        m = n;  
        n = r;  
    return m;
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Why is one more efficient than the other?

What does “efficient” even mean?

How can we talk about these things precisely?

Linear Search Example

A: Y x: 7 n: 7 j: 0

function find(A,x,n)

 j ← 0

while j < n

if A[j] = x

return j

 j ← j+1

return -1

A[j]

Assignment Project Exam Help

↓
Y <https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Let's trace the execution of find(Y,7,7)

(returns 4)

Linear Search Example

```
function find(A,x,n)
```

```
  j ← 0
```

```
  while j < n
```

```
    if A[j] = x
```

```
      return j
```

```
    j ← j+1
```

```
  return -1
```

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

5.

How many times does the loop run to find 6? 1.

How many times does the loop run to find 99? 7.

(the length of the array)



Assessing Algorithm “Efficiency”



- Resources consumed: **time** and **space**
- We want to assess efficiency as a function of input size
- Mathematical v
- Average case
- Knowledge about input peculiarities may affect the choice of algorithm
- The right choice of algorithm may also depend on the programming language used for implementation

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Running Time Dependencies



THE UNIVERSITY OF
MELBOURNE

- There are many things that a program's running time depends on:
 1. Complexity of the algorithms used
 2. Input to the program
 3. Underlying machine architecture
 4. Language/compiler/operating system
- Since we want to compare **algorithms** we ignore (3) and (4); just consider **units of time**
- Use a natural number n to quantify (2)—size of the input
- Express (1) as a function of n

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Linear Search Example

```
function find(A,x,n)
```

```
  j ← 0
```

```
  while j < n
```

```
    if A[j] = x
```

```
      return j
```

```
    j ← j+1
```

```
  return -1
```

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

measure the size, n ,

n = the length of the array

How should we quantify the cost to run this algorithm?

roughly, number of times the loop runs
(later in this lecture we will be more precise)

Linear Search Example

```
function find(A,x,n)
```

```
  j  $\leftarrow$  0
```

```
  while j < n
```

```
    if A[j] = x
```

```
      return j
```

```
    j  $\leftarrow$  j+1
```

```
  return -1
```

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Worst case input?
an array doesn't contain the
item, x, we are searching for

Worst case time complexity: n
(since the loop runs n times in that case)

Linear Search Example

```
function find(A,x,n)
```

```
  j  $\leftarrow$  0
```

```
  while j < n
```

```
    if A[j] = x
```

```
      return j
```

```
    j  $\leftarrow$  j+1
```

```
  return -1
```

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

best case input?

an array has the item, x,
we are searching for in the first position

Best case time complexity: 1
(since the loop runs once in that case)

Estimating Time Consumption



- Number of loop iterations is not a good estimate of running time.
- Better is to identify the algorithm's **basic operation** and how many times it is performed.
Assignment Project Exam Help
<https://eduassistpro.github.io/>
- If c is the cost of a **basic operation** and $g(n)$ is the number of times the operation is performed for input size n ,
Add WeChat edu_assist_pro

then running time $t(n) \approx c \cdot g(n)$

Linear Search Example

```
function find(A,x,n)
```

```
  j  $\leftarrow$  0
```

```
  while j < n
```

```
    if A[j] = x
```

```
      return j
```

```
    j  $\leftarrow$  j+1
```

```
  return -1
```

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

the comparison A[j] = x

ic operation here?

Rule of thumb: the most expensive operation executed each time in the inner-most loop of the program

Examples:

Input Size and Basic Operation



Problem	Size Measure	Basic Operation
Search in a list of n items	n	Key comparison
Multiply two matrices of floats	$(\text{rows} \times \text{cols})^2$	Float multiplication
Compute a^n	$\log n$	Float multiplication
Graph problem	Number of nodes and edges	Visiting a node

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Best, Average and Worst Case



THE UNIVERSITY OF
MELBOURNE

- The running time $t(n)$ may well depend on more than just n
- **Worse case:** analysis makes the most pessimistic assumptions about the input
- **Best case:** analysis makes the most optimistic assumptions about the input
<https://eduassistpro.github.io/>
- **Average case:** analysis aims to **expected** running time across all possible input of size n
(Note: **not** an average of the worst and best cases)
- **Amortised** analysis takes context of running an algorithm into account, calculates cost **spread over many runs**. Used for “self-organising” data structures that adapt to their usage

Large Input is what Matters



THE UNIVERSITY OF
MELBOURNE

- Small input does not properly stress an algorithm

Assignment Project Exam Help

<https://eduassistpro.github.io/>

for small values of m and n cost is similar

- Only as we let m and n grow large do we witness (big) differences in performance.

Guessing Game Example



- Guess which number I am thinking of, between 1 and n (inclusive). I will tell you if it is higher or lower than each guess.

Assignment Project Exam Help

1 <https://eduassistpro.github.io/> 100

Wrong. My number is ~~less than 75~~ ^{Add WeChat edu_assist_pro} ~~than 75~~ ^{than 50}.

We are **halving** the search space each time.

Basic operation:

(Worse case) complexity: $\log n$

The Tyranny of Growth Rate



n	$\log_2 n$	n	$n \log_2 n$	n^2	n^3	2^n	$n!$
10^1	3	10^1	$3 \cdot 10^1$	10^2	10^3	10^3	$4 \cdot 10^6$
10^2	7	10^2	$7 \cdot 10^2$	10^4	10^6	10^{30}	$9 \cdot 10^{157}$
10^3	10	10^3	$1 \cdot 10^4$	10^6	10^9	-	-

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

10^{30} is 1,000 times the number of nano-seconds since the Big Bang.

At a rate of a trillion (10^{12}) operations per second, executing 2^{100} operations would take a computer in the order of 10^{10} years.

That is more than the estimated age of the Earth

The Tyranny of Growth Rate



THE UNIVERSITY OF
MELBOURNE

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Functions Often Met in Algorithm Classification

- **1**: Running time independent of input
- **log n**: typical for “divide and conquer” solutions, for example lookup in a balanced search tree
- **Linear (n)**: When each input must be processed once
- **n log n**: Each input processing involves other elements for example, sorting.
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro
- **n², n³**: Quadratic, cubic. Processing all pairs (triples) of elements.
- **2ⁿ**: Exponential. Processing all subsets of elements.

Asymptotic Analysis

- We are interested in the asymptotic behavior of functions
- Ignore constant factors
- Ignore small input sizes

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Asymptotics

- $f(n) < g(n)$ iff $\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0$
- That is, g approaches infinity faster than f
- $1 < \log n < n^\varepsilon$ ~~Assignment Project Exam Help~~
where $0 < \varepsilon < 1$ <https://eduassistpro.github.io/>
[Add WeChat edu_assist_pro](#)
- In asymptotic analysis, **think big!**
 - e.g., $\log n < n^{0.0001}$, even though for $n = 10^{100}$, $100 > 1.023$.
 - Try it for $n = 10^{10000000}$

Big-Oh Notation

- $O(g(n))$ denotes the set of functions that grow no faster than g , asymptotically.

- **Formal definition:** We write

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

when, **for some c and n_0**

$$n > n_0 \Rightarrow t(n) < c \cdot g(n)$$

- For example: $1 + 2 + \dots + n \in O(n^2)$

Big-Oh: What $t(n) \in O(g(n))$ Means



THE UNIVERSITY OF
MELBOURNE

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Big-Oh Pitfalls

- Levitin's notation $t(n) \in O(g(n))$ is meaningful, but not standard.
- Other authors use $t(n) = O(g(n))$ for the same thing.
[Assignment Project Exam Help](https://eduassistpro.github.io/)
- As O provides an upper bound, it is correct to say both $3n \in O(n^2)$ and $3n \in O(n)$ (you can see why using '=' is confusing); the latter, $3n \in O(n)$, is of course more precise and useful.
<https://eduassistpro.github.io/>
[Add WeChat edu_assist_pro](#)
- Note that c and n_0 may be large.

Big-Omega and Big-Theta



- **Big Omega:** $\Omega(g(n))$ denotes the set of functions that grow no slower than g , asymptotically, so Ω is for **lower bounds**
[Assignment Project Exam Help](https://eduassistpro.github.io/)
- $t(n) \in \Omega(g(n))$ if $t(n) \geq c \cdot g(n)$,
for some n_0 and c .
[Add WeChat edu_assist_pro](https://eduassistpro.github.io/)
- **Big Theta:** Θ is for **exact** order of growth.
 - $t(n) \in \Theta(g(n))$ iff $t(n) \in O(g(n))$ and $t(n) \in \Omega(g(n))$.

Big-Omega: What $t(n) \in \Omega(g(n))$ Means



THE UNIVERSITY OF
MELBOURNE

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Big-Theta: What $t(n) \in \Theta(g(n))$ Means



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Establishing Growth Rate

- We can use the definition of O directly.

$$t(n) \in O(g(n)) \text{ iff: } n > n_0 \Rightarrow t(n) < c \cdot g(n)$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- **Exercise:** use this to show

Add WeChat edu_assist_pro

$$1 + 2 + \dots + n \in O(n^2)$$

- Also show that:

$$17n^2 + 85n + 1024 \in O(n^2)$$

$$1 + 2 + \dots + n \in O(n^2)$$

Find some c and n_0 such that, for all $n > n_0$

$$1 + 2 + \dots + n < c \cdot n^2$$

$$1 + 2 + \dots + n$$

$$= \frac{n(n+1)}{2}$$

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

$$= \frac{n^2 + n}{2}$$

$$< n^2 + n \quad (\text{for } n > 0)$$

$$< n^2 + n^2 \quad (\text{for } n > 1)$$

$$= 2n^2$$

$$\sum_{i=1}^n i = 1 + 2 + \dots + n = \frac{n(n+1)}{2} \approx \frac{1}{2}n^2$$

Choose $n_0 = 1$, $c = 2$

$$17n^2 + 85n + 1024 \in O(n^2)$$



Find some c and n_0 such that, for all $n > n_0$

$$17n^2 + 85n + 1024 < c \cdot n^2$$

Guess $c = 18$ Need to prove:

$$17n^2 + 85n + 1024 < 18n^2$$

i.e. $85n +$ <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Guess $n_0 = 1024$ Check if: $85n_0 + 1024 < n_0^2$

$$85 \cdot 1024 + 1024 < 1024 \cdot 1024$$

i.e. $86 \cdot 1024 < 1024 \cdot 1024$ Clearly true.

Choose $c = 18$, $n_0 = 1024$

$$17n^2 + 85n + 1024 \in O(n^2)$$



Find some c and n_0 such that, for all $n > n_0$

$$17n^2 + 85n + 1024 < c \cdot n^2$$

Alternative: Let $c = 17 + 85 + 1024$

$$17n^2 + 85n + 1024$$

$$< 17n^2 + 85n^2 \quad n > 1)$$

$$= (17 + 85 + 1024)n^2$$

Choose $c = 17 + 85 + 1024$, $n_0 = 1$

Of course, this works for *any* polynomial.