



THE UNIVERSITY OF
MELBOURNE

COMP90038

Algorithms and Complexity

Assignment Project Exam Help

Lecture 2 <https://eduassistpro.github.io/> Concepts
(with thanks to Hara ergaard)
Add WeChat edu_assist_pro

Toby Murray



toby.murray@unimelb.edu.au



DMD 8.17 (Level 8, Doug McDonnell Bldg)



<http://people.eng.unimelb.edu.au/tobym>



@tobycmurray

Approaching a problem

- Can we cover this board with 31 tiles of the following form?
- This is the **mutilated checkerboard problem**. <https://eduassistpro.github.io/> **Assignment Project Exam Help**
- There are only finitely many ways we can arrange the 31 tiles, so there is a brute-force (and very inefficient) way of solving the problem. **Add WeChat edu_assist_pro**

Approaching a problem



- Can we cover this board with 31 tiles of the following form?
- This is the **mutilated checkerboard problem**. <https://eduassistpro.github.io/> **Assignment Project Exam Help**
- There are only finitely many ways we can arrange the 31 tiles, so there is a brute-force (and very inefficient) way of solving the problem. **Add WeChat edu_assist_pro**

Approaching a problem



- Can we cover this board with 31 tiles of the following form?
- This is the **mutilated checkerboard problem**. <https://eduassistpro.github.io/> **Assignment Project Exam Help**
- There are only finitely many ways we can arrange the 31 tiles, so there is a brute-force (and very inefficient) way of solving the problem. **Add WeChat edu_assist_pro**

Approaching a problem



- Can we cover this board with 31 tiles of the following form?
- This is the **mutilated checkerboard problem**. <https://eduassistpro.github.io/>
- There are only finitely many ways we can arrange the 31 tiles, so there is a brute-force (and very inefficient) way of solving the problem.

Assignment Project Exam Help

Add WeChat edu_assist_pro

Approaching a problem




- Can we cover this board with 31 tiles of the following form?
- This is the **mutilated checkerboard problem**. <https://eduassistpro.github.io/> **Assignment Project Exam Help**
- There are only finitely many ways we can arrange the 31 tiles, so there is a brute-force (and very inefficient) way of solving the problem. **Add WeChat edu_assist_pro**

Approaching a problem



THE UNIVERSITY OF
MELBOURNE




- Can we cover this board with 31 tiles of the following form?

- This is the **mutilated checkerboard problem**. <https://eduassistpro.github.io/>

- There are only finitely many ways we can arrange the 31 tiles, so there is a brute-force (and very inefficient) way of solving the problem.

Transform and Conquer?

Use abstraction?



- Can we cover this board with 31 tiles of the form shown?

Assignment Project Exam Help

- Why can we quickly determine that the answer is no?

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- **Hint:** Using the way the squares are coloured helps.

Transform and Conquer?

Use abstraction?



THE UNIVERSITY OF
MELBOURNE



- Can we cover this board with 31 tiles of the form shown?

Assignment Project Exam Help

- Why can we quickly determine that the answer is no?

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



- **Hint:** Using the way the squares are coloured helps.

Transform and Conquer?

Use abstraction?



THE UNIVERSITY OF
MELBOURNE



- Can we cover this board with 31 tiles of the form shown?

Assignment Project Exam Help

- Why can we quickly determine that the answer is no?


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- **Hint:** Using the way the squares are coloured helps.

Transform and Conquer?

Use abstraction?



- Can we cover this board with 31 tiles of the form shown?

Assignment Project Exam Help

- Why can we quickly determine that the answer is no?

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- **Hint:** Using the way the squares are coloured helps.

Algorithms and Data Structures



THE UNIVERSITY OF
MELBOURNE

- **Algorithms**: for solving problems, transforming data.
- **Data structures**: for storing data, arranging data in a way that suits an algorithm.
 - **Linear** data structures: stacks and queues
 - Trees and graphs
 - Dictionaries
- Which data structures are you familiar with?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Exercise

- Pick your favourite data structure and describe it
 - How to insert an item <https://eduassistpro.github.io/>
 - How to find an item [Add WeChat edu_assist_pro](#)
 - How to handle duplicate items

Primitive Data Structures:

The Array

- An array corresponds to a sequence of consecutive cells in memory.
- Depending on programming language: $A[0]$ up to $A[n-1]$, or $A[1]$ up to $A[n]$.
- Locating a cell, and storing or retrieving data at that cell is very fast.
- The downside of an array is that maintaining a contiguous bank of cells with information can be difficult and time-consuming.

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Primitive Data Structures:

The Array



- An array corresponds to a sequence of consecutive cells in memory.
- Depending on programming language: $A[0]$ up to $A[n-1]$, or $A[1]$ up to $A[n]$.
- Locating a cell, and storing or retrieving data at that cell is very fast.
- The downside of an array is that maintaining a contiguous bank of cells with information can be difficult and time-consuming.

6	9	2	3	7	5	8
0	1	2	3	4	5	6

42148
42150
42152
42154
42156
42158
42160

6
9
2
3
7
5
8

Primitive Data Structures:

The Array



- An array corresponds to a sequence of consecutive cells in memory.
- Depending on programming language: $A[0]$ up to $A[n-1]$, or $A[1]$ up to $A[n]$.
- Locating a cell, and storing or retrieving data at that cell is very fast.
- The downside of an array is that maintaining a contiguous bank of cells with information can be difficult and time-consuming.

6	9	2	3	7	5	8
0	1	2	3	4	5	6

42148
42150
42152
42154
42156
42158
42160

6
9
2
3
7
5
8

How many bytes does each integer occupy here?

Primitive Data Structures:

The Array



- An array corresponds to a sequence of consecutive cells in memory.
- Depending on programming language: $A[0]$ up to $A[n-1]$, or $A[1]$ up to $A[n]$.
- Locating a cell, and storing or retrieving data at that cell is very fast.
- The downside of an array is that maintaining a contiguous bank of cells with information can be difficult and time-consuming.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

6	9	2	3	7	5	8
0	1	2	3	4	5	6

42148
42150
42152
42154
42156
42158
42160

6
9
2
3
7
5
8

How many bytes does each integer occupy here?

Answer: 2 (16-bit integers)

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE

An array x :

2	3	5	7
---	---	---	---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE




<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE




<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE




<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE




Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE

A linked list



<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE

A linked list



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE

A linked list



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:

Primitive Data Structures: The Linked List



THE UNIVERSITY OF
MELBOURNE

A linked list




Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:



Primitive Data Structures: The Linked List




A linked list



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:




Primitive Data Structures: The Linked List



A linked list




Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:




Primitive Data Structures: The Linked List



A linked list




Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:



Primitive Data Structures: The Linked List




A linked list



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:



Primitive Data Structures: The Linked List




A linked list



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:



Primitive Data Structures: The Linked List




A linked list



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Suppose variable **x** holds
the address 42160, then the
list could look like this in
memory:



Terminology




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Terminology




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Terminology

node




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Terminology

node




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Terminology

node




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Terminology

node



pointer

(in Java: “reference”)

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

Terminology



THE UNIVERSITY OF
MELBOURNE


node



pointer


(in Java: “reference”)

Assignment Project Exam Help



Terminology


node



pointer

(in Java: “reference”)

Assignment Project Exam Help




x is (a pointer to) the **head node** of the list

Terminology




node




pointer

(in Java: “reference”)

Assignment Project Exam Help



x is (a pointer to) the **head node** of the list




Terminology



THE UNIVERSITY OF
MELBOURNE


node




pointer

(in Java: “reference”)

Assignment Project Exam Help



x is (a pointer to) the **head node** of the list




“**y.val**” refers to

Terminology



THE UNIVERSITY OF
MELBOURNE


node




pointer

(in Java: “reference”)

Assignment Project Exam Help



x is (a pointer to) the **head node** of the list




“**y.val**” refers to

Terminology




node




pointer

(in Java: “reference”)

Assignment Project Exam Help



x is (a pointer to) the **head node** of the list




“**y.val**” refers to

“**y.next**”
refers to

Terminology




node




pointer

(in Java: “reference”)

Assignment Project Exam Help



x is (a pointer to) the **head node** of the list



Linked List

- Often we use a dummy head node that points to the first object, or to a special `null` object that represents an empty list. This makes it easier to write functions that insert
- Inserting and deleting elements is very fast if you have a few links around.
- Finding the i th element can be time-consuming.

Iterative Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Walk through the array (of length n)
- For example, to locate item x .

function find(A, x, n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

function find(A, x, n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

function find(A, x, n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

function find(A, x, n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y

function find(A,x,n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6 j : 0

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6 j : 0

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
↓
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6 j : 1

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
↓
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6 j : 1

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6 j : 2

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array



- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6 j : 3

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6 j : 4

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

A[j]
↓

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

Iterative Processing: Array

- Walk through the array (of length n)
- For example, to locate item x .

A: Y x : 7 n : 6 j : 4

function find(A, x , n)

$j \leftarrow 0$

while $j < n$

if $A[j] = x$

return j

$j \leftarrow j+1$

return -1

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[j]
↓

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Let's trace the execution of find(Y,7,6)

(returns 4)

Iterative Processing: List

- Walk through a linked list.
- For example, to locate item **x**.

function find(head,x)

 p ← head

while p ≠ null

if p.val = x

return p

 p ← p.next

return null

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

function find(head, x)

$p \leftarrow \text{head}$

while $p \neq \text{null}$


if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$

return null

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro



Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

(note similarity to array version)

function find(head, x) **function** find(A, x , n)

$p \leftarrow \text{head}$

while $p \neq \text{null}$

if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$

return null


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

return j

$j \leftarrow j+1$

return -1



Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

(note similarity to array version)

function find(head, x) **function** find(A, x , n)

$p \leftarrow \text{head}$

while $p \neq \text{null}$

if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$

return null


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro
 $\stackrel{n}{=} x$

return j

$j \leftarrow j+1$

return -1



Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

(note similarity to array version)

function find(head, x) **function** find(A, x , n)

$p \leftarrow \text{head}$

while $p \neq \text{null}$

if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$

return null


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

return j

$j \leftarrow j+1$

return -1



Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

(note similarity to array version)

function find(head, x) **function** find(A, x , n)

$p \leftarrow \text{head}$

while $p \neq \text{null}$

if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$

return null


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro
 $n \equiv x$

return j

$j \leftarrow j+1$

return -1



Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

(note similarity to array version)

function find(head, x) **function** find(A, x , n)

$p \leftarrow \text{head}$

while $p \neq \text{null}$

if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$

return null


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro
 $n \equiv x$

return j

$j \leftarrow j+1$

return -1



Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

(note similarity to array version)

function find(head, x) **function** find(A, x , n)

$p \leftarrow \text{head}$

while $p \neq \text{null}$

if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$

return null


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

return j

$j \leftarrow j+1$

return -1



Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

(note similarity to array version)

function find(head, x) **function** find(A, x , n)

$p \leftarrow \text{head}$

while $p \neq \text{null}$

if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$


return null

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

return j

$j \leftarrow j+1$

return -1



Iterative Processing: List

- Walk through a linked list.
- For example, to locate item x .

(note similarity to array version)

function find(head, x) **function** find(A, x , n)

$p \leftarrow \text{head}$

while $p \neq \text{null}$

if $p.\text{val} = x$

return p

$p \leftarrow p.\text{next}$

return null


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro
 $n \equiv x$

return j

$j \leftarrow j+1$

return -1



Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

```
function find(A,x,lo,hi)
```

```
    if lo > hi
```

```
        return -1
```

```
    else if A[lo] = x
```

```
        return lo
```

```
    else
```

```
        return find(A,x,lo+1,hi)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

```
function find(A,x,lo,hi)
```

```
    if lo > hi
```

```
        return -1
```

```
    else if A[lo] = x
```

```
        return lo
```

```
    else
```

```
        return find(A,x,lo+1,hi)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Initial call: find(A,x,0,n-1)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

```
function find(A,x,lo,hi)
```

```
    if lo > hi
```

```
        return -1
```

```
    else if A[lo] = x
```

```
        return lo
```

```
    else
```

```
        return find(A,x,lo+1,hi)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

```
function find(A,x,lo,hi)
```

```
    if lo > hi
```

```
        return -1
```

```
    else if A[lo] = x
```

```
        return lo
```

```
    else
```

```
        return find(A,x,lo+1,hi)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

```
function find(A,x,lo,hi)
```

```
  if lo > hi
```

```
    return -1
```

```
  else if A[lo] = x
```

```
    return lo
```

```
  else
```

```
    return find(A,x,lo+1,hi)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x : 7

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x : 7 lo: 0

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x: 7 lo: 0 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x: 7 lo: 0 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

↓
Add WeChat edu_assist_pro

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x: 7 lo: 0 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[hi]
↓

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x : 7 lo: 1 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[hi]
↓

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x: 7 lo: 1 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[hi]
↓

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x : 7 lo: 1 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[hi]
↓

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x: 7 lo: 2 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[hi]
↓

Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x: 7 lo: 3 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[lo]

A[hi]



Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x: 7 lo: 4 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[lo]



A[hi]



Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)

Recursive Processing: Array



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance
- For example, to locate item x .

A: Y x: 7 lo: 4 hi: 6

function find(A,x,lo,hi)

if lo > hi

return -1

else if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A[lo]



A[hi]



Y:

6	9	2	3	7	5	8
0	1	2	3	4	5	6

Initial call: find(A,x,0,n-1) Let's trace the execution of find(Y,7,0,6)
(returns 4)

Recursive Processing: List



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance

```
function find(p,x)
```

```
  if p = null
```

```
    return p
```

```
  else if p.val = x
```

```
    return p
```

```
  else
```

```
    return find(p.next,x)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Recursive Processing: List



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance

```
function find(p,x)
```

```
  if p = null
```

```
    return p
```

```
  else if p.val = x
```

```
    return p
```


```
  else
```

```
    return find(p.next,x)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Recursive Processing: List



THE UNIVERSITY OF
MELBOURNE

- Solve the problem for a sub-instance and use the solution to solve the full instance

```
function find(p,x)
```

```
  if p = null
```

```
    return p
```

```
  else if p.val = x
```

```
    return p
```

```
  else
```


```
    return find(p.next,x)
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Initial call: find(head,x)



Recursive Processing: List

- Solve the problem for a sub-instance and use the solution to solve the full instance

(note similarity to array version)

function find(p,x)

if p = null

return p

else if p.val = x

return p

else

return find(p.next,x)

function find(A,x,lo,hi)

if lo > hi

return -1

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

if A[lo] = x

else

return find(A,x,lo+1,hi)

Initial call: find(head,x)



Recursive Processing: List

- Solve the problem for a sub-instance and use the solution to solve the full instance

(note similarity to array version)

function find(p,x)

if p = null

return p

else if p.val = x

return p

else

return find(p.next,x) p:

function find(A,x,lo,hi)

if lo > hi

return -1

if A[lo] = x

return lo

else


return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Initial call: find(head,x)



Recursive Processing: List



- Solve the problem for a sub-instance and use the solution to solve the full instance

(note similarity to array version)

function find(p,x)

if p = null

return p

else if p.val = x

return p

else

return find(p.next,x)

function find(A,x,lo,hi)

if lo > hi

return -1

if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Initial call: find(head,x)

head:



Recursive Processing: List



- Solve the problem for a sub-instance and use the solution to solve the full instance

(note similarity to array version)

function find(p,x)

if p = null

return p

else if p.val = x

return p

else

return find(p.next,x)

function find(A,x,lo,hi)

if lo > hi

return -1

if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Initial call: find(head,x)

head:



Recursive Processing: List



- Solve the problem for a sub-instance and use the solution to solve the full instance

(note similarity to array version)

function find(p,x)

if p = null

return p

else if p.val = x

return p

else

return find(p.next,x)

function find(A,x,lo,hi)

if lo > hi

return -1

if A[lo] = x

return lo

else

return find(A,x,lo+1,hi)


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Initial call: find(head,x)

head:



Recursive Processing: List



- Solve the problem for a sub-instance and use the solution to solve the full instance

(note similarity to array version)

function find(p,x)

if p = null

return p

else if p.val = x

return p

else

return find(p.next,x)

function find(A,x,lo,hi)

if lo > hi

return -1

if A[lo] = x

else

return find(A,x,lo+1,hi)


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Initial call: find(head,x)

head:



Recursive Processing: List



- Solve the problem for a sub-instance and use the solution to solve the full instance

(note similarity to array version)

function find(p,x)

if p = null

return p

else if p.val = x

return p

else

return find(p.next,x)

function find(A,x,lo,hi)

if lo > hi

return -1

if A[lo] = x

return lo

else


return find(A,x,lo+1,hi)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Initial call: find(head,x)



Recursive Processing: List



- Solve the problem for a sub-instance and use the solution to solve the full instance

(note similarity to array version)

```
function find(p,x)
  if p = null
    return p
  else if p.val = x
    return p
  else
    return find(p.next,x)
```

```
function find(A,x,lo,hi)
```

```
  if lo > hi
```

```
    return -1
```


```
  if A[lo] = x
```

```
    else
```

```
      return find(A,x,lo+1,hi)
```

we will discuss this
Assignment Project Exam Help
<https://eduassistpro.github.io/>
W
Add WeChat edu_assist_pro

Initial call: find(head,x)



Abstract DataTypes

- A collection of data items, and a family of operations that operate on that data
- Think of an ADT as a set of contracts, an **interface**
- We must still **implement** it (an advantage to separate the implementation of the ADT from the “**interface**” it provides)
- Good programming practice is to support this separation
 - Nothing outside of the definition of the ADT should refer to anything inside, except through function calls and basic operations

Assignment Project Exam Help

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: The Stack

- Last-In-First-Out (LIFO)
- Operations:
 - CreateStack
 - Push
 - Pop
 - Top
 - EmptyStack?
 - ...
- Usually implemented as an ADT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Stack Implementation: Array



THE UNIVERSITY OF
MELBOURNE

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Stack Implementation: Array



THE UNIVERSITY OF
MELBOURNE

6	9	2	3	7		
0	1	2	3	4	5	6

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Stack Implementation: Array



THE UNIVERSITY OF
MELBOURNE

6	9	2	3	7		
0	1	2	3	4	5	6

top: 5

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Stack Implementation: Array



THE UNIVERSITY OF
MELBOURNE

6	9	2	3	7		
0	1	2	3	4	5	6

top: 5

Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Stack Implementation: Array



THE UNIVERSITY OF
MELBOURNE

6	9	2	3	7	5	
0	1	2	3	4	5	6

top: 5

Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Stack Implementation: Array



THE UNIVERSITY OF
MELBOURNE

6	9	2	3	7	5	
0	1	2	3	4	5	6

Assignment Project Exam Help

top: 6

<https://eduassistpro.github.io/>


Push(5)

Add WeChat edu_assist_pro

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Assignment Project Exam Help

function push(st,x)

ew node

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

X
st


st ← elt

return st

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Push(5)


```

    st ← elt
    return st
  
```


Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Assignment Project Exam Help

function push(st,x)

ew node

<https://eduassistpro.github.io/>

x

Add WeChat edu_assist_pro

st

Push(5)


st ← elt

return st

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

function push(st,x)

ew node

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro_{st}



st ← elt

return st

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

function push(st,x)

ew node

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro_{st}



st ← elt

return st

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

function push(st,x)

ew node

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro_{st}



st ← elt

return st

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



```

function push(st,x)
    ew node
    X
    st
    st ← elt
    return st
  
```

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro



```

function push(st,x)
    ew node
    st
    st ← elt
    return st
  
```

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


```

function push(st,x)
    ew node
    st
    st ← elt
    return st
  
```

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


```

function push(st,x)
    ew node
    st
    st ← elt
    return st
    
```


Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

```


    st ← elt
    return st

```

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


st ← elt

return st

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


st \leftarrow elt

return st

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


```

st ← elt
return st
  
```

Stack Implementation: Linked List



THE UNIVERSITY OF
MELBOURNE



Push(5)

Assignment Project Exam Help

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

```

    st ← elt
    return st

```

See

<https://www.cs.usfca.edu/~galles/visualization/Algorithms.html>
for more visualisations

Pseudo Code

- On the previous slide, we assumed that a “node” has two attributes: a “val” which is its value, and a “next” which points to the rest of the list.

<https://eduassistpro.github.io/>

- There is no standard for pseudo-code. Examples in Levitin as a guide. Cormen et al. pages 20–22 (in References) has a list of standard conventions used with pseudo-code which are good to follow, except we use \leftarrow as the assignment operator.

Fundamental Data Structure: Queues



THE UNIVERSITY OF
MELBOURNE

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue
- Enqueue
- Dequeue
- Head
- EmptyQueue?
- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Fundamental Data Structure: Queues



THE UNIVERSITY OF
MELBOURNE

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue
- Enqueue
- Dequeue
- Head
- EmptyQueue?
- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: Queues



THE UNIVERSITY OF
MELBOURNE

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue
- Enqueue
- Dequeue
- Head
- EmptyQueue?
- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: Queues

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue
- Enqueue
- Dequeue
- Head
- EmptyQueue?
- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: Queues

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue
- Enqueue
- Dequeue
- Head
- EmptyQueue?
- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: Queues



THE UNIVERSITY OF
MELBOURNE

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue

- Enqueue

- Dequeue

- Head

- EmptyQueue?

- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: Queues



THE UNIVERSITY OF
MELBOURNE

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue
- Enqueue
- Dequeue
- Head
- EmptyQueue?
- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: Queues

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue

- Enqueue

- Dequeue

- Head

- EmptyQueue?

- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: Queues

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue

- Enqueue

- Dequeue

- Head

- EmptyQueue?

- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Fundamental Data Structure: Queues

- First-In-First-Out (FIFO)

- Operations:

- CreateQueue

- Enqueue

- Dequeue

- Head

- EmptyQueue?

- ...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Other Data Structures



- We will meet many other (abstract) data structures, e.g.
 - The priority queue **Assignment Project Exam Help**
 - Various types of “tree” **<https://eduassistpro.github.io/>**
 - Various types of “graph” **Add WeChat edu_assist_pro**
- If you check out algorithm animation tools or advanced algorithm books, you will meet exotic data structures such as splay trees and skip lists.

Next Week



Assignment Project Exam Help

- Algorithm analysis—how to estimate algorithm's resource consumption.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro