

Lecture 4: Introduction to Probability Theory

Assignment Project Exam Help

<https://eduassistpro.github.io>

Sarah Erfani and Karin Verspoor, CIS

Add WeChat Search edu_assist_pro



THE UNIVERSITY OF

MELBOURNE

Lecture 4:
Introduction to
Probability
Theory

COMP90049
Knowledge
Technologies

Probability
Theory

The Basics

Conditional
Probability

Distributions

Entropy

Assignment Project Exam Help

"The calculus of probability theory provides us with a formal framework

<https://eduassistpro.github.io>

without reducing our conclusions to conte

Add WeChat <http://pgm.s>
From Probabilistic Graphical Models (El
koller and Friedman)

Lecture 4:
Introduction to
Probability
Theory

COMP90049
Knowledge
Technologies

Probability
Theory

The Basics

Conditional
Probability

Distributions

Entropy

Assignment Project Exam Help

- $P(A)$: the probability of A =
the fraction of times the event is true in independent trials

<https://eduassistpro.github.io>

Given a deck of 52 cards;

13 ranks (ace, king, queen, jack, 2-10)

of each of four suits (clubs, spades, hearts, diamonds)

$P(\text{ace}) = ?$, $P(\text{red}) = ?$

Add WeChat edu_assist_pro

Lecture 4:
Introduction to
Probability
Theory

COMP90049
Knowledge
Technologies

Probability
Theory

The Basics

Conditional
Probability

Distributions

Entropy

Assignment Project Exam Help

- $P(A)$: the probability of A =
the fraction of times the event is true in independent trials

<https://eduassistpro.github.io>

Given a deck of 52 cards;

13 ranks (ace, king, queen, jack, 2-10)

of each of four suits (clubs, spades, hearts, diamonds)

Add WeChat [edu_assist_pro](#)

$$P(\text{ace}) = \frac{1}{13}, P(\text{red}) = \frac{1}{2}$$

- Joint probability ($P(A, B)$):
the probability of both A and B occurring = $P(A \cap B)$



$$P(\text{ace, heart}) = ?, P(\text{heart, red}) = ?$$

Lecture 4:
Introduction to
Probability
Theory

COMP90049
Knowledge
Technologies

Probability
Theory

The Basics


Conditional

Probability

Distributions

Entropy


- Joint probability ($P(A, B)$):
the probability of both A and B occurring = $P(A \cap B)$



$$P(\text{ace, heart}) = \frac{1}{52}, P(\text{heart, red}) = \frac{1}{4}$$

- Conditional probability ($P(A|B)$):

the probability of A occurring given the occurrence of $B = \frac{P(A \cap B)}{P(B)}$



$$P(\text{ace}|\text{heart}) = \frac{1}{13}, P(\text{heart}|\text{red}) = \frac{1}{2}$$

Lecture 4:
Introduction to
Probability
Theory

COMP90049
Knowledge
Technologies

Probability
Theory

The Basics

Conditional
Probability

Distributions

Entropy

- *Sum rule:* $P(A) = \sum_B P(A \cap B)$

- *Multiplication rule:* $P(A \cap B) = P(A|B)P(B) = P(B|A)P(A)$



<https://eduassistpro.github.io>

- *Prior probability* ($P(A)$): the probability of A based on background knowledge about A

- *Posterior probability* ($P(A|B)$): the probability of A based on background knowledge about A and B

- *Independence:* A and B are independent iff $P(A \cap B) = P(A)P(B)$

$$P(A|B) = \frac{P(A \cap B)}{P(B)} = \frac{P(B|A)P(A)}{P(B)} \quad (1)$$

For proposition A and evidence B,

<https://eduassistpro.github.io>

Bayes' Rule is important because it allows us to calculate the probability of A given knowledge of the 'inverse' probability of B.

For instance, imagine we believe (from prior knowledge) that $P(H1|Smart) = 0.6$, $P(Smart) = 0.3$, and $P(H1) = 0.2$.

Now we learn that a particular student received a mark of H1. Can we estimate $P(Smart)$ for that student, e.g. $P(Smart|H1)$?

(What if the $P(H1) = 0.4$?)

- A **binomial distribution** results from a series of independent trials with only two outcomes

i. e. *Bernoulli trials*)

e.g. multiple coin tosses ($\langle H, T, H, H, \dots, T \rangle$)

- exactly m

<https://eduassistpro.github.io>

$$\binom{n}{m} = \frac{n!}{m!(n-m)!}$$

Add WeChat edu_assist_pro

$$P(m, n, p) = \binom{n}{m} p^m (1-p)^{n-m}$$

Intuition: we want m successes (p^m) and $n - m$ failures ($(1 - p)^{n-m}$). However, the m successes can occur anywhere among the n trials, and there are $C(n, m)$ different ways of distributing m successes in a sequence of n trials.

Assignment Project Exam Help

<https://eduassistpro.github.io>

Add WeChat edu_assist_pr

What is the probability that if we toss a fair coin 3 times, we will get 2 heads?

X =number of heads when flipping coin 3 times; $P(X = 2)$

<https://eduassistpro.github.io>

$$\binom{3}{2} = \frac{3!}{2!1!} =$$

So, 3 possible outcomes, 1 for each,

Add WeChat edu_assist_pro

$$P\left(2, 3, \frac{1}{8}\right) = \frac{3!}{2!(3-2)!} \left(\frac{1}{2}\right)^2 \left(\frac{1}{2}\right)^{3-2} = 3 \left(\frac{1}{4}\right) \left(\frac{1}{2}\right)$$

- A **multinomial distribution** results from a series of independent trials with more than two outcomes:
e.g. two players in a tournament, 3 outcomes: (Player A winner, Player B winner, draw);

<https://eduassistpro.github.io>

occurring exactly x_1, x_2, \dots, x_n times

$P(X_1 = x_1, X_2 = x_2, \dots, X_n = x_n) = \frac{n!}{x_1! x_2! \dots x_n!} p_1^{x_1} p_2^{x_2} \dots p_n^{x_n}$

Add WeChat: edu_assist_pro

If these two chess players played 12 games, what is the probability that Player A would win 7 games, Player B would win 2 games, and the remaining 3 games would be drawn?

Consider a message M composed of distinct symbols w_1, \dots, w_n , where each symbol w_i has a frequency f_i . The total length of the message is

$$|M| = \sum_{i=1}^n f_i.$$

Information theory tells us that the minimum length encoding of the

<https://eduassistpro.github.io>

$$E = \sum -f$$

Add WeChat edu_assist_pro

is the *entropy* of the message; this is the th
the message in the context of the provided information.

Relationship to information retrieval: we are interested in terms that have high entropy in a document collection (bursty), and documents in which these terms are a significant component of the document's 'message'.

- A measure of *unpredictability*
- Given a probability distribution, the information (in bits) required to predict an event is the distribution's *entropy* or *information value*
-

<https://eduassistpro.github.io>

Add WeChat [edu_assist_pro](https://eduassistpro.github.io)

$$H(x) = - \sum_{i=1}^n P(i) \log_2 P(i)$$

$$= - \frac{\text{freq}(*) \log_2(\text{freq}(*)/n)}{\text{freq}(*)}$$

where $0 \log_2 0 =_{\text{def}} 0$

entropy = information content

Measures the average missing information on a random source, or the *uncertainty* of a probability distribution.

- A high entropy value means x is unpredictable.



<https://eduassistpro.github.io>

$$= -((0.5 * -1) + (0.5 * 1)) = -(-1) = 1$$

- Two possible outcomes with equal probability
Learning the outcome contains on

Add WeChat edu_assist_pro

- A low entropy value means x is predictable.
 - A coin toss with two heads is perfectly predictable.

$$H(x) = -(1 \log_2 1 + 0 \log_2 0) = -(0 + 0) = 0$$

- We don't learn anything once we see the outcome.

Lecture 4:
Introduction to
Probability
Theory

COMP90049
Knowledge
Technologies

Probability
Theory

The Basics

Conditional
Probability

Distributions

Entropy

Assignment Project Exam Help

<https://eduassistpro.github.io>

$$= 0.47$$

Add WeChat edu_assist_pr

Assignment Project Exam Help

NB: The range of the entropy values is not $[0, 1]$.

<https://eduassistpro.github.io>

- Entropy=0 (minimum entropy) when one probability is 1, others 0
- Entropy= $\log(n)$ (maximum entropy) when all probabilities are equal values of $1/n$

Add WeChat edu_assist_pr

Assignment Project Exam Help

Probability forms the foundation of many knowledge technologies.

<https://eduassistpro.github.io>

- What is entropy, and how should you in

Next: Approximate matching
Add WeChat edu_assist_pr